IN-LB	Inch-Pound Units
SI	International System of Units

Report on Corrosion of Prestressing Steels

Reported by ACI Committee 222

ACI PRC-222.2-14(24)

American Concrete Institute
Always advancing

American Concrete Institute
Always advancing

First Printing
October 2014
ISBN: 978-0-87031-923-5

Report on Corrosion of Prestressing Steels

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at http://concrete.org/Publications/DocumentErrata.aspx. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided "as is" without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised ACI Manual of Concrete Practice (MCP).

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

www.concrete.org

ACI 222.2R-14(24)

Report on Corrosion of Prestressing Steels

Reported by ACI Committee 222

Mohammad S. Khan, Chair

Antonio J. Aldykiewicz Jr.
Michael C. Brown
David Darwin
Marwan A. Daye
Stephen D. Disch
Hamid Farzam
Per Fidjestol
David P. Gustafson
H. R. Trey Hamilton III

Carolyn M. Hansson*
William G. Hime
Brian B. Hope
Burkan Isgor
Tracy D. Marcotte*
David B. McDonald
Robert Moser
Theodore L. Neff
Charles K. Nmai

Keith A. Pashina
Randall W. Poston*
Ruben M. Salas
Arpad Savoly
Andrea J. Schokker*
Morris Schupack
Khaled A. Soudki
Paul G. Tourney
David Trejo

Yash Paul Virmani
Jeffrey S. West*
Richard E. Weyers
David W. Whitmore

Consulting Member
Richard O. Lewis

*Subcommittee member

This report covers various types of prestressing steel, including some discussion on metallurgical differences, and supplements information presented in ACI 222R to include topics specifically related to prestressing steels. Deterioration mechanisms are discussed, including hydrogen embrittlement and stress-corrosion cracking. Methods to protect prestressing steel against corrosion in new construction are presented, along with a discussion of field performance of prestressed concrete structures. Finally, field evaluation and remediation techniques are presented. Appendixes present detailed information on stress-corrosion cracking and hydrogen embrittlement issues in prestressed concrete and mitigation techniques.

Keywords: anchorage; bonded; corrosion; duct; durability; grout; hydrogen embrittlement; post-tensioned; prestressed; tendon; strand; stress-corrosion cracking; unbonded.

CONTENTS

CHAPTER 1—INTRODUCTION, p. 2
1.1—Background, p. 2
1.2—Scope, p. 3

CHAPTER 2—DEFINITIONS, p. 3

CHAPTER 3—PRESTRESSING STEELS, p. 3
3.1—Wire, p. 3
3.2—Strand, p. 3
3.3—Bar, p. 3

CHAPTER 4—DETERIORATION OF PRESTRESSING STEELS, p. 4

CHAPTER 5—PROTECTION AGAINST CORROSION IN NEW CONSTRUCTION, p. 5
5.1—Introduction and history, p. 5
5.2—Prestressing tendon materials selection, p. 5
5.3—Corrosion protection for prestressing systems, p. 8
5.4—Cathodic protection, p. 14

CHAPTER 6—FIELD EVALUATION, p. 14
6.1—Introduction, p. 14
6.2—Evaluation goals, p. 14
6.3—Pretensioned structures, p. 14
6.4—Post-tensioned structures, p. 17

CHAPTER 7—REMEDIATION TECHNIQUES, p. 20
7.1—Introduction, p. 20
7.2—General, p. 20
7.3—Bonded post-tensioned tendons, p. 20
7.4—Unbonded multistrand post-tensioned tendons, p. 22

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

ACI 222.2R-14 supercedes ACI 222.2R-01 and was adopted and published October 2014.

Copyright © 2014, American Concrete Institute

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

CHAPTER 8—FIELD PERFORMANCE OF PRESTRESSED CONCRETE STRUCTURES, p. 24
8.1—Introduction, p. 24
8.2—Corrosion of prestressing strand before construction, p. 25
8.3—Pretensioned structures, p. 26
8.4—Unbonded post-tensioned structures, p. 27
8.5—Bonded post-tensioned structures, p. 29
8.6—Wire-wrapped prestressed structures, p. 31

CHAPTER 9—REFERENCES, p. 31

APPENDIX A—PRESTRESSING STEEL METALLURGY , p. 37
A.1—Wire, p. 37
A.2—Strand, p. 38
A.3—Bar, p. 38

APPENDIX B—DETERIORATION OF PRESTRESSING STEEL, p. 38
B.1—Metallurgy of prestressing steels, p. 38
B.2—Stress-corrosion cracking and hydrogen embrittlement, p. 39
B.3—Case histories, p. 40
B.4—Stress-corrosion cracking, p. 41
B.5—Hydrogen embrittlement, p. 43
B.6—Corrosion effect on fatigue performance, p. 47
B.7—Testing for SCC and HE, p. 47

CHAPTER 1—INTRODUCTION

1.1—Background

Several attempts were made to prestress concrete in the 1800s, but modern development of prestressed concrete began in 1928 and is credited to E. Freyssinet of France (Lin and Burns 1981). Freyssinet understood the importance of prestressing using high-strength steel to avoid prestressing losses that significantly reduce the applied prestressing force. Use of prestressed concrete began in the United States with circular-wrapped prestressed tanks in 1941 (Schupack 1964). The first prestressed segmental concrete bridge in the United States was constructed in Madison County, TN, and opened to the public on October 28, 1950 (Bennett et al. 2002). The Walnut Lane Memorial Bridge, located in Pennsylvania, was completed in the fall of 1950 (Manning 1988). Applications of prestressing in bridge and building construction then spread rapidly and have proven to be a successful construction method. Prestressed concrete construction enhances structural efficiency, improves control of flexural cracking, and allows for structural members with reduced dimensions.

Although corrosion is not as well documented in prestressed concrete structures as in nonprestressed concrete structures, prestressed concrete members have a number of advantages regarding corrosion performance over conventional nonprestressed concrete elements. In general, prestressed concrete construction follows higher-quality control practices and material standards than conventional nonprestressed construction. These practices result in improved concrete properties that limit diffusion of chloride, which is further reduced in prestressed concrete members due to absence or reduced-level cracking. Corrosion of prestressed concrete structures appears to be restricted to specific circumstances, including improper design, construction details, and construction practices. The potential for accelerated corrosion still exists in environments contaminated with chloride ions and hydrogen sulfide and it is imperative to protect prestressing steel. Corrosion of prestressing steel in bridges and buildings may not display outward signs of corrosion. Because failure of prestressing tendons could compromise the integrity of the structure, structures subjected to corrosive conditions should be periodically inspected with specific attention focused on the condition of the prestressing system.

A number of surveys provide information concerning the potential for corrosion of prestressed structures. Burdekin and Rothwell (1981) summarized practice, specifications, and corrosion mechanisms (1981) and reported that failure to provide adequate structural details and follow proper construction practices, as well as use of low-quality materials, account for the vast majority of poor performance. Schupack reached similar conclusions in additional surveys (Schupack 1978a, 1994; Schupack and Suarez 1982). More recently, corrosion problems were discovered in grouted post-tensioned bridges (Poston et al. 2003; Hartt and Venugopalan 2002; Muszynski 2003). The problems were largely attributed to inadequate post-tensioning details and grouting practices and deficient grout materials that led to accumulation of bleedwater voids.

Because corrosion in prestressed concrete members can potentially result in fracture-critical modes of failure, more information needs to be developed, disseminated, and used. The magnitude of the corrosion problem, its projected extent, and measures that can resolve it are of vital concern to designers, contractors, and owners, and form the basis of this report.

Prestressed concrete is used in several types of construction and is described as either pretensioned or post-tensioned, depending on whether the tendons are stressed before (pre) or after (post) the concrete is placed. Pretensioned concrete refers to systems in which high-strength wires or strands are stressed in forms between bulkheads before placement of the concrete. Concrete is cast and allowed to cure to a specified strength. Because the prestressing steel is bonded with the concrete, when the steel is released from the bulkheads, the concrete is placed in compression to equilibrate the tensile forces present in the steel. Pretensioning is common practice for both standardized precast bridge girders and in precast structural building members, such as solid joists, solid and hollow-core planks, and single- and double-tee joists.

Post-tensioned concrete refers to systems in which the concrete is placed and allowed to cure to a specified strength before prestressing. Post-tensioning is applied using either bonded or unbonded tendons. Bonded post-tensioning requires that tubes or ducts with deformations be placed in

American Concrete Institute – Copyrighted © Material – www.concrete.org