| | |
|---|---|
| IN-LB | Inch-Pound Units |
| SI | International System of Units |

# Use of Silica Fume in Concrete—Guide

Reported by ACI Committee 234

ACI PRC-234-26

American Concrete Institute
*Always advancing*

American Concrete Institute
Always advancing

First Printing: August 2026
ISBN: 978-1-64195-368-9

# Use of Silica Fume in Concrete—Guide

© 2026 American Concrete Institute. All rights reserved.

This material may not be reproduced or copied, in whole or in part, in any form or by any means, including making copies by any photo process, or by electronic or mechanical device, printed, written, graphic, or oral, or recording for sound or visual reproduction for use in any knowledge or retrieval system or device, without the written consent of ACI. This material may not be used by data mining, robots, screen scraping, or similar data gathering and extraction tools such as artificial intelligence ("AI") for purposes of developing or training a machine learning or AI model, conducting computer analysis or creating derivatives of this material, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. Despite these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at http://concrete.org/Publications/DocumentErrata.aspx. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided "as is" without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations regarding health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

ACI documents are written via a consensus-based process. The characteristics of ACI technical committee operations include:
(a) Open committee membership
(b) Balance/lack of dominance
(c) Coordination and harmonization of information
(d) Transparency of committee activities to public
(e) Consideration of views and objections
(f) Resolution through consensus process

The technical committee documents of the American Concrete Institute represent the consensus of the committee and ACI. Technical committee members are individuals who volunteer their services to ACI and specific technical committees.

American Concrete Institute®, ACI®, and Always Advancing® are registered trademarks of American Concrete Institute.

American Concrete Institute, 3880 Country Club Drive, Farmington Hills, Michigan 48331.
Telephone: +1.248.848.3700. Facsimile: +1.248.848.3701
**www.concrete.org**

# ACI PRC-234-26

# Use of Silica Fume in Concrete—Guide

Reported by ACI Committee 234


Fouad H.Yazbeck, Chair

Julie K. Buffenbarger, Secretary

James M. Aldred
Ekart R. Buhler
Jedadiah F. Burroughs
Mark A. Bury
Rachel J. Detwiler
William Halczak
Robert D. Hooton
Mike Hopkins
Kamal H. Khayat
Robert C. Lewis
Faizul M. Mohee
Jan Olek
H. Celik Ozyildirim
Reza Saleh Ahari
Ben Sealey
William A. Thompson
Simon Wilson
James R. Wolsiefer

**Consulting Members**

Menashi D. Cohen
Tarif M. Jaber
Anthony N. Kojundic

**Liaison Member**

Craig Heidrich



Note: Special acknowledgment to T. Holland for his contribution to this guide.



*This guide describes the physical and chemical properties of silica fume; how it interacts with portland cement; its effects on the properties of fresh and hardened concrete; recent typical applications of silica fume concrete; how it is proportioned, specified, and handled in the field; how it contributes to sustainability; and areas where additional research is needed.*



**Keywords:** curing; durability; high-performance concrete (HPC); high-range water-reducing admixtures (HRWRAs); high-strength concrete; placing; plastic-shrinkage cracking; silica fume; sustainability; time of setting; water-reducing admixtures (WRAs); workability.


## CONTENTS


**CHAPTER 1—INTRODUCTION, p. 3**
1.1—Introduction, p. 3
1.2—Scope, p. 3

**CHAPTER 2—NOTATION AND TERMINOLOGY, p. 3**
2.1—Notation, p. 3
2.2—Terminology, p. 3

**CHAPTER 3—SILICA FUME MATERIALS, p. 4**
3.1—General, p. 4
3.2—Silica fume versus other forms of silica, p. 5
3.3—Using silica fume in concrete, p. 5
3.4—Using silica fume in blended cement, p. 6
3.5—Worldwide availability of silica fume, p. 6
3.6—Types of silica fume products available, p. 6
3.7—Health hazards, p. 7
3.8—Environmental impact, p. 8

**CHAPTER 4—PHYSICAL PROPERTIES AND CHEMICAL COMPOSITION OF SILICA FUME, p. 8**
4.1—Color, p. 8
4.2—Specific gravity, p. 8
4.3—Bulk density, p. 8



ACI Committee Reports and Guides are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the information it contains. ACI disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom. Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.



ACI PRC-234-26 supersedes ACI 234R-06(12) and was published August 2026. This guide was first published in 1987 as 226.1R and revised in 1996 and 2006 as 234R.



Copyright © 2026, American Concrete Institute.

This material may not be reproduced or copied, in whole or in part, in any form or by any means, including making copies by any photo process, or by electronic or mechanical device, printed, written, graphic, or oral, or recording for sound or visual reproduction for use in any knowledge or retrieval system or device, without the written consent of ACI. This material may not be used by data mining, robots, screen scraping, or similar data gathering and extraction tools such as artificial intelligence ("AI") for purposes of developing or training a machine learning or AI model, conducting computer analysis or creating derivatives of this material, without the written consent of ACI.

4.4—Fineness, particle shape, and oversize material, p. 8
4.5—Chemical composition, p. 9
4.6—Crystallinity, p. 10
4.7—Variability, p. 10
4.8—Relating physical and chemical properties to performance in concrete, p. 11
4.9—Quality control, p. 11

**CHAPTER 5—MECHANISMS BY WHICH SILICA FUME MODIFIES CEMENT PASTE, MORTAR, AND CONCRETE, p. 11**
5.1—General, p. 11
5.2—Physical effects, p. 12
5.3—Chemical effects, p. 12
5.4—Microstructure modifications, p. 13
5.5—Self-desiccation and water of hydration, p. 16
5.6—Autogenous shrinkage (autogenous volume change), p. 16
5.7—Chemical composition of pore fluid, p. 16
5.8—Reactions in combination with fly ash or slag cement, p. 17
5.9—Reactions with different types of portland cement, p. 18
5.10—Heat of hydration, p. 18
5.11—Interactions with chemical admixtures, p. 19

**CHAPTER 6—PROPORTIONING OF SILICA FUME CONCRETE MIXTURES, p. 20**
6.1—General, p. 20
6.2—Cement and silica fume content, p. 20
6.3—Water content, p. 20
6.4—Aggregate, p. 20
6.5—Chemical admixtures, p. 20
6.6—Proportioning, p. 20
6.7—Ternary and quaternary mixtures, p. 25

**CHAPTER 7—EFFECTS OF SILICA FUME ON PROPERTIES OF FRESH CONCRETE, p. 25**
7.1—Water demand, p. 25
7.2—Rheology, p. 26
7.3—Workability, p. 27
7.4—Slump loss, p. 27
7.5—Stability, p. 28
7.6—Pumping, p. 28
7.7—Setting time, p. 28
7.8—Plastic shrinkage cracking, p. 29
7.9—Color of concrete, p. 29
7.10—Air entrainment, p. 30
7.11—Bulk density (unit weight) of fresh concrete, p. 30
7.12—Evolution of hydrogen gas, p. 30

**CHAPTER 8—EFFECTS OF SILICA FUME ON PROPERTIES OF HARDENED CONCRETE, p. 30**
8.1—General, p. 30
8.2—Mechanical properties, p. 30
8.3—Durability aspects, p. 35
8.4—Miscellaneous properties, p. 46
8.5—Use of silica fume in combination with fibers, p. 48
8.6—Use of silica fume in ternary blends, p. 49
8.7—Property variations with respect to type, source, and form of delivery of silica fume, p. 53

**CHAPTER 9—WORKING WITH DENSIFIED SILICA FUME IN THE FIELD, p. 54**
9.1—Transporting and handling bulk and bagged densified silica fume, p. 54
9.2—Batching and mixing bulk and bagged silica fume concrete, p. 54
9.3—Placing and consolidating, p. 55
9.4—Finishing, p. 55
9.5—Curing, p. 56

**CHAPTER 10—SPECIFICATIONS AND STANDARDS, p. 56**
10.1—General, p. 56
10.2—Silica fume specification and standards, p. 56
10.3—Specifying silica fume materials, p. 58
10.4—Specifying silica fume blended cement, p. 58
10.5—Specifying silica fume concrete, p. 59

**CHAPTER 11—SUSTAINABILITY WITH SILICA FUME CONCRETE, p. 60**
11.1—Introduction, p. 60
11.2—Embodied energy of the built environment, p. 61
11.3—Embodied energy ($CO_2$) of concrete, p. 63
11.4—Whole building life cycle of concrete (cradle-to-grave), p. 65
11.5—Durability, resilience, and service life, p. 69
11.6—Environmental impact studies with silica fume concrete, p. 70

**CHAPTER 12—APPLICATIONS OF SILICA FUME IN CONCRETE, p. 74**
12.1—Tsing Ma Bridge, Hong Kong, Special Administration Region (SAR) China, p. 74
12.2—311 South Wacker Drive, Chicago, IL, p. 75
12.3—Kuala Lumpur City Center, Kuala Lumpur, Malaysia, p. 75
12.4—Kinzua Dam stilling basin repair, Warren, PA, p. 75
12.5—Stolma Bridge, Austevoll, Norway, p. 77
12.6—Highway bridges, United States, p. 78
12.7—Parking structures, United States, p. 79
12.8—Burj Khalifa, Dubai, United Arab Emirates, p. 80
12.9—East Sea Bridge, Shanghai, China, p. 80
12.10—STEP project, Abu Dhabi, United Arab Emirates, p. 82
12.11—Panama Canal: Third Set of Locks Project, p. 85
12.12—One World Trade Center, New York City, NY, p. 85
12.13—High Rise Towers, Toronto, ON, Canada, p. 85
12.14—The Great Stupa of Dharmakaya, Red Feather Lakes, CO, p. 86
12.15—Trump Hotel and Towers, Chicago, IL , p. 86

**CHAPTER 13—REFERENCES, p. 87**
Authored documents, p. 88

American Concrete Institute – Copyrighted © Material – www.concrete.org

# CHAPTER 1—INTRODUCTION

## 1.1—Introduction

Silica fume, a by-product of the silicon or ferrosilicon industry, is an ultrafine, highly reactive pozzolanic material used to enhance the mechanical and durability properties of concrete. It may be added directly to concrete as a supplementary cementitious material (SCM), combined with other SCMs such as slag cement or fly ash, or included as a constituent in blended cement.

Interest in using silica fume resulted from the strict enforcement of air pollution measures aimed at preventing the release of such materials into the atmosphere. The initial use of silica fume in concrete was primarily for cement replacement, in combination with water-reducing admixtures (WRAs). Eventually, the availability of high-range water-reducing admixtures (HRWRAs, often referred to as superplasticizers) allowed new possibilities for using silica fume to produce high-performance concrete (HPC).

## 1.2—Scope

This guide provides information and guidance on silica fume and its use in concrete. Topics covered include general information on silica fume; its physical and chemical properties; mechanisms by which silica fume modifies cement paste, mortar, and concrete; its performance in plastic and hardened concrete; proportioning; specifications; contributions to concrete sustainability; and examples of silica fume use in various concrete applications.

# CHAPTER 2—NOTATION AND TERMINOLOGY

## 2.1—Notation

$E_c$ = modulus of elasticity of concrete, ksi (GPa)
$f_c'$ = specified compressive strength, psi (MPa)
$f_{cr}'$ = required average strength, psi (MPa)
$f_{c\phi}'$ = load-bearing capacity, ksi (GPa)

## 2.2—Terminology

ACI provides a comprehensive list of definitions through an online resource, "ACI Concrete Terminology." Definitions provided herein complement that resource.

**abrasion-erosion of concrete**—a type of mechanical weathering where concrete is worn away by the friction and impact of particles carried by wind, water, or ice.

**autogenous drying shrinkage (autogenous volume change)**—change in volume due to the chemical process of hydration of cement, exclusive of effects of applied load and change in either thermal condition or moisture content.

**binder or binding materials**—an inorganic material or a mixture of inorganic materials that sets and develops strength by chemical reaction with water by the formation of hydrates and is capable of doing so under water—for example, portland cements and SCMs.

**binder intensity**—the amount of binder (lb/yd$^3$ [kg/m$^3$]) needed to achieve a specific mechanical strength or performance level. Binder intensity is used as an index to evaluate the environmental impact of concrete.

**chloride-ion penetration resistance**—the time-dependent resistance of concrete to penetration of chloride ions that may occur due to several mechanisms, including absorption, permeability, diffusion, and evaporative transport (wick action). It will also be affected by issues such as chloride binding.

**coefficient of permeability to water**—the rate of discharge of water under laminar flow conditions through a unit cross-sectional area of a porous medium under a unit hydraulic gradient and standard temperature conditions, usually 68°F (20°C). The hydraulic gradient or hydraulic pressure per unit thickness is the transport mechanism.

**cradle-to-gate**—corresponding to life cycle modules A1 through A3 according to ISO 21930.

**diffusion coefficient or diffusivity**—the rate at which a diffusing substance is transported between opposite faces of a unit cross section and depth of a porous medium when there is a unit concentration difference between them. Commonly, chloride diffusion rates in saturated concretes are reported. In practice, the chloride gradient occurs between one surface and the interior of the concrete.

**drying shrinkage**—shrinkage resulting from loss of moisture.

**durability**—the ability of a material to resist weathering action, chemical attack, abrasion, and other conditions of service.

**embodied energy**—the total amount of energy required to produce a product or service, including the energy used in extracting and processing raw materials, manufacturing construction materials, transportation and distribution, assembly and construction, and demolition and waste management.

**environmental product declaration (EPD)**—declaration providing environmental data using predetermined parameters meeting the requirements of ISO 21930.

**gas permeability**—the gas pressure gradient across the porous medium.

**global warming potential**—index is used to determine the energy absorption caused by the emissions of different gases associated with a product, normalized to an equivalent mass of carbon dioxide over 100 years.

**life cycle assessment**—compilation and evaluation of a product's input, output, and potential environmental impact throughout its life cycle.

**mineral addition**—inorganic materials, both natural minerals and industrial by-products, that are used in quantities of 5% or more by mass of the cement. Mineral additions may be blended or interground with portland cement or added directly to the concrete before or during mixing (RILEM Technical Committee 73-SBC 1988).

**oversize**—larger non-silica particles or silica fume agglomerates that remain after a silica fume sample is washed through a No. 325 (45 µm) sieve.

**product category rule (PCR)**—set of specific rules, requirements, and guidelines for developing EPDs for one or more product categories.

**resilience**—in a social or ecological system, resilience may include the ability to absorb disturbances while

American Concrete Institute – Copyrighted © Material – www.concrete.org