Manual of Petroleum Measurement Standards Chapter 11.2.4

Temperature Correction for the Volume of NGL and LPG Tables 23E, 24E, 53E, 54E, 59E, and 60E

GPA 8217
SECOND EDITION, JUNE 2019

REAFFIRMED, DECEMBER 2024

American Petroleum Institute

GPA MIDSTREAM ASSOCIATION

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Washington, DC 20001.

Copyright © 2019 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Washington, DC 20001, standards@api.org.

Contents

Page

Nomenclature vii

Implementation Guidelines 1

1 Introduction 1

2 Scope 2

3 Significant Digits 4

4 Comparison to the Previous Standards 4

5 Implementation Procedures 8
5.1 CTL (Table 24E) and Relative Density (Table 23E) for NGL and LPG using a 60 °F Base Temperature . . 8
5.2 CTL (Table 54) and Density (Table 53) for NGL and LPG using a 15 °C Base Temperature 58
5.3 CTL (Table 60E) and Density (Table 59E) for NGL and LPG using a 20 °C Base Temperature. 98

6 Sample Sections of Printed Tables 139

Bibliography 146

Figures
1 *MPMS* 11.2.4 Boundaries 3
2 Flow Chart of Implementation Procedure for Table 24E 11
3 Flow Chart of Implementation Procedure for Table 23E 37
4 Flow Chart of Implementation Procedure for Table 54E 61
5 Flow Chart of Implementation Procedure for Table 53E 82
6 Flow Chart of Implementation Procedure for Table 60E 101
7 Flow Chart of Implementation Procedure for Table 59E 122

Charts
1 C_{TL} Deviations of New Table 24E Values Compared to Old Table 24E Values (0.50 to 0.54 relative density range) 4
2 C_{TL} Deviations of New Table 24E Values Compared to Old Table 24E Values (0.56 to 0.59 relative density range) 5
3 C_{TL} Deviations of New Table 24E Values Compared to Old Table 24E Values (0.60 to 0.64 relative density range) 5
4 C_{TL} Deviations of New Table 24E Values Compared to Old Table 24E Values (0.65 to 0.70 relative density range) 6
5 C_{TL} Deviations of New Table 54E Values Compared to Old Table 54E Values (500 to 540 relative density range) 6
6 C_{TL} Deviations of New Table 54E Values Compared to Old Table 54E Values (550 to 590 relative density range) 7
7 C_{TL} Deviations of New Table 54E Values Compared to Old Table 54E Values (600 to 640 relative density range) 7
8 C_{TL} Deviations of New Table 54E Values Compared to Old Table 54E Values (650 to 680 relative density range) 8

Tables
1 *MPMS* 11.2.4 Correlation Limits 2
2 Reference Fluid Parameters 12

Nomenclature

A, B, C	parameters in Section 5.1.2 quadratic equation
C_{TL}	temperature correction factor
h_2	scaling factor
k_1, k_2, k_3, k_4	parameters in saturation density equation
T_B	base temperature (60 °F, 15 °C, or 20 °C)
T_{BK}	base temperature (288.15 K, or 293.15 K)
T_c	fluid critical temperature (K)
$T_{c,ref}$	reference fluid critical temperature (K)
T_F	observed measurement temperature (°F or °C)
$T_{r,x}$	reduced observed temperature
T_x	observed temperature (K)
V_{60}/V_{Tx}	ratio of volume at 60 °F to volume at temperature T_x. Is the basic definition of C_{TL}
X	interpolating factor
Z_c	critical compressibility factor
α, β, ϕ	parameters in Section 5.1.2 quadratic equation
δ	interpolation variable
τ	parameter in saturation density equation
τ_x	parameter in saturation density equation at observed temperature
γ_x	relative density at observed temperature
$\gamma_{x,high}$	relative density at the observed temperature corresponding to the upper boundary for the 60 °F relative density
$\gamma_{x,low}$	relative density at the observed temperature corresponding to the lower boundary for the 60 °F relative density
$\gamma_{x,mid}$	relative density at the observed temperature corresponding to the intermediate 60° F relative density used in Section 5.1.2 iteration procedure
$\gamma_{x,trial}$	trial relative density at the observed temperature used in Section 5.1.2 iteration procedure
γ_{TB}	relative density at the base temperature, T_B
γ_{60}	relative density at a base temperature of 60 °F
γ_{Tx}	relative density at the observed temperature, T_x
$\gamma_{60,high}$	upper bound for the observed fluid's 60 °F relative density
$\gamma_{60,low}$	lower bound for the observed fluid's 60 °F relative density
$\gamma_{60,mid}$	intermediate 60 °F relative density value used in Section 5.1.2 iteration procedure
$\gamma_{60,trial}$	trial 60 °F relative density value used in Section 5.1.2 iteration procedure
ρ_c	critical molar density (kmol/m^3)
ρ_{60}	density at a base temperature of 60 °F (kg/m^3)
ρ_{15}	density at a base temperature of 15 °C (kg/m^3)
ρ_{20}	density at a base temperature of 20 °C (kg/m^3)
ρ^{sat}	saturation molar density (kmol/m^3)
ρ_{60}^{sat}	saturation molar density at 60 °F (kmol/m^3)
ρ_T^{sat}	saturation molar density at observed temperature (kmol/m^3)
ρ_{w60}	density of water at 60 °F (kg/m^3)

Temperature Correction for the Volume of NGL and LPG Tables 23E, 24E, 53E, 54E, 59E, and 60E

Implementation Guidelines

This revised standard is effective upon the date of publication and supersedes the ASTM-IP 1952 Petroleum Measurement Tables, GPA 2142, GPA TP-16, Tables 33 and 34 of API *MPMS* Chapter 11.1-1980 Volumes XI/XII (Adjuncts to ASTM D1250-80 and IP 200/80), and API/ASTM/GPA TP-27. However, due to the nature of the changes in this revised standard and the fact that it is or may be incorporated by reference in various regulations, it is recognized that guidance concerning an implementation period may be needed in order to avoid disruptions within the industry and ensure proper application. An application, for this purpose, is defined as the point where the calculation is applied.

The actual standard represented by this report consists of the explicit implementation procedures. Sample tables and other examples created from a computerized version of these implementation procedures are presented within. However, these are for examples only and do not represent the standard.

Once the revised standard is implemented in a particular application, the previous standard will no longer be used in that application.

However, the use of API and GPA standards remains voluntary, and the decision on when to use a standard is an issue that is subject to the negotiations between the parties involved in the transaction.

1 Introduction

For custody transfer purposes, natural gas liquid (NGL) and liquefied petroleum gas (LPG) volumes are generally stated at a fixed base temperature and saturation pressure. As most volume transfers occur at temperatures and pressures other than standard conditions, these volumes are adjusted to standard conditions through the use of correction factors. The document is specifically titled as being suitable for NGL and LPG liquids. Light hydrocarbon mixtures containing significant quantities of methane, carbon dioxide and nitrogen which have density ranges which overlap those contained in these tables can be encountered. However, the two-fluid correlation which is the basis of these tables was not calibrated for such mixtures. Separate factors for temperature (C_{TL}) and pressure (C_{PL}) are used to make these corrections. This document presents a new method to calculate temperature correction factors. Pressure correction factors are not within the scope of this document, but can be calculated using American Petroleum Institute *Manual of Petroleum Measurement Standards* (*MPMS*) Chapter 11.1-2004 [1] (which superseded Chapter 11.2.1-1984 [2] and 11.2.1M-1984 [3]), Chapter 11.2.2-1986/GPA 8286-86 [4] or Chapter 11.2.2M-1986/GPA 8286-86 [5], depending on product type.

Previously, most NGL and LPG temperature correction factors have been obtained from a variety of sources:

— ASTM-IP “Petroleum Measurement Tables” [6], published in 1952. This publication is limited to a 60 °F relative density range of 0.500 and higher.

— GPA Standard 2142, “Standard Factors for Volume Correction and Specific Gravity Conversion of Liquefied Petroleum Gases” [7], published in 1957, also contains the same correction factors as the 1982 ASTM-IP document.

— GPA TP-16 “Composite Pressure and Temperature Volume Correction Factor Tables for Liquefied Petroleum Gas (LPG) and Natural Gasoline” [8], published in 1988. It is limited to the following products: HD-5 Propane with relative densities of 0.501, 0.505, and 0.510; iso-butane at a relative density of 0.565; normal butane at a relative density of 0.585; and natural gasoline (12-14 psia RVP) at a relative density of 0.664.

— API *MPMS* Chapter 11.1-1980/ASTM D1250-80 Volume XII, Table 33 “Specific Gravity Reduction to 60 °F For Liquefied Petroleum Gases and Natural Gasoline” [9].