Field Testing Nonaqueous-based Drilling Fluids

API RECOMMENDED PRACTICE 13B-2
SIXTH EDITION, JULY 2023

ADDENDUM 1, APRIL 2025
ERRATA 1, OCTOBER 2025



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Copyright © 2023 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

1 Scope 1
2 Normative References 2
3 Terms and Definitions 2
4 Symbols, Acronyms, and Abbreviations 3
4.1 Symbols 3
4.2 Acronyms and Abbreviations 11
5 Determination of Drilling Fluid Density (Mud Weight) 12
5.1 Principle 12
5.2 Apparatus 12
5.3 Mud Balance Procedure 13
5.4 Calculations 13
6 Determination of Drilling Fluid Density—Pressurized Balance Method 15
6.1 Principle 15
6.2 Apparatus 16
6.3 Pressurized Mud Balance Procedure 16
6.4 Calculation 17
7 Viscosity and Gel Strength 17
7.1 Principle 17
7.2 Determination of Viscosity Using the Marsh Funnel 18
7.3 Determination of Viscosity and Gel Strengths Using a Direct-indicating Viscometer 18
8 Static Filtration 23
8.1 Principle 23
8.2 HTHP Static Filtration, Test up to 175 °C (350 °F) 23
8.3 HTHP Static Filtration Test from 175 °C (350 °F) up to and Including 230 °C (450 °F) 26
9 Retort Test for NAF, Water, and Solids Concentrations 30
9.1 Principle 30
9.2 Apparatus 30
9.3 Procedure—Volumetric Method 32
9.4 Calculation—Volumetric Method 33
9.5 Procedure—Gravimetric Method 34
9.6 Gravimetric Method Calculation—Mass Balance 36
9.7 Gravimetric Method Calculation—Volume Fractions of NAF, Water, and Solids 37
10 Chemical Analysis of NADF 40
10.1 Principle 40
10.2 Reagents and Apparatus 41
10.3 Base Alkalinity Demand (BAD, V_B) 41
10.4 Whole-NADF Alkalinity (V_K) 42
10.5 Whole-NADF Chloride Concentration 44
10.6 Whole-NADF Calcium Concentration 45
11 Electrical Stability Test 47
11.1 Principle 47
11.2 Apparatus 47
11.3 Equipment Calibration/Performance Test 48
11.4 Procedure 48
12 Lime, Salinity, and Solids Calculations 49
12.1 Principle 49
12.2 Apparatus 50

12.3 Whole-NADF Calculations 50
12.4 Aqueous-phase Calculations 53
12.5 Whole-NADF Soluble and Insoluble Sodium Chloride Calculations 58
12.6 Calculation—Solids in the Whole-NADF 60

13 Sand Content 64
13.1 Principle 64
13.2 Apparatus 64
13.3 Procedure 64
13.4 Calculation 65

14 HTHP Filtration Testing of NADF Using the Permeability Plugging Apparatus 65
14.1 Principle 65
14.2 Safety Considerations 66
14.3 Apparatus—PPA 68
14.4 Procedure for HTHP Filtration Test Using the PPA 71
14.5 PPA Test Reports 76

Annex A (informative) **Measurement of Shear Strength Using Shearometer Tube** 78

Annex B (informative) **Determination of Nonaqueous Fluid Retained on Cuttings** 81

Annex C (informative) **Determination of Activity of Emulsified Water Using an Electro-hygrometer** 87

Annex D (informative) **Determination of Aniline-point Temperature of Base Nonaqueous Fluids** 91

Annex E (informative) **Lime, Salinity, and Solids Calculations** 94

Annex F (informative) **Sampling, Inspection, and Rejection of Drilling Materials** 107

Annex G (informative) **Rig-site Sampling** 109

Annex H (informative) **Determination of Cuttings Activity by the Chenevert Method** 112

Annex I (informative) **Chemical Analysis of Active Sulfides by the Garrett Gas Train Method** 116

Annex J (normative) **Calibration and Verification of Glassware, Thermometers, Viscometers, Retort Kit Cup, and Drilling Fluid Balances** 121

Annex K (informative) **Compatibility of Elastomeric Materials with Nonaqueous Drilling Fluids** 128

Annex L (informative) **Identification and Monitoring of Weight-material Sag** 132

Annex M (informative) **Static Heat Aging and Weight-material Sag Testing** 154

Annex N (informative) **Example Nonaqueous-based Drilling Fluid Daily Report** 168

Figures

1 Maximum Concentrations of NaCl in $CaCl_2$ Brine at 25 °C (77 °F) 55
2 Typical Permeability Plugging Apparatus 70
G.1 Side-stream Sampling Device 110
G.2 Sample Scoop 111
L.1 Example of Surface Density Variation with Temperature (NADF) 134
L.2 Example Surface Profile Based on Bottoms-up Data 135
L.3 Downhole Density Changes Measured While Running the Drill String in the Hole 138
L.4 Weight-material Sag Occurrence During Dynamic Conditions 139
L.5 Effect of Changes in Drill Pipe Rotational Speed on Downhole Pressure 140
L.6 ECD Fingerprinting for Three Flow Rates and Four Drill String Rotation Speeds 141
L.7 Distribution of Fluid Viscosity Across the Annular Gap Caused by Drill String Rotation in a Noncirculating Drilling Fluid 143
L.8 Key Equipment for VSST Method 144
L.9 Published "Sag Window" for Drilling Fluids Versus Shear Rate 150
L.10 Predicted Dynamic Sag as a Function of Calculated Values of Wall Shear Stress, τ_{Wi} 153

M.1 Typical Aging Cell with O-ring in Cell Body 155
M.2 Cell after Aging with Free NAF on Top 161
M.3 Alternative Pycnometer: Pressurized Sag Cup 162
M.4 Filling the Retort Cup with Lid with Drilling Fluid 162

Tables

1 Conversion of Density Units 14
2 Density Equivalents 15
3 Recommended Minimum Back-pressure 24
4 Tolerance for Liquid Receiver 31
5 Commonly Used Densities 63
6 Ceramic Discs—API Designation and Mean Pore Throat Diameter 69
7 Recommended Minimum Cell Heat-up Pressure and Back-pressure 74
B.1 Tolerance for Liquid Receiver 82
C.1 Standard Saturated Salt Solutions 88
E.1 Physical and Chemical Properties of Examples of Nonaqueous Drilling Fluids 94
H.1 Saturated Salt Solutions 112
I.1 Dräger H_2S Analysis Tubes 117
I.2 Dräger Tube (or Equivalent) Identification, Sample Volume, and Tube Factors to Be Used for Various Sulfide Concentration Ranges 119
J.1 Density of Water, ρ_W, as a Function of Temperature 123
L.1 Sample Trip-out Sag Reporting Sheet 136
L.2 Matrix for Fingerprinting Drill String Rotation Effects on Downhole Density 141
M.1 Recommended Pressure Aging at High Temperature 158
M.2 Weight-material Sag/Settling Description 161
M.3 Examples of Weight-material Sag Calculations for Different Densities of Drilling Fluid 165

Field Testing Nonaqueous-based Drilling Fluids

1 Scope

This recommended practice provides standard procedures for determining the following characteristics of nonaqueous drilling fluids (NADFs):

a) drilling fluid density (mud weight);

b) viscosity and gel strength;

c) filtration;

d) nonaqueous fluid (NAF), water, and solids concentrations;

e) alkalinity, chloride concentration, and calcium concentration;

f) electrical stability (ES);

g) lime and calcium concentrations, calcium chloride, and sodium chloride concentrations;

h) low-gravity solids and weighting material concentrations;

i) sand content;

j) high-temperature, high-pressure (HTHP) filtration using the permeability plugging apparatus (PPA).

Calibration and verification methods for glassware, thermometers, viscometers, retort kit cups, and drilling fluid balances shall be required for the application of recommended test methods; procedures are provided in Annex J.

Other annexes provide additional test methods or examples that can optionally be used for the determination of the following:

— shear strength (see Annex A);

— NAF retained on cuttings (see Annex B);

— drilling fluid activity (see Annex C);

— aniline point (see Annex D);

— example of lime, salinity, and solids concentration calculations (see Annex E);

— sampling, inspection, and rejection of drilling fluids materials (see Annex F);

— rig-site sampling (see Annex G);

— cuttings activity (see Annex H);

— active sulfides (see Annex I);

— elastomer compatibility with NADF (see Annex K);

— identification and monitoring of weight-material sag (see Annex L);

— NADF daily report form (see Annex N).