Tripping Operations with Surface Back-pressure Managed Pressure Drilling with Surface Blowout Preventer

API RECOMMENDED PRACTICE 79-2
FIRST EDITION, DECEMBER 2025

American Petroleum Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Copyright © 2025 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

Page

1 Scope ... 1

2 Normative References ... 1

3 Terms, Definitions, Acronyms, and Abbreviations ... 1
3.1 Terms and Definitions ... 1
3.2 Acronyms and Abbreviations ... 8

4 Tripping Operations Overview ... 9
4.1 General ... 9
4.2 Tripping Methods ... 9

5 Planning ... 12
5.1 General ... 12
5.2 Risk Assessment ... 13
5.3 Contingency Plans ... 13

6 Equipment ... 13
6.1 General ... 13
6.2 Valves ... 14
6.3 Rotating Control Devices ... 15
6.4 Trip Tanks ... 15
6.5 Mud Buckets ... 15
6.6 Alarms ... 16

7 Volume Management ... 16
7.1 General ... 16
7.2 Drilling Fluid Considerations ... 17
7.3 Fluid Transfers ... 17
7.4 Trip Volume Monitoring ... 18

8 Well Control ... 19
8.1 General ... 19
8.2 Well Barrier Elements ... 19
8.3 Kick Indicators ... 22
8.4 Determination of SBP and Mud Density Values ... 23
8.5 Dynamic Flow Checks and Pressure Buildup ... 23
8.6 Flow Checks ... 24

9 Tripping Operational Guidelines ... 25
9.1 General ... 25
9.2 Training ... 26
9.3 Tripping Operations ... 26

Bibliography ... 29

Contents

Page

Figures

1 Well Barrier Schematic Example 21

Introduction

These guidelines (recommended practices) represent a composite of the practices employed by various operating companies, service companies, and drilling contractors in overbalanced tripping operations. In some cases, a reconciled composite of the various practices employed by these companies was used.

Recommended practices set forth herein are considered acceptable for accomplishing the job as described; however, they do not present all the operational practices that can be employed to accomplish the same objectives. Individuals and organizations using this standard are cautioned that operations must comply with requirements of federal, state, or local regulations. These requirements should be reviewed to determine whether violations can occur.

The objective of these guidelines (recommended practices) within is to assist the oil and gas industry in promoting personnel safety, public safety, wellbore integrity, and preservation of the environment for land drilling operations.

It provides information and guidance on procedures related to tripping activities in overbalanced wells, which have inherent hazards and risks within the operation(s) and therefore require detailed care and attention to improve reliability and reduce risk to acceptable levels. The principles and recommendations have general relevance, regardless of classification, and are applicable to tripping operations with surface blowout preventers (BOPs)

Competent and technical judgment must be used in combination with these recommendations. Each operator, service provider, and drilling contractor involved in tripping operations should review and apply these guidelines (recommended practices) according to their own policies and procedures.

Overbalanced tripping operations are being conducted with full regard for personnel safety, public safety, and preservation of the environment in such diverse conditions as urban sites, wilderness areas, very hot barren deserts, cold weather areas including the arctic environment, and wildlife refuges. As tools and equipment continually improve and develop, technology has been applied in many geologic formations, including oil and gas reservoirs and on sour wells, thus driving the need for globally accepted standards and safe operating best practices.

The purpose of this document is to provide information and to recommend practices and procedures for planning, equipment considerations, and execution of tripping operations in overbalanced wells. It is also intended to assist operators, service providers, and drilling contractors in developing their own internal rig-specific procedures for safe tripping operations.

Tripping Operations with Surface Back-pressure Managed Pressure Drilling with Surface Blowout Preventer

1 Scope

This document provides guidelines for tripping operations with surface back-pressure (SBP) managed pressure drilling in accordance with API 92M. This document applies only to drilling rigs with surface BOPs.

This document does not address operations with service gas (e.g. nitrogen) injection.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document applies (including any addenda/errata).

API Standard 53, *Well Control Equipment Systems for Drilling Wells*

API Recommended Practice 54, *Occupational Safety and Health for Oil and Gas Well Drilling and Servicing Operations*

API Recommended Practice 59, *Recommended Practice for Well Control Operations*

API Recommended Practice 97L, *Onshore Well Construction Interface Document*

3 Terms, Definitions, Acronyms, and Abbreviations

3.1 Terms and Definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1
accumulator
Pressure vessel charged with inert gas and used to store and deliver hydraulic fluid under pressure.

3.1.2
alarm
An audible or visual, or a combination of thereof, indication to the user that equipment malfunction, process deviation, or other abnormal condition requires a prompt response from the user.

3.1.3
alarm flooding
An alarming condition determined by the user, during which the alarm rate is greater than the user's ability to effectively manage.

3.1.4
alarm shelving
The ability for the user to temporarily prevent the audible or visual, or a combination thereof reporting of an active alarm for a period of time.

3.1.5
alarm suppression
The ability for the user to inhibit audible and/or visual reporting of an alarm.