Guidelines for Avoiding Sulfidation (Sulfidic) Corrosion Failures in Oil Refineries

API RECOMMENDED PRACTICE 939-C
SECOND EDITION, JANUARY 2019

REAFFIRMED, OCTOBER 2024



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees makes any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assumes any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this Recommended Practice should consult with the appropriate authorities having jurisdiction.

Users of this Recommended Practice should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

Where applicable, authorities having jurisdiction should be consulted.

Work sites and equipment operations may differ. Users are solely responsible for assessing their specific equipment and premises in determining the appropriateness of applying the Recommended Practice. At all times users should employ sound business, scientific, engineering, and judgment safety when using this Recommended Practice.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Washington, DC 20001.

Copyright © 2019 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Washington, DC 20001, standards@api.org.

Contents

Page

1 Scope . . . 1

2 Normative References . . . 1

3 Terms, Definitions, Abbreviations, and Acronyms . . . 1
3.1 Terms and Definitions . . . 1
3.2 Abbreviations and Acronyms . . . 3

4 Basics of Sulfidation Corrosion . . . 4

5 Location of Sulfidation Corrosion . . . 7

6 Effects of Process and Material Variables on Corrosion Rates . . . 8
6.1 Introduction . . . 8
6.2 H_2-free Sulfidation . . . 8
6.3 H_2/H_2S Corrosion . . . 11

7 Practical Guidelines for Avoiding Sulfidation Corrosion Failures . . . 12
7.1 General . . . 12
7.2 Existing Units and Components . . . 12
7.3 New and Replacement Components . . . 18

8 Limitations of Current Knowledge Base . . . 19

9 Incidents . . . 20

Annex A (informative) Failure Experience Summary . . . 22

Annex B (informative) Sulfidation Corrosion Prediction Tools . . . 24

Annex C (informative) Corrosion Data for Carbon Steel Piping with Higher and Lower Si Contents . . . 36

Annex D (informative) Overview of Sulfidation Corrosion Throughout Refinery Units . . . 40

Annex E (informative) Simplified Inspection Checklist for Refinery Piping and Equipment in Sulfidation Service . . . 44

Bibliography . . . 48

Figures

1 NPS 8 Carbon Steel Piping Failed Due to Sulfidation Corrosion (H_2 Free) . . . 5
2 Corroded Carbon Steel Sight Glass Nipple . . . 5
3 FCC Fractionator Bottoms Carbon Steel Piping Operating at 150 psig (1 MPa) and 650 °F to 700 °F (340 °C to 370 °C) . . . 6
4 FCC Fractionator Bottoms Carbon Steel Piping Shown in Figure 3 Operating at 150 psig (1 MPa) and 650 °F to 700 °F (340 °C to 370 °C) . . . 7
5 Summary of Reported Failures by Type, Number of Reported Instances, and Percentage of the Total . . . 21
B.1 Modified McConomy Curves (0.6 % Sulfur Content) (USC Units) . . . 26
B.2 Modified McConomy Curves (0.6 % Sulfur Content) (SI Units) . . . 26
B.3 Couper-Gorman H_2/H_2S Curves for Carbon Steel for Both Naphtha and Gas Oil . . . 27
B.4 Couper-Gorman H_2/H_2S Curves for 1.25Cr-0.5Mo Steel for Both Naphtha and Gas Oil . . . 28
B.5 Couper-Gorman H_2/H_2S Curves for 2.25Cr-1Mo Steel for Both Naphtha and Gas Oil . . . 29
B.6 Couper-Gorman H_2/H_2S Curves for 5Cr-0.5Mo Steel for Both Naphtha and Gas Oil . . . 30
B.7 Couper-Gorman H_2/H_2S Curves for 7Cr-0.5Mo Steel for Both Naphtha and Gas Oil . . . 31
B.8 Couper-Gorman H_2/H_2S Curves for 9Cr-1Mo Steel for Both Naphtha and Gas Oil . . . 32

Contents

Page

B.9 Couper-Gorman H_2/H_2S Curves for 12Cr Steel (Same for Both Naphtha and Gas Oil) 33
B.10 Couper-Gorman H_2/H_2S Curves for 18Cr 8 Ni Steel (Same for Both Naphtha and Gas Oil) 33
B.11 Corrosion Rate in H_2S/High H_2 Partial Pressure—All Vapor 34
B.12 Corrosion Rate in H_2S/High H_2 Partial Pressure—Liquid Shifted by a Factor of 6 Lower vs Vapor 34
B.13 Corrosion Rate in H_2S/H_2 Vapor—Low H_2 Partial Pressure (High H_2 Partial Pressure—All Vapor Curves Adjusted by Experience) 35
C.1 Corrosion Rate vs Si Content for FCC Slurry Carbon Steel Piping Failure (Shown in Figure 3 and Figure 4) (Operating Conditions: 150 psig and 650 °F to 700 °F). 37
C.2 Corrosion Rate vs Si Content for FCC Slurry Carbon Steel Piping Failure (Shown in Figure 3 and Figure 4) (Operating Conditions: 1 MPa and 340 °C to 370 °C) 38
C.3 Corrosion Rate vs Si Content for Various H_2-free Services (USC Units) 39
C.4 Corrosion Rate vs Si Content for Various H_2-free Services (SI Units) 39

Introduction

Sulfidation corrosion, also often referred to as “sulfidic corrosion,” continues to be a significant cause of leaks in piping and equipment within the refining industry. The objective of this recommended practice (RP) is to provide a better understanding of sulfidation corrosion characteristics and give practical guidance to inspectors and maintenance, reliability, project, operations, and corrosion personnel on how to address sulfidation corrosion in petroleum refining operations. Examples of failures are discussed to highlight the common causes. The methods used to control and inspect for sulfidation corrosion are summarized. The data herein are a compilation of information extracted from published technical papers, industry information exchanges (NACE and API), and contributions from several owner/operators. Some refining companies have developed proprietary methods to predict sulfidation corrosion, and these were not made available as part of this effort.

There are two separate and distinct mechanisms of sulfidation corrosion. One occurs where H_2 is present in addition to the sulfidation-causing sulfur species, as is common in many refining processes, such as hydrotreating and hydrocracking. The other occurs in the absence of H_2 (hydrogen free) in processing units that do not employ H_2 as a component of the process. They both are non-aqueous, diffusion-based corrosion mechanisms that occur at elevated temperature. There is considerable debate in the industry as to the correct threshold temperature for hydrogen-free sulfidation, and in a change in this edition, the API 571 threshold of 500 °F (260 °C) for hydrogen-free services is adopted herein. Experience has shown that little significant corrosion will occur at operating temperatures below 500 °F for hydrogen-ree sulfidation services without the influence of naphthenic acid corrosion.

Common refinery units in which essentially H_2-free sulfidation corrosion can occur are the crude/vacuum, fluid catalytic cracker, coker, and visbreaker units. Hydroprocessing and hydrocracking units can experience H_2-free sulfidation corrosion in their feed sections before the hydrogen is introduced, and in their distillation sections downstream of where the hydrogen is removed. They experience sulfidation in the presence of hydrogen in their reaction sections. This sulfidation in the presence of H_2 is typically referred to as “H_2/H_2S corrosion” and the minimum temperature is 450 °F (230 °C).

Included in this RP are:

— background to damage mechanisms,

— the most common types of damage observed,

— root causes of sulfidation corrosion,

— methods to predict and monitor the corrosivity of systems,

— materials selection for new and revamped processes, and

— inspection and nondestructive examination (NDE) methods used for detecting sulfidation corrosion.

Materials and corrosion specialists should be consulted for additional unit-specific interpretation and application of this recommended practice.

Guidelines for Avoiding Sulfidation (Sulfidic) Corrosion Failures in Oil Refineries

1 Scope

This recommended practice (RP) is applicable to hydrocarbon process streams with sulfur-containing compounds, without the presence of hydrogen (H_2), which operate at temperatures above approximately 500 °F (260 °C) up to about 1000 °F (540 °C). There is considerable debate in the industry as to the correct threshold temperature for H_2-free sulfidation, and in a change in this edition, the API 571 threshold of 500 °F (260 °C) is adopted herein. Experience has shown that little significant corrosion will occur at operating temperatures below 500 °F (260 °C) for H_2-free sulfidation services without the influence of naphthenic acid corrosion. Mercaptan corrosion, particularly in condensate service, has been reported below this temperature but is not explicitly covered in the Second Edition of API 939-C. For H_2-containing services, the threshold temperature is set at 450 °F (230 °C).

A lower threshold limit for sulfur content is not provided because significant corrosion has occurred in the reboiler/fractionator sections of some hydroprocessing units (which do not contain H_2) at measured sulfur or hydrogen sulfide (H_2S) levels as low as 1 ppm.

Corrosion of nickel (Ni) base alloys in hot H_2S environments is excluded from the scope of this document. In addition, while sulfidation can be a problem in some sulfur recovery units, sulfur plant combustion sections and external corrosion of heater tubes due to firing sulfur-containing fuels in heaters are specifically excluded from the scope of this document.

2 Normative References

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any addenda) applies.

API 570, *Piping Inspection Code: In-service Inspection, Rating, Repair, and Alteration of Piping Systems*

API Recommended Practice 571, *Damage Mechanisms Affecting Fixed Equipment in the Refining Industry*

API Recommended Practice 578, *Guidelines for a Material Verification Program (MVP) for New and Existing Assets*

API 579-1/ASME [1] FFS-1, *Fitness-For-Service*, June 2007, Second Edition

API Recommended Practice 584, *Integrity Operating Windows*

ASME SA-516, *Specification for Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service*

ASTM A106/A106M [2], *Standard Specification for Seamless Carbon Steel Pipe for High-Temperature Service*

3 Terms, Definitions, Abbreviations, and Acronyms

3.1 Terms and Definitions

For the purpose of this document, the following terms and definitions apply.

[1] ASME International, 2 Park Avenue, New York, New York, 10016, www.asme.org.
[2] ASTM International, 100 Barr Harbor Drive, West Conshohocken, Pennsylvania 19428, www.astm.org.