Installation, Maintenance, and Repair of Safety Valves (SSV, USV, and BSDV)

API STANDARD 6AV2
SECOND EDITION, AUGUST 2020

REAFFIRMED, OCTOBER 2026



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this specification should consult with the appropriate authorities having jurisdiction.

Users of this standard should not rely exclusively on the information contained in this standard. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein. API is not undertaking to meet the duties of employers, service providers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the service provider or supplier of that material, or the material safety datasheet.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Copyright © 2020 American Petroleum Institute

Foreword

This standard is under the jurisdiction of the API Subcommittee on Valves and Wellhead Equipment.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this specification are as follows:

— the term “shall” denotes a minimum requirement to conform to the standard;

— the term “should” denotes a recommendation or that which is advised but not required to conform to the standard;

— the term “may” is used to express permission or a provision that is optional;

— the term “can” is used to express possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington DC 2001.

This standard shall become effective on the date printed on the cover.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington DC 2001, standards@api.org.

Contents

Page

1 Scope 1

2 Normative References 1

3 Terms, Definitions, Acronyms, and Abbreviations 1
3.1 Terms and Definitions 1
3.2 Acronyms and Abbreviations 2

4 Receiving Inspection 3

5 Installation, Maintenance, and Testing 3
5.1 General 3
5.2 Work Procedures 3
5.3 Installation 4
5.4 Testing 4
5.5 Maintenance 4

6 Repair and Remanufacture 5
6.1 Field Repair of Safety Valves 5
6.2 Off-site Repair/Remanufacture of Safety Valve 6

7 Testing Procedures 8
7.1 General 8
7.2 Periodic Operating/Pressure Holding Test 8
7.3 Testing After Installation/Field Repairs 10

8 Failure Reporting 12
8.1 General 12
8.2 Failure Report 12
8.3 Reporting Responsibilities 13

9 Documentation Requirements 13

Annex A (informative) Pressure Buildup Calculation 16

Bibliography 26

Figures

1 Safety Valve Field Repair Record Sheet 6
2 Safety Valve Functional Test Datasheet for Installation/Field Repairs 7
3 Safety Valve Functional Test Datasheet for Periodic Testing 10
4 Failure Checklist for Surface Safety Valves and Underwater Safety Valves 15
A.1 Calculation Flow Diagram 18

Contents

Page

Tables

A.1 Nomenclature 17

Introduction

The safety valve is a valve assembly that closes on loss of power supply. System architecture and power/control systems for safety valves are addressed in safety system documents such as API 14C.

The surface safety valve (SSV) or underwater safety valve (USV) is typically the second valve in the flow stream of the wellhead and tree. For an offshore surface facility, the boarding shutdown valve (BSDV) is typically the second valve in the flow stream, between an underwater production system and surface facility.

This edition of API 6AV2 contains the following major changes from prior editions:

— Changed the title of the standard to include boarding shutdown valves, which is a new type of safety valve in API 6A, 21st Edition.

— The term “safety valve” replaced “SSV” and “USV” throughout the document. This term now includes SSV, USV, and BSDV.

— The requirements for off-site repair of safety valves now refer to API 6AR.

— Test and possible repair of the safety valve is addressed. Complete system operation to meet operator and possible regulatory requirements is not specified.

— Requirements for establishment of product definition by service provider were added.

— The term “original product definition” and associated requirements were removed.

Installation, Maintenance, and Repair of Safety Valves (SSV, USV and BSDV)

1 Scope

This standard provides requirements for installing and maintaining safety valves. Included are requirements for receiving inspection, installation, and maintenance, field and off-site repair, testing procedures with acceptance criteria, failure reporting, and documentation. Power and control systems for safety valves are not included.

NOTE 1 "Safety valve" as used in this standard denotes a surface safety valve (SSV), an underwater safety valve (USV), or a boarding shutdown valve (BSDV).

NOTE 2 Testing the safety shutdown system and test frequency are outside the scope of this Standard.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Specification 6A, *Specification for Wellhead and Tree Equipment*

API Standard 6AR, *Repair and Remanufacture of Wellhead and Tree Equipment*

API Standard 18LCM (2017), *Product Life Cycle Management System Requirements for the Petroleum and Natural Gas Industries.*

3 Terms, Definitions, Acronyms, and Abbreviations

3.1 Terms and Definitions

For the purposes of this standard, the terms and definitions given in API 6A and the following shall apply.

3.1.1
choked flow
Flow condition in which the fluid velocity and mass-flow rate are insensitive to the pressure drop across the flow restriction and no phase change occurs.

NOTE Choked flow occurs when the ratio of downstream pressure to upstream pressure is lower than the critical pressure ratio.

3.1.2
critical pressure ratio
Ratio of pressure downstream of the flow restriction to pressure upstream of the flow restriction below which choked flow occurs.

3.1.3
direct measurement device
Instrument/equipment whose output is the measurement of flow rate (leakage) across the pressure-controlling components of the safety valves.

3.1.4
indirect measurement method
Use of equipment whose output is the measurement of one or more thermodynamic properties of the fluid moving across the safety valves, and the methodology used to convert the measured quantities into the equivalent flow rate (leakage) across the pressure-controlling components of the safety valves.