AS ISO/IEC 14443.2:2022
ISO/IEC 14443-2:2020
ISO/IEC 14443-2:2020/Amd 1:2021
ISO/IEC 14443-2:2020/Cor 1:2021

Australian STANDARD®

STANDARDS Australia

Cards and security devices for personal identification — Contactless proximity objects

Part 2: Radio frequency power and signal interface



AS ISO/IEC 14443.2:2022

This Australian Standard ® was prepared by IT-017, Cards and security devices for personal identification. It was approved on behalf of the Council of Standards Australia on 7 June 2022.

This Standard was published on 24 June 2022.

The following are represented on Committee IT-017:

Australia Post
Australian Hotels Association
Australian Industry Group
Australian Passport Office
Australian Security Industry Association
Department of Home Affairs — Identity and Biometrics Division
Department of Transport and Main Roads, QLD

This Standard was issued in draft form for comment as DR AS ISO/IEC 14443.2:2022.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:
www.standards.org.au

ISBN 978 1 76113 855 3

AS ISO/IEC 14443.2:2022
ISO/IEC 14443-2:2020
ISO/IEC 14443-2:2020/Amd 1:2021
ISO/IEC 14443-2:2020/Cor 1:2021

Cards and security devices for personal identification — Contactless proximity objects

Part 2: Radio frequency power and signal interface

Originated as AS 14443.2—2003.
Second edition 2022.

COPYRIGHT

© ISO/IEC 2022 — All rights reserved
© Standards Australia Limited 2022

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee IT-017, Cards and security devices for personal identification, to supersede AS 14443.2:2003, *Identification cards — Contactless integrated circuit(s) cards — Proximity cards, Part 2: Radio frequency power and signal interface.*

The objective of this document is to specify the characteristics of the fields to be provided for power and bi-directional communication between proximity coupling devices (PCDs) and proximity cards or objects (PICCs).

This document does not specify the means of generating coupling fields, nor the means of compliance with electromagnetic radiation and human exposure regulations, which can vary depending on the country.

This document is identical with, and has been reproduced from, ISO/IEC 14443-2:2020, *Cards and security devices for personal identification — Contactless proximity objects — Part 2: Radio frequency power and signal interface* and its Amendment No. 1 (2021) and Corrigendum No. 1 (2021) which have been added at the end of the source text.

As this document has been reproduced from an International document, a full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

© Standards Australia Limited 2022

Contents

Preface ii
Foreword v
Introduction vi
1 Scope 1
2 Normative references 1
3 Terms and definitions 1
4 Symbols and abbreviated terms 2
5 General considerations 5
5.1 Initial dialogue 5
5.2 Compliance 5
5.2.1 PICC compliance 5
5.2.2 PCD compliance 5
6 Power transfer 6
6.1 General 6
6.2 Frequency 6
6.3 Operating field strength 6
7 Signal interface 7
8 Communication signal interface Type A 9
8.1 Communication PCD to PICC 9
8.1.1 Bit rate 9
8.1.2 Modulation 9
8.1.3 Bit representation and coding 18
8.2 Communication PICC to PCD 23
8.2.1 Bit rate 23
8.2.2 PICC load modulation transmission 23
8.2.3 Subcarrier 28
8.2.4 Subcarrier modulation 28
8.2.5 PCD load modulation reception 29
8.2.6 Bit representation and coding 32
9 Communication signal interface Type B 34
9.1 Communication PCD to PICC 34
9.1.1 Bit rate 34
9.1.2 Modulation for bit rates of $f_c/128$, $f_c/64$, $f_c/32$, $f_c/16$, $f_c/8$, $f_c/4$, and $f_c/2$ 34
9.1.3 Bit representation and coding 43
9.2 Communication PICC to PCD 44
9.2.1 Bit rate 44
9.2.2 PICC load modulation transmission 44
9.2.3 Subcarrier 44
9.2.4 Subcarrier modulation 44
9.2.5 PCD load modulation reception 44
9.2.6 Bit representation and coding 44
10 Electromagnetic disturbance levels 44
10.1 PCD limits 44
10.2 PICC limits 45
Annex A (informative) **Complex envelope and constellation diagram** 46
Annex B (informative) **Inter symbol interference** 47
Bibliography 49
Amendment 1 50

Corrigendum 1 ..... **52**

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see http://patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Cards and security devices for personal identification*.

This fourth edition cancels and replaces the third edition (ISO/IEC 14443-2:2016), which has been technically revised.

The main changes compared to the previous edition are as follows:

— amendment of active and passive PICC transmissions;

— amendment of electromagnetic disturbance levels for all PICC classes.

A list of all parts in the ISO/IEC 14443 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user’s national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© Standards Australia Limited 2022

Introduction

ISO/IEC 14443 (all parts) is one of a group of International Standards describing the parameters for identification cards as defined in ISO/IEC 7810 and the use of such cards for international interchange.

This document describes the electrical characteristics of two types of contactless interface between a proximity card and a proximity coupling device. The interface includes both power and bi-directional communication. It is intended to be used in conjunction with other parts of the ISO/IEC 14443 series.

Contactless card standards cover a variety of types as embodied in ISO/IEC 10536 (all parts) (close-coupled cards), ISO/IEC 14443 (all parts) (proximity cards), and ISO/IEC 15693 (all parts) (vicinity cards). These are intended for operation when very near, nearby and at a longer distance from associated coupling devices, respectively.

© Standards Australia Limited 2022

Australian Standard®

Cards and security devices for personal identification — Contactless proximity objects

Part 2: Radio frequency power and signal interface

1 Scope

This document specifies the characteristics of the fields to be provided for power and bi-directional communication between proximity coupling devices (PCDs) and proximity cards or objects (PICCs).

This document does not specify the means of generating coupling fields, nor the means of compliance with electromagnetic radiation and human exposure regulations, which can vary depending on the country.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 10373-6, *Cards and security devices for personal identification — Test methods — Part 6: Contactless proximity objects*

ISO/IEC 14443-1:2018, *Cards and security devices for personal identification — Contactless proximity objects — Part 1: Physical characteristics*

ISO/IEC 14443-3:2018, *Cards and security devices for personal identification — Contactless proximity objects — Part 3: Initialization and anticollision*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

3.1
bit duration
time during which a logic level is defined, at the end of which a new bit starts

3.2
BPSK
phase shift keying where the phase shift is 180°, resulting in two phase state possibilities

3.3
modified Miller
method of bit coding whereby a logic level during a *bit duration* (3.1) is represented by the position of a pulse within the bit frame

© Standards Australia Limited 2022