ASME B30.10-2024
(Revision of ASME B30.10-2019)

Hooks

Safety Standard for Cableways, Cranes, Derricks, Hoists, Hooks, Jacks, and Slings

AN AMERICAN NATIONAL STANDARD

The American Society of Mechanical Engineers

ASME B30.10-2024
(Revision of ASME B30.10-2019)

Hooks

Safety Standard for Cableways, Cranes, Derricks, Hoists, Hooks, Jacks, and Slings

AN AMERICAN NATIONAL STANDARD

The American Society of Mechanical Engineers
Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: January 10, 2025

The next edition of this Standard is scheduled for publication in 2029. This Standard will become effective 1 year after the Date of Issuance.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The standards committee that approved the code or standard was balanced to ensure that individuals from competent and concerned interests had an opportunity to participate. The proposed code or standard was made available for public review and comment, which provided an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "certify," "rate," or "endorse" any item, construction, proprietary device, or activity. ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor does ASME assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representatives or persons affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

The endnotes and preamble in this document (if any) are part of this American National Standard.



ASME Collective Membership Mark

All rights reserved. "ASME" and the above ASME symbol are registered trademarks of The American Society of Mechanical Engineers. No part of this document may be copied, modified, distributed, published, displayed, or otherwise reproduced in any form or by any means, electronic, digital, or mechanical, now known or hereafter invented, without the express written permission of ASME. No works derived from this document or any content therein may be created without the express written permission of ASME. Using this document or any content therein to train, create, or improve any artificial intelligence and/or machine learning platform, system, application, model, or algorithm is strictly prohibited.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2025 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
Printed in U.S.A.

CONTENTS

Foreword v

Committee Roster vii

Correspondence With the B30 Committee ix

B30 Standard Introduction x

Summary of Changes xii

Chapter 10-0 **Scope, Definitions, References, Personnel Competence, and Translations** 1

Section 10-0.1 Scope of ASME B30.10 1

Section 10-0.2 Definitions 1

Section 10-0.3 References 1

Section 10-0.4 Personnel Competence 2

Section 10-0.5 Translations 2

Chapter 10-1 **Hooks: Selection, Use, and Maintenance** 3

Section 10-1.1 Scope 3

Section 10-1.2 Training 3

Section 10-1.3 Materials and Components 3

Section 10-1.4 Fabrication and Configurations 3

Section 10-1.5 Design Factor 3

Section 10-1.6 Rated Loads 3

Section 10-1.7 Proof Test Requirements 3

Section 10-1.8 Identification 4

Section 10-1.9 Effects of Environment 4

Section 10-1.10 Inspection, Removal, and Repair 4

Section 10-1.11 Operating Practices 6

Chapter 10-2 **Hooks — Miscellaneous: Selection, Use, and Maintenance** 10

Section 10-2.1 Scope 10

Section 10-2.2 Training 10

Section 10-2.3 Materials and Components 10

Section 10-2.4 Fabrication and Configurations 10

Section 10-2.5 Design Factor 10

Section 10-2.6 Rated Loads 10

Section 10-2.7 Proof Test Requirements 10

Section 10-2.8 Identification 10

Section 10-2.9 Effects of Environment 10

Section 10-2.10 Inspection, Removal, and Repair 11

Section 10-2.11 Operating Practices 12

Figures

10-1.1-1	Clevis Hook (Latch — When Required)	7
10-1.1-2	Eye Hook (Latch — When Required)	7
10-1.1-3	Shank Hook (Latch — When Required)	7
10-1.1-4	Duplex Hook (Sister) (Latch — When Required)	7
10-1.1-5	Articulated Duplex Hook (Sister) (Latch — When Required)	7
10-1.1-6	Self-Locking Eye Hook (Open)	8
10-1.1-7	Self-Locking Clevis Hook (Closed)	8
10-1.1-8	Self-Closing Bail (Eye Hook)	8
10-1.1-9	Self-Closing Gate Latch (Shank Hook)	8
10-1.1-10	Self-Closing Flapper Latch (Shank Hook)	8
10-1.1-11	Self-Closing Flapper Latch (Swivel Hook)	8
10-1.1-12	Self-Closing Flipper Latch (Eye Hook)	9
10-1.1-13	Self-Closing Tiplock Latch (Shank Hook)	9
10-1.1-14	Self-Closing Tiplock Latch (Eye Hook)	9
10-1.1-15	Single Plate Hook	9
10-1.1-16	Laminated Plate Hook	9
10-1.1-17	Quad Hook (Latch — When Required)	9
10-2.1-1	Eye Grab Hook	12
10-2.1-2	Clevis Grab Hook	12
10-2.1-3	Foundry Hook	13
10-2.1-4	Sorting Hook	13
10-2.1-5	Choker Hook	13
10-2.1-6	Clevis Foundry Hook	13

Table

10-1.7-1	Proof Test Load	4

FOREWORD

This American National Standard, Safety Standard for Cableways, Cranes, Derricks, Hoists, Hooks, Jacks, and Slings, has been developed under the procedures accredited by the American National Standards Institute (ANSI). This Standard had its beginning in December 1916, when an eight-page Code of Safety Standards for Cranes, prepared by the American Society of Mechanical Engineers (ASME) Committee on the Protection of Industrial Workers, was presented at the annual meeting of ASME.

Meetings and discussions regarding safety on cranes, derricks, and hoists were held from 1920 to 1925 involving the ASME Safety Code Correlating Committee, the Association of Iron and Steel Electrical Engineers, the American Museum of Safety, the American Engineering Standards Committee (AESC) [later changed to American Standards Association (ASA), then to the United States of America Standards Institute (USASI), and finally to ANSI], Department of Labor — State of New Jersey, Department of Labor and Industry — State of Pennsylvania, and the Locomotive Crane Manufacturers Association. On June 11, 1925, the AESC approved the ASME Safety Code Correlating Committee's recommendation and authorized the project with the U.S. Department of the Navy, Bureau of Yards and Docks, and ASME as sponsors.

In March 1926, invitations were issued to 50 organizations to appoint representatives to a Sectional Committee. The call for organization of this Sectional Committee was sent out October 2, 1926, and the Committee was organized on November 4, 1926, with 57 members representing 29 national organizations.

Commencing June 1, 1927, and using the eight-page Code published by ASME in 1916 as a basis, the Sectional Committee developed the Safety Code for Cranes, Derricks, and Hoists. The early drafts of this safety code included requirements for jacks, but, due to inputs and comments on those drafts, the Sectional Committee decided in 1938 to make the requirements for jacks a separate code. In January 1943, ASA B30.2-1943 was published addressing a multitude of equipment types, and in August 1943, ASA B30.1-1943 was published addressing only jacks. Both documents were reaffirmed in 1952 and widely accepted as safety standards.

Due to changes in design, advancement in techniques, and general interest of labor and industry in safety, the Sectional Committee, under the joint sponsorship of ASME and the Bureau of Yards and Docks (now the Naval Facilities Engineering Command), was reorganized on January 31, 1962, with 39 members representing 27 national organizations. The new Committee changed the format of ASA B30.2-1943 so that the multitude of equipment types it addressed could be published in separate volumes that could completely cover the construction, installation, inspection, testing, maintenance, and operation of each type of equipment that was included in the scope of ASA B30.2. This format change resulted in B30.3, B30.5, B30.6, B30.11, and B30.16 being designated as revisions of B30.2 with the remainder of the B30 volumes being published as totally new volumes. ASA changed its name to USASI in 1966 and to ANSI in 1969, which resulted in B30 volumes from 1943 to 1968 being designated as either ASA B30, USAS B30, or ANSI B30, depending on their date of publication.

In 1982, the Committee was reorganized as an Accredited Organization Committee operating under procedures developed by ASME and accredited by ANSI. This Standard presents a coordinated set of rules that may serve as a guide to government and other regulatory bodies and municipal authorities responsible for the guarding and inspection of the equipment falling within its scope. The suggestions leading to accident prevention are given both as mandatory and advisory provisions; compliance with both types may be required by employers of their employees.

In case of practical difficulties, new developments, or unnecessary hardship, the administrative or regulatory authority may grant variances from the literal requirements or permit the use of other devices or methods but only when it is clearly evident that an equivalent degree of protection is thereby secured. To secure uniform application and interpretation of this Standard, administrative or regulatory authorities are urged to consult the B30 Committee, in accordance with the format described on the Correspondence With the B30 Committee page, before rendering decisions on disputed points.

Safety codes and standards are intended to enhance public safety. Revisions result from committee consideration of factors such as technological advances, new data, and changing environmental and industry needs. Revisions do not imply that previous editions were inadequate.

The 2009 edition of B30.10 was rewritten entirely to improve the clarity of the Standard. The 2014 edition incorporated many global B30 changes, including the addition of personnel competence and translation requirements, as well as other revisions made throughout the document. The 2019 edition contained updates to definitions. The 2024 edition contains updates to hook identification.

This Volume of the Standard was approved by the B30 Committee and ASME, and was approved by ANSI and designated as an American National Standard on October 31, 2024.

ASME B30 COMMITTEE
Safety Standard for Cableways, Cranes, Derricks, Hoists, Hooks, Jacks, and Slings

(The following is the roster of the committee at the time of approval of this Standard.)

STANDARDS COMMITTEE OFFICERS

E. D. Fidler, *Chair*
T. Sicklesteel, *Vice Chair*
S. D. Wood, *Vice Chair*
K. Peterson, *Secretary*

STANDARDS COMMITTEE PERSONNEL

N. E. Andrew, Neil E. Andrew & Associates, LLC
B. B. Bacon, Tennessee Valley Authority
T. L. Blanton, OGR Consulting Services, LLC
P. A. Boeckman, The Crosby Group, LLC
J. R. Burkey, Columbus McKinnon Corp.
J. A. Danielson, The Boeing Co.
D. R. Decker, Becket Training & Consulting, Inc.
L. D. Demark, Sr., Equipment Training Solutions, LLC
D. W. Eckstine, Eckstine and Associates, Inc.
E. D. Fidler, Grove U.S., LLC
M. Gardiner, ICC Forensics, LLC
J. A. Gilbert, JAGwire Management, LLC
D. A. Henninger, Bridon Bekaert, The Ropes Group
M. M. Jaxtheimer, Navy Crane Center
T. W. Klein, Wireco
R. M. Kohner, Landmark Engineering Services
A. J. Lusi, Jr., LuMark Consulting, LLP
T. C. Mackey, HiLine Engineering & Fabrication, Inc.
J. P. Mihlbauer, All Ship & Cargo Surveys, Ltd.
R. M. Parnell, Industrial Training International, Inc.
J. T. Perkins, All Material Handling
K. Peterson, The American Society of Mechanical Engineers
B. A. Pickett, Systems Engineering and Forensic Services
J. A. Pilgrim, Manitowoc Cranes
S. K. Rammelsberg, CB&I Storage Solutions
J. M. Randall, J. E. Spear Consulting, LP
K. Rask, NationsBuilders Insurance Services, Inc.
K. Reynolds, Shell Exploration & Production
C. L. Richardson, Lone Star Rigging, LP
J. E. Richardson, Navy Crane Center
J. W. Rowland III, Consultant
A. R. Ruud, Atkinson Construction
L. K. Shapiro, Howard I. Shapiro & Associates Consulting Engineers, PC
T. Sicklesteel, National Commission for the Certification of Crane Operators, Inc.
C. H. Smith, Morrow Equipment Co., LLC
D. W. Smith, J. E. Spear Consulting, LP
W. J. Smith, Jr., NationsBuilder Insurance Services, Inc.
R. S. Stemp, Lampson International, LLC
R. G. Strain, Advanced Crane Technologies, LLC
J. Sturm, Sturm Corp.
D. Sullivan, IUOE Local 542 JATC
P. A. Vallejos, Hanford Mission Integration Solutions, LLC
C. Warren, Webber, LLC
J. D. Wiethorn, International Crane & Construction Safety Solutions, LLC
S. D. Wood, Terex Corp.
D. Boyle, *Alternate*, The Crosby Group, LLC
M. Chaudanson, *Alternate*, Howard I. Shapiro & Associates Consulting Engineers, PC
P. B. Debuigne, *Alternate*, Blue Origin
D. Duerr, *Alternate*, 2DM Associates, Inc.
M. Eckstine, *Alternate*, Eckstine and Associates, Inc.
D. Frerking, *Alternate*, XCMG American Research Corp.
T. Gordon, *Alternate*, International Union of Operating Engineers Local 14-14b
J. B. Greenwood, *Alternate*, Navy Crane Center
D. F. Jordan, *Alternate*, American International Crane Bureau, LLC
L. D. Means, *Alternate*, Means Engineering and Consulting
W. J. Merrill, *Alternate*, Merrill Safety Solutions, LLC
G. D. Miller, *Alternate*, Manitowoc Cranes
D. A. Moore, *Alternate*, Unified Engineering, LP
P. Quick, *Alternate*, Affiliated Engineering Laboratories, Inc.
G. M. Ray, *Alternate*, Tennessee Valley Authority
M. Riggs, *Alternate*, Riggsafe Solutions, Inc.
S. Santee, *Alternate*, Navy Crane Center
J. R. Schober, *Alternate*, American Bridge Co.
J. E. Spear, *Alternate*, J. E. Spear Consulting, LP
J. A. Stewart, *Alternate*, Stewart Safety Consulting
A. Thompson, *Alternate*, Wireco Worldgroup, Inc.
W. Tubbs, *Alternate*, Craneology, Inc.
J. J. Van Egeren, *Alternate*, Manitowoc Cranes
M. P. Zerba, *Alternate*, Lampson International, LLC
J. W. Downs, Jr., *Honorary Member*, Downs Crane & Hoist Co., Inc.
J. L. Franks, *Honorary Member*, Consultant
C. W. Ireland, *Honorary Member*, Consultant
J. M. Klibert, *Honorary Member*, Lift-All Co., Inc.
J. C. Ryan, *Honorary Member*, Boh Bros. Construction Co., LLC

B30.10 SUBCOMMITTEE PERSONNEL

D. Boyle, *Chair*, The Crosby Group, LLC
T. Cobb, Columbus McKinnon Forge Operations Chattanooga
J. A. Gilbert, JAGwire Management, LLC
P. S. Hughes, MAGNA Lifting
B. M. Kozickie, Peerless Chain Co.
A. L. Langer, Manitowoc Cranes
D. Lundy, U.S. Army Corps of Engineers
E. K. Marburg, Columbus McKinnon Corp.
R. Marcotte, Bruce Power, LP
C. Vencl, Kito Crosby
J. Wellwood, NAC International
P. A. Boeckman, The Crosby Group, LLC
T. Raines, Jr., CMCO

B30 INTEREST REVIEW GROUP

O. Akinboboye, Ropetech Engineering Services, Ltd.
B. Dobbs, Lifting Equipment Engineers Association
J. Edmundson, Konecranes Nuclear Equipment & Services, LLC
M. J. Eggenberger, Berry Contracting, Inc.
Y. T. Fathy Elhola, Axess Group
D. Ferland, AMECO
A. Gomes Rocha, Industrial Training International
J. Groce, Wireco Worldgroup, Inc.
N. C. Hargreaves, Hargreaves Consulting, LLC
J. Hui, School of Civil Engineering, People's Republic of China
D. Mabelane, The South African Nuclear Energy Corp.
A. Mattoli, Prowinch, LLC
T. McCullough, Allegiance Crane & Equipment
D. Modzeleski, Dematic Corp.
C. Neth, Neth Engineering, PLLC
A. Payne, Bureau of Safety and Environmental Enforcement

B30 REGULATORY AUTHORITY COUNCIL

C. N. Stribling, Jr., *Chair*, Kentucky Labor Department of Cabinet
K. Peterson, *Secretary*, The American Society of Mechanical Engineers
R. D. Jackson, U.S. Department of Labor
D. E. Latham, State of Maryland Department of Labor, Licensing, and Regulation
M. J. Nelmida, State of California, Occupational Safety and Health Standards Board
S. Sumeshwar, State of California, Occupational Safety and Health Standards Board
T. Taylor, North Carolina Department of Labor
N. Reynolds, *Alternate,* Maryland Occupational Safety and Health (MOSH)

CORRESPONDENCE WITH THE B30 COMMITTEE (24)

General. ASME codes and standards are developed and maintained by committees with the intent to represent the consensus of concerned interests. Users of ASME codes and standards may correspond with the committees to propose revisions or cases, report errata, or request interpretations. Correspondence for this Standard should be sent to the staff secretary noted on the committee's web page, accessible at https://go.asme.org/B30committee.

Revisions and Errata. The committee processes revisions to this Standard on a continuous basis to incorporate changes that appear necessary or desirable as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published in the next edition of the Standard.

In addition, the committee may post errata on the committee web page. Errata become effective on the date posted. Users can register on the committee web page to receive email notifications of posted errata.

This Standard is always open for comment, and the committee welcomes proposals for revisions. Such proposals should be as specific as possible, citing the paragraph number, the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent background information and supporting documentation.

Cases. The committee does not issue cases for this Standard.

Interpretations. Upon request, the committee will issue an interpretation of any requirement of this Standard. An interpretation can be issued only in response to a request submitted through the online Inquiry Submittal Form at https://go.asme.org/InterpretationRequest. Upon submitting the form, the inquirer will receive an automatic email confirming receipt.

ASME does not act as a consultant for specific engineering problems or for the general application or understanding of the Standard requirements. If, based on the information submitted, it is the opinion of the committee that the inquirer should seek assistance, the request will be returned with the recommendation that such assistance be obtained. Inquirers can track the status of their requests at https://go.asme.org/Interpretations.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME committee or subcommittee. ASME does not "approve," "certify," "rate," or "endorse" any item, construction, proprietary device, or activity.

Interpretations are published in the ASME Interpretations Database at https://go.asme.org/Interpretations as they are issued.

Committee Meetings. The B30 Standards Committee regularly holds meetings that are open to the public. Persons wishing to attend any meeting should contact the secretary of the committee. Information on future committee meetings can be found on the committee web page at https://go.asme.org/B30committee.

(24)

B30 STANDARD INTRODUCTION

SECTION I: SCOPE

The ASME B30 Standard contains provisions that apply to the construction, installation, operation, inspection, testing, maintenance, and use of cranes and other lifting and material-movement-related equipment. For the convenience of the reader, the Standard has been divided into separate volumes. Each volume has been written under the direction of the ASME B30 Standards Committee and has successfully completed a consensus approval process under the general auspices of the American National Standards Institute (ANSI).

As of the date of issuance of this Volume, the B30 Standard comprises the following volumes:

B30.1 Jacks, Industrial Rollers, Air Casters, and Hydraulic Gantries

B30.2 Overhead and Gantry Cranes (Top Running Bridge, Single or Multiple Girder, Top Running Trolley Hoist)

B30.3 Tower Cranes

B30.4 Portal and Pedestal Cranes

B30.5 Mobile and Locomotive Cranes

B30.6 Derricks

B30.7 Winches

B30.8 Floating Cranes and Floating Derricks

B30.9 Slings

B30.10 Hooks

B30.11 Monorails and Underhung Cranes (withdrawn 2018 — requirements found in latest revision of B30.17)

B30.12 Handling Loads Suspended From Rotorcraft

B30.13 Storage/Retrieval (S/R) Machines and Associated Equipment

B30.14 Side Boom and Rotating Pipelayers

B30.15 Mobile Hydraulic Cranes (withdrawn 1982 — requirements found in latest revision of B30.5)

B30.16 Overhead Underhung and Stationary Hoists

B30.17 Cranes and Monorails (With Underhung Trolley or Bridge)

B30.18 Stacker Cranes (Top or Under Running Bridge, Multiple Girder With Top or Under Running Trolley Hoist)

B30.19 Cableways

B30.20 Below-the-Hook Lifting Devices

B30.21 Lever Hoists

B30.22 Articulating Boom Cranes

B30.23 Personnel Lifting Systems

B30.24 Container Cranes

B30.25 Scrap and Material Handlers

B30.26 Rigging Hardware

B30.27 Material Placement Systems

B30.28 Balance Lifting Units

B30.29 Self-Erecting Tower Cranes

B30.30 Ropes

B30.31 Self-Propelled, Towed, or Remote-Controlled Hydraulic Platform Transporters[1]

B30.32 Unmanned Aircraft Systems (UAS) Used in Inspection, Testing, Maintenance, and Load-Handling Operations

SECTION II: SCOPE EXCLUSIONS

Any exclusion of, or limitations applicable to, the equipment, requirements, recommendations, or operations contained in this Standard are established in the affected volume's scope.

SECTION III: PURPOSE

The B30 Standard is intended to

(a) prevent or minimize injury to workers, and otherwise provide for the protection of life, limb, and property by prescribing safety requirements

(b) provide direction to manufacturers, owners, employers, users, and others concerned with, or responsible for, its application

(c) guide governments and other regulatory bodies in the development, promulgation, and enforcement of appropriate safety directives

SECTION IV: USE BY REGULATORY AGENCIES

These volumes may be adopted in whole or in part for governmental or regulatory use. If adopted for governmental use, the references to other national codes and standards in the specific volumes may be changed to refer to the corresponding regulations of the governmental authorities.

[1] This volume is currently in the development process.

SECTION V: EFFECTIVE DATE

(a) Effective Date. The effective date of this Volume of the B30 Standard shall be 1 yr after its date of issuance. Construction, installation, inspection, testing, maintenance, and operation of equipment manufactured and facilities constructed after the effective date of this Volume shall conform to the mandatory requirements of this Volume.

(b) Existing Installations. Equipment manufactured and facilities constructed prior to the effective date of this Volume of the B30 Standard shall be subject to the inspection, testing, maintenance, and operation requirements of this Standard after the effective date.

It is not the intent of this Volume of the B30 Standard to require retrofitting of existing equipment. However, when an item is being modified, its performance requirements shall be reviewed relative to the requirements within the current volume. The need to meet the current requirements shall be evaluated by a qualified person selected by the owner (user). Recommended changes shall be made by the owner (user) within 1 yr.

SECTION VI: REQUIREMENTS AND RECOMMENDATIONS

Requirements of this Standard are characterized by use of the word *shall*. Recommendations of this Standard are characterized by the word *should*.

SECTION VII: USE OF MEASUREMENT UNITS

This Standard contains SI (metric) units as well as U.S. Customary units. The values stated in U.S. Customary units are to be regarded as the standard. The SI units are a direct (soft) conversion from the U.S. Customary units.

SECTION VIII: ADDITIONAL GUIDANCE

The equipment covered by the B30 Standard is subject to hazards that cannot be abated by mechanical means, but only by the exercise of intelligence, care, and common sense. It is therefore essential to have personnel involved in the use and operation of equipment who are competent, careful, physically and mentally qualified, and trained in the proper operation of the equipment and the handling of loads. Serious hazards include, but are not limited to, improper or inadequate maintenance, overloading, dropping or slipping of the load, obstructing the free passage of the load, and using equipment for a purpose for which it was not intended or designed.

The B30 Standards Committee fully realizes the importance of proper design factors, minimum or maximum dimensions, and other limiting criteria of wire rope or chain and their fastenings, sheaves, sprockets, drums, and similar equipment covered by the Standard, all of which are closely connected with safety. Sizes, strengths, and similar criteria are dependent on many different factors, often varying with the installation and uses. These factors depend on

(a) the condition of the equipment or material

(b) the loads

(c) the acceleration or speed of the ropes, chains, sheaves, sprockets, or drums

(d) the type of attachments

(e) the number, size, and arrangement of sheaves or other parts

(f) environmental conditions causing corrosion or wear

(g) many variables that must be considered in each individual case

The requirements and recommendations provided in the volumes must be interpreted accordingly, and judgment used in determining their application.

ASME B30.10-2024
SUMMARY OF CHANGES

Following approval by the ASME B30 Standards Committee and ASME, and after public review, ASME B30.10-2024 was approved by the American National Standards Institute on October 31, 2024.

ASME B30.10-2024 includes the following changes identified by a margin note, **(24)**.

Page	*Location*	*Change*
ix	Correspondence With the B30 Committee	Added
x	B30 Standard Introduction	Updated
1	Section 10-0.3	Updated
4	Section 10-1.8	Revised
10	Section 10-2.8	Revised

Chapter 10-0
Scope, Definitions, References, Personnel Competence, and Translations

SECTION 10-0.1: SCOPE OF ASME B30.10

Volume B30.10 includes provisions that apply to the fabrication, attachment, use, inspection, and maintenance of hooks shown in Chapters 10-1 and 10-2 used for load handling purposes, in conjunction with equipment described in other volumes of the B30 Standard. Hooks supporting a load in the base (bowl/saddle or pinhole) of the hook are covered in Chapter 10-1. Hooks that may be loaded in other than the base (bowl/saddle or pinhole) are covered in Chapter 10-2.

SECTION 10-0.2: DEFINITIONS

abnormal operating conditions: environmental conditions that are unfavorable, harmful, or detrimental to or for the use of a hook, such as excessively high or low ambient temperatures, exposure to weather, corrosive fumes, dust-laden or moisture-laden atmospheres, and hazardous locations.

design factor: ratio between nominal or minimum breaking strength and rated load of the hook.

heavy service: service that involves operating at 85% to 100% of rated load as a regular specified procedure.

hook latch: a device used to bridge or close the throat opening of a hook for the purpose of retaining loose attachments during slack rigging conditions (see Figures 10-1.1-1 through 10-1.1-5 and 10-1.1-17). A rigging aid, not intended to support the load.

load: the total force or weight imposed on the hook.

load handling: the act of lifting or pulling a load from one location to another by using a hook as the connector between the load and the load handling equipment.

mouse: a method to close the throat opening of a hook using a device such as rope, wire, or other suitable means.

nick or gouge: sharp notch in hook surface that may act as stress riser in the area of the notch.

nondestructive test: a test that does not destroy the functional use of the hook, such as, but not limited to, dye-penetrant, magnetic particle, radiography, and ultrasonic tests.

normal service: service that involves operating at less than 85% of rated load except for isolated instances.

proof load: the specific load applied in performance of the proof test.

proof test: a nondestructive load test made to verify the manufacturing integrity of the hook.

qualified person: a person who, by possession of a recognized degree in an applicable field or certificate of professional standing or who by extensive knowledge, training, and experience, has successfully demonstrated the ability to solve problems relating to the subject matter and work.

rated load: the maximum allowable working load established by the manufacturer. The terms *rated capacity* and *working load limit* are commonly used to describe rated load.

rated load identification: actual rated load information or a designation provided by the manufacturer for grade and type or size to allow determination of hook rated load.

self-closing hook: a hook with a throat opening that is closed by a spring-loaded latch, gate, or bail that is manually opened for loading and closes upon release. It may be locked in the closed position (see Figures 10-1.1-8 through 10-1.1-14).

self-locking hook: a hook with a throat opening that will close and lock when a load is applied and will not open until unloaded and the lock released (see Figures 10-1.1-6 and 10-1.1-7).

severe service: service that involves normal service coupled with abnormal rigging or operating conditions.

shall: a word indicating a requirement.

should: a word indicating a recommendation.

SECTION 10-0.3: REFERENCES (24)

The following is a list of publications referenced in this Standard.

ISO 7000. Graphical symbols for use on equipment — Registered symbols. International Organization for Standardization.

ISO 7296. Cranes — Graphic symbols — Parts 1-3. International Organization for Standardization.