PD IEC TS 61496-5:2023



BSI Standards Publication

Safety of machinery — Electro-sensitive protective equipment

Part 5: Particular requirements for radar-based protective devices

bsi.

National foreword

This Published Document is the UK implementation of IEC TS 61496-5:2023.

The UK participation in its preparation was entrusted to Technical Committee MCE/3, Safeguarding of machinery.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2023
Published by BSI Standards Limited 2023

ISBN 978 0 539 06247 2

ICS 13.110; 29.260.99

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 September 2023.

Amendments/corrigenda issued since publication

Date	Text affected

IEC TS 61496-5

Edition 1.0 2023-08

TECHNICAL SPECIFICATION

colour inside

Safety of machinery – Electro-sensitive protective equipment – Part 5: Particular requirements for radar-based protective devices

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 13.110; 29.260.99

ISBN 978-2-8322-7299-2

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 8
3 Terms and definitions 8
4 Functional, design and environmental requirements 10
4.1 Functional requirements 10
4.1.1 Normal operation 10
4.1.3 Types of ESPE 10
4.1.6 Zone with limited position accuracy 10
4.2 Design requirements 11
4.2.2 Fault detection requirements 11
4.2.12 Integrity of the RPD detection capability 12
4.2.13 Test targets for type testing 14
4.2.14 Radiation frequencies 15
4.2.15 Radiation intensity 15
4.2.16 Mechanical construction 15
4.3 Environmental requirements 15
4.3.5 Radio interference 15
4.3.6 Pollution interference 16
4.3.7 Interference by surrounding objects 16
4.3.8 Manual interference 16
4.3.9 Drift and ageing of components 16
5 Testing 16
5.1.2 Test conditions 17
5.2 Functional tests 18
5.2.1 Sensing function 18
5.2.2 Response time 20
5.2.3 Limited functional tests 24
5.2.9 Test target for type testing 25
5.2.10 Position accuracy 25
5.2.11 Sensitivity 25
5.2.12 Influences on detection 26
5.2.13 Radiation frequencies 26
5.2.14 Radiation intensity 27
5.2.15 Mechanical construction 27
5.3 Performance testing under fault conditions 27
5.3.2 Type 1 ESPE 27
5.3.3 Type 2 ESPE 27
5.3.4 Type 3 ESPE 27
5.3.5 Type 4 ESPE 27
5.4 Environmental tests 27
5.4.6 Radio frequency interference 27
5.4.7 Interference by surrounding objects 31
5.4.8 Manual interference 40
6 Marking for identification and for safe use 40

6.1 General 40
7 Accompanying documents 41
Annex A (normative) Optional functions of the ESPE 42
Annex BB (informative) Relationship between resolution cell and probability of detection 44
Annex CC (informative) Corner reflector 47
Bibliography 49

Figure 1 – Definition of zones inside field of view of an RPD 13
Figure 2 – Radial approaches 21
Figure 3 – Picture illustrating a perpendicular approach (top view) 22
Figure 4 – Overhead setup 23
Figure 5 – Sensitivity test setup 26
Figure 6 – Test setup for continuous wave interference 29
Figure 7 – Example of placement of several additional RPDs 30
Figure 8 – Examples of interfering by moving object setup 32
Figure 9 – Typical installation for the static object interference test 34
Figure 10 – Example of setup for interference in the zone with limited position accuracy 36
Figure 11 – Example of setup for occlusion 38
Figure 12 – Example of detection with high RCS target test setup 39
Figure BB.1 – Relationship between position accuracy and detection zone 44
Figure BB.2 – Relationship between resolution cell and the probabilistic part of the tolerance zone 45
Figure BB.3 – Relationship between resolution cell and tolerance zone 46
Figure CC.1 – Example of a trihedral corner reflector 47
Figure CC.2 – Example values of σ for illuminating radars at 24 GHz and 80 GHz 48

Table 51 – Minimum tests required for the verification of detection capability requirements (see also 4.2.12) 19

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

SAFETY OF MACHINERY – ELECTRO-SENSITIVE PROTECTIVE EQUIPMENT –

Part 5: Particular requirements for radar-based protective devices

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 61496-5 has been prepared by IEC technical committee 44: Safety of machinery – Electrotechnical aspects. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
44/986/DTS	44/1007/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

This document is to be used in conjunction with IEC 61496-1:2020.

This document supplements or modifies the corresponding clauses in IEC 61496-1:2020 to specify particular requirements for the design, construction and testing of electro-sensitive protective equipment (ESPE) for the safeguarding of machinery, employing radar protective devices (RPDs) responsive to diffuse reflection for the sensing function.

Where a particular clause or subclause of IEC 61496-1:2020 is not mentioned in this document, that clause or subclause applies as far as is reasonable. Where this document states "*Addition*", "*Modification*" or "*Replacement*", the relevant text of IEC 61496-1:2020 is adapted accordingly.

Clauses and subclauses which are additional to those of IEC 61496-1:2020 are numbered sequentially, following on the last available number in IEC 61496-1:2020. Terminological entries (in Clause 3) which are additional to those in IEC 61496-1:2020 are numbered starting from 3.501. Additional annexes are lettered from AA onwards and additional tables are numbered with prefix 5.

A list of all the parts in the IEC 61496 series, published under the general title *Safety of machinery – Electro-sensitive protective equipment*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Electro-sensitive protective equipment (ESPE) is applied to machinery presenting a risk of personal injury. It provides protection by causing the machine to revert to a safe condition before a person can be placed in a hazardous situation.

Each type of machine presents its own particular hazards, and it is not the purpose of this document to recommend the manner of application of the ESPE to any particular machine. The application of the ESPE is a matter for agreement between the equipment supplier, the machine user and the enforcing authority. In this context, attention is drawn to the relevant guidance established internationally, for example, IEC 62046 and ISO 12100.

Due to the complexity of the technology, there are many issues that are highly dependent on analysis and expertise in specific test and measurement techniques. In order to provide a high level of confidence, independent review by relevant expertise is recommended.

Differences between worldwide frequency allocation can affect some tests due to national regulations.

SAFETY OF MACHINERY – ELECTRO-SENSITIVE PROTECTIVE EQUIPMENT –

Part 5: Particular requirements for radar-based protective devices

1 Scope

Replacement:

This part of IEC 61496 provides particular requirements for the design, construction and testing of non-contact electro-sensitive protective equipment (ESPE) designed specifically to provide whole-body detection of a person or persons as part of a safety-related system, employing radar protective devices (RPDs) responsive to diffuse reflection of radar signals for the sensing function using frequency-modulated continuous-wave (FMCW) technique. Special attention is directed to features which ensure that an appropriate safety-related performance is achieved. An ESPE can include optional safety-related functions, the requirements for which are given in Annex A of IEC 61496-1:2020 and Annex A of this document.

The requirements given in this document are related to the detection of adult persons being present in an industrial manufacturing environment.

This document does not specify the dimensions or configurations of the detection zone and its disposition in relation to hazardous parts for any particular application, nor what constitutes a hazardous state of any machine. It is restricted to the functioning of the ESPE and how it interfaces with the machine.

This document does not consider the aspects of a moving RPD application. Additional consideration can be necessary, if the RPD supplier specifies the RPD for use on moving application.

Additional requirements and tests can apply if setup of the RPD differs from Figure 2 and Figure 4.

NOTE The Radar cross-section stated in this document is based on measurements using horizontal arrangements.

Where this document does not contain all necessary provisions, IEC TS 62998-1 is used.

For those aspects not considered in this document it is also possible to additionally use provisions from IEC TS 62998-1.

Excluded from this document are RPDs that employ electromagnetic radiation outside the range 9 GHz to 81 GHz (identified as subset of band 10 and band 11 in accordance with ITU Radio Regulations). For sensing devices that employ electromagnetic radiation outside this range, this document can be used as a guide. National regulations can limit the available frequencies.

This document can be relevant to applications other than those for the protection of persons, for example for the protection of machinery or products from mechanical damage. In those applications, different requirements can be appropriate, for example when the materials to be recognized by the sensing function have different properties from those of persons.

This document does not deal with requirements for ESPE functions not related to the protection of persons (e.g. using sensing unit data for navigation).

While a data interface can be used to control optional safety-related ESPE functions (Annex A), this document does not provide specific requirements. Requirements for these safety-related functions can be determined by consulting other standards (for example, IEC 61508, IEC 62046, IEC 62061, and ISO 13849-1).

This document does not deal with EMC emission requirements.

2 Normative references

Clause 2 of IEC 61496-1:2020 applies, except as follows.

Addition:

IEC 61496-1:2020, *Safety of machinery – Electro-sensitive protective equipment – Part 1: General requirements and tests*

3 Terms and definitions

Clause 3 of IEC 61496-1:2020 applies, except as follows.

Replacement of 3.3 and 3.4:

3.3
detection capability
sensing function parameter limit(s) specified by the supplier that will cause actuation of the RPD

Note 1 to entry: Detection capability of RPD is often described by the minimum detectable object radar cross section, which refers to its size, the angle and the object properties (e.g. reflectivity, geometry, distance, velocity, approaching angle).

Note 2 to entry: A list of influences which can affect the RPD detection capability is given in 4.2.12.1.

3.4
detection zone
zone within which the specified test target(s) is detected by the RPD with a minimum required probability of detection

Addition:

3.501
radar protective device
RPD
device whose sensing function is performed by radio wave emitting and receiving elements that detect the diffuse reflection of an object present in a detection zone

3.502
radar cross section
RCS
equivalent echoing area which is 4π times the ratio of the power per unit solid angle scattered in a specified direction to the power per unit area in a plane wave incident on the scatterer from a specified direction

Note 1 to entry: See Bibliography [1] chapter 2.

[SOURCE: ISO 8729-2:2009, 3.3, modified – Note 1 to entry has been replaced.]