PD IEC TS 61851-3-5:2023



BSI Standards Publication

Electric vehicles conductive charging system

Part 3-5: DC EV supply equipment where protection relies on double or reinforced insulation — Pre-defined communication parameters and general application objects

bsi.

National foreword

This Published Document is the UK implementation of IEC TS 61851-3-5:2023.

The UK participation in its preparation was entrusted to Technical Committee PEL/69, Electric vehicles.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2023
Published by BSI Standards Limited 2023

ISBN 978 0 580 88156 5

ICS 43.120

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 July 2023.

Amendments/corrigenda issued since publication

Date	Text affected



IEC TS 61851-3-5

Edition 1.0 2023-07

TECHNICAL SPECIFICATION

Electric vehicles conductive charging system – Part 3-5: DC EV supply equipment where protection relies on double or reinforced insulation – Pre-defined communication parameters and general application objects

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 43.120

ISBN 978-2-8322-5770-8

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 12
INTRODUCTION 14
1 Scope 15
2 Normative references 15
3 Terms and definitions 15
4 Symbols and abbreviated terms 15
5 Pre-defined communication objects 16
5.1 General 16
5.1.1 Overview 16
5.1.2 Object 1000_h: Device type 16
5.1.3 Object 1001_h: Error register 17
5.1.4 Object 1003_h: Pre-defined error field 17
5.1.5 Object 1005_h: COB-ID SYNC 17
5.1.6 Object 1006_h: Communication cycle period 17
5.1.7 Object 1007_h: Communication window length 18
5.1.8 Object 1016_h: Heartbeat consumer time 18
5.1.9 Object 1017_h: Heartbeat producer time 18
5.1.10 Object 1018_h: Identity 18
5.1.11 Object 1029_h: Error behaviour 18
5.2 PDO communication 19
6 General application objects for CANopen devices 19
6.1 General 19
6.2 Application objects produced by CANopen devices with NMT slave functionality 20
6.2.1 General 20
6.2.2 Object 6000_h: Supported virtual devices 20
6.2.3 Object 6002_h: Status word 23
6.2.4 Object 6003_h: Device capability 25
6.2.5 Object 6004_h: System date and time (optional) 27
6.2.6 Object 6005_h: Device unique part number (optional) 28
6.2.7 Object 6006_h: Device electronic production date (optional) 28
6.2.8 Object 6007_h: Device installation date (optional) 29
6.2.9 Object 6008_h: Device nominal voltage (optional, mandatory for active devices) 30
6.2.10 Object 6009_h: Device alarm status 32
6.2.11 Object $600A_h$: Device alarm capability 33
6.2.12 Object $600B_h$: Device warning status (optional) 35
6.2.13 Object $600C_h$: Device warning capability (optional) 37
6.2.14 Object $600E_h$: Implemented specification versions 39
6.2.15 Object 6020_h: Device request dynamic voltage limitation 41
6.2.16 Object 6022_h: Device request dynamic current input limitation 42

6.2.17 Object 6023_h: Device request dynamic current output limitation 44
6.2.18 Object 6024_h: Device maximum continuous input current 46
6.2.19 Object 6025_h: Device maximum continuous output current 48
6.2.20 Object 6026_h: Device maximum voltage 49
6.2.21 Object 6027_h: Device minimum voltage 51
6.2.22 Object 6039_h: Device actual external voltage (optional) 52
6.2.23 Object $603A_h$: Device peak input current 54
6.2.24 Object $603B_h$: Device peak input current time (optional) 55
6.2.25 Object $603C_h$: Device peak output current (optional) 57
6.2.26 Object $603D_h$: Device peak output current time (optional) 58
6.2.27 Object $603E_h$: Device actual current 59
6.2.28 Object 6040_h: Device actual voltage 61
6.2.29 Object 6042_h: Device internal temperature (optional) 62
6.2.30 Object 6043_h: Device time on (optional) 64
6.2.31 Object 6044_h: Device time standby (optional) 64
6.2.32 Object 6045_h: Device switch on counter (optional) 65
6.2.33 Object 6060_h: CANopen device measurement timing (optional) 65
6.2.34 Object 6064_h: Device maximum AUX continuous input current (optional) 69
6.2.35 Object 6065_h: Device maximum AUX continuous output current (optional) 70
6.2.36 Object 6066_h: Device maximum AUX voltage (optional) 72
6.2.37 Object 6067_h: Device minimum AUX voltage (optional) 73
6.2.38 Object 6070_h: Device actual AUX current (optional) 75
6.2.39 Object 6071_h: Device actual AUX voltage (optional) 77
6.2.40 Object 6072h: Device available output voltage 78
6.2.41 Object 6073h: Device available output current 79
6.2.42 Object 6074h: Device available input current (optional) 81
6.3 Security 82
6.3.1 General 82
6.3.2 Object 6311h: Locking status 83
6.4 Application objects consumed by CANopen devices with NMT slave functionality (mandatory) 84
6.4.1 General 84
6.4.2 Object 6001_h: Control word 85
6.4.3 Object 6046_h: Device set maximum voltage 86
6.4.4 Object 6047_h: Device set minimum voltage 88
6.4.5 Object $604A_h$: Device set maximum continuous input current 89
6.4.6 Object $604B_h$: Device set maximum continuous output current 90
6.4.7 Object $604C_h$: Device set maximum peak input current 91
6.4.8 Object $604D_h$: Device set maximum peak input current time 92
6.4.9 Object $604E_h$: Device set maximum peak output current 93
6.4.10 Object $604F_h$: Device set maximum peak output current time 94

6.5 Application objects consumed by CANopen devices with NMT slave functionality (optional) 95
6.5.1 General 95
6.5.2 Object $600D_h$: Error behaviour at process interface (optional) 95
6.5.3 Object 6058_h: Device security key (optional) 96
6.5.4 Object 6059_h: Devices' user name and address (optional) 97
6.5.5 Object $605A_h$: Device password (optional) 99
6.5.6 Object 6053_h: Prefixes and SI units for analogue values (optional) 100
7 Application objects relevant for fleet management (optional) 103
7.1 General 103
7.2 Object 63D5h: Travelled distance 103
7.3 Object 63D6h: Travelled distance current trip 104
7.4 Object $63D7_h$: Travelled time 105
7.5 Object $63D8_h$: Travelled time current trip 106
7.6 Object $63D9_h$: Transferred watt hours 107
7.7 Object $63DA_h$: Current trip transferred watt hours 108
8 Stationary applications (optional) 110
8.1 General application objects relevant for stationary applications 110
8.2 Object 6010_h: Ambient temperature 110
8.3 Object 6011_h: Phase 1 AC Current 111
8.4 Object 6012_h: Phase 2 AC Current 113
8.5 Object 6013_h: Phase 3 AC Current 114
8.6 Object 6014_h: Phase 1 AC voltage 115
8.7 Object 6015_h: Phase 2 AC voltage 117
8.8 Object 6016_h: Phase 3 AC voltage 118
8.9 Object 6017_h: Line 12 AC voltage 120
8.10 Object 6018_h: Line 23 AC voltage 121
8.11 Object 6019_h: Line 13 AC voltage 123
8.12 Object $601A_h$: Phase 1 AC reactive power 124
8.13 Object $601B_h$: Phase 2 AC reactive power 126
8.14 Object $601C_h$: Phase 3 AC reactive power 127
8.15 Object $601D_h$: Phase 1 AC apparent power 129
8.16 Object $601E_h$: Phase 2 AC apparent power 130
8.17 Object $601F_h$: Phase 3 AC apparent power 132
8.18 Object 6030_h: Phase 1 AC real power 134
8.19 Object 6031_h: Phase 2 AC real power 135
8.20 Object 6032_h: Phase 3 AC real power 137
8.21 Object 6033_h: Total AC reactive power 138
8.22 Object 6034_h: Total AC apparent power 140
8.23 Object 6035_h: Total AC real power 141
8.24 Object 6036_h: Phase1 power factor (cos phi) 143
8.25 Object 6037_h: Phase 2 power factor (cos phi) 144

8.26 Object 6038_h: Phase 3 power factor (cos phi) 146
8.27 Object 6050_h: AC Frequency 147
8.28 Object 6051_h: Isolation resistance 149
8.29 Object 6052_h: Rated power 150
Annex A (informative) Measured values 152
A.1 General 152
A.2 Actual voltage 152
Annex B (normative) Process data object (PDO) communication for EMS 153
B.1 General 153
B.2 Specification of messages 153
B.3 Allocation of PDOs to virtual devices 153
B.4 Detailed PDO parameters 159
B.4.1 General 159
B.4.2 TPDO parameters for message number 1 159
B.4.3 TPDO parameters for message number 2 162
B.4.4 TPDO parameters for message number 3 164
B.4.5 TPDO parameters for message number 4 to 9 167
B.4.6 TPDO parameters for message number 10 168
B.4.7 TPDO parameters for message number 12 170
Bibliography 173

Figure 1 – Object structure 16
Figure 2 – Object structure supported virtual devices 20
Figure 3 – Object structure device status 23
Figure 4 – Value structure 25
Figure 5 – Value structure 32
Figure 6 – Value structure 33
Figure 7 – Value structure 35
Figure 8 – Value structure 37
Figure 9 – Value structure 39
Figure 10 – Object structure security status 83
Figure 11 – Value structure 85
Figure 12 – Object structure for prefixes 101
Figure A.1 – Voltage measurement at generic active device 152

Table 1 – Value definition for the bit field additional information 16
Table 2 – Object description 17
Table 3 – Entry description 17
Table 4 – Default value definition object 1005_h 17
Table 5 – Value definition 18
Table 6 – Object description (optional) 18
Table 7 – Entry description 19
Table 8 – Value definition for bit fields 21
Table 9 – Object description 22

Table 10 – Entry description 22
Table 11 – Value definition device status 23
Table 12 – Object description 24
Table 13 – Entry description 24
Table 14 – Value definition 25
Table 15 – Object description 26
Table 16 – Entry description 26
Table 17 – Object description 27
Table 18 – Entry description 27
Table 19 – Object description 28
Table 20 – Entry description 28
Table 21 – Object description 28
Table 22 – Entry description 29
Table 23 – Object description 29
Table 24 – Entry description 30
Table 25 – Object description 30
Table 26 – Entry description 31
Table 27 – Value definition 32
Table 28 – Object description 33
Table 29 – Entry description 33
Table 30 – Value definition 34
Table 31 – Object description 35
Table 32 – Entry description 35
Table 33 – Value definition 36
Table 34 – Object description 37
Table 35 – Entry description 37
Table 36 – Value definition 37
Table 37 – Object description 38
Table 38 – Entry description 39
Table 39 – Value definition 39
Table 40 – Object description 40
Table 41 – Entry description 40
Table 42 – Value definition 41
Table 43 – Object description 41
Table 44 – Entry description 41
Table 45 – Value definition 43
Table 46 – Object description 43
Table 47 – Entry description 43
Table 48 – Value definition 45
Table 49 – Object description 45
Table 50 – Entry description 45
Table 51 – Object description 46
Table 52 – Entry description 47

Table 53 – Object description 48
Table 54 – Entry description 48
Table 55 – Object description 49
Table 56 – Entry description 50
Table 57 – Object description 51
Table 58 – Entry description 51
Table 59 – Object description 53
Table 60 – Entry description 53
Table 61 – Object description 54
Table 62 – Entry description 54
Table 63 – Object description 56
Table 64 – Entry description 56
Table 65 – Object description 57
Table 66 – Entry description 57
Table 67 – Object description 58
Table 68 – Entry description 59
Table 69 – Object description 60
Table 70 – Entry description 60
Table 71 – Object description 61
Table 72 – Entry description 61
Table 73 – Object description 63
Table 74 – Entry description 63
Table 75 – Object description 64
Table 76 – Entry description 64
Table 77 – Object description 64
Table 78 – Entry description 64
Table 79 – Object description 65
Table 80 – Entry description 65
Table 81 – Object description 66
Table 82 – Entry description 66
Table 83 – Object description 69
Table 84 – Entry description 69
Table 85 – Object description 70
Table 86 – Entry description 71
Table 87 – Object description 72
Table 88 – Entry description 72
Table 89 – Object description 74
Table 90 – Entry description 74
Table 91 – Object description 75
Table 92 – Entry description 75
Table 93 – Object description 77
Table 94 – Entry description 77
Table 95 – Object description 78

Table 96 – Entry description 78
Table 97 – Object description 80
Table 98 – Entry description 80
Table 99 – Object description 81
Table 100 – Entry description 81
Table 101 – Value definition security status 83
Table 102 – Object description 83
Table 103 – Entry description 84
Table 104 – Value definition 85
Table 105 – Object description 85
Table 106 – Entry description 86
Table 107 – Object description 87
Table 108 – Entry description 87
Table 109 – Object description 88
Table 110 – Entry description 88
Table 111 – Object description 89
Table 112 – Entry description 89
Table 113 – Object description 90
Table 114 – Entry description 90
Table 115 – Object description 91
Table 116 – Entry description 91
Table 117 – Object description 92
Table 118 – Entry description 92
Table 119 – Object description 93
Table 120 – Entry description 93
Table 121 – Object description 94
Table 122 – Entry description 94
Table 123 – Value definition 95
Table 124 – Object description 95
Table 125 – Entry description 96
Table 126 – Object description 97
Table 127 – Entry description 97
Table 128 – Object description 98
Table 129 – Entry description 98
Table 130 – Object description 99
Table 131 – Entry description 99
Table 132 – Additional units 101
Table 133 – Allocation of powerlines to sub-indices 101
Table 134 – Object description 101
Table 135 – Entry description 101
Table 136 – Object description 103
Table 137 – Entry description 104
Table 138 – Object description 105

Table 139 – Entry description 105
Table 140 – Object description..... 106
Table 141 – Entry description 106
Table 142 – Object description..... 107
Table 143 – Entry description 107
Table 144 – Object description..... 108
Table 145 – Entry description 108
Table 146 – Object description..... 109
Table 147 – Entry description 109
Table 148 – Object description..... 110
Table 149 – Entry description 110
Table 150 – Object description..... 111
Table 151 – Entry description 112
Table 152 – Object description..... 113
Table 153 – Entry description 113
Table 154 – Object description..... 114
Table 155 – Entry description 114
Table 156 – Object description..... 116
Table 157 – Entry description 116
Table 158 – Object description..... 117
Table 159 – Entry description 117
Table 160 – Object description..... 118
Table 161 – Entry description 119
Table 162 – Object description..... 120
Table 163 – Entry description 120
Table 164 – Object description..... 121
Table 165 – Entry description 122
Table 166 – Object description..... 123
Table 167 – Entry description 123
Table 168 – Object description..... 124
Table 169 – Entry description 124
Table 170 – Object description..... 126
Table 171 – Entry description 126
Table 172 – Object description..... 127
Table 173 – Entry description 128
Table 174 – Object description..... 129
Table 175 – Entry description 129
Table 176 – Object description..... 131
Table 177 – Entry description 131
Table 178 – Object description..... 132
Table 179 – Entry description 132
Table 180 – Object description..... 134
Table 181 – Entry description 134

Table 182 – Object description 135
Table 183 – Entry description 136
Table 184 – Object description 137
Table 185 – Entry description 137
Table 186 – Object description 138
Table 187 – Entry description 139
Table 188 – Object description 140
Table 189 – Entry description 140
Table 190 – Object description 141
Table 191 – Entry description 142
Table 192 – Object description 143
Table 193 – Entry description 143
Table 194 – Object description 144
Table 195 – Entry description 145
Table 196 – Object description 146
Table 197 – Entry description 146
Table 198 – Object description 147
Table 199 – Entry description 148
Table 200 – Object description 149
Table 201 – Entry description 149
Table 202 – Object description 150
Table 203 – Entry description 151
Table B.1 – PDO mapping entries 153
Table B.2 – PDO assignment for active devices 154
Table B.3 – PDO assignment for VCU 9 to 16 156
Table B.4 – Additional PDO assignment for some active devices 156
Table B.5 – PDO assignment for passive devices 158
Table B.6 – Object description 159
Table B.7 – Entry description 159
Table B.8 – Object description 161
Table B.9 – Entry description 161
Table B.10 – Object description 162
Table B.11 – Entry description 162
Table B.12 – Object description 164
Table B.13 – Entry description 164
Table B.14 – TPDO communication parameter 165
Table B.15 – Entry description 165
Table B.16 – Object description 166
Table B.17 – Entry description 167
Table B.18 – Object description 168
Table B.19 – Entry description 168
Table B.20 – Object description 169
Table B.21 – Entry description 170

Table B.22 – Object description 170
Table B.23 – Entry description 171
Table B.24 – Object description 172
Table B.25 – Entry description 172

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

ELECTRIC VEHICLES CONDUCTIVE CHARGING SYSTEM –

Part 3-5: DC EV supply equipment where protection relies on double or reinforced insulation – Pre-defined communication parameters and general application objects

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 61851-3-5 has been prepared by s IEC technical committee 69: Electrical power/energy transfer systems for electrically propelled road vehicles and industrial trucks. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
69/651/DTS	69/672/RVDTS 69/672A/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The following print types are used:

– requirements: in roman type;
– notes: in small roman type;
– **text formatted in bold and using mixed capital and underline are used as state names and are not to be translated**.

A list of all parts in the IEC 61851 series, published under the general title *Electric vehicles conductive charging system,* can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

This document is published in separate parts according to the following structure:

IEC TS 61851-3-1, *Electric vehicles conductive charging system – Part 3-1: DC EV supply equipment where protection relies on double or reinforced insulation – General rules and requirements for stationary equipment*

IEC TS 61851-3-2, *Electric vehicles conductive charging system – Part 3-2: DC EV supply equipment where protection relies on double or reinforced insulation – Particular requirements for portable and mobile equipment*

IEC TS 61851-3-4, *Electric vehicles conductive charging system – Part 3-4: DC EV supply equipment where protection relies on double or reinforced insulation – General definitions and requirements for CANopen communication*

IEC TS 61851-3-5, *Electric vehicles conductive charging system – Part 3-5: DC EV supply equipment where protection relies on double or reinforced insulation – Pre-defined communication parameters and general application objects*

IEC TS 61851-3-6, *Electric vehicles conductive charging system – Part 3-6: DC EV supply equipment where protection relies on double or reinforced insulation – Voltage converter unit communication*

IEC TS 61851-3-7, *Electric vehicles conductive charging system – Part 3-7: DC EV supply equipment where protection relies on double or reinforced insulation – Battery system communication*

ELECTRIC VEHICLES CONDUCTIVE CHARGING SYSTEM –

Part 3-5: DC EV supply equipment where protection relies on double or reinforced insulation – Pre-defined communication parameters and general application objects

1 Scope

This part of IEC 61851, which is a Technical Specification, applies to CANopen communication for the conductive transfer of electric power between the supply network and an electric road vehicle or a removable RESS or traction-battery of an electric road vehicle.

This document provides specifications with regard to the pre-defined communication parameters and general application objects.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TS 61851-3-1:2023, *Electric vehicles conductive charging system – Part 3-1: DC EV supply equipment where protection relies on double or reinforced insulation – General rules and requirements for stationary equipment*

IEC TS 61851-3-4:2023, *Electric vehicles conductive charging system – Part 3-4: DC EV supply equipment where protection relies on double or reinforced insulation – General definitions and requirements for CANopen communication*

EN 50325-4:2002: *Industrial communications subsystem based on ISO 11898 (CAN) For controller-device interface - Part 4: Canope*n

CiA 302-2:2009, CANopen *additional application layer functions – Part 2: Network management* (available at www.can-cia.org)

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC TS 61851-3-4:20231 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

4 Symbols and abbreviated terms

For the purposes of this document, the symbols and abbreviated terms given in IEC TS 61851-3-4:2023 apply.