PD ISO/TR 10982:2013



BSI Standards Publication

Road vehicles — Test procedures for evaluating out-of-position vehicle occupant interactions with deploying air bags

bsi.

...making excellence a habit.™

National foreword

This Published Document is the UK implementation of ISO/TR 10982:2013.

The UK participation in its preparation was entrusted to Technical Committee AUE/15, Safety related to vehicles.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2013.
Published by BSI Standards Limited 2013

ISBN 978 0 580 82792 1
ICS 43.100

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 Dezember 2013.

Amendments/corrigenda issued since publication

Date	Text affected

PD ISO/TR 10982:2013

TECHNICAL REPORT

ISO/TR 10982

Second edition
2013-11-15

Road vehicles — Test procedures for evaluating out-of-position vehicle occupant interactions with deploying air bags

Véhicules routiers — Méthodes d'essai pour l'évaluation des interactions d'un occupant en position anormale dans un véhicule et des sacs gonflables en cours de déploiement

Reference number
ISO/TR 10982:2013(E)

© ISO 2013



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword ..... **iv**

Introduction ..... **v**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Test drive **1**
4.1 General 1
4.2 50th percentile male Hybrid III dummy 2
4.3 “Small female” Hybrid III dummy 2
4.4 Three-year-old child Hybrid III dummy 2

5 Instrumentation **2**
5.1 Adult size dummy 2
5.2 Three-year-old child dummy 2
5.3 Data requirements 3
5.4 Dummy test temperature 3

6 Sled pulses **3**
6.1 General 3
6.2 Mild severity crash pulse 3
6.3 Moderate severity crash pulse 3

7 Static and dynamic test for driver air bag systems **6**
7.1 Test set-up 6
7.2 Prepositioned driver tests 6
7.3 Acceleration-induced out-of-position driver dynamic tests 7

8 Static and dynamic tests for passenger air bag systems, using child dummy **8**
8.1 General 8
8.2 Test set-up 8
8.3 Child dummy test positions 8
8.4 Child dummy static tests for passenger air bag systems 10
8.5 Child dummy dynamic tests for passenger air bag systems 10

9 Static and dynamic tests for passenger air bag systems using adult dummies **10**
9.1 General 10
9.2 Test set-up 10
9.3 Adult dummy positions near instrument panel 11
9.4 Adult dummy static tests for passenger air bag systems 11
9.5 Adult dynamic tests for passenger air bag systems 11

Bibliography **13**

© ISO 2013 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 10, *Impact test procedures*.

This second edition cancels and replaces the first edition (ISO/TR 10982:1998), which has been technically revised.

Annex A of this Technical Report is for information only.

© ISO 2013 – All rights reserved

Introduction

Although laws concerning the mandatory use of seat belts and child restraints have been enacted in most ISO member countries, surveys and accident statistics indicate that between 10 % and 50 % of front seat occupants involved in accidents had not used these restraint systems. Most, if not all, new vehicles marketed with air bags in ISO member countries specify that the air bag is supplemental to the existing belt/child seat restraint systems. However, front seat occupants may not comply with manufacturer's recommendations and laws. Hence, they may be near or against deploying driver and/or passenger air bag modules during collisions. Some data indicate that small, unrestrained children may get into such positions due to voluntary precrash riding positions[1] and/or due to preimpact braking and/or collision forces.[2] These factors may also cause some adults to be near the air bag modules, but preimpact braking is likely to have less effect on adults.

During the inflation process, an air bag generates a considerable amount of kinetic energy and as a result substantial forces can be developed between the deploying air bag and the out-of-position occupant. Accident data and laboratory test results[4][9] have indicated that these forces could cause injuries to the head, neck, thorax, abdomen and legs.

Both mild and moderate severity crash pulses are described in this Technical Report. These pulses represent general deceleration-time histories. The mild severity crash pulse is near the threshold of many air bag deployments and represents a frequent accident event. This pulse can be used for child testing, since they are more likely than adults to be near the air bag modules in threshold deployment collisions. Since preimpact braking has much less of an effect on adults, the moderate severity crash pulse can be used for adult testing. These described pulses or other vehicle-specific pulses may be used.

This Technical Report describes the more common interactions, recognizing that the range of possible interactions is essentially limitless.

This document is published as a Technical Report, rather than as an International Standard, because of the general inexperience in air bag testing and lack of real-world accident data correlation. When sufficient real-world data are available and/or there is sufficient testing experience, it may be appropriate to develop an International Standard.

© ISO 2013 – All rights reserved

TECHNICAL REPORT ISO/TR 10982:2013(E)

Road vehicles — Test procedures for evaluating out-of-position vehicle occupant interactions with deploying air bags

1 Scope

This Technical Report outlines a number of test procedures that can be used for investigating the interactions that could occur between the deploying air bag and the occupant who is near the module at the time of deployment. Static and dynamic tests to investigate both driver and passenger systems are described. Comparative evaluation of the designs can be conducted using static tests. Favourable systems may be evaluated, if deemed necessary, by appropriate dynamic tests.

Children and infants restrained in child or infants seats are the subject of another Technical Report.[20]

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6487:2012, *Road vehicles — Measurement techniques in impact tests — Instrumentation*

SAE J211, *Part-1 Instrumentation for impact test*

3 Terms and definitions

For the purposes of this document, the following definitions apply.

3.1
passenger air bag module location
<low mounted> rearward deploying module location in the area of the instrument panel, normally used for knee bolsters

3.2
passenger air bag module location
<mid mounted> rearward deploying module location above the knee bolster area in the instrument panel

3.3
passenger air bag module location
<top mounted> air bag system that deploys through the top surface of the instrument panel

3.4
out-of-position occupant
vehicle occupant who is near the air bag module at the time of deployment

4 Test drive

4.1 General

Two sizes of adult dummies and one child size dummy are available for out-of-position occupant investigations. It is suggested that the adult dummies be equipped with an optional neck cover to give a more humanlike shape to the neck and neck-head junction.

© ISO 2013 – All rights reserved