INTERNATIONAL STANDARD

ISO 20077-1

First edition
2017-12

Road Vehicles — Extended vehicle (ExVe) methodology —

Part 1: General information

Véhicules routiers — Méthodologie du véhicule étendu (ExVe) —

Partie 1: Information générale

Reference number
ISO 20077-1:2017(E)

© ISO 2017



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword ... **iv**

Introduction ... **v**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms and definitions ... **1**

4 Abbreviated terms ... **5**

5 The extended vehicle ... **5**
5.1 Background ... 5
5.2 The "extended vehicle" concept ... 7
5.3 The design constraints applicable to an extended vehicle ... 10
5.4 The areas where the extended vehicles are expected to be used ... 10

6 ISO standards dealing with the extended vehicles ... **11**
6.1 General ... 11
6.2 Generic ExVe standards: The ISO 20077 series ... 12
6.2.1 Content of the ISO 20077 series ... 12
6.2.2 ISO 20077-2: The ISO methodology standard for designing an extended vehicle ... 12
6.3 Standards related to ExVe interfaces ... 14
6.3.1 Content of the standards related to ExVe interfaces ... 14
6.3.2 Standards defining an ExVe interface in the case of web services ... 14
6.4 Standards related to ExVe use case clusters ... 15
6.4.1 Content of the standards related to ExVe use case clusters ... 15
6.4.2 Example of the ISO 20080 project on remote diagnostics ... 15
6.5 Practical usage of the extended vehicles standards ... 15
6.5.1 Example of designing an extended vehicle for remote diagnostics purposes ... 15
6.5.2 Generalization ... 17

Annex A (informative) **Diagnostic and prognostic processes — Practical cases: The malfunction of an air conditioning system** ... **18**

Annex B (informative) **Practical usage of the extended vehicles standards (Generalization)** ... **21**

Bibliography ... **23**

© ISO 2017 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22 *Road vehicles*, Subcommittee SC 31, *Data communication*.

A list of all parts in the ISO 20077 series can be found on the ISO website.

© ISO 2017 – All rights reserved

Introduction

This document is the first part of a series of ISO Standards dedicated to the extended vehicle.

© ISO 2017 – All rights reserved

Road Vehicles — Extended vehicle (ExVe) methodology —

Part 1: General information

1 Scope

This document defines the concepts and the terms related to extended vehicles.

It presents general information regarding these vehicles, specifies the dedicated terminology and describes the interrelation with other standards related to extended vehicles.

It concerns:

— road vehicles with four or more wheels designed and constructed primarily for the carriage of persons that are defined as Category 1 vehicles in the United Nations Special Resolution No.1 *in TRANS*/WP.29/1045, as last amended on 19 June 2012;

— road vehicles with four or more wheels designed and constructed primarily for the carriage of goods that are defined as Category 2 vehicles in the United Nations Special Resolution No.1 *in TRANS*/WP.29/1045, as last amended on 19 June 2012,

where these road vehicles are still in accordance with the specifications of the vehicle manufacturer.

While this document mentions already standardized interfaces and devices (e.g. external test equipment) connected to these interfaces, the specification of these interfaces and devices is not within the scope of this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 20077-2:—[1)], *Road vehicles – Extended vehicle (ExVe) methodology – Part 2: Methodology for designing the extended vehicle*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— IEC Electropedia: available at http://www.electropedia.org/

— ISO Online browsing platform: available at http://www.iso.org/obp

NOTE Illustration through a practical case of the interrelation between the diagnostics and prognostics concepts defined respectively in 3.2 to 3.4 and 3.13 may be found in Annex A.

3.1
diagnosis
result of a *diagnostic process* (3.2) carried out on a vehicle

1) Under preparation. Stage at the time of publication: ISO/FDIS 20077-2:2017

© ISO 2017 – All rights reserved

3.2
diagnostics
diagnostic process
process including the detection process of possible vehicle *malfunctions* (3.10), the identification of the likely root cause of these malfunctions and the appraisal of its relevance for the operation of the vehicle

3.3
diagnostics step 1
detection process of possible vehicle *malfunctions* (3.10)

Note 1 to entry: The detection process of possible vehicle malfunctions (diagnostics step 1) may lead to the conclusion of an absence of malfunction.

3.4
diagnostics step 2
identification of the likely root cause of *malfunctions* (3.10)

Note 1 to entry: Root cause analysis (diagnostics step 2) is only performed in presence of a malfunction. Root cause analysis is performed if diagnostics step 1 has been performed.

3.5
extended vehicle
entity, still in accordance with the specifications of the *vehicle manufacturer* (3.20), that extends beyond the physical boundaries of the road vehicle and consists of the road vehicle, *off-board systems* (3.11), external interfaces and the data communication between the road vehicle and the off-board systems

Note 1 to entry: Road vehicles without off-board systems and road vehicles equipped with telematics units are extended vehicles.

3.6
ExVe manufacturer
vehicle manufacturer (3.20) responsible for the *extended vehicle* (3.5)

3.7
function
task, action or activity that should be achieved to satisfy a functional requirement

EXAMPLE "KEY ON-ENGINE OFF".

Note 1 to entry: The same function may be used in several different *use cases* (3.17).

3.8
functionality
set of *functions* (3.7) that ensures the overall capability of the system to satisfy a *functional requirement* (3.9)

EXAMPLE The set of functions necessary for "establishing the communication with an *extended vehicle* (3.5)".

Note 1 to entry: In the set of functions necessary for "establishing the communication with an extended vehicle", one can find such functions as "KEY ON-ENGINE OFF", etc.

Note 2 to entry: The same functionality may be used in several different *use cases* (3.17).

3.9
functional requirement
<extended vehicles> statement issued by the *vehicle manufacturer* (3.20) that identifies what a product or process must accomplish to produce required behaviour and/or results

Note 1 to entry: The functional requirement is issued by the body in charge of the design of the product or process.

© ISO 2017 – All rights reserved

[SOURCE: ISO/IEC/IEEE 24765:2010, 3.1229, definition 1, modified — source entry has been modified to introduce that, in the case of extended vehicles, the statement is issued by the vehicle manufacturer and Note 1 has been added to source entry.]

3.10
malfunction
state of a system or a component that deviates from the specifications of the *vehicle manufacturer* (3.20)

Note 1 to entry: A malfunction may be the object of an alert on board the vehicle and possibly lead to a DTC, but a malfunction does not necessarily preclude a DTC.

Note 2 to entry: A slight deterioration of a system, such as the normal wear of that system, is not a malfunction as long as it does not impair the performance of that system against the design specifications of the vehicle manufacturer.

3.11
off-board system
<road vehicles> software and hardware components off-board a road vehicle that have been specified, designed, developed and/or manufactured to address the requested *functionalities* (3.8)

3.12
prognosis
prediction which is the result of a *prognostic process* (3.13)

3.13
prognostics
prognostic process
<automotive> process of forecasting the possible occurrence of vehicle *malfunctions* (3.10) and appraising the likely remaining operation time of the vehicle until these malfunctions occur

Note 1 to entry: A prognostic process cannot be performed without having performed the detection process of possible malfunctions of the same functionally related system [*diagnostics step 1* (3.3)].

Note 2 to entry: A *diagnostic process* (3.2) may be performed without performing a prognostic process (for example, in the case of the presence of a malfunction, when *diagnostics step 2* (3.4) is performed).

3.14
remote, adjective
performed on a vehicle from a distance where the operator responsible for the concerned operation is not co-located with the vehicle and where the vehicle is connected via an external network

EXAMPLE Remote diagnostics, remote access.

Note 1 to entry: The "operator responsible for the concerned operation" is a specific actor in terms of *use case* (3.17).

3.15
remote diagnostician
remote diagnostics operator
physical person that performs a remote diagnostic process

3.16
remote diagnostic support
information provided to a *remote diagnostician* (3.15) to assist in the performance of the remote diagnostic process of a vehicle

Note 1 to entry: Typical examples of remote diagnostics support are:

— information for performing a remote diagnostic process on a vehicle (for example, instructions, training material, etc.),

— information specified for remote diagnostics *use cases* (3.17), and

— information used by the after-sales remote diagnostics tool equipment systems.

© ISO 2017 – All rights reserved

Note 2 to entry: Diagnostic support that is provided for performing conventional diagnostics is the foundation for remote diagnostic support (the access to that information in the case of conventional diagnostics is standardized in ISO 18541-1).

3.17
use case
sequence of interactions between one or several actors and the concerned system, which has a defined goal and provides a measurable result

EXAMPLE Read all active DTCs

Note 1 to entry: "Read all active DTCs" may be comprised of the following interactions: initialization of the communication, identification of the vehicle, sending the request to get DTC information ("read DTC"), receiving DTC information, terminating of the communication.

Note 2 to entry: Actors may be both human and machines.

Note 3 to entry: In the case of an *extended vehicle* (3.5), the concerned system is the extended vehicle itself.

Note 4 to entry: In order to be able to perform the design of an extended vehicle, it is necessary that the use cases are completed by the appropriate use case scenarios and use case functional requirements.

3.18
use case cluster
<road vehicles> grouping of *use cases* (3.17) that together have the same goal measurable result

EXAMPLE Remote diagnostics, fleet management.

Note 1 to entry: Use case clusters may be themselves regrouped into areas, the typology of which may generate different types of technical solutions, although some solutions may be common to several areas.

Note 2 to entry: Extended vehicles have been developed to be used in all the use case clusters areas where vehicle connectivity is expected, for example, cooperative ITS, fleet management, remote diagnostic, car sharing, etc.

3.19
use case scenario
set of circumstances under which the sequence of interaction describing a *use case* (3.17) takes place

EXAMPLE Vehicle is in a workshop, vehicle is in a manufacturing process, vehicle is immobilized, etc.

Note 1 to entry: The same use case may take place under different scenarios, but the sequence of interaction may also be affected by the circumstances. In that case, one would have more than one use case.

Note 2 to entry: In the case of an operation performed on an immobilized vehicle, the presence or absence of a technician may be part of the use case scenario.

3.20
vehicle manufacturer
person or body who is responsible to the approval authority for all aspects of the type approval or authorization process and for ensuring conformity of production of a vehicle

Note 1 to entry: It is not essential that the person or body be directly involved in all stages of the construction of the vehicle, system, component or separate technical unit which is the subject of the approval process.

Note 2 to entry: Adapted from Directive 2007/46/EC.

[SOURCE: ISO 18541-1:2014, 3.1.46]

© ISO 2017 – All rights reserved

3.21
web service
software system, with an interface described in a machine-processable format and designed to support interoperable machine-to-machine interaction over a network

[SOURCE: WORLD WIDE WEB Consortium Glossary - W3C Working Group Note 11 - February 2004, modified — source entry has been modified not to restrict the concept to one protocol or one type of messages and to partly include Note 1 to source entry and Note 2 to source entry has been disregarded.]

4 Abbreviated terms

DTC	Diagnostic trouble code
ExVe	Extended Vehicle
FMS	Fleet Management System
IT	Information Technology
ITS	Intelligent Transport Systems
OBD	On-board Diagnostics
PTI	Periodical Technical Inspection
RDS	Remote Diagnostic Support
rFMS	remote Fleet Management System
RMI	Repair and Maintenance Information
RSI	Road Side Inspection
VCI	Vehicle Communication Interface
VM	Vehicle Manufacturer
V2I	Vehicle-to-Infrastructure
V2V	Vehicle-to-Vehicle
W3C	World Wide Web Consortium
WS	Web Service

5 The extended vehicle

5.1 Background

The technology improvements, especially IT improvements, have permitted vehicle manufacturers to address the constant evolution of the needs of its customers by providing solutions that are not solely on-board the conventional vehicle (whether car, truck or bus) but that also involve off-board components and systems.

Typically, these improvements have been based on new ways of communicating with the vehicle where information can be accessed wirelessly.

© ISO 2017 – All rights reserved