IEC 60068-2-86

Edition 1.0 2024-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Environmental testing – Part 2-86: Tests –Test Fx: Vibration – Multi-exciter and multi-axis method

Essais d'environnement – Partie 2-86: Essais – Essai Fx: Vibrations – Méthode par excitateurs multiples et axes multiples



IEC 60068-2-86:2024-02(en-fr)



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC
La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC
Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC - webstore.iec.ch/advsearchform
La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, …). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished
Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc
Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications, symboles graphiques et le glossaire. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org
Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 500 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 25 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

IEC 60068-2-86

Edition 1.0 2024-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Environmental testing –
Part 2-86: Tests –Test Fx: Vibration – Multi-exciter and multi-axis method

Essais d'environnement –
Partie 2-86: Essais – Essai Fx: Vibrations – Méthode par excitateurs multiples et axes multiples

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 19.040

ISBN 978-2-8322-8242-7

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

® Registered trademark of the International Electrotechnical Commission
Marque déposée de la Commission Electrotechnique Internationale

CONTENTS

FOREWORD 4
1 Scope 6
2 Normative references 7
3 Terms and definitions 8
4 Background 9
4.1 General 9
4.2 Multi-axis and/or multi-exciter testing to achieve an improved distribution of dynamic responses 9
4.3 Multi-exciter testing for large equipment 10
4.4 Multi-axis testing for reliability growth 10
4.5 Multi-axis testing to reduce test durations 10
5 Test apparatus and control strategy 11
6 Test severities and tolerances 11
6.1 Test severities 11
6.2 Tolerances 11
6.3 Excitations outside the specified test frequency range 11
6.4 Cross-axis motions 12
7 Mounting of specimen and installation of measurement systems 12
8 Precursor testing 13
9 Vibration response investigation 13
10 Pre-conditioning 13
11 Initial measurement and functional performance test 14
12 Low level excitation for equalisation prior to testing 14
13 Testing 14
14 Intermediate measurement and functional performance 14
15 Recovery 14
16 Final measurement and functional performance and vibration response investigation 15
17 Test verification 15
18 Information to be specified in the relevant specification 15
19 Information to be given in the test report 16
Annex A (informative) Guidance on multi-axis and multi-exciter test control systems 18
A.1 General 18
A.2 Multi-exciter control strategies 18
A.3 Determined and over determined control strategies 19
A.4 Quantifying the inter-relationship between exciters for vibration testing 20
A.5 Quantifying the inter-relationship between exciters for time history replication testing 21
Annex B (informative) Additional testing guidance 23
B.1 Fixing, monitor, control and reference points 23
B.2 Control equalisation 23
B.3 Cross-axis motion, signal distortion and out of test frequency range responses 24
B.4 Precursor testing 25
B.5 Vibration response investigation 25

B.6 Temperature conditioning and stabilization 25
B.7 Performance evaluation 26
B.8 Verification of test procedure 26
Annex C (informative) Guidance on the application of multi-axis / multi-vibrator tests 28
C.1 General 28
C.2 Advice on using multi-exciter systems for the testing of large specimens 28
C.2.1 General 28
C.2.2 Data measurements 28
C.2.3 Multi-exciter test fixture 28
C.2.4 Test control 29
C.2.5 Testing 29
C.3 Advice on using multi-axis systems for multi-degree of freedom testing 29
C.3.1 General 29
C.3.2 Data measurements 30
C.3.3 Multi-exciter test fixture 30
C.3.4 Test control 30
C.3.5 Testing 30
C.4 Advice on using multiple shakers attached directly to the specimen via flexible couplings 31
C.4.1 General 31
C.4.2 Data measurements 31
C.4.3 Multi-exciter test fixture 32
C.4.4 Test control 33
C.4.5 Interrelationship in testing 34
Annex D (informative) Guidance on the use of measured data for multi-axis/multi-vibrator tests 35
D.1 General 35
D.2 Use of measured data to derive test severities 35
Annex E (informative) Guidance on the selection of test tolerances 37
E.1 General 37
E.2 Test tolerances associated with measured data 37
E.3 Test tolerances applicable to different parameters 37
Bibliography 39

Figure A.1 – Power Spectral Density (PSD) and Cross-Spectral Density (CSD) for a two exciter system 20
Figure A.2 – Power Spectral Density (PSD) and Cross-Spectral Density (CSD) for a six exciter system 20
Figure C.1 – Examples of spherical bearings 33

Table E.1 – Test tolerances applicable to different parameters 38

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

ENVIRONMENTAL TESTING –

Part 2-86: Tests – Test Fx: Vibration – Multi-exciter and multi-axis method

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 60068-2-86 has been prepared by IEC technical committee 104: Environmental conditions, classification and methods of test. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
104/1035/FDIS	104/1043/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 60068 series, published under the general title *Environmental testing*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

ENVIRONMENTAL TESTING –

Part 2-86: Tests – Test Fx: Vibration – Multi-exciter and multi-axis method

1 Scope

This document provides a test procedure for use with multi-exciter and multi-axis vibration test systems. The vibration test is intended for general application to components, equipment, and other products, hereinafter referred to as "specimens", subjected to dynamic environments that could arise during an equipment life cycle. Although this document is mainly intended for vibration testing, the procedure is also applied to certain types of shock and transient tests.

The test procedure set out in this document is applicable where a specimen is required to demonstrate its adequacy to resist specified vibration, shock and transient conditions, without unacceptable degradation of functional or structural performance. The test procedure has significant similarity to test procedures of other IEC 60068-2 documents and encompasses the same range of vibration and shock excitation types.

This document is applicable to specimens subjected to vibration, shock and transient conditions resulting from transportation and/or operational environments, for example in aircraft, space vehicles and land vehicles. It is primarily intended for unpackaged specimens. It is applicable to specimens in their transportation container when the latter are considered as part of the specimen itself.

The test method and associated techniques addressed within this document are primarily intended for use with multiple electrodynamic or servo-hydraulic vibration generators along with an associated computer-based digital control system to control of the specimen excitations.

This document encompasses two testing approaches, commonly referred to as multi-exciter single-axis (MESA), and multi-exciter multi-axis (MEMA). These are:

a) Utilising fixed base shakers either in a single axis or a selected combination of fixed X, Y, Z configurations, also allowing for rotations dependent upon fixture coupling design.

b) Utilising multiple shakers attached directly to the specimen via flexible couplings or similar methods. Here the shakers are attached at any point and in any direction on the specimen. This approach is quite similar to that used for modal testing, but using environmental test severities.

It is emphasised that MESA and MEMA testing currently requires a high degree of engineering judgement and relevant experience, and both test specifier and tester are fully aware of this fact. Generally, MESA and MEMA testing requires greater resources to set up an appropriate test, but potentially provides a more accurate outcome.

For the purpose of this document, the creator of the relevant testing specification, the test specifier, is expected to select the procedure and the values of severity appropriate to the specimen and its use. Precursor testing is included within the procedure of this document, as an option, to permit the test specifier to establish the practicality of the test specification and severities with the specimen. A separate specimen is usually provisioned for such precursor testing.

The existing single axis, single vibrator test procedures within the IEC 60068-2 series can be used with a wide range of different excitations, such as broad band random, random on random, sine on random, swept sine, shock, and long-time history replication. Theoretically these different forms of excitations, can also be applied using multi-axis and multi-exciter methods. However, suitable techniques and commercially available test control software, for some of these types of testing, are not necessarily currently commonly available. For this reason, the procedure of this document is currently primarily intended for broad band random and time history replication as facilities to undertake these types of tests are commonly available. With that said, the procedure of this document may be adapted, by the user, for other forms of excitation and advice is provided.

Traditionally, vibration, shock and transient test severities are specified using acceleration as the control parameter. However, this is not an essential pre-requisite of the procedure within this document. For the purpose of this document, vibration, shock and transient test severities are specified by the user and may be in the form of acceleration, velocity, displacement, or force. The need to include different control parameters within this document arises because there is a greater likelihood when using multi-exciter testing to specify mixed parameters for control purposes. In which case the vibration, shock and transient waveforms applied to the specimen will be controlled based upon the feedback from transducers measuring the appropriate parameter.

Although primarily intended for electrotechnical specimens, this document is not restricted to them and may be used in other fields where desired.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-1, *Environmental testing – Part 1: General and guidance*

IEC 60068-2-6, *Environmental testing – Part 2-6: Tests –Test Fc: Vibration, (Sinusoidal)*

IEC 60068-2-27, *Environmental testing – Part 2-27: Tests – Test Ea and guidance: Shock*

IEC 60068-2-57, *Environmental testing - Part 2-57: Tests – Test Ff: Vibration – Time-history and sine-beat method*

IEC 60068-2-64, *Environmental testing – Part 2-64: Tests –Test Fh: Vibration, broadband random and guidance*

IEC 60068-2-80, *Environmental testing – Part 2-80: Tests –Test Fi: Vibration – Mixed mode*

IEC 60068-2-85, *Environmental testing – Part 2-85: Tests –Test Fj: Vibration – Long time history replication*

ISO 2041, *Mechanical vibration, shock and condition monitoring – Vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 2041, IEC 60068-1, IEC 60068-2-6, IEC 60068-2-27, IEC 60068-2-57, IEC 60068-2-64, IEC 60068-2-80 and IEC 60068-2-85 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1
multi-exciter single-axis
MESA
method of applying vibration test waveforms using multiple vibration exciters, but all applying the vibrations in a single specimen axis

3.2
multi-exciter multi-axis
MEMA
method of applying vibration test waveforms using multiple vibration exciters in two or more specimen axis

Note 1 to entry: The applied excitations may be in the translation axes, rotational axes or both translation and rotational axes.

3.3
single-input single-output
SISO
method of applying vibration test waveforms using input of a single drive signal to an exciter system in a single-degree of freedom configuration and a single measured output from the test specimen or its fixing points in a single-degree of freedom configuration

Note 1 to entry: This is essentially a conventional single axis/exciter test arrangement using a single measured response for control purposes.

3.4
single-input multiple-output
SIMO
method of applying vibration test waveforms using input of a single drive signal to an exciter system in a single degree of freedom configuration, and multiple measured outputs from the test specimen or its fixing points in a multi-degree of freedom configuration

Note 1 to entry: This is essentially an extension of a conventional single axis/exciter test arrangement, but manipulating multiple measured responses for control purposes.

3.5
multiple-input single-output
MISO
method of applying vibration test waveforms using input of multiple drive signals that are applied to the multiple exciters, to produce a single measured output from the test specimen or its fixing points

Note 1 to entry: Unless the multiple inputs are applying the identical waveform, this arrangement is often not possible as multi-exciter test control systems often require the number of outputs to match the number of inputs.

3.6
multiple-input multiple-output
MIMO
method of applying vibration test waveforms using input of multiple drive signals that are applied to the exciters, to produce multiple measured outputs from the test specimen or its fixing points

Note 1 to entry: Commonly, as a minimum, the number of inputs and outputs should be the same, but many systems used for multi-exciter control, allow the number of outputs to exceed the number of inputs. Commonly, multi-exciter and multi-axis test control systems operate as multiple-input multiple-output systems.

4 Background

4.1 General

The capability to undertake multi-exciter testing has been available for some time for seismic as well as durability / fatigue testing. Generally, such tests utilise excitations which occur at relatively low frequencies. It is only comparatively recently that capabilities have become commonly available to undertake multi-axis and/or multi-exciter tests, at frequencies necessary for general purpose vibration, shock and transient testing.

The use of multi-axis and/or multi-exciter testing equipment [1][1] for certain types of vibration, shock and transient testing is currently perceived as having advantage in a number of applications, some of which are set out below. This list should not be considered as exhaustive as applications for multi-axis and/or multi-exciter testing are still being identified. Broadly the advantages of multi-axis and/or multi-exciter testing include better loading distribution, more realistic excitations, and the potential for test time reduction.

4.2 Multi-axis and/or multi-exciter testing to achieve an improved distribution of dynamic responses

Multi-axis and/or multi-exciter testing is in regular use for large and/or dynamically complex specimens, where there is a need to ensure that the dynamic response motions of the specimen are correctly achieved. In such cases multi-exciter testing can achieve a far more accurate distribution of dynamic responses than the traditional vibration, shock and transient testing methods. This is particularly the case when the specimen would experience, in-service, dynamic excitations from multiple excitation sources. An example of this would be a road vehicle were somewhat different dynamic excitations arise from each wheel.

Using multi-axis and/or multi-exciter testing to achieve an improved distribution of dynamic responses within a specimen, usually requires test severities which are derived from vibration, shock or transient data, measured during actual life cycle conditions. The applied dynamic excitations are commonly controlled from measurements at multiple response locations. This is essentially a "controlled response" test control strategy. This is a fundamentally different control strategy, to that used for the majority of the single axis vibration, shock and transient tests within IEC 60068-2. Those single axis tests are basically "controlled excitation" tests both applying and controlling the excitations to the specimen’s fixing points. Such a control strategy is not profoundly influenced by the dynamic responses of the specimen. Consequently, the test severities for such "controlled excitation" tests can readily adopt "generic" severities as the severities are independent of the dynamic responses of the specimen.

For some applications "generic" severities have advantage in that they may represent a wide range of life cycles conditions. For example, the generic test severities for transportation encompass a range of usage conditions and a variety of transportation platforms. The use of simple generic test severities with multi-axis and/or multi-exciter testing may limit the ability to achieve an accurate distribution of dynamic responses.

---

1 Numbers in square brackets refer to the Bibliography.