IEC 60728-11

Edition 5.0 2023-02
REDLINE VERSION

INTERNATIONAL STANDARD

colour inside

Cable networks for television signals, sound signals and interactive services – Part 11: Safety



IEC 60728-11:2023-02 RLV(en)



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC 60728-11

Edition 5.0 2023-02
REDLINE VERSION

INTERNATIONAL STANDARD

colour inside

Cable networks for television signals, sound signals and interactive services – Part 11: Safety

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.060.40

ISBN 978-2-8322-6530-7

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 6
INTRODUCTION 2
1 Scope 10
2 Normative references 10
3 Terms, definitions, symbols and abbreviated terms 11
3.1 Terms and definitions 12
3.2 Symbols 20
3.3 Abbreviated terms 21
4 Fundamental requirements 22
4.1 General 22
4.2 Mechanical requirements 22
4.2.1 General 22
4.2.2 Equipment design and construction 22
4.2.3 Accessible parts 23
~~4.4 Laser radiation ..... 23~~
4.3 Radiation 23
4.4 Electromagnetic radiation 23
4.5 Thermal protection 23
4.6 Safety in case of fire and fire reaction 23
5 Protection against environmental influences 23
6 Equipotential bonding and earthing 23
6.1 General requirements 23
6.2 Equipotential bonding mechanisms 24
6.3 Equipotential bonding in meshed systems 38
6.3.1 References to other standards 38
6.3.2 General on AC mains 38
6.3.3 AC power distribution and connection of the protective conductor 38
6.3.4 Dangers and malfunction 38
6.3.5 Measures 39
7 Mains-supplied equipment 39
8 Remote power feeding in cable networks 39
8.1 Remote power feeding 40
8.1.1 Maximum allowed voltages 40
8.1.2 General requirements for equipment 40
8.1.3 Current-carrying capacity and dielectric strength of the components 40
8.2 Remote powering from subscriber premises 41
9 Segregation distances and protection against indirect contact ~~and proximity~~ to electric power distribution systems 41
9.1 General 41
9.2 Overhead lines 42
9.2.1 Overhead lines up to 1 000 V 42
9.2.2 Overhead lines above 1 000 V 42
9.3 House installations up to 1 000 V 42
10 System outlets and transfer points 42
10.1 General 42
10.2 System outlet 43

10.2.1 Types of system outlets 43
10.2.2 Fully isolated system outlet 43
10.2.3 Semi-isolated system outlet 43
10.2.4 Non-isolated system outlet with protective element 43
10.2.5 Non-isolated system outlet without protective element 44
10.2.6 Fully-isolated system outlet provided by means of a FTTH system 44
10.3 Transfer point 46
11 Protection against atmospheric overvoltages and elimination of potential differences 47
11.1 General 47
11.2 Protection of the antenna system 48
11.2.1 Selection of appropriate methods for protection of antenna systems 48
11.2.2 Building equipped with a lightning protection system (LPS) 49
11.2.3 Building not equipped with an LPS 60
11.3 Earthing and bonding of the antenna system 66
11.3.1 Internal protection system 66
11.3.2 Earthing conductors 66
11.3.3 Earth termination system 69
11.4 Overvoltage protection 72
12 Mechanical stability 73
12.1 General requirements 73
12.2 Bending moment 73
12.3 Wind-pressure values 75
12.4 Mast construction 75
12.5 Data to be published 76
Annex A (~~informative~~normative) Earth loop impedance 77
A.1 General 77
A.2 Earthing for fault conditions 77
A.3 Earthing to protect against hazardous touch voltage 78
A.4 Temporary safety measures 79
Annex B (informative) Use of shield wires to protect installations with coaxial cables 80
B.1 General 80
B.2 Soil quality determines shield-wiring necessity 80
B.3 Protective measures against direct lightning strikes on underground cables 80
Annex C (informative) Differences in some countries 83
C.1 Subclause 6.1 83
C.1.1 France 83
C.1.2 Japan 83
C.2 Subclause 6.2 83
C.2.1 France 83
C.2.2 Norway 83
C.2.3 Japan and Poland 83
C.3 Subclause 6.3 – Norway 83
C.3.1 Justification 83
C.3.2 Equipotential bonding mechanism for cable networks 84
C.3.3 Use of galvanic isolation in a cable network with remote power feeding 90
C.3.4 Use of voltage dependent protective device in a cable network 91
C.4 Subclause 8.1.1 – Japan 92

C.5 Subclause 9.1 – France 93
C.6 Subclause 9.2 – Japan 93
C.7 Subclause 10.1 93
C.7.1 Sweden 93
C.7.2 UK 93
C.8 Subclause 10.2 – Japan 93
C.9 Subclause 11.1 – Japan 93
C.10 Subclause 11.2 94
C.10.1 Germany 94
C.10.2 Japan 94
C.11 Subclause 11.3.2 – Japan 96
C.12 Subclause 11.3.3 – Japan 96
C.13 Subclause 12.2 – Japan 97
C.14 Subclause 12.3 – Finland 97
Bibliography 98

Figure 1 – Example of equipotential bonding and earthing of a metal enclosure inside a non-conductive cabinet for outdoor-use 26
Figure 2 – Example of equipotential bonding of a building installation 27
Figure 3 – Example of equipotential bonding and indirect earthing of a metal enclosure inside a non-conductive cabinet for outdoor-use 28
Figure 4 – Example of equipotential bonding and earthing of a building installation (underground connection) 30
Figure 5 – Example of equipotential bonding and earthing of a building installation (above ground connection) 32
Figure 6 – Example of equipotential bonding with a galvanic isolated cable entering a building (underground connection) 34
Figure 7 – Example of maintaining equipotential bonding whilst a unit is removed 37
Figure 8 – MDU building installed with FTTH technology 46
Figure 9 – Areas of antenna-mounting in or on buildings, where earthing is not mandatory 48
Figure 10 – Flow chart for selection of the appropriate method for protecting the antenna system against atmospheric overvoltages 51
Figure 11 – Example of equipotential bonded headends and antennas in a protected volume of the building LPS 53
Figure 12 – Example of equipotential bonded headends and antennas in a protected volume of ~~the building LPS~~ an external horizontally isolated ATS 55
Figure 13 – Example of equipotential bonded headends and antennas in a protected volume of an external vertically isolated ATS 57
Figure 14 – Example of equipotential bonded antennas (not installed in a protected volume) and headend with direct connection to building LPS 59
Figure 15 – Example of equipotential bonded headend and earthed antennas (building without LPS) 63
Figure 16 – Example of bonding for antennas and headend (building without LPS and lightning risk lower than or equal to the tolerable risk) 65
Figure 17 – Example of protecting an antenna system (not installed in a protected volume) by additional bonding conductors ($R > R_T$) 69
Figure 18 – Examples of earthing mechanisms ~~(minimum dimensions)~~ 72
Figure 19 – Example of an overvoltage protective device for single dwelling unit 73

Figure 20 – Example of bending moment of an antenna mast 74
Figure A.1 – Systematic of earth loop resistance 78
Figure B.1 – Principle of single shield wire 82
Figure B.2 – Principle of two shield wires 82
Figure C.1 – IT power distribution system in Norway 84
Figure C.2 – Example of installations located farther than 20 m away from a transforming station 85
Figure C.3 – Example of installations located closer than 20 m from a transforming station 86
Figure C.4 – Example of cabinets for cable network with locally fed equipment and mains placed less than 2 m apart 87
Figure C.5 – Example of cabinets for cable network with remotely fed equipment and mains placed less than 2 m apart 88
Figure C.6 – Example of cabinets for cable network with locally fed equipment and mains placed more than 2 m apart 89
Figure C.7 – Example of cabinets for cable network with remotely fed equipment and mains placed more than 2 m apart 90
Figure C.8 – Example of an installation placing the amplifier in front of the galvanic isolator 91
Figure C.9 – Example of protection using a voltage depending device on network installations on poles 92
Figure C.10 – Example of the installation of a safety terminal in Japan 94
Figure C.11 – Examples of installation of a lightning protection system in Japan 96

Table 1 – Maximum allowed operation voltages and maximum recommended currents for coaxial cables ~~in the EN 50117 series~~ 41
Table 2 – Solutions for protection of antenna systems against atmospheric overvoltage 49
Table B.1 – Conductivity of different types of soil 80
Table B.2 – Protection factors (K_p) of protection measures against direct lightning strokes for buried cables 81

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 11: Safety

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 60728-11:2016. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

IEC 60728-11 has been prepared by technical area 5: Cable networks for television signals, sound signals and interactive services, of IEC technical committee 100: Audio, video and multimedia systems and equipment. It is an International Standard.

This fifth edition cancels and replaces the fourth edition published in 2016. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition.

a) Replacement of references to IEC 60065 and IEC 60950-1 with references to IEC 62368-1.
b) Addition of subclauses 4.4 to 4.6.
c) Revised definition of class I equipment, class II equipment, main earthing terminal, see 3.1.6, 3.1.8 and 3.1.31.
d) Addition of definitions for harm, hazard, ordinary person, instructed person, skilled person, see 3.1.22, 3.1.23, 3.1.39, 3.1.40 and 3.1.41.
e) Additional requirement to provide details on the equipment installed, see 4.1.
f) Additional mechanical, design and construction requirements, see 4.2.2.
g) Changes to the accessible part requirements, see 4.2.3.
h) The current carrying capacity and dielectric strength of components is now obligatory, see 8.1.3.
i) The assessment of the risk of lightning strike is now obligatory, see Figure 10.
j) Extension of remote feeding voltage on subscriber feeder, see Table 1.

The text of this standard is based on the following documents:

Draft	Report on voting
100/3866/FDIS	100/3882/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

The list of all the parts of the IEC 60728 series, under the general title *Cable networks for television signals, sound signals and interactive services,* can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Standards and other deliverables of the IEC 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television and sound signals and for processing, interfacing and transmitting all kinds of data signals for interactive services using all applicable transmission media. These signals are typically transmitted in networks by frequency-multiplexing techniques.

This includes for instance:

- regional and local broadband cable networks,
- extended satellite and terrestrial television distribution networks and systems,
- individual satellite and terrestrial television receiving systems,

and all kinds of equipment, systems and installations used in such cable networks, distribution and receiving systems.

The extent of this standardization work is from the antennas and/or special signal source inputs to the headend or other interface points to the network up to the terminal input of the customer premises equipment.

The standardization work will consider coexistence with users of the RF spectrum in wired and wireless transmission systems.

The standardization of any user terminals (i.e. tuners, receivers, decoders, multimedia terminals, etc.) as well as of any coaxial, balanced and optical cables and accessories thereof is excluded.

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 11: Safety

1 Scope

This part of IEC 60728 deals with the safety requirements applicable to fixed sited systems and equipment. As far as applicable, it is also valid for mobile and temporarily installed systems, for example, caravans.

Additional requirements may be applied, for example, referring to:

- electrical installations of buildings and overhead lines,
- other telecommunication services distribution systems,
- water distribution systems,
- gas distribution systems,
- lightning systems.

This document is intended to provide requirements specifically for the safety of the system, personnel working on it, subscribers and subscriber equipment. It deals only with safety aspects and is not intended to define a standard for the protection of the equipment used in the system.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

~~IEC 60065:2014, *Audio, video and similar electronic apparatus – Safety requirements*~~

IEC 60364-1:2005, *Low-voltage electrical installations – Part 1: Fundamental principles, assessment of general characteristics, definitions*

IEC 60364-4-44:2007, *Low-voltage electrical installations – Part 4-44: Protection for safety – Protection against voltage disturbances and electromagnetic disturbances*
IEC 60364-4-44:2007/AMD1:2015
IEC 60364-4-44:2007/AMD2:2018

IEC 60364-5-52:2009, *Low-voltage electrical installations – Part 5-52: Selection and erection of electrical equipment – Wiring systems*

IEC 60364-5-54:2011, *Low-voltage electrical installations – Part 5-54: Selection and erection of electrical equipment – Earthing arrangements and protective conductors*
IEC 60364-5-54:2011/AMD1:2021

IEC 60529:1989, *Degrees of protection provided by enclosures (IP Code)*
IEC 60529:1989/AMD1:1999
IEC 60529:1989/AMD2:2013

~~IEC 60728-2, *Cable networks for television signals, sound signals and interactive services – Part 2: Electromagnetic compatibility for equipment*~~

~~IEC 60825-1, *Safety of laser products – Part 1: Equipment classification and requirements*~~

~~IEC 60825-2, *Safety of laser products – Part 2: Safety of optical fibre communication systems (OFCS)*~~

~~IEC 60950-1:2005, *Information technology equipment – Safety – Part 1: General requirements*~~

IEC 60990:2016, *Methods of measurement of touch current and protective conductor current*

~~IEC 61140:2001, *Protection against electric shock – Common aspects for installation and equipment*~~
~~IEC 61140:2001/AMD1:2004~~

~~IEC 62305 (all parts), *Protection against lightning*~~

IEC 62305-2:2010, *Protection against lightning – Part 2: Risk management*

IEC 62305-3:2010, *Protection against lightning – Part 3: Physical damage to structures and life hazard*

~~IEC 62305-4:2010, *Protection against lightning – Part 4: Electrical and electronic systems within structures*~~

IEC 62368-1:2018, *Audio/video, information and communication technology equipment – Part 1: Safety requirements*

IEC 62561-1:2017, *Lightning protection system components (LPSC) – Part 1: Requirements for connection components*

IEC 62561-2, *Lightning protection system components (LPSC) – Part 2: Requirements for conductors and earth electrodes*

~~ISO 3864-1:2011, *Graphical symbols – Safety colours and safety signs – Part 1: Design principles for safety signs in workplaces and public areas*~~

ISO 7010, *Graphical symbols – Safety colours and safety signs – Registered safety signs*

ISO/IEC 30129:2015, *Information technology – Telecommunications bonding networks for buildings and other structures*
ISO/IEC 30129:2015/AMD1:2019

~~EN 50117 (all parts), *Coaxial cables*~~

~~EN 50164-1, *Lightning Protection Components (LPC) – Part 1: Requirements for connection components*~~

~~EN 50164-2, *Lightning Protection Components (LPC) – Part 2: Requirements for conductors and earth electrodes*~~

~~EN 50174-2, *Information technology – Cabling installation – Part 2: Installation planning and practices inside buildings*~~

~~EN 50310, *Application of equipotential bonding and earthing in buildings with information technology equipment*~~

EN 50575:2014, *Power, control and communication cables – Cables for general applications in construction works subject to reaction to fire requirements*

3 Terms, definitions, symbols and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp.

~~NOTE Some terms have been taken from IEC 60050-195, IEC 60050-826 and IEC 60050-851, with the reference number in square brackets, and from other IEC standards, also referenced to in square brackets.~~

3.1.1
air-termination system
part of an external LPS using metallic elements such as rods, mesh conductors or catenary wires intended to intercept lightning flashes

[SOURCE: IEC 62305-3:2010, 3.6]

3.1.2
amplifier
device to compensate for attenuation

3.1.3
attenuation
ratio of the input power to the output power

Note 1 to entry: The ratio is expressed in decibels.

3.1.4
cable networks
television signals, sound signals and interactive services, regional and local broadband cable networks, extended satellite and terrestrial television distribution networks or systems and individual satellite and terrestrial television receiving systems

Note 1 to entry: These networks and systems can be used in downstream and upstream directions.

3.1.5
CATV network
regional and local broadband cable networks designed to provide sound and television signals as well as signals for interactive services to a regional or local area

Note 1 to entry: Originally defined as Community Antenna Television network.

3.1.6
class I equipment
~~equipment with basic insulation as provision for basic protection and protective bonding as provision for fault protection, in accordance with IEC 61140:2001, 7.1~~

~~[SOURCE: IEC 60050-851:2008, 851-15-10]~~

equipment in which protection against electric shock does not rely on basic insulation only, but that includes a supplementary safeguard in such a way that means are provided for the connection of accessible conductive parts to the protective earthing conductor in the fixed wiring of the installation

Note 1 to entry: For equipment intended for use with a flexible cord or cable, this provision includes a protective conductor as part of the flexible cord or cable.

Note 2 to entry: Class I equipment can be provided with class II construction.

Note 3 to entry: This entry is based on IEC 62368-1:2018, 3.3.15.1.

3.1.7
class II construction
part of an equipment for which protection against electric shock relies upon double insulation or reinforced insulation

Note 1 to entry: This entry is based on IEC 62368-1:2018, 3.3.15.2.

3.1.8
class II equipment
~~equipment with basic insulation as provision for basic protection, and supplementary insulation as provision for fault protection, or in which basic and fault protection are provided by reinforced insulation, in accordance with IEC 61140:2001, 7.3~~

~~[SOURCE: IEC 60050-851:2008, 851-15-11]~~

equipment in which protection against electric shock does not rely on basic insulation only, but in which a supplementary safeguard is provided, there being no provision for protective earthing or reliance upon installation conditions

Note 1 to entry: This entry is based on IEC 62368-1:2018, 3.3.15.3.

3.1.9
earthing arrangement
~~all the electric connections and devices involved in the earthing of a system, an installation and equipment~~

~~[SOURCE: IEC 60050-195:1998, 195-02-20, modified – The preferred term "grounding arrangement (US), and the deprecated term "earthing system" have been deleted.]~~

all electrical means involved in the earthing of a system, installation or equipment

Note 1 to entry: Electric connection and devices used for earthing are examples of electrical means.

[SOURCE: IEC 60050-195:2021, 195-02-20, modified – The preferred term "grounding arrangement (US)" has been deleted.]

3.1.10
earthing conductor
~~conductor which provides a conductive path, or part of the conductive path, between a given point in a system or in an installation or in equipment and an earth electrode or an earth-electrode network~~

~~Note 1 to entry: In the electrical installation of a building, the given point is usually the main earthing terminal, and the earthing conductor connects this point to the earth electrode or the earth-electrode network.~~

~~[SOURCE: IEC 60050-826:2004, 826-13-12, modified – The preferred term "grounding conductor (US)", and the deprecated term "earth conductor" have been deleted.]~~

conductor forming a conductive path between a conductive part and an earth electrode

EXAMPLE A conductor connected between a main earthing terminal or busbar and an earth electrode.

[SOURCE: IEC 60050-195:2021, 195-02-03, modified – The preferred term "grounding conductor (US)" has been deleted.]

3.1.11
earth electrode
~~conductive part, which may be embedded in the soil or in a specific conductive medium, e.g. concrete or coke, in electric contact with the Earth~~

~~[SOURCE: IEC 60050-826:2004, 826-13-05, modified – The preferred term "ground electrode (US)" has been deleted.]~~

conductive part that is in electric contact with local earth, directly or through an intermediate conductive medium

[SOURCE: IEC 60050-195:2021, 195-02-01, modified – The preferred term "grounding electrode (US)" has been deleted.]

3.1.12
earthing terminal
terminal provided on equipment ~~or on a device~~ and intended for the electric connection with the earthing arrangement

[SOURCE: IEC 60050-195:~~1998~~2021, 195-02-31, modified – The preferred term "grounding terminal (US)"~~, and the deprecated term "earth terminal" have~~ has been deleted.]

3.1.13
electric shock
physiological effect resulting from an electric current passing through a human or ~~animal body~~ livestock

[SOURCE: ~~IEC 60050-826:2004, 826-12-01~~ IEC 60050-195:2021, 195-01-04, modified – The specific use <protection against electric shock> has been deleted.]

3.1.14
equipotential bonding
~~provision of electric connections between conductive parts, intended to achieve equipotentiality~~

~~[SOURCE: IEC 60050-826:2004, 826-13-19]~~

set of electric connections intended to achieve equipotentiality between conductive parts

[SOURCE: IEC 60050-195:2021, 195-01-10]

3.1.15
equipotential bonding bar
busbar which is part of an equipotential bonding system and enables the electric connection of a number of conductors for equipotential bonding purposes

[SOURCE: IEC 60050-826:~~2004~~2022, 826-13-35]

3.1.16
protective bonding conductor
protective conductor provided for protective-equipotential-bonding

[SOURCE: ~~IEC 60050-826:2004, 826-13-24, modified – The deprecated term "equipotential bonding conductor" has been deleted~~ IEC 60050-195:2021, 195-02-10.]

3.1.17
exposed conductive part
conductive part of equipment that can be touched and that is not ~~normally~~ live under normal conditions, but that can become live when basic insulation fails

[SOURCE: IEC 60050-195:~~1998~~2021, 195-06-10]

~~**3.1.17**~~
~~**extended satellite television distribution network or system**~~
~~distribution network or system designed to provide sound and television signals received by satellite receiving antenna to households in one or more buildings~~

~~Note 1 to entry: This kind of network or system can be combined with terrestrial antennas for the additional reception of TV and/or radio signals via terrestrial networks.~~

~~Note 2 to entry: This kind of network or system can also carry control signals for satellite switched systems or other signals for special transmission systems (e.g. MoCA or WiFi) in the return path direction.~~

3.1.18
extended terrestrial television distribution network or system
distribution network or system designed to provide sound and television signals received by terrestrial receiving antenna to households in one or more buildings

Note 1 to entry: This kind of network or system can possibly be combined with a satellite antenna for the additional reception of TV and/or radio signals via satellite networks.

Note 2 to entry: This kind of network or system can also carry other signals for special transmission systems (e.g. MoCA or Wi-Fi) in the return path direction.

3.1.19
extraneous conductive part
conductive part not forming part of the electrical installation and ~~liable~~ that is likely to introduce an electric potential, generally the electric potential of a local earth

[SOURCE: IEC 60050-195:~~1998~~2021, 195-06-11]

3.1.20
feeder
transmission path forming part of a cable network

Note 1 to entry: Such a path may consist of a metallic cable, optical fibre, waveguide or any combination of them.

Note 2 to entry: By extension, the term is also applied to paths containing one or more radio links.

3.1.21
galvanic isolator
device providing electrical isolation below a certain frequency range

3.1.22
harm
physical injury or damage to persons, property, and domestic animals

Note 1 to entry: Physical injury or damage to persons also includes health aspects.

Note 2 to entry: This entry is based on ISO/IEC Guide 51:2014, 3.1.

3.1.23
hazard
potential source of harm

Note 1 to entry: The term hazard can be qualified in order to define its origin (e.g. electrical hazard, mechanical hazard) or the nature of the potential harm (e.g. electric shock hazard, cutting hazard, toxic hazard, fire hazard).

Note 2 to entry: This entry is based on ISO/IEC Guide 51:2014, 3.2.

3.1.24
hazardous voltage
electrical condition of an object from which a hazardous touch current (electric shock) could be drawn

[SOURCE: IEC 60065:2014, 2.6.10, modified – The term "hazardous live" has been replaced by "hazardous voltage".]

3.1.25
headend
equipment connected between receiving antennas or other signal sources and the remainder of the cable network, to process the signals to be distributed

3.1.26
home distributor
HD
physical distribution point within a home where cables terminate

Note 1 to entry: This note applies to the French language only.

~~**3.1.25**~~
~~**individual satellite television receiving system**~~
~~system designed to provide sound and television signals received from satellite(s) to an individual household~~

~~Note 1 to entry: This kind of system can also carry control signals for satellite switched systems or other signals for special transmission systems (e.g. MoCA or WiFi) in the return path direction.~~

3.1.27
individual terrestrial television receiving system
system designed to provide sound and television signals received via terrestrial broadcast networks to an individual household

Note 1 to entry: This kind of system can also carry other signals for special transmission systems (e.g. MoCA or Wi-Fi) in the return path direction.

3.1.28
let-go threshold current
~~maximum~~ value of the maximum electric current through the human body ~~of a person~~ at which that ~~person~~ human being can release himself or herself

[SOURCE: IEC 60050-195:~~1998~~2021, 195-03-09~~, modified – Current has been included in the preferred term and the deprecated terms "releasing current" and "let-go current (US)" have been deleted~~.]

3.1.29
lightning protection system
LPS
complete system used to ~~protect a space against the effects of lightning consisting of both external and internal lightning protection systems~~ reduce physical damage due to lightning flashes to a structure

Note 1 to entry: ~~In particular cases, an LPS may consist of an external LPS or an internal LPS only.~~ It consists of both external and internal lightning protection systems.

[SOURCE: IEC 62305-3:2010, 3.1]

3.1.30
local broadband cable network
network designed to provide sound and television signals as well as signals for interactive services to a local area (e.g. one town or one village)

3.1.31
main earthing terminal
main earthing bar
terminal or busbar that is part of the earthing arrangement of an installation and enabling the electric connection of a number of conductors used for earthing or bonding purposes

[SOURCE: ~~IEC 60050-826:2004, 826-13-15~~ IEC 60050-195:2021, 195-02-33, modified – The preferred terms "main grounding terminal (US)" and "main grounding busbar (US)" have been deleted and, in the term, "busbar" has been abbreviated to "bar".]

3.1.32
MATV network
extended terrestrial television distribution networks or systems designed to provide sound and television signals received by terrestrial receiving antenna to households in one or more buildings

Note 1 to entry: Originally defined as master antenna television network.

Note 2 to entry: This kind of network or system can possibly be combined with a satellite antenna for the additional reception of TV and/or radio signals via satellite networks.

Note 3 to entry: This kind of network or system can also carry other signals for special transmission systems (e.g. MoCA or Wi-Fi) in the return path direction.

3.1.33
metal installation
extended metal items in the structure to be protected which may form a path for lightning current, such as pipework, staircases, elevator guide rails, ventilation, heating and air conditioning ducts, and interconnected reinforcing steel

[SOURCE: IEC 62305-3:2010, 3.18]

3.1.34
multiple-stranded conductor
stranded conductor consisting of a number of groups of wires assembled together in one or more helical layers, the wires in each group being either bunched or stranded

[SOURCE: IEC 60050-461:2008, 461-01-10]

3.1.35
natural component of LPS
conductive component installed not specifically for lightning protection which can be used in addition to the LPS or in some cases could provide the function of one or more parts of the LPS

Note 1 to entry: Examples of the use of this term include:

- natural air-termination;
- natural down-conductor;
- natural earthing electrode.

[SOURCE: IEC 62305-3:2010, 3.15]

3.1.36
network interface unit
NIU
interface between the cable network and the network inside an apartment

Note 1 to entry: The network interface unit can contain an overvoltage protective element and/or a galvanic isolation.

Note 2 to entry: This note applies to the French language only.

3.1.37
neutral conductor
~~**N conductor**~~
conductor electrically connected to the neutral point and capable of contributing to the distribution of electric energy

[SOURCE: ~~IEC 60050-826:2004, 826-14-07, modified – An identifaction symbol has been added~~ IEC 60050-195:2021, 195-02-06.]

3.1.38
PEN conductor
conductor combining the functions of both a protective earthing conductor and a neutral conductor

~~Note 1 to entry: The acronym PEN results from the combination of both symbols PE for the protective conductor and N for neutral conductor.~~

[SOURCE: ~~IEC 60050-826:2004, 826-13-25, modified – An note to entry has been added~~ IEC 60050-195:2021, 195-02-12.]

3.1.39
ordinary person
person other than an electrically instructed person and an electrically skilled person

Note 1 to entry: Ordinary persons include not only users of the equipment, but also all persons who may have access to the equipment or who may be in the vicinity of the equipment. Under normal operating conditions or abnormal operating conditions, ordinary persons should not be exposed to parts comprising energy sources capable of causing pain or injury. Under single fault condition, ordinary persons should not be exposed to parts comprising energy sources capable of causing injury.

3.1.40
electrically instructed person
person who has been electrically instructed and trained by an electrically skilled person, or who is supervised by an electrically skilled person, to identify energy sources that may cause pain and to take precautions to avoid unintentional contact with or exposure to those energy sources

Note 1 to entry: Under normal operating conditions, abnormal operating conditions or single fault conditions, electrically instructed persons should not be exposed to parts comprising energy sources capable of causing injury.

3.1.41
electrically skilled person
person who has training or experience in the technology of the equipment, particularly in knowing the various energies and energy magnitudes used in the equipment

Note 1 to entry: Electrically skilled persons are expected to use their training to and experience to recognise energy sources capable of causing pain or injury and to take action for protection from injury from those energies. Electrically skilled persons should also be protected against unintentional contact or exposure to energy sources capable of causing injury.

3.1.42
protective conductor
PE conductor
conductor provided for purposes of electrical safety~~, for example protection against electric shock~~

~~Note 1 to entry: In an electrical installation, the conductor identified PE is normally also considered as protective earthing conductor.~~

[SOURCE: ~~IEC 60050-826:2004, 826-13-22, modified – An identifaction symbol has been added~~ IEC 60050-195:2021, 195-12-09, modified – The term "PE conductor" has been added.]

3.1.43
receiver lead
lead, which connects the system outlet to the subscriber equipment

3.1.44
receiving antenna
device with proper electrical characteristics that intercepts desired signals in the atmosphere and transfers these to the remainder of the cable network

3.1.45
regional broadband cable network
network designed to provide sound and television signals as well as signals for interactive services to a regional area covering several towns and/or villages

3.1.46
remote power feeding voltage
voltage for supplying power to network equipment via the cable network or a separate line

3.1.47
safety distance
minimum distance between two conductive parts within the space to be protected between which no dangerous sparking can occur

~~**3.1.43**~~
~~**service person**~~
~~person having appropriate technical training and experience necessary to be aware of hazards to which that person may be exposed in performing a task and of measures to minimize the risks to that person or other persons~~

~~[SOURCE: IEC 60950-1:2005, 1.2.13.5]~~

3.1.48
SMATV network
extended distribution networks or systems designed to provide sound and television signals received by satellite receiving antenna to households in one or more buildings

Note 1 to entry: Originally defined as satellite master antenna television network.

Note 2 to entry: This kind of network or system can possibly be combined with terrestrial antennas for the additional reception of TV and/or radio signals via terrestrial networks.

Note 3 to entry: This kind of network or system can also carry control signals for satellite switched systems or other signals for special transmission systems (e.g. MoCA or Wi-Fi) in the return path direction.

3.1.49
splitter
spur unit
device in which the signal power at the (input) port is divided equally or unequally between two or more (output) ports

Note 1 to entry: Some forms of this device may be used in the reverse direction for combining signal energy.

3.1.50
spur feeder
feeder to which splitters, subscriber taps or looped system outlets are connected

3.1.51
subscriber equipment
equipment at the subscriber premises such as receivers, tuners, decoders, video recorders, multimedia terminals

3.1.52
subscriber feeder
feeder connecting a subscriber tap to a system outlet or, where the latter is not used, direct to the subscriber equipment.

Note 1 to entry: The subscriber feeder can consist of either a coaxial cable, a fibre optic cable or an armoured fibre optic cable.

3.1.53
subscriber tap
device for connecting a subscriber feeder to a spur feeder

3.1.54
surge protective device
device that is intended to limit transient overvoltage and divert surge currents

Note 1 to entry: A surge protective device contains at least one non-linear component.

3.1.55
surge suppressor
device designed to limit the surge voltage between two parts within the space to be protected, such as spark gap, surge diverter or semiconductor device

3.1.56
system outlet
device for interconnecting a subscriber feeder and a receiver lead

3.1.57
touch voltage
<effective> voltage between conductive parts when touched simultaneously by a ~~person~~ human being or ~~an animal~~ livestock


Note 1 to entry: The value of the ~~effective~~ touch voltage ~~may be appreciably~~ is influenced by the impedance of the ~~person~~ human being or the ~~animal~~ livestock in electric contact with these conductive parts.

[SOURCE: ~~IEC 60050-826:2004, 826-11-05~~ IEC 60050-195:2021, 195-05-11.]

3.1.58
transfer point
interface between the cable network and the building's internal network, each of which may be separately owned and which may contain a voltage-dependent device and/or galvanic isolator

3.2 Symbols


The following graphical symbols are used in the figures of this document. These symbols are either listed in IEC 60617 or based on symbols defined in IEC 60617.



Coaxial conductor
[IEC 60617-S00011:
2001-07-01]



Amplifier
[IEC 60617-S01240:
2001-07-01]



System outlet



Galvanic isolator



Overvoltage protective device



Coaxial overvoltage protective device

3.3 Abbreviated terms

AC	alternating current
AM	amplitude modulation
ATS	air termination system
CATV	community antenna television (network)
COPD	coaxial overvoltage protective device
DC	direct current
DTH	direct to home
HD	home distributor
FTTH	fibre to the home
IP	international protection (class)
IT	isolated earth
LNB	low noise block converter
LPS	lightning protection system
LSR	lightning stroke risk
MATV	master antenna television (network)
MDU	multi dwelling unit
N	neutral (conductor)
NIU	network interface unit
NTP	network termination point
OPD	overvoltage protective device
OTP	optical transfer point
PE	protective conductor
PEN	PEN conductor
RCD	residual current device
RF	radio frequency
RMS	root mean square
SMATV	satellite master antenna television (network)
SPD	surge protective device
STB	set top box
TV	television