IEC 60747-5-6

Edition 2.0 2021-07

INTERNATIONAL STANDARD

Semiconductor devices –
Part 5-6: Optoelectronic devices – Light emitting diodes

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.080.99

ISBN 978-2-8322-9853-4

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 8
1 Scope 10
2 Normative references 10
3 Terms, definitions and abbreviations 11
3.1 General terms and definitions 11
3.2 Terms and definitions relating to the measurement of the quantity of radiation 14
3.3 Terms and definitions relating to the measurement of the photometric quantity 17
3.4 Terms and definitions relating to the measurement of the thermal quantity 21
3.5 Abbreviations 22
4 Absolute maximum ratings 22
5 Electrical and optical characteristics 23
6 Measuring method 24
6.1 Basic requirements 24
6.1.1 Measuring conditions 24
6.1.2 Measuring instruments and equipment 25
6.1.3 Essential requirements 26
6.1.4 General precautions 27
6.2 Forward voltage (V_F) measurement 27
6.2.1 Purpose 27
6.2.2 Circuit diagram 27
6.2.3 Requirements 27
6.2.4 Measurement procedure 29
6.2.5 Precautions to be observed 29
6.2.6 Specified conditions 29
6.3 Reverse voltage (V_R) measurement 29
6.3.1 Purpose 29
6.3.2 Circuit diagram 29
6.3.3 Measurement procedure 29
6.3.4 Precautions to be observed 30
6.3.5 Specified conditions 30
6.4 Differential resistance (r_f) measurement 30
6.4.1 Purpose 30
6.4.2 Circuit diagram 30
6.4.3 Requirements 30
6.4.4 Measurement procedure 30
6.4.5 Precautions to be observed 31
6.4.6 Specified conditions 31
6.5 Reverse current (I_R) measurement 31
6.5.1 Purpose 31
6.5.2 Circuit diagram 31
6.5.3 Provisions 32
6.5.4 Measurement procedure 32
6.5.5 Precautions to be observed 32

6.5.6 Specified conditions 32
6.6 Measurement of capacitance between terminals (C_t) 32
6.6.1 General 32
6.6.2 Measurement using LCR meter 33
6.6.3 Measurement using AC bridge 33
6.7 Measurement of junction temperature (T_j) and thermal resistance ($R_{th(j-X)el}$, $R_{th(j-X)real}$) 35
6.7.1 Purpose 35
6.7.2 Measurement principle 35
6.7.3 Measurement procedure 37
6.7.4 Precautions to be observed 42
6.7.5 Specified conditions 42
6.8 Response time measurement 42
6.8.1 Purpose 42
6.8.2 Circuit diagram 42
6.8.3 Provisions 43
6.8.4 Measurement procedure 43
6.8.5 Precautions to be observed 43
6.8.6 Specified conditions 44
6.9 Frequency response and cut-off frequency (f_c) measurement 44
6.9.1 Purpose 44
6.9.2 Circuit diagram 44
6.9.3 Provisions 45
6.9.4 Measurement procedure 45
6.9.5 Precautions to be observed 46
6.9.6 Specified conditions 46
6.10 Luminous flux (Φ_v) measurement 46
6.10.1 Purpose 46
6.10.2 Measurement principle 46
6.10.3 Measuring circuit 46
6.10.4 Measurement procedure 47
6.10.5 Precautions to be observed 47
6.10.6 Measurement conditions to be defined 48
6.11 Radiant flux (Φ_e) measurement 48
6.11.1 Purpose 48
6.11.2 Measurement principle 48
6.11.3 Measuring circuit 49
6.11.4 Measurement procedure 49
6.11.5 Precautions to be observed 49
6.11.6 Measurement conditions to be defined 50
6.12 Luminous intensity (I_v) measurement 50
6.12.1 Purpose 50
6.12.2 Measurement principle 50
6.12.3 Measuring circuit 51
6.12.4 Measurement procedure 52
6.12.5 Precautions to be observed 52
6.12.6 Measurement conditions to be defined 52
6.13 Radiant intensity (I_e) measurement 52

6.13.1 Purpose 52
6.13.2 Measurement principle 52
6.13.3 Measuring circuit 53
6.13.4 Measurement procedure 53
6.13.5 Measurement conditions to be defined 53
6.14 Luminance (L_V) measurement 53
6.14.1 Purpose 53
6.14.2 Measuring circuit 54
6.14.3 Measurement procedure 54
6.14.4 Measurement conditions to be defined 54
6.15 Emission spectrum distribution, peak emission wavelength (λ_p), and spectral half bandwidth ($\Delta\lambda$) measurement 55
6.15.1 Purpose 55
6.15.2 Measuring circuit 55
6.15.3 Measurement procedure 56
6.15.4 Measurement conditions to be defined 57
6.16 Chromaticity measurement 57
6.16.1 Purpose 57
6.16.2 Measurement principle 57
6.16.3 Measuring circuit 60
6.16.4 Measurement procedure 60
6.16.5 Measuring conditions to be defined 60
6.17 Directional characteristics and full width half maximum of an intensity measurement 60
6.17.1 Purpose 60
6.17.2 Measuring circuit 61
6.17.3 Measurement procedure 61
6.17.4 Measuring conditions to be defined 62
6.18 Illuminance (E_V) measurement 63
6.18.1 Purpose 63
6.18.2 Measuring circuit 63
6.18.3 Measurement procedure 63
6.18.4 Measuring conditions to be defined 63
7 Items to be indicated on the package 63
8 Quality evaluation 64
8.1 General 64
8.2 Classification of quality evaluations 64
8.2.1 General 64
8.2.2 Classification I 64
8.2.3 Classification II 64
8.2.4 Classification III 64
8.2.5 Precautions to be observed 64
8.3 Quality evaluation test 70
8.3.1 General 70
8.3.2 Specimens 71
8.4 Lot quality inspection 71
8.4.1 General 71
8.4.2 Specimens 71

8.5 Periodical quality inspection 71
8.5.1 General 71
8.5.2 Specimens 71
8.5.3 Inspection period 71
8.6 Easing of the lot quality inspection standards 71
8.7 Periodical evaluation maintenance tests 72
8.7.1 Test items and specimens 72
8.7.2 Test period 72
8.8 Long-term storage products 72
8.9 Continuous current test 72
8.9.1 General 72
8.9.2 Initial measurement 72
8.9.3 Test circuits 72
8.9.4 Test conditions 73
8.9.5 Post-treatment 73
8.9.6 Final measurement 73
Annex A (normative) Standard luminous efficiency 74
Annex B (normative) How to obtain the self-absorption correction factor 77
B.1 Purpose 77
B.2 LED light sources for self-absorption measurement 77
B.3 Method 77
Annex C (normative) How to obtain the colour correction factor 79
C.1 Purpose 79
C.2 Method 79
C.2.1 Luminous flux and luminous intensity measurement 79
C.2.2 Radiant flux and radiant intensity measurement 80
Annex D (normative) Calibration of the luminance meter 81
D.1 Purpose 81
D.2 How to perform the calibration 81
Annex E (normative) Colour-matching function of the XYZ colour system 83
Annex F (normative) Spectral chromaticity coordinates 88
Annex G (normative) Illuminance meter calibration 93
G.1 Purpose 93
G.2 How to perform the calibration 93
Bibliography 94

Figure 1 – Radiant intensity 15
Figure 2 – Radiance 16
Figure 3 – Radiant exitance 16
Figure 4 – Irradiance 17
Figure 5 – Spectral luminous efficiency 18
Figure 6 – Circuit diagram for V_F measurement 27
Figure 7 – Circuit diagram for V_F measurement with a constant voltage source and a current-limiting resistor 28
Figure 8 – Circuit diagram for V_F measurement using an SMU 28
Figure 9 – Circuit diagram for V_R measurement 29

Figure 10 – Circuit diagram for r_f measurement 30
Figure 11 – Circuit diagram for I_R measurement 32
Figure 12 – Circuit diagram for C_t measurement 33
Figure 13 – Circuit diagram for C_t measurement 34
Figure 14 – An example of the temperature dependence of η_{PE} 35
Figure 15 – Heating time duration dependence of the measured thermal resistance 36
Figure 16 – Cumulative thermal capacitance versus cumulative thermal resistance characteristics (structural function) 37
Figure 17 – Circuit diagram for measurement of change in V_F 38
Figure 18 – Change in V_F during the measurement 39
Figure 19 – Example of the time variation in V_F 40
Figure 20 – Transient vibration waveform immediately after the heating is off 40
Figure 21 – Circuit diagram for response time measurement 42
Figure 22 – Waveform of response time measurement 44
Figure 23 – Circuit diagram for f_c measurement 45
Figure 24 – Circuit diagram for Φ_V measurement 47
Figure 25 – Circuit diagram for Φ_e measurement 49
Figure 26 – Schematic diagram for I_V measurement 51
Figure 27 – Circuit diagram for I_V measurement 51
Figure 28 – Circuit diagram for I_e measurement 53
Figure 29 – Circuit diagram for L_v measurement 54
Figure 30 – Circuit diagram for λ_p measurement 55
Figure 31 – Circuit diagram for λ_p measurement 56
Figure 32 – Schematic diagram of $\Delta\lambda$ measurement 57
Figure 33 – Chromaticity 59
Figure 34 – Circuit diagram for chromaticity measurement 61
Figure 35 – Directional characteristics (example 1) 62
Figure 36 – Directional characteristics (example 2) 62
Figure 37 – Circuit diagram for E_v measurement 63
Figure 38 – Circuit diagram for continuous current test 73
Figure B.1 – Schematic diagram for self-absorption measurement 77
Figure D.1 – Schematic diagrams for calibration 82
Figure G.1 – Schematic diagram for calibration 93

Table 1 – Absolute maximum ratings 22
Table 2 – Electrical and optical characteristics 23
Table 3 – CIE averaged LED intensity measurements 51
Table 4 – Items for the screening test and their conditions(reference) 64
Table 5 – Quality evaluation tests 65
Table 6 – Lot quality inspection 67

Table 7 – Periodical quality inspection 70
Table A.1 – Definitive values of the spectral luminous efficiency function for photopic vision $V(\lambda)$ 74
Table E.1 – Colour-matching function of the XYZ colour system 83
Table F.1 – Spectral chromaticity coordinates 88

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

SEMICONDUCTOR DEVICES –

Part 5-6: Optoelectronic devices – Light emitting diodes

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 60747-5-6 has been prepared by subcommittee 47E: Discrete semiconductor devices, of IEC technical committee 47: Semiconductor devices. It is an International Standard.

This second edition cancels and replaces the first edition published in 2016. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) ultraviolet-emitting diodes (UV LED) and their related technical contents were added;
b) power efficiency (η_{PE}) as part of electrical and optical characteristics were added;
c) new measuring methods related to thermal resistance were added;
d) hydrogen sulphide corrosion test was added to quality evaluation;
e) some standards were added to the bibliography.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
47E/745/FDIS	47E/752/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 60747 series, published under the general title *Semiconductor devices*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

SEMICONDUCTOR DEVICES –

Part 5-6: Optoelectronic devices – Light emitting diodes

1 Scope

This part of IEC 60747 specifies the terminology, the essential ratings and characteristics, the measuring methods and the quality evaluations of light emitting diodes (LEDs) for general industrial applications such as signals, controllers, sensors, etc.

LEDs for lighting applications are out of the scope of this part of IEC 60747.

LEDs are classified as follows:

a) LED package;
b) LED flat illuminator;
c) LED numeric display and alpha-numeric display;
d) LED dot-matrix display;
e) infrared-emitting diode (IR LED);
f) ultraviolet-emitting diode (UV LED).

LEDs with a heat spreader or having a terminal geometry that performs the function of a heat spreader are within the scope of this part of IEC 60747.

An integration of LEDs and controlgears, integrated LED modules, semi-integrated LED modules, integrated LED lamps or semi-integrated LED lamps, are out of the scope of this part of IEC 60747.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60051 (all parts), *Direct acting indicating analogue electrical measuring instruments and their accessories*

IEC 60068-2-17, *Basic environmental testing procedures – Part 2-17: Tests – Test Q: Sealing*

IEC 60068-2-30, *Environmental testing – Part 2-30: Tests – Test Db: Damp heat, cyclic (12 h + 12 h cycle)*

IEC 60747-5-13, *Semiconductor devices – Part 5-13: Optoelectronic devices – Hydrogen sulphide corrosion test for LED packages*

IEC 60749-6, *Semiconductor devices – Mechanical and climatic test methods – Part 6: Storage at high temperature*

IEC 60749-10, *Semiconductor devices – Mechanical and climatic test methods – Part 10: Mechanical shock*

IEC 60749-12, *Semiconductor devices – Mechanical and climatic test methods – Part 12: Vibration, variable frequency*

IEC 60749-14, *Semiconductor devices – Mechanical and climatic test methods – Part 14: Robustness of terminations (lead integrity)*

IEC 60749-15, *Semiconductor devices – Mechanical and climatic test methods – Part 15: Resistance to soldering temperature for through-hole mounted devices*

IEC 60749-20, *Semiconductor devices – Mechanical and climatic test methods – Part 20: Resistance of plastic encapsulated SMDs to the combined effect of moisture and soldering heat*

IEC 60749-21, *Semiconductor devices – Mechanical and climatic test methods – Part 21: Solderability*

IEC 60749-24, *Semiconductor devices – Mechanical and climatic test methods – Part 24: Accelerated moisture resistance – Unbiased HAST*

IEC 60749-25, *Semiconductor devices – Mechanical and climatic test methods – Part 25: Temperature cycling*

IEC 60749-36, *Semiconductor devices – Mechanical and climatic test methods – Part 36: Acceleration, steady state*

ISO 2859-1, *Sampling procedures for inspection by attributes – Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection*