IEC 60810

Edition 5.0 2017-09

REDLINE VERSION

colour inside

Lamps, light sources and led packages for road vehicles – Performance requirements

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.140.99

ISBN 978-2-8322-4855-3

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 8
1 Scope 10
2 Normative references 10
3 Terms and definitions 12
4 Requirements and test conditions for filament lamps 16
4.1 Basic function and interchangeability 16
4.2 Torsion strength 16
4.3 Characteristic life T_C 17
4.4 Life B_3 17
4.5 Luminous flux maintenance 17
4.6 Resistance to vibration and shock 17
4.7 Glass-bulb strength 18
5 Filament lamp data 18
6 Requirements and test conditions for discharge lamps 23
6.1 Basic function and interchangeability 23
6.2 Mechanical strength 23
6.2.1 Bulb-to-cap connection 23
6.2.2 Cable-to-cap connection (if any) 23
6.3 Characteristic life T_C 23
6.4 Life B_3 23
6.5 Luminous flux maintenance 23
6.6 Resistance to vibration and shock 23
6.7 Discharge lamps with integrated starting device 23
6.8 Discharge lamps with integrated starting device and integrated ballast 24
7 Requirements and test conditions for LED light sources 24
7.1 Basic function and interchangeability 24
7.2 UV radiation 25
7.3 Luminous flux and colour maintenance 25
7.4 Resistance to vibration and shock 27
7.5 Electromagnetic compatibility 28
7.6 Powered thermal cycling test 28
7.7 Mass 29
7.8 Typical circuits for LED light sources 29
7.8.1 General 29
7.8.2 Typical circuits for LR3, LR5, LY3, LY5, LW3 and LW5 LED light sources 29
7.8.3 Typical circuits for LR4 LED light sources 30
7.9 Maximum power consumption 31
7.10 Overvoltage test 31
7.11 Reverse voltage test 31
7.12 Transient voltage test (field decay) 32
7.13 Transient voltage test (load dump) 33
7.14 Electrostatic discharge test (ESD) 34
7.15 Pulsed operating life (PLT) test 34
8 Requirements and test conditions for LED packages 34
8.1 LED package stress test qualification 34

8.2 Test samples 35
8.2.1 Lot requirements 35
8.2.2 Production requirements 35
8.2.3 Pre- and post-stress test requirements 36
8.2.4 Assembly of LED packages on test boards 36
8.2.5 Moisture pre-conditioning (MP) 36
8.2.6 Thermal resistance (TR) test 36
8.3 Definition of failure criteria 36
8.4 Choice between test conditions 37
8.5 Criteria for passing qualification/requalification 37
8.6 Qualification test ~~definition~~ 37
8.6.1 Pre- and post- electrical and photometric test 37
8.6.2 Pre- and post- external visual (EV) test 37
8.6.3 High temperature operating life (HTOL) test 38
8.6.4 Temperature cycling (TMCL) test 38
8.6.5 Wet high temperature operating life (WHTOL) test 38
8.6.6 Power temperature cycling (PTMCL) test 39
8.6.7 Electrostatic discharge, human body model (ESD-HBM) test 39
8.6.8 Electrostatic discharge, machine model (ESD-MM) test 39
8.6.9 Destructive physical analysis (DPA) test 39
8.6.10 Physical dimensions (PD) test 39
8.6.11 Vibrations variable frequency (VVF) test 39
8.6.12 Mechanical shock (MS) test 40
8.6.13 Resistance to soldering heat (RSH-TTW) test 40
8.6.14 Resistance to soldering heat (RSH-reflow) test 40
8.6.15 Solderability (SO) test 40
8.6.16 Thermal shock (TMSK) test 40
8.6.17 Hydrogen sulphide (H_2S) test 41
8.6.18 Pulsed operating life (PLT) test 41
8.6.19 Dew (DEW) test 41
8.6.20 Flowing mixed gas corrosion (FMGC) test 42
8.6.22 Bond shear test (BS) 43
8.6.23 Die shear test (DS) 43
8.6.21 Wire bond pull test (WBP) 43
Annex A (normative) Life test conditions for filament lamps 44
A.1 Ageing 44
A.2 Test voltage 44
A.3 Operating position and operating conditions 44
A.4 Switching cycle 44
A.4.1 Single-filament lamps 44
A.4.2 Dual-filament lamps for headlamps 45
A.4.3 Dual-filament lamps for light signalling equipment 45
A.5 Luminous flux and colour maintenance 45
Annex B (normative) Vibration tests 46
B.1 General 46
B.2 Test conditions 47
B.2.1 General 47
B.2.2 Mounting (see IEC 60068-2-47) 47
B.2.3 Measuring points 47

B.2.4 Control point 47
B.2.5 Conditioning 47
B.2.6 Axis of vibration 47
B.2.7 WBR test – Basic motion 48
B.3 Test conditions 48
B.3.1 General 48
B.3.2 Narrowband random vibration tests 48
B.3.3 Wideband random vibration tests 49
Annex C (normative) Glass-bulb strength test 51
C.1 General 51
C.2 Test equipment and procedure 51
C.2.1 Principle of the test equipment 51
C.2.2 Test conditions 51
C.2.3 Requirements for plates 52
C.3 Requirements 52
C.4 Evaluation 53
C.4.1 General 53
C.4.2 Assessment based on attributes 53
C.4.3 Assessment based on variables 53
Annex D (normative) Life and luminous flux maintenance test conditions for discharge lamps 55
D.1 Ageing 55
D.2 Test circuit and test voltage 55
D.3 Burning position and operating conditions 55
D.4 Switching cycle 55
D.5 Luminous flux maintenance 57
Annex E (normative) Bulb deflection test 58
E.1 General 58
E.2 Test set-up and procedure 58
E.3 Requirement 58
Annex F (informative) Guidance on equipment design 59
F.1 Pinch temperature limit 59
F.2 Solder temperature limit 59
F.3 Maximum filament lamp outline 59
F.4 Maximum surge voltage 59
F.5 Recommended instructions for use and handling of halogen filament lamps 59
F.6 Recommended instructions for use and handling of discharge lamps 60
Annex G (informative) ~~Information for~~ Ballast design 65
Annex H (informative) Symbols 66
H.1 General 66
H.2 Symbol indicating that lamps operate at high temperatures 67
H.3 Symbol indicating that care should be taken to avoid touching the bulb 67
H.4 Symbol indicating that the use of protective gloves is advised 67
H.5 Symbol indicating that lamps with scratched or otherwise damaged bulbs should not be used 67
H.6 Symbol indicating that before handling, the lamp shall be switched off 67
H.7 Symbol indicating that the use of eye protection is advised 67
H.8 Symbol indicating that during operation, the lamp emits UV-radiation 68

H.9 Symbol indicating that the lamp shall be operated only in a luminaire with a protective shield 68
H.10 Symbol indicating dangerous voltage 69
H.11 Pictogram for instruction "Non-ECE" 69
H.12 Pictogram for instruction "Interior lighting only" 70
Annex I (normative) Luminous flux maintenance test conditions for LED light sources 71
I.1 Ageing 71
I.2 Test voltage 71
I.3 Operating conditions 71
I.3.1 Test rack 71
I.3.2 LED light sources with integrated thermal management 71
I.3.3 LED light sources with external thermal management 71
I.4 Switching cycle 72
I.4.1 Single-function LED light sources 72
I.4.2 Dual-function LED light sources for headlamps 72
I.4.3 Multiple-function LED light sources for light signalling equipment 72
I.5 Luminous flux maintenance measurements 73
I.6 Colour measurement 73
Annex J (normative) Destructive physical analysis for LED packages 74
J.1 Description 74
J.2 Equipment 74
J.3 Procedure 74
J.4 Failure criteria 74
Annex K (informative) Communication sheet LED package testing 75
Annex L (normative) Re-testing matrix for LED packages testing 78
Annex M (informative) Guidelines for LED packages robustness validation 79
M.1 General 79
M.2 Test samples 81
M.2.1 Lot requirements 81
M.2.2 Production requirements 82
M.2.3 Pre- and post-stress test requirements 82
M.2.4 Assembly of LED packages on test boards 82
M.3 Definition of end-of-test criteria 82
M.4 Test sequence of over-stress testing 82
M.5 Over-stress test definition 83
M.5.1 Pre- and post-electrical and photometric test 83
M.5.2 Pre- and post-external visual (EV) test 83
M.5.3 High temperature operating life (HTOL) and low temperature operating life (LTOL) tests 83
M.5.4 Temperature cycling (TMCL) test 84
M.5.5 Wet high temperature operating life (WHTOL) test 84
M.5.6 Power temperature cycling (PTMCL) test 85
M.5.7 Thermal shock (TMSK) test 85
M.6 Destructive physical analysis (DPA) test 86
M.7 Projection models 86
Bibliography 90

Figure 1 – Examples of LED packages 14

Figure 2 – Example of an LED module without integrated heatsink 14
Figure 3 – Example of an LED module with integrated heatsink 15
Figure 4 – Example of a replaceable LED light source 15
Figure 5 – Example of a non-replaceable LED light source 16
Figure 6 – Position of the centre of gravity (shaded areas) 24
Figure 7 – Extract from IEC 60068-2-14 Test Nb, showing the temperature cycle profile 28
Figure 8 – Typical electrical circuit for an LR3, LR5, LY3, LY5, LW3 and LW5 LED light source 30
Figure 9 – Typical electrical circuit for an LR4 LED light source 30
Figure 10 – Profile of pulse 1 from ISO 7637-2 32
Figure 11 – Profile of pulse 2a from ISO 7637-2 33
Figure 12 – Temperature–humidity characteristics for the DEW test 42
Figure B.1 – Recommended equipment layout for vibration testing 50
Figure C.1 – Diagrammatic sketch of the principle of the test equipment 51
Figure D.1 – Superposition of on/off switching and power switching cycle 56
Figure E.1 – Sketch of the test set-up 58
Figure F.1 – Voltage surges for 12 V filament lamps – Maximum tolerable duration for a voltage surge as a function of its height 60
Figure F.2 – Maximum filament lamp outlines H1 61
Figure F.3 – Maximum filament lamp outlines H2 62
Figure F.4 – Maximum filament lamp outlines H3 63
Figure F.5 – Maximum filament lamp outlines P21W, PY21W, P21/4W and P21/5W 64
Figure H.1 – Pictogram for instruction "Non-ECE" 69
Figure H.2 – Pictogram for instruction "Interior lighting only" 70
Figure M.1 – Concept of over-stress testing for two stress parameters 80
Figure M.2 – Flow diagram for the robustness validation process 81

Table 1 – Conditions of compliance for life B_3 17
Table 2 – Conditions of compliance for the vibration test 17
Table 3 – Rated life values for continuous operation 19
Table 4 – Rated luminous flux-maintenance values for continuous operation 22
Table 5 – Minimum $L_{70}B_{10}$ values for ~~standardised~~ replaceable LED light sources 26
Table 6 – Typical “on”-times for the different functions per 100 000 km drive distance, based on an average speed of 33,6 km/h [a] 27
Table 7 – Example of product data 27
Table 8 – Temperature classes for the powered thermal cycling test 28
Table 9 – Maximum mass for LED light sources 29
Table 10 – Maximum power consumption 31
Table 11 – Test parameters for pulse 1 from ISO 7637-2 32
Table 12 – Test parameters for pulse 2a from ISO 7637-2 33
Table B.1 – Vibration test on motor vehicle lamps – Test conditions 48
Table B.2 – Vibration test on motor vehicle lamps – Standard test conditions (narrowband) 48
Table B.3 – Vibration test on motor vehicle lamps – Heavy-duty test conditions 49

Table B.4 – Vibration test on motor vehicle lamps – Standard test conditions(wideband) (wideband) 49
Table C.1 – Compression strength 52
Table C.2 – Inspection by attributes – Double sampling plan 53
Table C.3 – Inspection by variables – "S" method of assessment 54
Table D.1 – On/off switching cycle 55
Table D.2 – Power switching cycle 56
Table D.3 – Fast power switching cycle 57
Table G.1 – Open circuit voltage 65
Table I.1 – Examples of possible product data 72
~~Table L.1 – Retesting matrix ..... .~~
Table M.1 – Typical over-stress matrix for two stress parameters 83
Table M.2 – Acceleration models 87

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

LAMPS, LIGHT SOURCES AND LED PACKAGES FOR ROAD VEHICLES – PERFORMANCE REQUIREMENTS

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60810 has been prepared by subcommittee 34A: Lamps, of IEC technical committee 34: Lamps and related equipment.

This fifth edition cancels and replaces the fourth edition published in 2014 and Amendment 1:2017. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) update and clarification of the title and scope;
b) introduction of new LED light sources;
c) introduction of requirements for LED light sources;
d) introduction of guidelines on LED package robustness validation for LED packages.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
34A/2021/FDIS	34A/2033/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

LAMPS, LIGHT SOURCES AND LED PACKAGES FOR ROAD VEHICLES – PERFORMANCE REQUIREMENTS

1 Scope

This document is applicable to ~~lamps (~~filament lamps, discharge lamps, LED light sources~~)~~ and LED packages to be used in road vehicles, i.e. in headlamps, fog-lamps, signalling lamps and interior lighting. It is especially applicable to those lamps and light sources which are listed in IEC 60809. ~~However, the standard may also be used for other lamps falling under the scope of this standard.~~

It specifies requirements and test methods for the measurement of performance characteristics such as lamp life, luminous flux maintenance, torsion strength, glass bulb strength and resistance to vibration and shock. Moreover, information on temperature limits, maximum lamp outlines and maximum tolerable voltage surges is given as guidance for lighting and electrical equipment design.

For some of the requirements given in this document, reference is made to data given in tables. For lamps not listed in such tables, the relevant data are supplied by the lamp manufacturer or responsible vendor.

The performance requirements are additional to the basic requirements specified in IEC 60809. They are, however, not intended to be used by authorities for legal type-approval purposes.

NOTE 1 In the various vocabularies and standards, different terms are used for "incandescent lamp" (IEC 60050-845:1987, 845-07-04) and "discharge lamp" (IEC 60050-845:1987, 845-07-17). In this document, "filament lamp" and "discharge lamp" are used. However, where only “lamp” is written both types are meant, unless the context clearly shows that it applies to one type only.

NOTE 2 This document does not apply to luminaires.

NOTE 3 In this document, the term LED light source is used, in other standards the term LED lamps can be used to describe similar products.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

~~IEC 60050 (all parts), *International Electrotechnical Vocabulary* (available at <http://www.electropedia.org/)~~

IEC 60050-845, *International Electrotechnical Vocabulary – Part 845: Lighting* (available at http://www.electropedia.org)

IEC 60061-1, *Lamp caps and holders together with gauges for the control of interchangeability and safety – Part 1: Lamp caps*

~~IEC 60068-2-6:1995, *Environmental testing – Part 2-6: Tests – Test Fc: Vibration (sinusoidal)*~~

IEC 60068-2-14, *Environmental testing – Part 2–14: Tests – Test N: Change of temperature*

IEC 60068-2-43, *Environmental testing – Part 2-43: Tests – Test Kd: Hydrogen sulphide test for contacts and connections*

IEC 60068-2-58, *Environmental testing – Part 2-58: Tests – Test Td: Test methods for solderability, resistance to dissolution of metallization and to soldering heat of surface mounting devices (SMD)*

IEC 60068-2-60, *Environmental testing – Part 2-60: Tests – Test Ke: Flowing mixed gas corrosion test*

~~IEC 60410:1973, *Sampling plans and procedures for inspection by attributes*~~

IEC 60809:2014, *Lamps for road vehicles – Dimensional, electrical and luminous requirements*

CISPR 25, *Vehicles, boats and internal combustion engines – Radio disturbance characteristics – Limits and methods of measurement for the protection of on-board receivers*

ISO 7637-2:2011, *Road vehicles – Electrical disturbances from conduction and coupling – Part 2: Electrical transient conduction along supply lines only*

ISO 10605, *Road vehicles – Test methods for electrical disturbances from electrostatic discharge*

United Nations Vehicle Regulations – 1958 Agreement, *Agreement concerning the adoption of uniform technical prescriptions for wheeled vehicles, equipment and parts which can be fitted and/or be used on wheeled vehicles and the conditions for reciprocal recognition of approvals granted on the basis of these prescriptions*
(available at www.unece.org/trans/main/wp29/wp29regs.html)[1]

Addendum 36: Regulation No. 37, *Uniform provisions concerning the approval of filament lamps for use in approved lamp units of power-driven vehicles and of their trailers*

~~Addendum 37: Regulation No. 38, *Uniform provisions concerning the approval of rear fog lamps for power-driven vehicles and their trailers*~~

Addendum 47: Regulation No 48, *Uniform provisions concerning the approval of vehicles with regard to the installation of lighting and light-signalling devices*

Addendum 100: Regulation No. 101, *Uniform provisions concerning the approval of passenger cars powered by an internal combustion engine only, or powered by a hybrid electric power train with regard to the measurement of the emission of carbon dioxide and fuel consumption and/or the measurement of electric energy consumption and electric range, and of categories M1 and N1 vehicles powered by an electric power train only with regard to the measurement of electric energy consumption and electric range*

Addendum 122: Regulation No. 123, *Uniform provisions concerning the approval of adaptive front-lighting systems (AFS) for motor vehicles*

Addendum 127: Regulation No. 128, *Uniform provisions concerning the approval of light emitting diode (LED) light sources for use in approved lamp units on power-driven*

~~JESD22-A100D, *Cycled temperature humidity bias life test*~~

JESD22-A101C, *Steady-state temperature humidity bias life test*

~~JESD22-A104D~~ JESD22-A104E, *Temperature cycling*

---

[1] Also known as The 1958 Agreement. In the text of this document the regulations under this agreement are referred to as, for example, UN Regulation 37 or R37.

JESD22-A105C, *Power and temperature cycling*

JESD22-A106B, *Thermal shock*

JESD22-A108D, *Temperature, bias, and operating life*

JESD22-A113F, *Preconditioning of plastic surface mount devices prior to reliability testing*

JESD22-A115C, *Electrostatic discharge (ESD) sensitivity testing machine model (MM)*

JESD22-B101B, *External visual*

JESD22-B103B, *Vibration, variable frequency*

JESD22-B110B, *Mechanical shock*

JESD22-B106D, *Resistance to solder shock for through-hole mounted devices*

JESD22-B116:1998, *Wire Bond Shear Test Method*

JESD51-50:2012-04, *Overview of methodologies for the thermal measurement of single- and multi-chip, single- and multi-pnjunction light-emitting diodes (LEDs)*

JESD51-51:2012-04, *Implementation of the electrical test method for the measurement of real thermal resistance and impedance of light-emitting diodes with exposed cooling surface*

JESD51-52:2012-04, *Guidelines for combining CIE 127-2007 total flux measurements with thermal measurements of leds with exposed cooling surface*

JESD51-53:2012-05, *Terms, definitions and units glossary for LED thermal testing*

ANSI/IPC/ECA J-STD-002C, *Solderability tests for component leads, terminations, lugs, terminals and wires*

ANSI/ESDA/JEDEC JS-001-2012, *Joint JEDEC/ESDA standard for electrostatic discharge sensitivity testing human body model (HBM) – component level*

MIL-STD-883E:2015, *Visual Inspection Criteria*

ZVEI "*Guideline for Customer Notifications of Product and/or Process Changes (PCN) of Electronic Components specified for Automotive Applications*" 4th revised Edition, October 2016, Rev. 3

IEC 60810

Edition 5.0 2017-09

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

Lamps, light sources and led packages for road vehicles – Performance requirements

Lampes, sources lumineuses et led encapsulées pour véhicules routiers – Exigences de performances



IEC 60810:2017-09(en-fr)

CONTENTS

FOREWORD 8
1 Scope 10
2 Normative references 10
3 Terms and definitions 12
4 Requirements and test conditions for filament lamps 16
4.1 Basic function and interchangeability 16
4.2 Torsion strength 16
4.3 Characteristic life T_c 16
4.4 Life B_3 16
4.5 Luminous flux maintenance 17
4.6 Resistance to vibration and shock 17
4.7 Glass-bulb strength 17
5 Filament lamp data 17
6 Requirements and test conditions for discharge lamps 22
6.1 Basic function and interchangeability 22
6.2 Mechanical strength 22
6.2.1 Bulb-to-cap connection 22
6.2.2 Cable-to-cap connection (if any) 22
6.3 Characteristic life T_c 22
6.4 Life B_3 22
6.5 Luminous flux maintenance 22
6.6 Resistance to vibration and shock 22
6.7 Discharge lamps with integrated starting device 22
6.8 Discharge lamps with integrated starting device and integrated ballast 23
7 Requirements and test conditions for LED light sources 23
7.1 Basic function and interchangeability 23
7.2 UV radiation 24
7.3 Luminous flux and colour maintenance 24
7.4 Resistance to vibration and shock 26
7.5 Electromagnetic compatibility 27
7.6 Powered thermal cycling test 27
7.7 Mass 28
7.8 Typical circuits for LED light sources 28
7.8.1 General 28
7.8.2 Typical circuits for LR3, LR5, LY3, LY5, LW3 and LW5 LED light sources 28
7.8.3 Typical circuits for LR4 LED light sources 29
7.9 Maximum power consumption 30
7.10 Overvoltage test 30
7.11 Reverse voltage test 30
7.12 Transient voltage test (field decay) 31
7.13 Transient voltage test (load dump) 32
7.14 Electrostatic discharge test (ESD) 33
7.15 Pulsed operating life (PLT) test 33
8 Requirements and test conditions for LED packages 33
8.1 LED package stress test qualification 33

8.2 Test samples 34
8.2.1 Lot requirements 34
8.2.2 Production requirements 34
8.2.3 Pre- and post-stress test requirements 34
8.2.4 Assembly of LED packages on test boards 35
8.2.5 Moisture pre-conditioning (MP) 35
8.2.6 Thermal resistance (TR) test 35
8.3 Definition of failure criteria 35
8.4 Choice between test conditions 36
8.5 Criteria for passing qualification/requalification 36
8.6 Qualification test 36
8.6.1 Pre- and post- electrical and photometric test 36
8.6.2 Pre- and post- external visual (EV) test 36
8.6.3 High temperature operating life (HTOL) test 36
8.6.4 Temperature cycling (TMCL) test 37
8.6.5 Wet high temperature operating life (WHTOL) test 37
8.6.6 Power temperature cycling (PTMCL) test 37
8.6.7 Electrostatic discharge, human body model (ESD-HBM) test 38
8.6.8 Electrostatic discharge, machine model (ESD-MM) test 38
8.6.9 Destructive physical analysis (DPA) test 38
8.6.10 Physical dimensions (PD) test 38
8.6.11 Vibrations variable frequency (VVF) test 38
8.6.12 Mechanical shock (MS) test 38
8.6.13 Resistance to soldering heat (RSH-TTW) test 38
8.6.14 Resistance to soldering heat (RSH-reflow) test 39
8.6.15 Solderability (SO) test 39
8.6.16 Thermal shock (TMSK) test 39
8.6.17 Hydrogen sulphide (H_2S) test 39
8.6.18 Pulsed operating life (PLT) test 39
8.6.19 Dew (DEW) test 40
8.6.20 Flowing mixed gas corrosion (FMGC) test 41
8.6.21 Wire bond pull test (WBP) 41
8.6.22 Bond shear test (BS) 42
8.6.23 Die shear test (DS) 42
Annex A (normative) Life test conditions for filament lamps 43
A.1 Ageing 43
A.2 Test voltage 43
A.3 Operating position and operating conditions 43
A.4 Switching cycle 43
A.4.1 Single-filament lamps 43
A.4.2 Dual-filament lamps for headlamps 44
A.4.3 Dual-filament lamps for light signalling equipment 44
A.5 Luminous flux and colour maintenance 44
Annex B (normative) Vibration tests 45
B.1 General 45
B.2 Test conditions 46
B.2.1 General 46
B.2.2 Mounting (see IEC 60068-2-47) 46
B.2.3 Measuring points 46

B.2.4 Control point 46
B.2.5 Conditioning 46
B.2.6 Axis of vibration 46
B.2.7 WBR test – Basic motion 47
B.3 Test conditions 47
B.3.1 General 47
B.3.2 Narrowband random vibration tests 47
B.3.3 Wideband random vibration tests 48
Annex C (normative) Glass-bulb strength test 50
C.1 General 50
C.2 Test equipment and procedure 50
C.2.1 Principle of the test equipment 50
C.2.2 Test conditions 50
C.2.3 Requirements for plates 51
C.3 Requirements 51
C.4 Evaluation 52
C.4.1 General 52
C.4.2 Assessment based on attributes 52
C.4.3 Assessment based on variables 52
Annex D (normative) Life and luminous flux maintenance test conditions for discharge lamps 54
D.1 Ageing 54
D.2 Test circuit and test voltage 54
D.3 Burning position and operating conditions 54
D.4 Switching cycle 54
D.5 Luminous flux maintenance 56
Annex E (normative) Bulb deflection test 57
E.1 General 57
E.2 Test set-up and procedure 57
E.3 Requirement 57
Annex F (informative) Guidance on equipment design 58
F.1 Pinch temperature limit 58
F.2 Solder temperature limit 58
F.3 Maximum filament lamp outline 58
F.4 Maximum surge voltage 58
F.5 Recommended instructions for use and handling of halogen filament lamps 58
F.6 Recommended instructions for use and handling of discharge lamps 59
Annex G (informative) Ballast design 64
Annex H (informative) Symbols 65
H.1 General 65
H.2 Symbol indicating that lamps operate at high temperatures 66
H.3 Symbol indicating that care should be taken to avoid touching the bulb 66
H.4 Symbol indicating that the use of protective gloves is advised 66
H.5 Symbol indicating that lamps with scratched or otherwise damaged bulbs should not be used 66
H.6 Symbol indicating that before handling, the lamp shall be switched off 66
H.7 Symbol indicating that the use of eye protection is advised 66
H.8 Symbol indicating that during operation, the lamp emits UV-radiation 67

H.9 Symbol indicating that the lamp shall be operated only in a luminaire with a protective shield 67
H.10 Symbol indicating dangerous voltage 68
H.11 Pictogram for instruction "Non-ECE" 68
H.12 Pictogram for instruction "Interior lighting only" 69
Annex I (normative) Luminous flux maintenance test conditions for LED light sources 70
I.1 Ageing 70
I.2 Test voltage 70
I.3 Operating conditions 70
I.3.1 Test rack 70
I.3.2 LED light sources with integrated thermal management 70
I.3.3 LED light sources with external thermal management 70
I.4 Switching cycle 71
I.4.1 Single-function LED light sources 71
I.4.2 Dual-function LED light sources for headlamps 71
I.4.3 Multiple-function LED light sources for light signalling equipment 71
I.5 Luminous flux maintenance measurements 72
I.6 Colour measurement 72
Annex J (normative) Destructive physical analysis for LED packages 73
J.1 Description 73
J.2 Equipment 73
J.3 Procedure 73
J.4 Failure criteria 73
Annex K (informative) Communication sheet LED package testing 74
Annex L (normative) Re-testing matrix for LED packages testing 77
Annex M (informative) Guidelines for LED packages robustness validation 78
M.1 General 78
M.2 Test samples 80
M.2.1 Lot requirements 80
M.2.2 Production requirements 81
M.2.3 Pre- and post-stress test requirements 81
M.2.4 Assembly of LED packages on test boards 81
M.3 Definition of end-of-test criteria 81
M.4 Test sequence of over-stress testing 81
M.5 Over-stress test definition 82
M.5.1 Pre- and post-electrical and photometric test 82
M.5.2 Pre- and post-external visual (EV) test 82
M.5.3 High temperature operating life (HTOL) and low temperature operating life (LTOL) tests 82
M.5.4 Temperature cycling (TMCL) test 83
M.5.5 Wet high temperature operating life (WHTOL) test 83
M.5.6 Power temperature cycling (PTMCL) test 84
M.5.7 Thermal shock (TMSK) test 84
M.6 Destructive physical analysis (DPA) test 85
M.7 Projection models 85
Bibliography 89

Figure 1 – Examples of LED packages 14

Figure 2 – Example of an LED module without integrated heatsink 14
Figure 3 – Example of an LED module with integrated heatsink 14
Figure 4 – Example of a replaceable LED light source 15
Figure 5 – Example of a non-replaceable LED light source 15
Figure 6 – Position of the centre of gravity (shaded areas) 23
Figure 7 – Extract from IEC 60068-2-14 Test Nb, showing the temperature cycle profile 27
Figure 8 – Typical electrical circuit for an LR3, LR5, LY3, LY5, LW3 and LW5 LED light source 29
Figure 9 – Typical electrical circuit for an LR4 LED light source 29
Figure 10 – Profile of pulse 1 from ISO 7637-2 31
Figure 11 – Profile of pulse 2a from ISO 7637-2 32
Figure 12 – Temperature–humidity characteristics for the DEW test 41
Figure B.1 – Recommended equipment layout for vibration testing 49
Figure C.1 – Diagrammatic sketch of the principle of the test equipment 50
Figure D.1 – Superposition of on/off switching and power switching cycle 55
Figure E.1 – Sketch of the test set-up 57
Figure F.1 – Voltage surges for 12 V filament lamps – Maximum tolerable duration for a voltage surge as a function of its height 59
Figure F.2 – Maximum filament lamp outlines H1 60
Figure F.3 – Maximum filament lamp outlines H2 61
Figure F.4 – Maximum filament lamp outlines H3 62
Figure F.5 – Maximum filament lamp outlines P21W, PY21W, P21/4W and P21/5W 63
Figure H.1 – Pictogram for instruction "Non-ECE" 68
Figure H.2 – Pictogram for instruction "Interior lighting only" 69
Figure M.1 – Concept of over-stress testing for two stress parameters 79
Figure M.2 – Flow diagram for the robustness validation process 80

Table 1 – Conditions of compliance for life B_3 17
Table 2 – Conditions of compliance for the vibration test 17
Table 3 – Rated life values for continuous operation 18
Table 4 – Rated luminous flux-maintenance values for continuous operation 21
Table 5 – Minimum $L_{70}B_{10}$ values for replaceable LED light sources 25
Table 6 – Typical “on”-times for the different functions per 100 000 km drive distance, based on an average speed of 33,6 km/h [a] 26
Table 7 – Example of product data 26
Table 8 – Temperature classes for the powered thermal cycling test 27
Table 9 – Maximum mass for LED light sources 28
Table 10 – Maximum power consumption 30
Table 11 – Test parameters for pulse 1 from ISO 7637-2 31
Table 12 – Test parameters for pulse 2a from ISO 7637-2 32
Table B.1 – Vibration test on motor vehicle lamps – Test conditions 47
Table B.2 – Vibration test on motor vehicle lamps – Standard test conditions (narrowband) 47
Table B.3 – Vibration test on motor vehicle lamps – Heavy-duty test conditions 48

Table B.4 – Vibration test on motor vehicle lamps – Standard test conditions (wideband) 48
Table C.1 – Compression strength 51
Table C.2 – Inspection by attributes – Double sampling plan 52
Table C.3 – Inspection by variables – "S" method of assessment 53
Table D.1 – On/off switching cycle 54
Table D.2 – Power switching cycle 55
Table D.3 – Fast power switching cycle 56
Table G.1 – Open circuit voltage 64
Table I.1 – Examples of possible product data 71
Table M.1 – Typical over-stress matrix for two stress parameters 82
Table M.2 – Acceleration models 86

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

LAMPS, LIGHT SOURCES AND LED PACKAGES FOR ROAD VEHICLES – PERFORMANCE REQUIREMENTS

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60810 has been prepared by subcommittee 34A: Lamps, of IEC technical committee 34: Lamps and related equipment.

This fifth edition cancels and replaces the fourth edition published in 2014 and Amendment 1:2017. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) update and clarification of the title and scope;
b) introduction of new LED light sources;
c) introduction of requirements for LED light sources;
d) introduction of guidelines on LED package robustness validation for LED packages.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
34A/2021/FDIS	34A/2033/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

LAMPS, LIGHT SOURCES AND LED PACKAGES FOR ROAD VEHICLES – PERFORMANCE REQUIREMENTS

1 Scope

This document is applicable to filament lamps, discharge lamps, LED light sources and LED packages to be used in road vehicles, i.e. in headlamps, fog-lamps, signalling lamps and interior lighting. It is especially applicable to those lamps and light sources which are listed in IEC 60809.

It specifies requirements and test methods for the measurement of performance characteristics such as lamp life, luminous flux maintenance, torsion strength, glass bulb strength and resistance to vibration and shock. Moreover, information on temperature limits, maximum lamp outlines and maximum tolerable voltage surges is given as guidance for lighting and electrical equipment design.

For some of the requirements given in this document, reference is made to data given in tables. For lamps not listed in such tables, the relevant data are supplied by the lamp manufacturer or responsible vendor.

The performance requirements are additional to the basic requirements specified in IEC 60809. They are, however, not intended to be used by authorities for legal type-approval purposes.

NOTE 1 In the various vocabularies and standards, different terms are used for "incandescent lamp" (IEC 60050-845:1987, 845-07-04) and "discharge lamp" (IEC 60050-845:1987, 845-07-17). In this document, "filament lamp" and "discharge lamp" are used. However, where only “lamp” is written both types are meant, unless the context clearly shows that it applies to one type only.

NOTE 2 This document does not apply to luminaires.

NOTE 3 In this document, the term LED light source is used, in other standards the term LED lamps can be used to describe similar products.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-845, *International Electrotechnical Vocabulary – Part 845: Lighting* (available at http://www.electropedia.org)

IEC 60061-1, *Lamp caps and holders together with gauges for the control of interchangeability and safety – Part 1: Lamp caps*

IEC 60068-2-14, *Environmental testing – Part 2–14: Tests – Test N: Change of temperature*

IEC 60068-2-43, *Environmental testing – Part 2-43: Tests – Test Kd: Hydrogen sulphide test for contacts and connections*

IEC 60068-2-58, *Environmental testing – Part 2-58: Tests – Test Td: Test methods for solderability, resistance to dissolution of metallization and to soldering heat of surface mounting devices (SMD)*

IEC 60068-2-60, *Environmental testing – Part 2-60: Tests – Test Ke: Flowing mixed gas corrosion test*

IEC 60809:2014, *Lamps for road vehicles – Dimensional, electrical and luminous requirements*

CISPR 25, *Vehicles, boats and internal combustion engines – Radio disturbance characteristics – Limits and methods of measurement for the protection of on-board receivers*

ISO 7637-2:2011, *Road vehicles – Electrical disturbances from conduction and coupling – Part 2: Electrical transient conduction along supply lines only*

ISO 10605, *Road vehicles – Test methods for electrical disturbances from electrostatic discharge*

United Nations Vehicle Regulations – 1958 Agreement, *Agreement concerning the adoption of uniform technical prescriptions for wheeled vehicles, equipment and parts which can be fitted and/or be used on wheeled vehicles and the conditions for reciprocal recognition of approvals granted on the basis of these prescriptions*
(available at www.unece.org/trans/main/wp29/wp29regs.html)[1]

Addendum 36: Regulation No. 37, *Uniform provisions concerning the approval of filament lamps for use in approved lamp units of power-driven vehicles and of their trailers*

Addendum 47: Regulation No 48, *Uniform provisions concerning the approval of vehicles with regard to the installation of lighting and light-signalling devices*

Addendum 100: Regulation No. 101, *Uniform provisions concerning the approval of passenger cars powered by an internal combustion engine only, or powered by a hybrid electric power train with regard to the measurement of the emission of carbon dioxide and fuel consumption and/or the measurement of electric energy consumption and electric range, and of categories M1 and N1 vehicles powered by an electric power train only with regard to the measurement of electric energy consumption and electric range*

Addendum 122: Regulation No. 123, *Uniform provisions concerning the approval of adaptive front-lighting systems (AFS) for motor vehicles*

Addendum 127: Regulation No. 128, *Uniform provisions concerning the approval of light emitting diode (LED) light sources for use in approved lamp units on power-driven*

JESD22-A101C, *Steady-state temperature humidity bias life test*

JESD22-A104E, *Temperature cycling*

JESD22-A105C, *Power and temperature cycling*

JESD22-A106B, *Thermal shock*

JESD22-A108D, *Temperature, bias, and operating life*

JESD22-A113F, *Preconditioning of plastic surface mount devices prior to reliability testing*

JESD22-A115C, *Electrostatic discharge (ESD) sensitivity testing machine model (MM)*

JESD22-B101B, *External visual*

JESD22-B103B, *Vibration, variable frequency*

[1] Also known as The 1958 Agreement. In the text of this document the regulations under this agreement are referred to as, for example, UN Regulation 37 or R37.

JESD22-B110B, *Mechanical shock*

JESD22-B106D, *Resistance to solder shock for through-hole mounted devices*

JESD22-B116:1998, *Wire Bond Shear Test Method*

JESD51-50:2012-04, *Overview of methodologies for the thermal measurement of single- and multi-chip, single- and multi-pnjunction light-emitting diodes (LEDs)*

JESD51-51:2012-04, *Implementation of the electrical test method for the measurement of real thermal resistance and impedance of light-emitting diodes with exposed cooling surface*

JESD51-52:2012-04, *Guidelines for combining CIE 127-2007 total flux measurements with thermal measurements of leds with exposed cooling surface*

JESD51-53:2012-05, *Terms, definitions and units glossary for LED thermal testing*

ANSI/IPC/ECA J-STD-002C, *Solderability tests for component leads, terminations, lugs, terminals and wires*

ANSI/ESDA/JEDEC JS-001-2012, *Joint JEDEC/ESDA standard for electrostatic discharge sensitivity testing human body model (HBM) – component level*

MIL-STD-883E:2015, *Visual Inspection Criteria*

ZVEI "*Guideline for Customer Notifications of Product and/or Process Changes (PCN) of Electronic Components specified for Automotive Applications*" 4th revised Edition, October 2016, Rev. 3

SOMMAIRE

AVANT-PROPOS 96
1 Domaine d'application 98
2 Références normatives 98
3 Termes et définitions 100
4 Exigences et conditions d'essai relatives aux lampes à filament 104
4.1 Fonction principale et interchangeabilité 104
4.2 Résistance à la torsion 104
4.3 Durée de vie caractéristique T_C 105
4.4 Durée de vie B_3 105
4.5 Conservation du flux lumineux 105
4.6 Résistance aux vibrations et aux chocs 105
4.7 Résistance de l'ampoule en verre 106
5 Fiches techniques des lampes à filament 106
6 Exigences et conditions d'essai relatives aux lampes à décharge 110
6.1 Fonction principale et interchangeabilité 110
6.2 Résistance mécanique 110
6.2.1 Fixation de l'ampoule au culot 110
6.2.2 Fixation de fil au culot (le cas échéant) 110
6.3 Durée de vie caractéristique T_C 110
6.4 Durée de vie B_3 110
6.5 Conservation du flux lumineux 110
6.6 Résistance aux vibrations et aux chocs 110
6.7 Lampes à décharge à dispositif d'amorçage intégré 110
6.8 Lampes à décharge à dispositif d'amorçage et à ballast intégrés 111
7 Exigences et conditions d'essai relatives aux sources lumineuses à LED 111
7.1 Fonction principale et interchangeabilité 111
7.2 Rayonnement ultraviolet 112
7.3 Conservation du flux lumineux et de la couleur 112
7.4 Résistance aux vibrations et aux chocs 114
7.5 Compatibilité électromagnétique 115
7.6 Essai de cycle thermique sous tension 115
7.7 Masse 116
7.8 Circuits typiques pour les sources lumineuses à LED 116
7.8.1 Généralités 116
7.8.2 Circuits typiques pour les sources lumineuses à LED LR3, LR5, LY3, LY5, LW3 et LW5 116
7.8.3 Circuits typiques pour les sources lumineuses à LED LR4 117
7.9 Puissance maximale consommée 118
7.10 Essai de surtension 118
7.11 Essai de tension inverse 119
7.12 Essai de tension transitoire (décroissance de champ) 119
7.13 Essai de tension transitoire (perte de charge) 120
7.14 Essai de décharge électrostatique (ESD, *electrostatic discharge*) 121
7.15 Essai de durée de vie en fonctionnement pulsé (PLT, *pulsed operating life*) 122
8 Exigences et conditions d'essai relatives aux LED encapsulées 122
8.1 Qualification par essai de contrainte des LED encapsulées 122

8.2 Échantillons pour essai 123
8.2.1 Exigences concernant les lots 123
8.2.2 Exigences concernant la production 123
8.2.3 Exigences concernant les essais de pré- et de post-contrainte 123
8.2.4 Assemblage des LED encapsulées sur des tableaux d'essai 124
8.2.5 Préconditionnement sous atmosphère humide (MP, *moisture pre-conditioning*) 124
8.2.6 Essai de résistance thermique (TR, *thermal resistance*) 124
8.3 Définition des critères de mise hors d'usage 124
8.4 Choix entre les conditions d'essai 125
8.5 Critères de satisfaction aux essais de qualification/requalification 125
8.6 Essai de qualification 125
8.6.1 Essai pré- et post-électrique et photométrique 125
8.6.2 Essai pré- et post-visuel externe (EV, *external visual*) 125
8.6.3 Essai de durée de vie en fonctionnement sous température élevée (HTOL, *high temperature operating life*) 126
8.6.4 Essai de cycle de température (TMCL, *temperature cycling*) 126
8.6.5 Essai de durée de vie en fonctionnement sous température élevée humide (WHTOL, *wet high temperature operating life*) 126
8.6.6 Essai de cycle de température de puissance (PTMCL, *power temperature cycling*) 127
8.6.7 Essai de décharge électrostatique, avec utilisation du modèle du corps humain (ESD-HBM, *electrostatic discharge, human body model*) 127
8.6.8 Essai de décharge électrostatique, avec utilisation du modèle machine (ESD-MM, *electrostatic discharge, machine model*) 127
8.6.9 Essai par analyse physique destructive (DPA, *destructive physical analysis*) 127
8.6.10 Essai de dimensions physiques (PD, *physical dimensions*) 127
8.6.11 Essai de vibrations à fréquence variable (VVF, *vibrations variable frequency*) 128
8.6.12 Essai de choc mécanique (MS, *mechanical shock*) 128
8.6.13 Essai de résistance à la chaleur de brasage (RSH-TTW, *resistance to soldering heat, through the wave*) 128
8.6.14 Essai de résistance à la chaleur de brasage (RSH-refusion) 128
8.6.15 Essai de brasabilité (SO, *solderability*) 128
8.6.16 Essai de choc thermique (TMSK, *thermal shock*) 128
8.6.17 Essai au sulfure d'hydrogène(H_2S) 129
8.6.18 Essai de durée de vie en fonctionnement pulsé (PLT, *pulsed operating life*) 129
8.6.19 Essai d'humidité 129
8.6.20 Essai de corrosion dans un flux de mélange de gaz (FMGC, *flowing mixed gas corrosion*) 131
8.6.21 Essai de traction du fil de connexion (WBP – *wire bond pull*) 131
8.6.22 Essai de cisaillement de la connexion (BS, *Bond shear*) 131
8.6.23 Essai de cisaillement de la puce (DS, *Die shear*) 131
Annexe A (normative) Conditions d'essai de durée de vie relatives aux lampes à filament 132
A.1 Vieillissement 132
A.2 Tension d'essai 132
A.3 Position et conditions de fonctionnement 132
A.4 Cycle d'allumage 132

A.4.1 Lampes à un seul filament 132
A.4.2 Lampes à deux filaments pour projecteurs avant 133
A.4.3 Lampes à deux filaments pour les feux de signalisation 133
A.5 Conservation du flux lumineux et de la couleur 133
Annexe B (normative) Essais de vibrations 134
B.1 Généralités 134
B.2 Conditions d'essai 135
B.2.1 Généralités 135
B.2.2 Montage (voir l'IEC 60068-2-47) 135
B.2.3 Points de mesure 135
B.2.4 Point de contrôle 135
B.2.5 Préparation 135
B.2.6 Axe de vibration 136
B.2.7 Essai WBR – Mouvement principal 136
B.3 Conditions d'essai 136
B.3.1 Généralités 136
B.3.2 Essai de vibrations aléatoires à bande étroite 136
B.3.3 Essais de vibrations aléatoires à large bande 137
Annexe C (normative) Essai de résistance des ampoules en verre 139
C.1 Généralités 139
C.2 Matériel d'essai et procédure 139
C.2.1 Principe du matériel d'essai 139
C.2.2 Conditions d'essai 139
C.2.3 Exigences concernant les plaques 140
C.3 Exigences 140
C.4 Évaluation 141
C.4.1 Généralités 141
C.4.2 Estimation par attributs 141
C.4.3 Estimation par variables 141
Annexe D (normative) Conditions d'essai de durée de vie et de conservation du flux lumineux relatives aux lampes à décharge 143
D.1 Vieillissement 143
D.2 Circuit d'essai et tension d'essai 143
D.3 Position et conditions de fonctionnement 143
D.4 Cycle d'allumage 143
D.5 Conservation du flux lumineux 145
Annexe E (normative) Essai de fléchissement de l'ampoule 146
E.1 Généralités 146
E.2 Montage et procédure d'essai 146
E.3 Exigence 147
Annexe F (informative) Recommandations pour la conception des matériels 148
F.1 Limite de température au pincement 148
F.2 Limite de température de la soudure 148
F.3 Encombrement maximal des lampes à filament 148
F.4 Surtension maximale 148
F.5 Recommandations pour l'utilisation et la manipulation des lampes à filament aux halogènes 148
F.6 Recommandations pour l'utilisation et la manipulation des lampes à décharge 149

Annexe G (informative) Conception du ballast 155
Annexe H (informative) Symboles 156
H.1 Généralités 156
H.2 Symbole indiquant que les lampes fonctionnent à des températures élevées 157
H.3 Symbole indiquant qu'il convient de prendre des précautions afin d'éviter de toucher l'ampoule 157
H.4 Symbole indiquant qu'il est conseillé d'utiliser des gants de protection 157
H.5 Symbole indiquant qu'il convient de ne pas utiliser de lampes dont l'ampoule est rayée ou endommagée 157
H.6 Symbole indiquant qu'avant manipulation, l'alimentation de la lampe doit être coupée 157
H.7 Symbole indiquant qu'il est conseillé d'utiliser une protection oculaire 157
H.8 Symbole indiquant qu'en fonctionnement, la lampe émet un rayonnement UV 158
H.9 Symbole indiquant que la lampe ne doit être utilisée que dans un luminaire à écran de protection 158
H.10 Symbole indiquant une tension dangereuse 159
H.11 Pictogramme pour instruction «Non CEE» 159
H.12 Pictogramme pour instruction «Eclairage intérieur uniquement» 160
Annexe I (normative) Conditions d'essai de conservation du flux lumineux relatives aux sources lumineuses à LED 161
I.1 Vieillissement 161
I.2 Tension d'essai 161
I.3 Conditions de fonctionnement 161
I.3.1 Banc d'essai 161
I.3.2 Sources lumineuses à LED avec gestion thermique intégrée 161
I.3.3 Sources lumineuses à LED avec gestion thermique externe 161
I.4 Cycle d'allumage 162
I.4.1 Sources lumineuses à LED monofonction 162
I.4.2 Sources lumineuses à LED double fonction pour projecteurs avant 162
I.4.3 Sources lumineuses à LED à plusieurs fonctions pour les feux de signalisation 162
I.5 Mesurages de la conservation du flux lumineux 163
I.6 Mesurage de la couleur 163
Annexe J (normative) Analyse physique destructive pour LED encapsulées 164
J.1 Description 164
J.2 Matériel 164
J.3 Procédure 164
J.4 Critères de défaillance 164
Annexe K (informative) Fiche de communication pour essai des LED encapsulées 165
Annexe L (normative) Matrice de contre-essai pour essai des LED encapsulées 168
Annexe M (informative) Lignes directrices pour la validation de la robustesse des LED encapsulées 169
M.1 Généralités 169
M.2 Échantillons pour essai 171
M.2.1 Exigences concernant les lots 171
M.2.2 Exigences concernant la production 172
M.2.3 Exigences concernant les essais de pré- et de post-contrainte 172
M.2.4 Assemblage des LED encapsulées sur des tableaux d'essai 172
M.3 Définition des critères de fin d'essai 172

M.4 Séquence d'essai pour l'essai de surcharge 172
M.5 Définition des essais de surcharge 173
M.5.1 Essai pré- et post-électrique et photométrique 173
M.5.2 Essai pré- et post-visuel externe (EV, *external visual*) 174
M.5.3 Essais de durée de vie en fonctionnement sous température élevée (HTOL, *high temperature operating life*) et de durée de vie en fonctionnement sous température faible (LTOL, *low temperature operating life*) 174
M.5.4 Essai de cycle de température (TMCL, *temperature cycling*) 174
M.5.5 Essai de durée de vie en fonctionnement sous température élevée humide (WHTOL, *wet high temperature operating life*) 175
M.5.6 Essai de cycle de température de puissance (PTMCL, *power temperature cycling*) 175
M.5.7 Essai de choc thermique (TMSK, *thermal shock*) 176
M.6 Essai par analyse physique destructive (DPA, *destructive physical analysis*) 177
M.7 Modèles de projection 177
Bibliographie 181

Figure 1 – Exemples de LED encapsulées 102
Figure 2 – Exemple de module à LED sans dissipateur thermique intégré 102
Figure 3 – Exemple de module à LED avec dissipateur thermique intégré 103
Figure 4 – Exemple de source lumineuse à LED remplaçable 103
Figure 5 – Exemple de source lumineuse à LED non remplaçable 104
Figure 6 – Position du centre de gravité (zones ombrées) 111
Figure 7 – Extrait de l'essai Nb défini dans l'IEC 60068-2-14, présentant le profil de cycle de température 116
Figure 8 – Circuit électrique typique pour les sources lumineuses à LED LR3, LR5, LY3, LY5, LW3 et LW5 117
Figure 9 – Circuit électrique typique d'une source lumineuse à LED LR4 118
Figure 10 – Profil de l'impulsion 1 de l'ISO 7637-2 120
Figure 11 – Profil de l'impulsion 2a de l'ISO 7637-2 121
Figure 12 – Caractéristiques température-humidité de l'essai d'humidité 130
Figure B.1 – Schéma de principe du matériel recommandé pour l'essai de vibrations 138
Figure C.1 – Schéma de principe du matériel d'essai 139
Figure D.1 – Superposition du cycle d'allumage/extinction et du cycle de commutation de puissance 144
Figure E.1 – Schéma du montage d'essai 146
Figure F.1 – Surtensions pour les lampes à filament de 12 V – Durée maximale tolérable pour une surtension en fonction de sa valeur 150
Figure F.2 – Encombrement maximal des lampes à filament H1 151
Figure F.3 – Encombrement maximal des lampes à filament H2 152
Figure F.4 – Encombrement maximal des lampes à filament H3 153
Figure F.5 – Encombrement maximal des lampes à filament P21W, PY21W, P21/4W et P21/5W 154
Figure H.1 – Pictogramme pour instruction «Non CEE» 159
Figure H.2 – Pictogramme pour instruction «Eclairage intérieur uniquement» 160
Figure M.1 – Concept de l'essai de surcharge pour deux paramètres d'essai 170

Figure M.2 – Organigramme du processus de validation de la robustesse 171

Tableau 1 – Conditions de conformité pour la durée de vie B_3 105
Tableau 2 – Conditions de conformité pour l'essai de vibrations 106
Tableau 3 – Valeurs des durées de vie assignées, en fonctionnement continu 106
Tableau 4 – Valeurs assignées de conservation du flux lumineux, en fonctionnement continu 109
Tableau 5 – Valeurs $L_{70}B_{10}$ minimales pour les sources lumineuses à LED remplaçables 113
Tableau 6 – Valeurs typiques de durée de fonctionnement pour les différentes fonctions pour une distance de parcours de 100 000 km, sur la base d'une vitesse moyenne de 33,6 km/h [a] 114
Tableau 7 – Exemple de données relatives au produit 114
Tableau 8 – Classes de température pour l'essai de cycle thermique sous tension 115
Tableau 9 – Masse maximale des sources lumineuses à LED 116
Tableau 10 – Puissance maximale consommée 118
Tableau 11 – Paramètres d'essai pour l'impulsion 1 de l'ISO 7637-2 120
Tableau 12 – Paramètres d'essai pour l'impulsion 2a de l'ISO 7637-2 121
Tableau B.1 – Essai de vibrations sur lampes pour véhicules à moteur – Conditions d'essai 136
Tableau B.2 – Essai de vibrations sur lampes pour véhicules à moteur – Conditions d'essai normal (bande étroite) 136
Tableau B.3 – Essai de vibrations sur lampes pour véhicules à moteur – Conditions d'essai renforcé 137
Tableau B.4 – Essai de vibrations sur les lampes pour véhicules à moteur – Conditions d'essai normal (large bande) 137
Tableau C.1 – Résistance à la compression 140
Tableau C.2 – Contrôle par attributs – Plan d'échantillonnage double 141
Tableau C.3 – Contrôle par variables – méthode de l'écart-type «S» 142
Tableau D.1 – Cycle d'allumage/extinction 143
Tableau D.2 – Cycle de commutation de puissance 144
Tableau D.3 – Cycle de commutation de puissance rapide 145
Tableau G.1 – Tension à circuit ouvert 155
Tableau I.1 – Exemples de données potentielles relatives au produit 162
Tableau M.1 – Matrice typique de surcharge pour deux paramètres de contrainte 173
Tableau M.2 – Modèles d'accélération 178

COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

_____

LAMPES, SOURCES LUMINEUSES ET LED ENCAPSULÉES POUR VÉHICULES ROUTIERS – EXIGENCES DE PERFORMANCES

AVANT-PROPOS

1) La Commission Electrotechnique Internationale (IEC) est une organisation mondiale de normalisation composée de l'ensemble des comités électrotechniques nationaux (Comités nationaux de l'IEC). L'IEC a pour objet de favoriser la coopération internationale pour toutes les questions de normalisation dans les domaines de l'électricité et de l'électronique. A cet effet, l'IEC – entre autres activités – publie des Normes internationales, des Spécifications techniques, des Rapports techniques, des Spécifications accessibles au public (PAS) et des Guides (ci-après dénommés "Publication(s) de l'IEC"). Leur élaboration est confiée à des comités d'études, aux travaux desquels tout Comité national intéressé par le sujet traité peut participer. Les organisations internationales, gouvernementales et non gouvernementales, en liaison avec l'IEC, participent également aux travaux. L'IEC collabore étroitement avec l'Organisation Internationale de Normalisation (ISO), selon des conditions fixées par accord entre les deux organisations.
2) Les décisions ou accords officiels de l'IEC concernant les questions techniques représentent, dans la mesure du possible, un accord international sur les sujets étudiés, étant donné que les Comités nationaux de l'IEC intéressés sont représentés dans chaque comité d'études.
3) Les Publications de l'IEC se présentent sous la forme de recommandations internationales et sont agréées comme telles par les Comités nationaux de l'IEC. Tous les efforts raisonnables sont entrepris afin que l'IEC s'assure de l'exactitude du contenu technique de ses publications; l'IEC ne peut pas être tenue responsable de l'éventuelle mauvaise utilisation ou interprétation qui en est faite par un quelconque utilisateur final.
4) Dans le but d'encourager l'uniformité internationale, les Comités nationaux de l'IEC s'engagent, dans toute la mesure possible, à appliquer de façon transparente les Publications de l'IEC dans leurs publications nationales et régionales. Toutes divergences entre toutes Publications de l'IEC et toutes publications nationales ou régionales correspondantes doivent être indiquées en termes clairs dans ces dernières.
5) L'IEC elle-même ne fournit aucune attestation de conformité. Des organismes de certification indépendants fournissent des services d'évaluation de conformité et, dans certains secteurs, accèdent aux marques de conformité de l'IEC. L'IEC n'est responsable d'aucun des services effectués par les organismes de certification indépendants.
6) Tous les utilisateurs doivent s'assurer qu'ils sont en possession de la dernière édition de cette publication.
7) Aucune responsabilité ne doit être imputée à l'IEC, à ses administrateurs, employés, auxiliaires ou mandataires, y compris ses experts particuliers et les membres de ses comités d'études et des Comités nationaux de l'IEC, pour tout préjudice causé en cas de dommages corporels et matériels, ou de tout autre dommage de quelque nature que ce soit, directe ou indirecte, ou pour supporter les coûts (y compris les frais de justice) et les dépenses découlant de la publication ou de l'utilisation de cette Publication de l'IEC ou de toute autre Publication de l'IEC, ou au crédit qui lui est accordé.
8) L'attention est attirée sur les références normatives citées dans cette publication. L'utilisation de publications référencées est obligatoire pour une application correcte de la présente publication.
9) L'attention est attirée sur le fait que certains des éléments de la présente Publication de l'IEC peuvent faire l'objet de droits de brevet. L'IEC ne saurait être tenue pour responsable de ne pas avoir identifié de tels droits de brevets et de ne pas avoir signalé leur existence.

La Norme internationale IEC 60810 a été établie par le sous-comité 34A: Lampes, du comité d'études 34 de l'IEC: Lampes et équipements associés.

Cette cinquième édition annule et remplace la quatrième édition parue en 2014 et l'Amendement 1:2017. Cette édition constitue une révision technique.

Cette édition inclut les modifications techniques majeures suivantes par rapport à l'édition précédente:

a) actualisation et clarification du titre et du domaine d'application;
b) introduction de nouvelles sources lumineuses à LED;
c) introduction des exigences applicables aux sources lumineuses à LED;
d) introduction de lignes directrices pour la validation de la robustesse des LED encapsulées.

Le texte de cette Norme internationale est issu des documents suivants:

FDIS	Rapport de vote
34A/2021/FDIS	34A/2033/RVD

Le rapport de vote indiqué dans le tableau ci-dessus donne toute information sur le vote ayant abouti à l'approbation de cette norme.

Ce document a été rédigé selon les Directives ISO/IEC, Partie 2.

Le comité a décidé que le contenu de ce document ne sera pas modifié avant la date de stabilité indiquée sur le site web de l'IEC sous "http://webstore.iec.ch" dans les données relatives au document recherché. A cette date, le document sera

- reconduit,
- supprimé,
- remplacé par une édition révisée, ou
- amendé.

IMPORTANT – Le logo *"colour inside"* qui se trouve sur la page de couverture de cette publication indique qu'elle contient des couleurs qui sont considérées comme utiles à une bonne compréhension de son contenu. Les utilisateurs devraient, par conséquent, imprimer cette publication en utilisant une imprimante couleur.

LAMPES, SOURCES LUMINEUSES ET LED ENCAPSULÉES POUR VÉHICULES ROUTIERS – EXIGENCES DE PERFORMANCES

1 Domaine d'application

Le présent document est applicable aux lampes à filament,aux lampes à décharge, aux sources lumineuses à LED et aux LED encapsulées destinées à être utilisées dans les véhicules routiers, c'est-à-dire dans les projecteurs avant, les feux de brouillard, les feux de signalisation et l'éclairage intérieur. Il s'applique particulièrement aux lampes et sources lumineuses figurant dans l'IEC 60809.

Il spécifie les exigences et les méthodes d'essai pour le mesurage des caractéristiques de performance telles que la durée de la lampe, la conservation du flux lumineux, la résistance à la torsion, la résistance de l'ampoule de verre et la résistance aux vibrations et aux chocs. En outre, des renseignements sont donnés sur les limites de température, les encombrements maximaux et les surtensions maximales admissibles, à titre de guide pour la conception des équipements électriques et d'éclairage.

Pour certaines des exigences du présent document, le texte renvoie à des données figurant dans des tableaux. Pour les lampes qui n'apparaissent pas dans ces tableaux, les données correspondantes sont fournies par le fabricant ou le fournisseur responsable.

Les exigences de performance sont un complément aux exigences principales spécifiées dans l'IEC 60809. Elles ne sont cependant pas destinées à être utilisées par les administrations pour les homologations légales de type.

NOTE 1 Dans les différents vocabulaires et normes, différents termes sont utilisés pour désigner une «lampe à incandescence» (IEC 60050-845:1987, 845-07-04) et une «lampe à décharge» (IEC 60050-845:1987, 845-07-17). Le présent document utilise les termes «lampe à filament» et «lampe à décharge». Cependant, lorsque le terme «lampe» apparaît seul, ce terme désigne les deux types, à moins que le contexte n'indique clairement qu'il ne s'applique qu'à l'un des types.

NOTE 2 Le présent document ne s'applique pas aux luminaires.

NOTE 3 Le présent document utilise le terme source lumineuse à LED; dans d'autres normes, le terme lampes à LED peut être utilisé pour décrire des produits similaires.

2 Références normatives

Les documents suivants cités dans le texte constituent, pour tout ou partie de leur contenu, des exigences du présent document. Pour les références datées, seule l'édition citée s'applique. Pour les références non datées, la dernière édition du document de référence s'applique (y compris les éventuels amendements).

IEC 60050-845, *Vocabulaire Electrotechnique International – Partie 845: Eclairage* (disponible à l'adresse http://www.electropedia.org)

IEC 60061-1, *Culots de lampes et douilles ainsi que calibres pour le contrôle de l'interchangeabilité et de la sécurité – Partie 1: Culots de lampes*

IEC 60068-2-14, *Essais d'environnement – Partie 2-14: Essais – Essai N: Variation de température*

IEC 60068-2-43, *Essais d'environnement – Partie 2-43: Essais – Essai Kd: Essai à l'hydrogène sulfuré pour contacts et connexions*

IEC 60068-2-58, *Essais d'environnement – Partie 2-58: Essais – Essai Td: Méthodes d'essai de la soudabilité, résistance de la métallisation à la dissolution et résistance à la chaleur de brasage des composants pour montage en surface (CMS)*

IEC 60068-2-60, *Essais d'environnement – Partie 2-60: Essais – Essai Ke: Essai de corrosion dans un flux de mélange de gaz*

IEC 60809:2014, *Lampes pour véhicules routiers – Exigences dimensionnelles, électriques et lumineuses*

CISPR 25, *Véhicules, bateaux et moteurs à combustion interne – Caractéristiques des perturbations radioélectriques – Limites et méthodes de mesure pour la protection des récepteurs embarqués*

ISO 7637-2:2011, *Véhicules routiers – Perturbations électriques par conduction et par couplage – Partie 2: Perturbations électriques transitoires par conduction uniquement le long des lignes d'alimentation*

ISO 10605, *Véhicules routiers – Méthodes d'essai des perturbations électriques provenant de décharges électrostatiques*

Règlements Nations Unies sur les Véhicules – Accord 1958, *Accord concernant l'adoption de prescriptions techniques uniformes applicables aux véhicules à roues, aux équipements et aux pièces susceptibles d'être montés ou utilisés sur un véhicule à roues et les conditions de reconnaissance réciproque des homologations délivrées conformément à ces prescriptions* (disponible à l'adresse www.unece.org/trans/main/wp29/wp29regs.html)[1]

Additif 36: Règlement N° 37, Prescriptions uniformes relatives à l'homologation des lampes à *incandescence destinées à être utilisées dans les feux homologués des véhicules à moteur et de leurs remorques*

Additif 47: Règlement N° 48, *Prescriptions uniformes relatives à l'homologation des véhicules en ce qui concerne l'installation des dispositifs d'éclairage et de signalisation lumineuse*

Additif 100: Règlement N° 101, *Prescriptions uniformes relatives à l'homologation des voitures particulières mues uniquement par un moteur à combustion interne ou mues par une chaîne de traction électrique hybride en ce qui concerne la mesure des émissions de dioxyde de carbone et de la consommation de carburant et/ou la mesure de la consommation d'énergie électrique et de l'autonomie en mode électrique, et des véhicules des catégories M1 et N1 mus uniquement par une chaîne de traction électrique en ce qui concerne la mesure de la consommation d'énergie électrique et de l'autonomie*

Additif 122: Règlement N° 123, *Prescriptions uniformes concernant l'homologation des systèmes d'éclairage avant adaptatifs (AFS) destinés aux véhicules automobiles*

Additif 127: Règlement N° 128, *Prescriptions uniformes concernant l'homologation des sources lumineuses à diodes électroluminescentes (DEL) destinées à être utilisées dans les feux de signalisation homologués des véhicules à moteur et de leurs remorques*

JESD22-A101C, *Steady-state temperature humidity bias life test* (disponible en anglais seulement)

JESD22-A104E, *Temperature cycling* (disponible en anglais seulement)

JESD22-A105C, *Power and temperature cycling* (disponible en anglais seulement)

JESD22-A106B, *Thermal shock* (disponible en anglais seulement)

_____

[1] Également désigné *Accord 1958.* Dans le texte du présent document, les règlements relevant de cet accord sont référencés sous la forme, par exemple, Règlement ONU 37 ou R37.

JESD22-A108D, *Temperature, bias, and operating life* (disponible en anglais seulement)

JESD22-A113F, *Preconditioning of plastic surface mount devices prior to reliability testing* (disponible en anglais seulement)

JESD22-A115C, *Electrostatic discharge (ESD) sensitivity testing machine model (MM)* (disponible en anglais seulement)

JESD22-B101B, *External visual* (disponible en anglais seulement)

JESD22-B103B, *Vibration, variable frequency* (disponible en anglais seulement)

JESD22-B110B, *Mechanical shock* (disponible en anglais seulement)

JESD22-B106D, *Resistance to solder shock for through-hole mounted devices* (disponible en anglais seulement)

JESD22-B116:1998, *Wire Bond Shear Test Method* (disponible en anglais seulement)

JESD51-50:2012-04, *Overview of methodologies for the thermal measurement of single- and multi-chip, single- and multi-pn-junction light-emitting diodes (LEDs)* (disponible en anglais seulement)

JESD51-51:2012-04, *Implementation of the electrical test method for the measurement of real thermal resistance and impedance of light-emitting diodes with exposed cooling surface* (disponible en anglais seulement)

JESD51-52:2012-04, *Guidelines for combining CIE 127-2007 total flux measurements with thermal measurements of leds with exposed cooling surface* (disponible en anglais seulement)

JESD51-53:2012-05, *Terms, definitions and units glossary for LED thermal testing* (disponible en anglais seulement)

ANSI/IPC/ECA J-STD-002C, *Solderability tests for component leads, terminations, lugs, terminals and wires* (disponible en anglais seulement)

ANSI/ESDA/JEDEC JS-001-2012, *Joint JEDEC/ESDA standard for electrostatic discharge sensitivity testing human body model (HBM) – component level* (disponible en anglais seulement)

MIL-STD-883E:2015, *Visual Inspection Criteria* (disponible en anglais seulement)

ZVEI "*Guideline for Customer Notifications of Product and/or Process Changes (PCN) of Electronic Components specified for Automotive Applications*" 4th revised Edition, October 2016, Rev. 3 (disponible en anglais seulement)