IEC 61156-13

Edition 1.0 2023-05

INTERNATIONAL STANDARD

Multicore and symmetrical pair/quad cables for digital communications – Part 13: Symmetrical single pair cables with transmission characteristics up to 20 MHz – Horizontal floor wiring – Sectional specification

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.040.20

ISBN 978-2-8322-7034-9

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 4
1 Scope 6
2 Normative references 6
3 Terms and definitions 7
4 Installation considerations 7
4.1 General remarks 7
4.2 Bending radius of installed cable 7
4.3 Climatic conditions 7
5 Materials and cable construction 7
5.1 General remarks 7
5.2 Cable construction 7
5.3 Conductor 7
5.4 Insulation 8
5.5 Cable element 8
5.6 Screening of the cable element 8
5.7 Cable make-up 8
5.8 Screening of the cable core 8
5.9 Sheath 8
5.10 Identification 8
5.11 Finished cable 9
6 Characteristics and requirements 9
6.1 General remarks 9
6.2 Electrical characteristics and tests 9
6.2.1 Conductor resistance 9
6.2.2 Resistance unbalance within a pair 9
6.2.3 Dielectric strength 9
6.2.4 Insulation resistance 9
6.2.5 Mutual capacitance 9
6.2.6 Capacitance unbalance 9
6.2.7 Transfer impedance 10
6.2.8 Low frequency coupling attenuation 10
6.2.9 Current-carrying capacity 10
6.3 Transmission characteristics 10
6.3.1 Velocity of propagation (phase velocity) 10
6.3.2 Phase delay 10
6.3.3 Attenuation (α) 11
6.3.4 Unbalance attenuation (TCL and $EL\ TCTL$) 12
6.3.5 Alien (exogenous) near-end crosstalk ($ANEXT$) 13
6.3.6 Alien (exogenous) far-end crosstalk ($PS\ AACR\text{-}F$) 13
6.3.7 Impedance 13
6.3.8 Return loss (RL) 13
6.4 Mechanical and dimensional characteristics and requirements 14
6.4.1 Dimensional requirements 14
6.4.2 Elongation at break of the conductors 14
6.4.3 Tensile strength of the insulation 14
6.4.4 Elongation at break of the insulation 14

6.4.5 Adhesion of the insulation to the conductor 14
6.4.6 Elongation at break of the sheath 14
6.4.7 Tensile strength of the sheath 14
6.4.8 Crush test of the cable 14
6.4.9 Impact test of the cable 14
6.4.10 Bending under tension 15
6.4.11 Repeated bending of the cable 15
6.4.12 Tensile performance of the cable 15
6.4.13 Shock test requirements of the cable 15
6.4.14 Bump test requirements of the cable 15
6.4.15 Vibration test requirements of a cable 15
6.5 Environmental characteristics 15
6.5.1 Shrinkage of insulation 15
6.5.2 Wrapping test of insulation after thermal ageing 15
6.5.3 Bending test of insulation at low temperature 15
6.5.4 Elongation at break of the sheath after ageing 15
6.5.5 Tensile strength of the sheath after ageing 15
6.5.6 Sheath pressure test at high temperature 15
6.5.7 Cold bend test of the cable 16
6.5.8 Heat shock test 16
6.5.9 Damp heat steady state 16
6.5.10 Solar radiation (UV test) 16
6.5.11 Solvents and contaminating fluids 16
6.5.12 Salt mist and sulphur dioxide 16
6.5.13 Water immersion 16
6.5.14 Hygroscopicity 16
6.5.15 Wicking 16
6.5.16 Flame propagation characteristics of bunched cables 16
6.5.17 Halogen gas evolution 16
6.5.18 Smoke generation 16
6.5.19 Toxic gas emission 17
6.5.20 Integrated fire test 17
7 Bundled cables requirements 17
8 Introduction to the blank detail specification (BDS) 17
Annex A (informative) Blank detail specification 18
Annex B (informative) Background information for coupling attenuation and low frequency coupling attenuation requirements 23
Bibliography 24

Table 1 – Transfer impedance 10
Table 2 – Low frequency coupling attenuation 10
Table 3 – Attenuation equation constants 11
Table 4 – Attenuation temperature coefficients 11
Table 5 – *TCL* requirements 12
Table 6 – *EL TCTL* requirements 12
Table 7 – *PS ANEXT* requirements 13
Table 8 – *PS AACR-F* requirements 13
Table 9 – *RL* requirements 14

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 13: Symmetrical single pair cables with transmission characteristics up to 20 MHz – Horizontal floor wiring – Sectional specification

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61156-13 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
46C/1256/FDIS	46C/1260/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61156 series, published under the general title *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 13: Symmetrical single pair cables with transmission characteristics up to 20 MHz – Horizontal floor wiring – Sectional specification

1 Scope

This part of IEC 61156 describes cables intended to be used for transmission of 10 Mbit/s over a single twisted pair and distances of up to 1 km. The transmission characteristics of these cables are specified up to a frequency of 20 MHz and at a temperature of 20 °C. Depending on the MICE environment and the installation conditions, either unscreened or screened cables can be used. Furthermore, to consider different maximum transmission lengths, two sets of requirements are specified. The cable type A-1000 is a design supporting up to 1 km channel length while the cable type A-400 is supporting up to 400 m channel length. A blank detail specification can be found in Annex A.

The cables covered by this document are intended to operate with voltages and currents normally encountered in communication systems. While these cables are not intended to be used in conjunction with low impedance sources, for example the electric power supplies of public utility mains, they are intended to be used to support the delivery of DC low voltage remote powering applications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60708, *Low-frequency cables with polyolefin insulation and moisture barrier polyolefin sheath*

IEC 61156-1, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*

IEC TS 61156-1-2, *Multicore and symmetrical pair/quad cables for digital communications – Part 1-2: Electrical transmission characteristics and test methods of symmetrical pair/quad cables*

IEC 61156-5*, Multicore and symmetrical pair/quad cables for digital communications – Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Horizontal floor wiring – Sectional specification*

IEC 62153-4-3, *Metallic communication cable test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method*

IEC 62153-4-9, *Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method*