IEC 61156-5

Edition 3.0 2020-04

REDLINE VERSION

colour inside

Multicore and symmetrical pair/quad cables for digital communications – Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Horizontal floor wiring – Sectional specification

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.20

ISBN 978-2-8322-8147-5

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 5
1 Scope 7
2 Normative references 7
3 Terms and definitions 8
4 Installation considerations 8
4.1 General remarks 8
4.2 Bending radius of installed cable 8
4.3 Climatic conditions 8
5 Materials and cable construction 8
5.1 General remarks 9
5.2 Cable construction 9
5.2.1 Conductor 9
5.2.2 Insulation 9
5.2.3 Cable element 9
5.2.4 Cable make-up 9
5.2.5 Screening of the cable core 9
5.2.6 Sheath 9
5.2.7 Identification 10
5.2.8 Finished cable 10
6 Characteristics and requirements 10
6.1 General remarks 10
6.2 Electrical characteristics and tests 10
6.2.1 Conductor resistance 10
6.2.2 Resistance unbalance 11
6.2.3 Dielectric strength 11
6.2.4 Insulation resistance 11
6.2.5 Mutual capacitance 11
6.2.6 Capacitance unbalance 11
6.2.7 Transfer impedance 11
6.2.8 Coupling attenuation 12
6.2.9 Current-carrying capacity 13
6.3 Transmission characteristics 13
6.3.1 Velocity of propagation (phase velocity) 13
6.3.2 Phase delay and differential delay (delay skew) 13
6.3.3 Attenuation (α) 14
6.3.4 Unbalance attenuation (TCL) 15
6.3.5 Near-end crosstalk ($NEXT$) 16
6.3.6 Far-end crosstalk (~~$FEXT$~~ $ACR\text{-}F$) 16
6.3.7 Alien (exogenous) near-end crosstalk ($ANEXT$) 17
6.3.8 Alien (exogenous) far-end crosstalk (~~$AFEXT$~~ $AACR\text{-}F$) 17
6.3.9 Alien (exogenous) crosstalk of bundled cables 17
6.3.10 Impedance 17
6.3.11 Return loss (RL) 17
6.4 Mechanical and dimensional characteristics and requirements 20
6.4.1 Dimensional requirements 20
6.4.2 Elongation at break of the conductors 20

6.4.3 Tensile strength of the insulation 20
6.4.4 Elongation at break of the insulation 20
6.4.5 Adhesion of the insulation to the conductor 20
6.4.6 Elongation at break of the sheath 20
6.4.7 Tensile strength of the sheath 20
6.4.8 Crush test of the cable 20
6.4.9 Impact test of the cable 20
6.4.10 Bending under tension 20
6.4.11 Repeated bending of the cable 20
6.4.12 Tensile performance of the cable 20
6.4.13 Shock-test requirements of the cable 20
6.4.14 Bump-test requirements of the cable 21
6.4.15 Vibration-test requirements of the cable 21
6.5 Environmental characteristics 21
6.5.1 Shrinkage of insulation 21
6.5.2 Wrapping test of insulation after thermal ageing 21
6.5.3 Bending test of insulation at low temperature 21
6.5.4 Elongation at break of the sheath after ageing 21
6.5.5 Tensile strength of the sheath after ageing 21
6.5.6 Sheath pressure test at high temperature 21
6.5.7 Cold bend test of the cable 21
6.5.8 Heat shock test 21
6.5.9 Damp heat steady state 21
6.5.10 Solar radiation (UV test) 21
6.5.11 Solvents and contaminating fluids 22
6.5.12 Salt mist and sulphur dioxide 22
6.5.13 Water immersion 22
6.5.14 Hygroscopicity 22
6.5.15 Wicking 22
6.5.16 Flame propagation characteristics of a single cable 22
6.5.17 Flame propagation characteristics of bunched cables 22
6.5.18 Halogen gas evolution 22
6.5.19 Smoke generation 22
6.5.20 Toxic gas emission 22
6.5.21 Integrated fire test 22
7 Category 5e multipair cable 22
7.1 General 22
7.2 Transmission 23
8 Introduction to the blank detail specification 23
~~Annex A (informative) Acronyms for common cable constructions ....~~
Annex A (informative) Blank detail specification 26
Bibliography 31

~~Figure 1 – Impedance template ....~~
~~Figure A.1 – Common cable construction examples ....~~

Table 1 – Cable categories 7
Table 2 – Transfer impedance 12

Table 3 – Coupling attenuation in dB 13
Table 4 – Attenuation equation constants 14
Table 5 – Near-end unbalance attenuation 15
Table 6 – Worst-pair *PS NEXT*(1) values 16
Table 7 – Worst-pair *PS ~~EL FEXT~~ ACR-F* (1) values 16
Table 8 – *PS ANEXT* 17
Table 9 – *PS AACR-F* 17
Table 10 – Return loss 19
~~Table A.1 – Cable construction acronyms .....~~

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Horizontal floor wiring – Sectional specification

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

DISCLAIMER
This Redline version is not an official Standard and is intended to provide the user with an indication of what changes have been made to the previous version. Only the IEC International Standard provided in this package is to be considered the official Standard.

This Redline version provides you with a quick and easy way to compare all the changes between this standard and its previous edition. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

International Standard IEC 61156-5 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories.

This third edition cancels and replaces the second edition published in 2009 and Amendment 1:2012. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) additional balance levels with respect to MICE implementation by certain cabling specifications;
b) reference to current standards and technical reports with respect to measurement techniques and remote powering.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
46C/1140/FDIS	46C/1144/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

This International Standard is to be used in conjunction with IEC 61156-1:2007 and IEC 61156-1:2007/AMD1:2009.

A list of all parts in the IEC 61156 series, published under the general title *Multicore and symmetrical pair/quad cables for digital communications,* can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Horizontal floor wiring – Sectional specification

1 Scope

This part of IEC 61156 describes the cables intended primarily for horizontal floor wiring as defined in ISO/IEC 11801 (all parts).

It covers cable designs comprising individually screened, common screened and unscreened pairs or quads ~~(see Annex A)~~. The transmission characteristics and the frequency range (see Table 1) of the cables are specified at 20 °C.

Table 1 – Cable categories

Cable designation	Maximum referenced frequency MHz
Category 5e	100
Category 6	250
Category 6_A	500
Category 7	600
Category 7_A	1 000

These cables can be used for various communication channels which use as many as four pairs simultaneously. In this sense, this document provides the cable characteristics required by system developers to evaluate new systems.

The cables covered by this document are intended to operate with voltages and currents normally encountered in communication systems. While these cables are not intended to be used in conjunction with low impedance sources, for example the electric power supplies of public utility mains, they are intended to be used to support the delivery of low voltage ~~and~~ remote powering applications such as IEEE 802.3af (Power over Ethernet) ~~and~~ or further developments for example according to IEEE 802.3at ~~(Power over Ethernet Plus)~~ or IEEE 802.3bt. More information on the capacity to support these applications according to the installation practices are given in IEC 61156-1-4, IEC TR 61156-1-6 and ISO/IEC TS 29125.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61156-1:2007, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*
IEC 61156-1:2007/AMD1:2009

~~IEC 61156-5-1, *Multicore and symmetrical pair/quad cables for digital communications – Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Horizontal floor wiring – Blank detail specification*~~

IEC 62153-4-3, *Metallic communication cables test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method*

IEC 62153-4-5, *Metallic communication cables test methods – Part 4-5: Electromagnetic compatibility (EMC) – Coupling or screening attenuation – Absorbing clamp method*

IEC 62153-4-9, *Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method*

IEC 61156-6

Edition 4.0 2020-04

INTERNATIONAL STANDARD

Multicore and symmetrical pair/quad cables for digital communications – Part 6: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Work area wiring – Sectional specification



IEC 61156-6:2020-04(en)

CONTENTS

FOREWORD 5
1 Scope 7
2 Normative references 7
3 Terms and definitions 8
4 Installation considerations 8
4.1 General remarks 8
4.2 Bending radius of installed cable 8
4.3 Climatic conditions 8
5 Materials and cable construction 8
5.1 General remarks 8
5.2 Cable construction 9
5.2.1 Conductor 9
5.2.2 Insulation 9
5.2.3 Cable element 9
5.2.4 Cable make-up 9
5.2.5 Screening of the cable core 9
5.2.6 Sheath 9
5.2.7 Identification 10
5.2.8 Finished cable 10
6 Characteristics and requirements 10
6.1 General remarks 10
6.2 Electrical characteristics and tests 10
6.2.1 Conductor resistance 10
6.2.2 Resistance unbalance 10
6.2.3 Dielectric strength 11
6.2.4 Insulation resistance 11
6.2.5 Mutual capacitance 11
6.2.6 Capacitance unbalance 11
6.2.7 Transfer impedance 11
6.2.8 Coupling attenuation 11
6.2.9 Current-carrying capacity 12
6.3 Transmission characteristics 12
6.3.1 Velocity of propagation (phase velocity) 12
6.3.2 Phase delay and differential delay (delay skew) 12
6.3.3 Attenuation 12
6.3.4 Unbalance attenuation (TCL) 13
6.3.5 Near-end crosstalk ($NEXT$) 14
6.3.6 Attenuation to crosstalk ratio far end ($PS\ ACR\text{-}F$) 15
6.3.7 Alien (exogenous) near end crosstalk 15
6.3.8 Alien (exogenous) far-end crosstalk ($AACR\text{-}F$) 16
6.3.9 Alien (exogenous) crosstalk of bundled cables 16
6.3.10 Impedance 16
6.3.11 Return loss (RL) 16
6.4 Mechanical and dimensional characteristics and requirements 17
6.4.1 Dimensional requirements 17
6.4.2 Elongation at break of the conductors 17

6.4.3 Tensile strength of the insulation 17
6.4.4 Elongation at break of the insulation 17
6.4.5 Adhesion of the insulation to the conductor 17
6.4.6 Elongation at break of the sheath 17
6.4.7 Tensile strength of the sheath 17
6.4.8 Crush test of the cable 17
6.4.9 Impact test of the cable 18
6.4.10 Bending under tension 18
6.4.11 Repeated bending of the cable 18
6.4.12 Tensile performance of the cable 18
6.4.13 Shock-test requirements of the cable 18
6.4.14 Bump-test requirements of the cable 18
6.4.15 Vibration-test requirements of the cable 18
6.5 Environmental characteristics 18
6.5.1 Shrinkage of the insulation 18
6.5.2 Wrapping test of the insulation after thermal ageing 18
6.5.3 Bending test of the insulation at low temperature 18
6.5.4 Elongation at break of the sheath after ageing 18
6.5.5 Tensile strength of the sheath after ageing 18
6.5.6 Sheath pressure test at high temperature 19
6.5.7 Cold bend test of the cable 19
6.5.8 Heat shock test 19
6.5.9 Damp heat steady state 19
6.5.10 Solar radiation 19
6.5.11 Solvents and contaminating fluids 19
6.5.12 Salt mist and sulphur dioxide 19
6.5.13 Water immersion 19
6.5.14 Hygroscopicity 19
6.5.15 Wicking 19
6.5.16 Flame propagation characteristics of a single cable 19
6.5.17 Flame propagation characteristics of bunched cables 19
6.5.18 Halogen gas evolution 19
6.5.19 Smoke generation 20
6.5.20 Toxic gas emission 20
6.5.21 Integrated fire test 20
7 Introduction to the blank detail specification 20
Annex A (informative) Blank detail specification 21
Bibliography 26

Table 1 – Cable categories 7
Table 2 – Transfer impedance 11
Table 3 – Coupling attenuation in dB 12
Table 4 – Attenuation, constant values 13
Table 5 – Near-end unbalance attenuation 14
Table 6 – Worst pair $PS\ NEXT(1)$ values 14
Table 7 – Worst pair $PS\ ACR\text{-}F(1)$ 15
Table 8 – $PS\ ANEXT$ 15

Table 9 – *PS AACR-F* 16
Table 10 – Return loss 17

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 6: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Work area wiring – Sectional specification

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61156-6 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories.

This fourth edition cancels and replaces the third edition published in 2010 and Amendment 1:2012. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) additional balance levels with respect to MICE implementation by certain cabling specifications;

b) reference to current standards and technical reports with respect to measurement techniques and remote powering.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
46C/1141/FDIS	46C/1145/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

This International Standard is to be used in conjunction with IEC 61156-1:2007 and IEC 61156-1:2007/AMD1:2009.

A list of all parts in the IEC 61156 series, published under the general title *Multicore and symmetrical pair/quad cables for digital communications,* can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 6: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Work area wiring – Sectional specification

1 Scope

This part of IEC 61156 describes the cables intended primarily for working area wiring as defined in ISO/IEC 11801 (all parts).

It covers cable designs comprising individually screened, common screened and unscreened pairs or quads. The transmission characteristics and the frequency range (see Table 1) of the cables are specified at 20 °C.

Table 1 – Cable categories

Cable designation	**Maximum referenced frequency** MHz
Category 5e	100
Category 6	250
Category 6_A	500
Category 7	600
Category 7_A	1 000

These cables can be used for various communication channels which use as many as four pairs simultaneously. In this sense, this document provides the cable characteristics required by system developers to evaluate new systems.

The cables covered by this document are intended to operate with voltages and currents normally encountered in communication systems. While these cables are not intended to be used in conjunction with low impedance sources, for example the electric power supplies of public utility mains, they are intended to be used to support the delivery of low voltage remote powering applications such as IEEE 802.3af (Power over Ethernet) or further developments for example according to IEEE 802.3at or IEEE 802.3bt. More information on the capacity to support these applications according to the installation practices are given in IEC 61156-1-4, IEC TR 61156-1-6 and ISO/IEC TS 29125.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61156-1:2007, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*
IEC 61156-1:2007/AMD1:2009

IEC 62153-4-3, *Metallic communication cables test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method*

IEC 62153-4-5, *Metallic communication cables test methods – Part 4-5: Electromagnetic compatibility (EMC) – Coupling or screening attenuation – Absorbing clamp method*

IEC 62153-4-9, *Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method*