IEC 61156-7

Edition 2.0 2023-02

INTERNATIONAL STANDARD

Multicore and symmetrical pair/quad cables for digital communications – Part 7: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Sectional specification for digital and analogue communication cables



IEC 61156-7:2023-02(en)



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC 61156-7

Edition 2.0 2023-02

INTERNATIONAL STANDARD

Multicore and symmetrical pair/quad cables for digital communications – Part 7: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Sectional specification for digital and analogue communication cables

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.20

ISBN 978-2-8322-6374-7

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 5
1 Scope 7
2 Normative references 7
3 Terms and definitions 7
4 Installation consideration 8
4.1 General remarks 8
4.2 Bending radius of installed cable 8
4.3 Climatic conditions 8
5 Material and cable construction 8
5.1 General remarks 8
5.2 Cable construction 8
5.2.1 General 8
5.2.2 Conductor 8
5.2.3 Insulation 9
5.2.4 Cable element 9
5.2.5 Cable make-up 9
5.2.6 Screening of the cable core 9
5.2.7 Sheath 9
5.2.8 Identification 10
5.2.9 Finished cable 10
6 Characteristics and requirements 10
6.1 General remarks 10
6.2 Electrical characteristics and tests 10
6.2.1 Conductor resistance 10
6.2.2 Resistance unbalance within a pair 10
6.2.3 Dielectric strength 10
6.2.4 Insulation resistance 11
6.2.5 Mutual capacitance 11
6.2.6 Capacitance unbalance pair to ground 11
6.2.7 Transfer impedance 11
6.2.8 Coupling attenuation 11
6.2.9 Current-carrying capacity 12
6.2.10 Resistance of the screen 12
6.3 Transmission characteristics 12
6.3.1 General remark 12
6.3.2 Velocity of propagation (phase velocity) 12
6.3.3 Phase delay and differential phase delay (delay skew) 12
6.3.4 Attenuation (α) 13
6.3.5 Unbalance attenuation near-end (TCL, $EL\ TCTL$) 13
6.3.6 Near-end crosstalk ($PS\ NEXT$, $NEXT$) 14
6.3.7 Far-end crosstalk ($PS\ ACR\text{-}F$, $ACR\text{-}F$) 15
6.3.8 Alien (exogenous) near-end crosstalk 16
6.3.9 Alien (exogenous) far-end crosstalk 16
6.3.10 Alien (exogenous) crosstalk of bundled cables 16
6.3.11 Impedance 16
6.3.12 Return loss (RL) 16

6.4 Mechanical and dimensional characteristics and requirements 17
6.4.1 Dimensional requirements 17
6.4.2 Elongation at break of the conductors 17
6.4.3 Tensile strength of the insulation 17
6.4.4 Elongation at break of the insulation 17
6.4.5 Adhesion of the insulation to the conductor 17
6.4.6 Elongation at break of the sheath 17
6.4.7 Tensile strength of the sheath 17
6.4.8 Crush test of the cable 17
6.4.9 Impact test of the cable 17
6.4.10 Bending under tension 18
6.4.11 Repeated bending of the cable 18
6.4.12 Tensile performance of the cable 18
6.4.13 Shock-test requirements of the cable 18
6.4.14 Bump-test requirements of the cable 18
6.4.15 Vibration-test requirements of the cable 18
6.5 Environmental characteristics 18
6.5.1 Shrinkage of insulation 18
6.5.2 Wrapping test of insulation after thermal ageing 18
6.5.3 Bending test of insulation at low temperature 18
6.5.4 Elongation at break of the sheath after ageing 18
6.5.5 Tensile strength of the sheath after ageing 18
6.5.6 Sheath pressure at high temperature 18
6.5.7 Cold bend test of the cable 19
6.5.8 Hot shock test 19
6.5.9 Damp heat steady state 19
6.5.10 Solar radiation (UV) 19
6.5.11 Solvents and contaminating fluids 19
6.5.12 Salt mist and sulphur dioxide 19
6.5.13 Water immersion 19
6.5.14 Hygroscopicity 19
6.5.15 Wicking 19
6.5.16 Flame propagation characteristics of a single cable 19
6.5.17 Flame propagation characteristics of bunched cables 19
6.5.18 Resistance to fire 19
6.5.19 Halogen gas evolution 19
6.5.20 Smoke generation 20
6.5.21 Toxic gas emission 20
6.5.22 Integrated fire test 20
7 Introduction to the blank detail specification 20
Annex A (informative) Blank detail specification 21
Bibliography 26

Table 1 – Transfer impedance 11
Table 2 – Coupling attenuation 11
Table 3 – Attenuation, constant values 13
Table 4 – Attenuation values 13
Table 5 – Near-end crosstalk, power-sum ($PS\ NEXT$) 15

Table 6 – Far-end crosstalk ($PS\ ACR\text{-}F$) 16
Table 7 – Return loss 17

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 7: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Sectional specification for digital and analogue communication cables

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61156-7 has been prepared by subcommittee 46C: Wires and symmetrical cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

This part of IEC 61156 is to be read in conjunction with IEC 61156-1:2023.

This second edition cancels and replaces the first edition published in 2003 and Amendment 1:2012. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) restructure all text to comply with ISO/IEC Directives Part 2;

b) align clauses with IEC 61156-1:2023;

c) remove the clause related to screening attenuation as it is no longer a test to be performed (replaced by coupling attenuation);

d) replace the IEC 62153-4-2 method (injection clamp) with IEC 61156-4-5 (absorbing clamp) for coupling attenuation measurement to be consistent with all other parts of the IEC 61156 series;

e) include IEC 62153-4-9 test method (triaxial) for coupling attenuation measurement to be consistent with all other parts of the IEC 61156 series;

f) incorporate the blank detail specification.

The text of this International Standard is based on the following documents:

Draft	Report on voting
46C/1228/CDV	46C/1233/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61156 series, published under the general title *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 7: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Sectional specification for digital and analogue communication cables

1 Scope

This part of IEC 61156 specifies cables that can be used for various communication systems as well as for analogue systems, such as video, that exist or are under development and which may use as many as four pairs simultaneously. In this sense, this sectional specification provides the cable characteristics required by system developers to evaluate new systems as well as to enhance present systems.

It covers a cable having four individually screened (S/FTP) pairs. The cable can be provided with a common screen over the cable core.

The transmission characteristics are specified up to a frequency of 1 200 MHz and at a temperature of 20 °C.

The cables covered by this sectional specification are intended to operate with voltages and currents normally encountered in communication systems and support the delivery of DC low voltage remote powering applications. These cables are not intended to be used in conjunction with low impedance sources, for example the electric power supply of public utility mains.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60304, *Standard colours for insulation for low-frequency cables and wires*

IEC 61156-1, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*

IEC 62153-4-3, *Metallic communication cable test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method*

IEC 62153-4-5, *Metallic communication cable test methods – Part 4-5: Electromagnetic compatibility (EMC) − Screening or coupling attenuation – Absorbing clamp method*

IEC 62153-4-9, *Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 61156-1 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

4 Installation consideration

4.1 General remarks

Installation considerations are defined in IEC 61156-1.

4.2 Bending radius of installed cable

The bending radius of the installed cable shall not be less than 4 times the outside diameter of the cable.

4.3 Climatic conditions

Under static conditions, the cables shall operate in the temperature range from –20 °C to +60 °C. The temperature dependence of the cables is specified for screened cables and should be taken into account for the design of actual cabling systems.

The recommended temperature range during installation should be indicated in the relevant detail specification.

When applications demand remote powering, the maximum temperature of the conductor shall not exceed the maximum operating temperature of the cable. Dielectric performance can be changed permanently due to over exposure of high temperatures.

5 Material and cable construction

5.1 General remarks

The choice of materials and cable construction shall be suitable for the intended application and installation of the cable. Particular care should be taken to meet any special requirements for fire performance (such as burning properties, smoke generation, evolution of halogen gas, etc.) and remote powering.

5.2 Cable construction

5.2.1 General

The cable construction shall be in accordance with the materials, dimensions and assembly details given in the relevant detail specification.

5.2.2 Conductor

The conductor shall be a solid annealed copper conductor, in accordance with IEC 61156-1, and should have a nominal diameter between 0,5 mm and 0,65 mm.

A conductor diameter of up to 0,8 mm may be used.