IEC 61158-5-2

Edition 5.0 2023-03

INTERNATIONAL STANDARD

Industrial communication networks – Fieldbus specifications – Part 5-2: Application layer service definition – Type 2 elements

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 25.040.40; 35.100.70; 35.110

ISBN 978-2-8322-6569-7

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 6
INTRODUCTION 8
1 Scope 9
1.1 General 9
1.2 Specifications 10
1.3 Conformance 10
2 Normative references 10
3 Terms, definitions, symbols, abbreviated terms and conventions 12
3.1 ISO/IEC 7498-1 terms 13
3.2 ISO/IEC 8822 terms 13
3.3 ISO/IEC 9545 terms 13
3.4 ISO/IEC 8824-1 terms 13
3.5 Type 2 fieldbus data-link layer terms 13
3.6 Type 2 fieldbus application-layer specific definitions 14
3.7 Type 2 abbreviated terms and symbols 22
3.8 Conventions 23
3.8.1 Overview 23
3.8.2 General conventions 23
3.8.3 Conventions for class definitions 24
3.8.4 Conventions for service definitions 25
4 Common concepts 26
5 Data type ASE 26
5.1 General 26
5.2 Formal definition of data type objects 26
5.3 FAL defined data types 26
5.3.1 Fixed length types 26
5.3.2 String types 33
5.3.3 Structure types 34
5.4 Data type ASE service specification 37
6 Communication model specification 37
6.1 Concepts 37
6.1.1 General 37
6.1.2 General concepts 38
6.1.3 Relationships between ASEs 38
6.1.4 Naming and addressing 40
6.1.5 Data types 41
6.1.6 Diagnostic connection points 48
6.2 ASEs 49
6.2.1 Object management ASE 49
6.2.2 Connection manager ASE 175
6.2.3 Connection ASE 193
6.3 ARs 207
6.3.1 Overview 207
6.3.2 UCMM AR formal model 218
6.3.3 Transport AR formal model 220
6.3.4 AR ASE services 230

6.4 Summary of FAL classes 237
6.5 Permitted FAL services by AR type 238
Bibliography 240

Figure 1 – Overview of ASEs and object classes 40
Figure 2 – Addressing format using MAC, class, instance and attribute IDs 40
Figure 3 – Identity object state transition diagram 67
Figure 4 – Explicit and Implicit Setting interaction 70
Figure 5 – Static Assembly state transition diagram 75
Figure 6 – Dynamic Assembly state transition diagram 76
Figure 7 – Variable Assembly state transition diagram 78
Figure 8 – Typical timing relationships for acknowledged data production 89
Figure 9 – Example of a COS system with two acking devices 89
Figure 10 – Message flow in COS connection – one Connection object, one consumer 90
Figure 11 – Message flow in COS connection – multiple consumers 90
Figure 12 – Path Reconfiguration in a ring topology 103
Figure 13 – Doubly attached clocks in a PRP network 104
Figure 14 – Type 2 Time Synchronization offset clock model 106
Figure 15 – Type 2 Time Synchronization system with offset clock model 106
Figure 16 – Type 2 time synchronization group startup sequence 109
Figure 17 – Parameter object state transition diagram 115
Figure 18 – Example of Find_Next_Object_Instance service 141
Figure 19 – State Transition Diagram for Fragmentation Session 172
Figure 20 – Transmission Trigger Timer behavior 201
Figure 21 – Inactivity watchdog timer 202
Figure 22 – Using tools for configuration 202
Figure 23 – Production Inhibit Timer behavior 203
Figure 24 – Context of transport services within the connection model 210
Figure 25 – Application–to–application view of data transfer 210
Figure 26 – Data flow diagram for a link producer 211
Figure 27 – Data flow diagram for a link consumer 212
Figure 28 – Triggers 213
Figure 29 – Binding transport instances to the producer and consumer of a transport connection that does not have a reverse data path 214
Figure 30 – Binding transport instances to the producers and consumers of a transport connection that does have a reverse data path 214
Figure 31 – Binding transport instances to the producer and consumers of a multipoint connection when the transport connection does not have a reverse data path 215
Figure 32 – Binding transport instances to the producers and consumers of a multipoint connection when the transport connection does have reverse data paths 215

Table 1 – Valid IANA MIB printer codes for character set selection 36
Table 2 – Common elements 43
Table 3 – ST language elements 44
Table 4 – Type conversion operations 45

Table 5 – Values of implementation-dependent parameters 47
Table 6 – Extensions to IEC 61131-3:2003 47
Table 7 – Identity object state event matrix 68
Table 8 – Static Assembly state event matrix 76
Table 9 – Static Assembly instance attribute access 76
Table 10 – Dynamic Assembly state event matrix 77
Table 11 – Dynamic Assembly instance attribute access 77
Table 12 – Variable Assembly state event matrix 78
Table 13 – Variable Assembly instance attribute access 78
Table 14 – Message Router object Forward_Open parameters 82
Table 15 – Acknowledge Handler object state event matrix 85
Table 16 – Producing I/O application object state event matrix 87
Table 17 – PTPEnable attribute default values 94
Table 18 – Profile identification 101
Table 19 – Profile default settings and ranges 101
Table 20 – Default PTP clock settings 102
Table 21 – HAND set clock quality management 103
Table 22 – Path Reconfiguration Signalling message 104
Table 23 – Parameter object state event matrix 116
Table 24 – Status codes 118
Table 25 – Get_Attributes_All service parameters 120
Table 26 – Set_Attributes_All service parameters 122
Table 27 – Get_Attribute_List service parameters 124
Table 28 – Set_Attribute_List service parameters 126
Table 29 – Reset service parameters 128
Table 30 – Start service parameters 130
Table 31 – Stop service parameters 131
Table 32 – Create service parameters 133
Table 33 – Delete service parameters 135
Table 34 – Get_Attribute_Single service parameters 136
Table 35 – Set_Attribute_Single service parameters 138
Table 36 – Find_Next_Object_Instance service parameters 140
Table 37 – NOP service parameters 142
Table 38 – Apply_Attributes service parameters 143
Table 39 – Save service parameters 145
Table 40 – Restore service parameters 146
Table 41 – Get_Member service parameters 148
Table 42 – Set_Member service parameters 150
Table 43 – Insert_Member service parameters 151
Table 44 – Remove_Member service parameters 153
Table 45 – Group_Sync service parameters 154
Table 46 – Add_AckData_Path service parameters 156
Table 47 – Remove_AckData_Path service parameters 157

Table 48 – Get_Enum_String service parameters 158
Table 49 – Symbolic_Translation service parameters 160
Table 50 – Flash_LEDs service parameters 161
Table 51 – Multiple_Service_Packet service parameters 163
Table 52 – Get_Connection_Point_Member_List service parameters 165
Table 53 – Send_Receive_Fragment service parameters 167
Table 54 – Fragmentation Session Manager Event/Activity Matrix 171
Table 55 – Fragmentation State Event Matrix 172
Table 56 – CM_Open service parameters 184
Table 57 – CM_Close service parameters 186
Table 58 – CM_ Unconnected_Send service parameters 188
Table 59 – CM_Get_Connection_Data service parameters 189
Table 60 – CM_Search_Connection_Data service parameters 190
Table 61 – CM_Get_Connection_Data service parameters 192
Table 62 – I/O Connection object attribute access 197
Table 63 – Bridged Connection object attribute access 198
Table 64 – Explicit messaging object attribute access 199
Table 65 – Connection_Bind service parameters 204
Table 66 – Service_Name service parameters 206
Table 67 – How production trigger, transport class, and CM_RPI determine when data is produced 209
Table 68 – Transport classes 220
Table 69 – UCMM_Create service parameters 230
Table 70 – UCMM_Delete service parameters 231
Table 71 – UCMM_Write service parameters 232
Table 72 – UCMM_Abort service parameters 234
Table 73 – TR_Write service parameters 234
Table 74 – TR_Trigger service parameters 235
Table 75 – TR_Packet_arrived service parameters 235
Table 76 – TR_Ack_received service parameters 236
Table 77 – TR_Verify service parameters 237
Table 78 – FAL class summary 237
Table 79 – FAL services by AR type 238

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 5-2: Application layer service definition – Type 2 elements

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

Attention is drawn to the fact that the use of the associated protocol type is restricted by its intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a layer protocol type to be used with other layer protocols of the same type, or in other type combinations explicitly authorized by its intellectual-property-right holders.

NOTE Combinations of protocol types are specified in the IEC 61784-1 series and the IEC 61784-2 series.

IEC 61158-5-2 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation. It is an International Standard.

This fifth edition cancels and replaces the fourth edition published in 2019. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) update of normative and bibliographic references;
b) new STIME, UTIME and NTIME data types in 5.3.1.5;
c) updated list of managements objects in 6.1.3;
d) new attributes and services for the ASE general formal model in 6.2.1.2.1, 6.2.1.3 and 6.5;
e) clarifications, new attributes and services for the Identity ASE in 6.2.1.2.2;
f) clarifications, new attributes and other extensions for the Assembly ASE in 6.2.1.2.3;
g) new attributes and services for the Message Router ASE in 6.2.1.2.4;
h) addition of missing class attributes for the Acknowledge Handler ASE in 6.2.1.2.5;
i) clarifications, new attributes and services for the Time Sync ASE in 6.2.1.2.6;
j) addition of missing class attributes for the Parameter ASE in 6.2.1.2.7;
k) clarifications of service parameters, status codes and procedures in 6.2.1.3;
l) addition of a new service for the Message Router ASE in 6.2.1.3;
m) clarifications and new services for the Connection Manager ASE in 6.2.2;
n) clarifications and new services for the Connection ASE in 6.2.3;
o) removal of obsoleted transport options and related services in 6.3.3;
p) removal of all references to CPF and CPs (material moved to profile documents);
q) miscellaneous editorial corrections.

The text of this International Standard is based on the following documents:

Draft	Report on voting
65C/1203/FDIS	65C/1244/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts of the IEC 61158 series, published under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the "three-layer" fieldbus reference model described in IEC 61158-1.

The application service is provided by the application protocol making use of the services available from the data-link or other immediately lower layer. This document defines the application service characteristics that fieldbus applications and/or system management can exploit.

Throughout the set of fieldbus standards, the term "service" refers to the abstract capability provided by one layer of the OSI Basic Reference Model to the layer immediately above. Thus, the application layer service defined in this document is a conceptual architectural service, independent of administrative and implementation divisions.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 5-2: Application layer service definition – Type 2 elements

1 Scope

1.1 General

The fieldbus application layer (FAL) provides user programs with a means to access the fieldbus communication environment. In this respect, the FAL can be viewed as a "window between corresponding application programs."

This part of IEC 61158 provides common elements for basic time-critical and non-time-critical messaging communications between application programs in an automation environment and material specific to Type 2 fieldbus. The term "time-critical" is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This document defines in an abstract way the externally visible service provided by the Type 2 fieldbus application layer in terms of:

- an abstract model for defining application resources (objects) capable of being manipulated by users via the use of the FAL service;
- the primitive actions and events of the service;
- the parameters associated with each primitive action and event, and the form which they take; and
- the interrelationship between these actions and events, and their valid sequences.

The purpose of this document is to define the services provided to:

- the FAL user at the boundary between the user and the application layer of the fieldbus reference model; and
- Systems Management at the boundary between the application layer and Systems Management of the fieldbus reference model.

This document specifies the structure and services of the Type 2 fieldbus application layer, in conformance with the OSI Basic Reference Model (ISO/IEC 7498-1) and the OSI application layer structure (ISO/IEC 9545).

FAL services and protocols are provided by FAL application-entities (AE) contained within the application processes. The FAL AE is composed of a set of object-oriented application service elements (ASEs) and a layer management entity (LME) that manages the AE. The ASEs provide communication services that operate on a set of related application process object (APO) classes. One of the FAL ASEs is a management ASE that provides a common set of services for the management of the instances of FAL classes.

Although these services specify, from the perspective of applications, how request and responses are issued and delivered, they do not include a specification of what the requesting and responding applications are to do with them. That is, the behavioral aspects of the applications are not specified; only a definition of what requests and responses they can send/receive is specified. This permits greater flexibility to the FAL users in standardizing such object behavior. In addition to these services, some supporting services are also defined in this document to provide access to the FAL to control certain aspects of its operation.

1.2 Specifications

The principal objective of this document is to specify the characteristics of conceptual application layer services suitable for time-critical communications, and thus supplement the OSI Basic Reference Model in guiding the development of application layer protocols for time-critical communications.

A secondary objective is to provide migration paths from previously-existing industrial communications protocols. It is this latter objective which gives rise to the diversity of services standardized as the various Types of IEC 61158, and the corresponding protocols standardized in subparts of IEC 61158-6.

This document can be used as the basis for formal application programming interfaces. Nevertheless, it is not a formal programming interface, and any such interface will need to address implementation issues not covered by this specification, including

a) the sizes and octet ordering of various multi-octet service parameters, and

b) the correlation of paired request and confirm, or indication and response, primitives.

1.3 Conformance

This document does not specify individual implementations or products, nor does it constrain the implementations of application layer entities within industrial automation systems.

There is no conformance of equipment to this application layer service definition standard. Instead, conformance is achieved through implementation of conforming application layer protocols that fulfill the Type 2 application layer services as defined in this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE All parts of the IEC 61158 series, as well as the IEC 61784-1 series and the IEC 61784-2 series are maintained simultaneously. Cross -references to these documents within the text therefore refer to the editions as dated in this list of normative references.

IEC 61131-3:2003[1], *Programmable controllers – Part 3: Programming languages*

IEC 61158-1:2023, *Industrial communication networks – Fieldbus specifications – Part 1: Overview and guidance for the IEC 61158 and IEC 61784 series*

IEC 61158-3-2:2023, *Industrial communication networks – Fieldbus specifications – Part 3-2: Data-link layer service definition – Type 2 elements*

[1] A newer edition of this standard has been published, but only the cited edition applies.

IEC 61158-4-2:2023, *Industrial communication networks – Fieldbus specifications – Part 4-2: Data-link layer protocol specification – Type 2 elements*

IEC 61158-6-2:2023, *Industrial communication networks – Fieldbus specifications – Part 6-2: Application layer protocol specification – Type 2 elements*

IEC 61588:2021, *Precision clock synchronization protocol for networked measurement and control systems*

IEC 61784-3-2, *Industrial communication networks – Profiles – Part 3-2: Functional safety fieldbuses – Additional specifications for CPF 2*

IEC 62439-3:2016, *Industrial communication networks – High availability automation networks – Part 3: Parallel Redundancy Protocol (PRP) and High-availability Seamless Redundancy (HSR)*

ISO/IEC 646, *Information technology – ISO 7–bit coded character set for information interchange*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*

ISO/IEC/IEEE 8802-3, *Telecommunications and exchange between information technology systems − Requirements for local and metropolitan area networks − Part 3: Standard for Ethernet*

ISO/IEC 8859-1, *Information technology – 8-bit single-byte coded graphic character sets – Part 1: Latin alphabet No. 1*

ISO/IEC 9545, *Information technology – Open Systems Interconnection – Application Layer structure*

ISO/IEC 10646, *Information technology – Universal Coded Character Set (UCS)*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*

ISO/IEC 60559, *Information technology – Microprocessor Systems – Floating-Point arithmetic*

ISO 639-2, *Codes for the representation of names of languages – Part 2: Alpha-3 code*

ISO 8601-1, *Date and time – Representations for information interchange – Part 1: Basic rules*

ISO 8859-1[2]:1987, *Information processing – 8-bit single-byte coded graphic character sets – Part 1: Latin alphabet No. 1*

ISO 8859-2[3]:1987, *Information processing – 8-bit single-byte coded graphic character sets – Part 2: Latin alphabet No. 2*

---

[2] A newer edition of this standard has been published by ISO/IEC, but the cited edition is the one used in the referenced IETF standards.

[3] A newer edition of this standard has been published by ISO/IEC, but the cited edition is the one used in the referenced IETF standards.

ISO 8859-3[4]:1988, *Information processing – 8-bit single-byte coded graphic character sets – Part 3: Latin alphabet No. 3*

ISO 8859-4[5]:1988, *Information processing – 8-bit single-byte coded graphic character sets – Part 4: Latin alphabet No. 4*

ISO 8859-5[6]:1988, *Information processing – 8-bit single-byte coded graphic character sets – Part 5: Latin/Cyrillic alphabet*

ISO 8859-6[7]:1987, *Information processing – 8-bit single-byte coded graphic character sets – Part 6: Latin/Arabic alphabet*

ISO 8859-7[8]:1987, *Information processing – 8-bit single-byte coded graphic character sets – Part 7: Latin/Greek alphabet*

ISO 8859-8[9]:1988, *Information processing – 8-bit single-byte coded graphic character sets – Part 8: Latin/Hebrew alphabet*

ISO 8859-9[10]:1989, *Information processing – 8-bit single-byte coded graphic character sets – Part 9: Latin alphabet No. 5*

ISO 11898-1:2015, *Road vehicles – Controller area network (CAN) – Part 1:Data link layer and physical signalling*

IETF RFC 1759, R. Smith, F. Wright, T. Hastings, S. Zilles, J. Gyllenskog, *Printer MIB,* March 1995, available at https://www.rfc-editor.org/info/rfc1759 [viewed 2022-02-18]

---

4 A newer edition of this standard has been published by ISO/IEC, but the cited edition is the one used in the referenced IETF standards.

5 A newer edition of this standard has been published by ISO/IEC, but the cited edition is the one used in the referenced IETF standards.

6 A newer edition of this standard has been published by ISO/IEC, but the cited edition is the one used in the referenced IETF standards.

7 A newer edition of this standard has been published by ISO/IEC, but the cited edition is the one used in the referenced IETF standards.

8 A newer edition of this standard has been published by ISO/IEC, but the cited edition is the one used in the referenced IETF standards.

9 A newer edition of this standard has been published by ISO/IEC, but the cited edition is the one used in the referenced IETF standards.

10 A newer edition of this standard has been published by ISO/IEC, but the cited edition is the one used in the referenced IETF standards.