IEC 61158-5-8

Edition 1.0 2007-12

INTERNATIONAL STANDARD

Industrial communication networks – Fieldbus specifications – Part 5-8: Application layer service definition – Type 8 elements

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE XD

ICS 35.100.70; 25.040.40

ISBN 2-8318-9456-5

CONTENTS

FOREWORD 4
INTRODUCTION 6
1 Scope 7
1.1 Overview 7
1.2 Specifications 8
1.3 Conformance 8
2 Normative references 8
3 Terms and definitions 9
3.1 ISO/IEC 7498-1 terms 9
3.2 ISO/IEC 8822 terms 9
3.3 ISO/IEC 9545 terms 9
3.4 ISO/IEC 8824 terms 9
3.5 Fieldbus data-link layer terms 9
3.6 Fieldbus application layer specific definitions 10
3.7 Abbreviations and symbols 16
3.8 Conventions 16
4 Concepts 20
4.1 Overview 20
4.2 Architectural relationships 20
4.3 Fieldbus Application Layer structure 22
4.4 FAL naming and addressing 32
4.5 Architecture summary 33
4.6 FAL service procedures 33
4.7 Notional FAL service procedures [INFORMATIVE] 33
4.8 Common FAL attributes 34
4.9 Common FAL service parameters 35
4.10 APDU size 36
5 Data type ASE 36
5.1 General 36
5.2 Formal definition of data type objects 38
5.3 FAL defined data types 38
5.4 Data type ASE service specification 42
6 Communication model specification 42
6.1 ASEs 42
6.2 ARs 85
6.3 Summary of FAL classes 91
6.4 Permitted FAL services by AREP role 91
Bibliography 93

Figure 1 – Relationship to the OSI basic reference model 20
Figure 2 – Architectural positioning of the Type 8 FAL 21
Figure 3 – Client/server interactions 23
Figure 4 – Push model interactions 24
Figure 5 – APOs services conveyed by the FAL 25
Figure 6 – Application entity structure 27

Figure 7 – Example FAL ASEs 28
Figure 8 – FAL management of objects 29
Figure 9 – ASE service conveyance 30
Figure 10 – Defined and established AREPs 32
Figure 11 – FAL architectural components 33
Figure 12 – Data type class hierarchy example 36
Figure 13 – The AR ASE conveys APDUs between APs 58
Figure 14 – 1-to-1 AR establishment 65

Table 1 – Get attributes service parameters 43
Table 2 – Identify 50
Table 3 – Get status 51
Table 4 – Initiate 53
Table 5 – Terminate 55
Table 6 – Reject 57
Table 7 – Conveyance of service primitives by AREP role 59
Table 8 – Valid combinations of AREP roles involved in an AR 59
Table 9 – AR-unconfirmed send 63
Table 10 – AR-establish service 64
Table 11 – Valid combinations of AREP classes to be related 66
Table 12 – AR-abort 67
Table 13 – AR-Data-Send-Acknowledge service parameters 68
Table 14 – Read service parameters 73
Table 15 – Write service parameters 74
Table 16 – Information report service 75
Table 17 – Start service parameters 79
Table 18 – Stop service parameters 80
Table 19 – Resume service parameters 81
Table 20 – Reset service parameters 82
Table 21 – State transitions for a function invocation object 84
Table 22 – FAL class summary 91
Table 23 – Services by AREP role 92

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 5-8: Application layer service definition – Type 8 elements

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the IEC 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

International Standard IEC 61158-5-8 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This first edition and its companion parts of the IEC 61158-5 subseries cancel and replace IEC 61158-5:2003. This edition of this part constitutes a technical revision.

This edition of IEC 61158-5 includes the following significant changes from the previous edition:

a) deletion of the former Type 6 fieldbus for lack of market relevance;
b) addition of new types of fieldbuses;
c) partition of part 5 of the third edition into multiple parts numbered -5-2, -5-3, …

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/475/FDIS	65C/486/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under http://webstore.iec.ch in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

The list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158-1.

The application service is provided by the application protocol making use of the services available from the data-link or other immediately lower layer. This standard defines the application service characteristics that fieldbus applications and/or system management may exploit.

Throughout the set of fieldbus standards, the term “service” refers to the abstract capability provided by one layer of the OSI Basic Reference Model to the layer immediately above. Thus, the application layer service defined in this standard is a conceptual architectural service, independent of administrative and implementation divisions.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 5-8: Application layer service definition – Type 8 elements

1 Scope

1.1 Overview

The fieldbus application layer (FAL) provides user programs with a means to access the fieldbus communication environment. In this respect, the FAL can be viewed as a “window between corresponding application programs.”

This standard provides common elements for basic time-critical and non-time-critical messaging communications between application programs in an automation environment and material specific to Type 8 fieldbus. The term “time-critical” is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard defines in an abstract way the externally visible service provided by the Type 8 fieldbus application layer in terms of

a) an abstract model for defining application resources (objects) capable of being manipulated by users via the use of the FAL service,
b) the primitive actions and events of the service;
c) the parameters associated with each primitive action and event, and the form which they take; and
d) the interrelationship between these actions and events, and their valid sequences.

The purpose of this standard is to define the services provided to

1) the FAL user at the boundary between the user and the application layer of the fieldbus reference model, and
2) Systems Management at the boundary between the application layer and Systems Management of the fieldbus reference model.

This standard specifies the structure and services of the Type 8 fieldbus application layer, in conformance with the OSI Basic Reference Model (ISO/IEC 7498) and the OSI application layer structure (ISO/IEC 9545).

FAL services and protocols are provided by FAL application-entities (AE) contained within the application processes. The FAL AE is composed of a set of object-oriented application service elements (ASEs) and a layer management entity (LME) that manages the AE. The ASEs provide communication services that operate on a set of related application process object (APO) classes. One of the FAL ASEs is a management ASE that provides a common set of services for the management of the instances of FAL classes.

Although these services specify, from the perspective of applications, how request and responses are issued and delivered, they do not include a specification of what the requesting and responding applications are to do with them. That is, the behavioral aspects of the applications are not specified; only a definition of what requests and responses they can send/receive is specified. This permits greater flexibility to the FAL users in standardizing

such object behavior. In addition to these services, some supporting services are also defined in this standard to provide access to the FAL to control certain aspects of its operation.

1.2 Specifications

The principal objective of this standard is to specify the characteristics of conceptual application layer services suitable for time-critical communications, and thus supplement the OSI Basic Reference Model in guiding the development of application layer protocols for time-critical communications.

A secondary objective is to provide migration paths from previously-existing industrial communications protocols. It is this latter objective which gives rise to the diversity of services standardized as the various Types of IEC 61158, and the corresponding protocols standardized in subparts of IEC 61158-6.

This specification may be used as the basis for formal application programming interfaces. Nevertheless, it is not a formal programming interface, and any such interface will need to address implementation issues not covered by this specification, including

a) the sizes and octet ordering of various multi-octet service parameters, and

b) the correlation of paired request and confirm, or indication and response, primitives.

1.3 Conformance

This standard does not specify individual implementations or products, nor does it constrain the implementations of application layer entities within industrial automation systems.

There is no conformance of equipment to this application layer service definition standard. Instead, conformance is achieved through implementation of conforming application layer protocols that fulfill the Type 8 application layer services as defined in this standard.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60559, *Binary Floating-point Arithmetic for Microprocessor Systems*

ISO/IEC 646, *Information technology – ISO 7–bit coded character set for information interchange*

ISO/IEC 7498–1, *Information technology – Open Systems Interconnection – Basic Reference Model – Part 1: The Basic Model*

ISO/IEC 7498–3, *Information technology – Open Systems Interconnection – Basic Reference Model – Part 3: Naming and addressing*

ISO/IEC 8822, *Information technology – Open Systems Interconnection – Presentation service definition*

ISO/IEC 8824, *Information Technology – Abstract Syntax notation One (ASN-1): Specification of basic notation*

ISO/IEC 9545, *Information technology – Open Systems Interconnection – Application Layer structure*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*