IEC 61158-6-17

Edition 1.0 2007-12

INTERNATIONAL STANDARD

Industrial communication networks – Fieldbus specifications – Part 6-17: Application layer protocol specification – Type 17 elements

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE XB

ICS 35.100.70; 25.040.40

ISBN 2-8318-9495-6

CONTENTS

FOREWORD 5
INTRODUCTION 7
1 Scope 8
1.1 General 8
1.2 Specifications 8
1.3 Conformance 8
2 Normative reference 9
3 Definitions 9
3.1 Terms and definitions 9
3.2 Abbreviations and symbols 15
3.3 Conventions 16
4 Abstract syntax description 18
4.1 FAL PDU abstract syntax 18
4.2 Abstract syntax of PDU body 18
4.3 PDUs for ASEs 20
4.4 Type definitions 23
4.5 Data types 26
5 Transfer syntax 28
5.1 Overview of encoding 28
5.2 APDU header encoding 28
5.3 APDU body encoding 29
5.4 Data type encoding rules 30
6 FAL protocol state machines structure 34
7 AP-context state machine 35
8 FAL service protocol machines (FSPMs) 35
8.1 General 35
8.2 Common parameters of the primitives 35
8.3 Variable ASE protocol machine (VARM) 36
8.4 Event ASE protocol machine (EVTM) 39
8.5 Load region ASE protocol machine (LDRM) 41
8.6 Function invocation ASE protocol machine (FNIM) 43
8.7 Time ASE protocol machine (TIMM) 47
8.8 Network management ASE protocol machine (NWMM) 51
9 Application relationship protocol machines (ARPMs) 55
9.1 General 55
9.2 Primitive definitions 55
9.3 State machine 56
9.4 Functions 64
10 DLL mapping protocol machine (DMPM) 65
10.1 General 65
10.2 Primitive definitions 66
10.3 DMPM state machine 67
Bibliography 70

Figure 1 – APDU overview 28

Figure 2 – Type field 29
Figure 3 – Identifier octet 29
Figure 4 – Length octet (one-octet format) 30
Figure 5 – Length octets (three-octet format) 30
Figure 6 – Relationships among protocol machines and adjacent layers 34
Figure 7 – State transition diagram of VARM 37
Figure 8 – State transition diagram of EVTM 40
Figure 9 – State transition diagram of LDRM 42
Figure 10 – State transition diagram of FNIM 44
Figure 11 – State transition diagram of TIMM 48
Figure 12 – State transition diagram of NWMM 52
Figure 13 – State transition diagram of the PTC-ARPM 57
Figure 14 – State transition diagram of the PTU-ARPM 59
Figure 15 – State transition diagram of the PSU-ARPM 60
Figure 16 – State transition diagram of the MTU-ARPM 62
Figure 17 – State transition diagram of the MSU-ARPM 63
Figure 18 – State transition diagram of DMPM 67

Table 1 – Conventions used for AE state machine definitions 17
Table 2 – Encoding of FalArHeader field 28
Table 3 – Primitives exchanged between FAL user and VARM 36
Table 4 – Parameters used with primitives exchanged FAL user and VARM 36
Table 5 – VARM state table – Sender transitions 37
Table 6 – VARM state table – Receiver transitions 38
Table 7 – Functions used by the VARM 39
Table 8 – Primitives exchanged between FAL user and EVTM 39
Table 9 – Parameters used with primitives exchanged FAL user and EVTM 39
Table 10 – EVTM state table – Sender transitions 40
Table 11 – EVTM state table – Receiver transitions 40
Table 12 – Functions used by the EVTM 40
Table 13 – Primitives exchanged between FAL user and LDRM 41
Table 14 – Parameters used with primitives exchanged FAL user and LDRM 41
Table 15 – LDRM state table – Sender transitions 42
Table 16 – LDRM state table – Receiver transitions 43
Table 17 – Functions used by the LDRM 43
Table 18 – Primitives exchanged between FAL user and FNIM 44
Table 19 – Parameters used with primitives exchanged FAL user and FNIM 44
Table 20 – FNIM state table – Sender transitions 45
Table 21 – FNIM state table – Receiver transitions 45
Table 22 – Functions used by the FNIM 47
Table 23 – Primitives exchanged between FAL user and TIMM 47
Table 24 – Parameters used with primitives exchanged FAL user and TIMM 47
Table 25 – TIMM states 48

Table 26 – TIMM state table – Sender transitions 49
Table 27 – TIMM state table – Receiver transitions 50
Table 28 – Functions used by the TIMM 51
Table 29 – Primitives exchanged between FAL user and NWMM 51
Table 30 – Parameters used with primitives exchanged FAL user and NWMM 52
Table 31 – NWMM states 52
Table 32 – NWMM state table – Sender transitions 53
Table 33 – NWMM state table – Receiver transitions 54
Table 34 – Functions used by the NWMM 55
Table 35 – Primitives exchanged between FSPM and ARPM 56
Table 36 – Parameters used with primitives exchanged FSPM user and ARPM 56
Table 37 – PTC-ARPM states 56
Table 38 – PTC-ARPM state table – Sender transitions 57
Table 39 – PTC-ARPM state table – Receiver transitions 58
Table 40 – PTU-ARPM states 59
Table 41 – PTU-ARPM state table – Sender transitions 59
Table 42 – PTU-ARPM state table – Receiver transitions 60
Table 43 – PSU-ARPM states 60
Table 44 – PSU-ARPM state table – Sender transitions 61
Table 45 – PSU-ARPM state table – Receiver transitions 61
Table 46 – MTU-ARPM states 62
Table 47 – MTU-ARPM state table – Sender transitions 62
Table 48 – MTU-ARPM state table – Receiver transitions 63
Table 49 – MSU-ARPM states 63
Table 50 – MSU-ARPM state table – Sender transitions 64
Table 51 – MSU-ARPM state table – Receiver transitions 64
Table 52 – Functions used by the ARPMs 65
Table 53 – Primitives exchanged between DMPM and ARPM 66
Table 54 – Primitives exchanged between data-link layer and DMPM 66
Table 55 – DMPM states 67
Table 56 – DMPM state table – Sender transitions 67
Table 57 – DMPM state table – Receiver transitions 69
Table 58 – Functions used by the DMPM 69

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 6-17: Application layer protocol specification – Type 17 elements

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the IEC 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

IEC draws attention to the fact that it is claimed that compliance with this standard may involve the use of patents as follows, where the [xx] notation indicates the holder of the patent right:

Type 17:

PCT Application No. PCT/JP2004/011537	[YEC]	Communication control method
PCT Application No. PCT/JP2004/011538	[YEC]	Communication control method

IEC takes no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured IEC that they are willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holders of these patent rights are registered with IEC. Information may be obtained from:

[YEC]: Yokogawa Electric Corporation
2-9-32 Nakacho, Musashino-shi, 180-8750 Tokyo,
180-8750 Tokyo,
Japan
Attention: Intellectual Property & Standardization Center

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61158-6-17 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This first edition and its companion parts of the IEC 61158-6 subseries cancel and replace IEC 61158-6:2003. This edition of this part constitutes a technical addition. This part and its Type 17 companion parts also cancel and replace IEC/PAS 62405, published in 2005.

This edition of IEC 61158-6 includes the following significant changes from the previous edition:

a) deletion of the former Type 6 fieldbus for lack of market relevance;

b) addition of new types of fieldbuses;

c) partition of part 6 of the third edition into multiple parts numbered -6-2, -6-3, …

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/476/FDIS	65C/487/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under http://webstore.iec.ch in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

The list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the "three-layer" fieldbus reference model described in IEC/TR 61158-1.

The application protocol provides the application service by making use of the services available from the data-link or other immediately lower layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer application entities (AEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- as a guide for implementors and designers;
- for use in the testing and procurement of equipment;
- as part of an agreement for the admittance of systems into the open systems environment;
- as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 6-17: Application layer protocol specification – Type 17 elements

1 Scope

1.1 General

The fieldbus application layer (FAL) provides user programs with a means to access the fieldbus communication environment. In this respect, the FAL can be viewed as a “window between corresponding application programs.”

This standard provides common elements for basic time-critical and non-time-critical messaging communications between application programs in an automation environment and material specific to Type 17 fieldbus. The term “time-critical” is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard specifies interactions between remote applications and defines the externally visible behavior provided by the Type 17 fieldbus application layer in terms of

a) the formal abstract syntax defining the application layer protocol data units conveyed between communicating application entities;
b) the transfer syntax defining encoding rules that are applied to the application layer protocol data units;
c) the application context state machine defining the application service behavior visible between communicating application entities;
d) the application relationship state machines defining the communication behavior visible between communicating application entities.

The purpose of this standard is to define the protocol provided to

1) define the wire-representation of the service primitives defined in IEC 61158-5-17, and
2) define the externally visible behavior associated with their transfer.

This standard specifies the protocol of the Type 17 fieldbus application layer, in conformance with the OSI Basic Reference Model (ISO/IEC 7498) and the OSI application layer structure (ISO/IEC 9545).

1.2 Specifications

The principal objective of this standard is to specify the syntax and behavior of the application layer protocol that conveys the application layer services defined in IEC 61158-5-17.

A secondary objective is to provide migration paths from previously-existing industrial communications protocols. It is this latter objective which gives rise to the diversity of protocols standardized in the IEC 61158-6 series.

1.3 Conformance

This standard does not specify individual implementations or products, nor does it constrain the implementations of application layer entities within industrial automation systems.

Conformance is achieved through implementation of this application layer protocol specification.

2 Normative reference

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61158-5-17, *Industrial communication networks – Fieldbus specifications - Part 5-17: Application layer service definition – Type 17 elements*

ISO/IEC 7498 (all parts), *Information technology – Open Systems Interconnection – Basic Reference Model*

ISO/IEC 8824-2, *Information technology – Abstract Syntax Notation One (ASN.1): Information object specification*

ISO/IEC 8825-1, *Information technology – ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)*

ISO/IEC 9545, *Information technology – Open Systems Interconnection – Application Layer structure*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*