IEC 61158-6-2

Edition 5.0 2023-03

INTERNATIONAL STANDARD

Industrial communication networks – Fieldbus specifications – Part 6-2: Application layer protocol specification – Type 2 elements

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 25.040.40; 35.100.70; 35.110

ISBN 978-2-8322-6631-1

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 14
INTRODUCTION 17
1 Scope 18
1.1 General 18
1.2 Specifications 18
1.3 Conformance 19
2 Normative references 19
3 Terms, definitions, symbols, abbreviated terms and conventions 21
3.1 Terms and definitions from other ISO/IEC standards 21
3.1.1 Terms and definitions from ISO/IEC 7498-1 21
3.1.2 Terms and definitions from ISO/IEC 9545 21
3.1.3 Terms and definitions from ISO/IEC 8824-1 22
3.1.4 Terms and definitions from ISO/IEC 8825-1 22
3.2 Terms and definitions from IEC 61158-5-2 22
3.3 Additional terms and definitions 22
3.4 Abbreviated terms and symbols 30
3.5 Conventions 30
3.5.1 General concept 30
3.5.2 Attribute specification 31
3.5.3 Common services 31
3.5.4 State machine conventions 34
4 Abstract syntax 36
4.1 FAL PDU abstract syntax 36
4.1.1 General 36
4.1.2 PDU structure 36
4.1.3 UCMM_PDUs 39
4.1.4 Transport_Headers 40
4.1.5 CM_PDUs 43
4.1.6 CM PDU components 56
4.1.7 MR headers 65
4.1.8 OM_Service_PDU 66
4.1.9 Message and connection paths 130
4.1.10 Class, attribute and service codes 146
4.1.11 Error codes 154
4.2 Data abstract syntax specification 169
4.2.1 Transport format specification 169
4.2.2 Abstract syntax notation 170
4.2.3 Control network data specification 170
4.2.4 Data type specification / dictionaries 172
4.3 Encapsulation abstract syntax 174
4.3.1 Encapsulation protocol 174
4.3.2 Encapsulation messages 175
4.3.3 Command descriptions 178
4.3.4 Common packet format 190
5 Transfer syntax 194
5.1 Compact encoding 194

5.1.1 Encoding rules 194
5.1.2 Encoding constraints 195
5.1.3 Examples 195
5.2 Data type reporting 202
5.2.1 Object data representation 202
5.2.2 Elementary data type reporting 202
5.2.3 Constructed data type reporting 203
6 Structure of FAL protocol state machines 209
7 AP-Context state machine 210
7.1 Overview 210
7.2 Connection object state machine 210
7.2.1 I/O Connection instance behavior 210
7.2.2 Bridged Connection instance behavior 215
7.2.3 Explicit Messaging Connection instance behavior 217
8 FAL service protocol machine (FSPM) 219
8.1 General 219
8.2 Primitive definitions 219
8.3 Parameters of primitives 224
8.4 FSPM state machines 225
9 Application relationship protocol machines (ARPMs) 225
9.1 General 225
9.2 Connection-less ARPM (UCMM) 226
9.2.1 General 226
9.2.2 Primitive definitions 226
9.2.3 Parameters of primitives 227
9.2.4 UCMM state machines 228
9.2.5 Examples of UCMM sequences 233
9.2.6 Management UCMM 235
9.3 Connection-oriented ARPMs (transports) 236
9.3.1 Transport PDU buffer 236
9.3.2 Transport classes 237
9.3.3 Common primitive definitions 237
9.3.4 Parameters of common primitives 238
9.3.5 Transport state machines – class 0 238
9.3.6 Transport state machines – class 1 242
9.3.7 Transport state machines – class 2 247
9.3.8 Transport state machines – class 3 255
10 DLL mapping protocol machine 1 (DMPM 1) 265
10.1 General 265
10.2 Link producer 265
10.3 Link consumer 266
10.4 Primitive definitions 266
10.4.1 Primitives exchanged between DMPM and ARPM 266
10.4.2 Parameters of ARPM/DMPM primitives 266
10.4.3 Primitives exchanged between data-link layer and DMPM 266
10.4.4 Parameters of DMPM/Data-link Layer primitives 267
10.4.5 Network connection ID 268
10.5 DMPM state machine 268

10.5.1 DMPM states 268
10.5.2 Functions used by DMPM 270
10.6 Data-link Layer service selection 270
11 DLL mapping protocol machine 2 (DMPM 2) 270
11.1 General 270
11.2 Mapping of UCMM PDUs 270
11.2.1 General 270
11.2.2 Common requirements for Connection Manager PDU's 272
11.2.3 Forward_Open PDU for class 2 and class 3 connections 274
11.2.4 Forward_Open for class 0 and class 1 connections 274
11.2.5 Forward_close 279
11.3 Mapping of transport class 0 and class 1 PDUs 279
11.3.1 Class 0 and class 1 PDUs 279
11.3.2 No dependency on TCP connections 279
11.3.3 Class 0 and class 1 packet ordering 280
11.3.4 Screening incoming connected data 280
11.4 Mapping of transport class 2 and class 3 PDU's 280
11.5 IGMP Usage 281
11.5.1 Background (informative) 281
11.5.2 IGMP Membership Report messages 282
11.5.3 IGMP Leave Group messages 282
11.6 Quality of Service (QoS) for Type 2 Ethernet messages 282
11.6.1 Overview 282
11.6.2 DSCP format 283
11.6.3 IEEE Std 802.1Q-2018 format 284
11.6.4 Mapping Type 2 traffic to DSCP and IEEE Std 802.1Q-2018 284
11.6.5 Usage of DSCP for Type 2 Ethernet 285
11.6.6 Usage of IEEE Std 802.1Q-2018 for Type 2 Ethernet 285
11.6.7 User considerations with IEEE Std 802.1Q-2018 286
11.7 Encapsulation using TCP 286
11.7.1 General 286
11.7.2 Management of a TCP encapsulation session 286
11.7.3 TCP connection management 287
11.8 Encapsulation using UDP 288
12 DLL mapping protocol machine 3 (DMPM 3) 288
Bibliography 289

Figure 1 – Attribute table format and terms 31
Figure 2 – Service request/response parameter 31
Figure 3 – Example of an STD 34
Figure 4 – Network connection parameters 56
Figure 5 – Priority/Tick_time bit definition 59
Figure 6 – Member ID/EX description (WORD) 74
Figure 7 – Transport Class Trigger attribute 118
Figure 8 – DN_initial_comm_characteristics attribute format 122
Figure 9 – Segment type 131
Figure 10 – Port segment 132

Figure 11 – Logical segment encoding 134
Figure 12 – Extended network segment 141
Figure 13 – Symbolic segment encoding 142
Figure 14 – Encapsulation message 175
Figure 15 – FixedLengthBitString compact encoding bit placement rules 199
Figure 16 – Example compact encoding of a SWORD FixedLengthBitString 199
Figure 17 – Example compact encoding of a WORD FixedLengthBitString 199
Figure 18 – Example compact encoding of a DWORD FixedLengthBitString 200
Figure 19 – Example compact encoding of a LWORD FixedLengthBitString 200
Figure 20 – Example 1 of formal encoding of a structure type specification 205
Figure 21 – Example 2 of formal encoding of a structure type specification 205
Figure 22 – Example 3 of formal encoding of a handle structure type specification 206
Figure 23 – Example 4 of formal encoding of a handle structure type specification 206
Figure 24 – Example 5 of abbreviated encoding of a structure type specification 207
Figure 25 – Example 1 of formal encoding of an array type specification 207
Figure 26 – Example 2 of formal encoding of an array type specification 208
Figure 27 – Example 1 of abbreviated encoding of an array type specification 209
Figure 28 – Example 2 of abbreviated encoding of an array type specification 209
Figure 29 – I/O Connection object state transition diagram 210
Figure 30 – Bridged Connection object state transition diagram 215
Figure 31 – Explicit Messaging Connection object state transition diagram 217
Figure 32 – State transition diagram of UCMM client9 229
Figure 33 – State transition diagram of high–end UCMM server 231
Figure 34 – State transition diagram of low–end UCMM server 233
Figure 35 – Sequence diagram for a UCMM with one outstanding message 234
Figure 36 – Sequence diagram for a UCMM with multiple outstanding messages 235
Figure 37 – TPDU buffer 236
Figure 38 – Data flow diagram using a client transport class 0 and server transport class 0 239
Figure 39 – Sequence diagram of data transfer using transport class 0 239
Figure 40 – Class 0 client STD 240
Figure 41 – Class 0 server STD 241
Figure 42 – Data flow diagram using client transport class 1 and server transport class 1 242
Figure 43 – Sequence diagram of data transfer using client transport class 1 and server transport class 1 243
Figure 44 – Class 1 client STD 245
Figure 45 – Class 1 server STD 246
Figure 46 – Data flow diagram using client transport class 2 and server transport class 2 248
Figure 47 – Diagram of data transfer using client transport class 2 and server transport class 2 without returned data 249
Figure 48 – Sequence diagram of data transfer using client transport class 2 and server transport class 2 with returned data 250
Figure 49 – Class 2 client STD 251

Figure 50 – Class 2 server STD 253
Figure 51 – Data flow diagram using client transport class 3 and server transport class 3 256
Figure 52 – Sequence diagram of data transfer using client transport class 3 and server transport class 3 without returned data 257
Figure 53 – Sequence diagram of data transfer using client transport class 3 and server transport class 3 with returned data 258
Figure 54 – Class 3 client STD 260
Figure 55 – Class 3 server STD 263
Figure 56 – Data flow diagram for a link producer and consumer 265
Figure 57 – State transition diagram for a link producer 269
Figure 58 – State transition diagram for a link consumer 270
Figure 59 – DS field in the IP header 284
Figure 60 – IEEE Std 802.1Q-2018 tagged frame 284

Table 1 – Get_Attributes_All response service rules 32
Table 2 – Example class level object/service specific response data of Get_Attributes_All 32
Table 3 – Set_Attributes_All request service rules 33
Table 4 – Example request data of Set_Attributes_All 33
Table 5 – State event matrix format 35
Table 6 – Example state event matrix 35
Table 7 – UCMM_PDU header format 39
Table 8 – UCMM command codes 39
Table 9 – Transport class 0 header 40
Table 10 – Transport class 1 header 40
Table 11 – Transport class 2 header 40
Table 12 – Transport class 3 header 41
Table 13 – Real-time data header – exclusive owner 41
Table 14 – Real-time data header– redundant owner 41
Table 15 – Forward_Open request format 46
Table 16 – Forward_Open_Good response format 47
Table 17 – Forward_Open_Bad response format 47
Table 18 – Large_Forward_Open request format 48
Table 19 – Large_Forward_Open_Good response format 49
Table 20 – Large_Forward_Open_Bad response format 49
Table 21 – Forward_Close request format 50
Table 22 – Forward_Close_Good response format 50
Table 23 – Forward_Close_Bad response format 51
Table 24 – Unconnected_Send request format 52
Table 25 – Unconnected_Send_Good response format 52
Table 26 – Unconnected_Send_Bad response format 53
Table 27 – Get_Connection_Data request format 54
Table 28 – Get_Connection_Data response format 54

Table 29 – Search_Connection_Data request format 55
Table 30 – Get_Connection_Owner request format 55
Table 31 – Get_Connection_Owner response format 56
Table 32 – Time-out multiplier 59
Table 33 – Tick time units 60
Table 34 – Encoded application path ordering 64
Table 35 – Transport class, trigger and Is_Server format 65
Table 36 – MR_Request_Header format 65
Table 37 – MR_Response_Header format 66
Table 38 – Structure of Get_Attributes_All_ResponsePDU body 66
Table 39 – Structure of Set_Attributes_All_RequestPDU body 67
Table 40 – Structure of Get_Attribute_List_RequestPDU body 67
Table 41 – Structure of Get_Attribute_List_ResponsePDU body 67
Table 42 – Structure of Set_Attribute_List_RequestPDU body 67
Table 43 – Structure of Set_Attribute_List_ResponsePDU body 68
Table 44 – Structure of Reset_RequestPDU body 68
Table 45 – Structure of Reset_ResponsePDU body 68
Table 46 – Structure of Start_RequestPDU body 68
Table 47 – Structure of Start_ResponsePDU body 68
Table 48 – Structure of Stop_RequestPDU body 69
Table 49 – Structure of Stop_ResponsePDU body 69
Table 50 – Structure of Create_RequestPDU body 69
Table 51 – Structure of Create_ResponsePDU body 69
Table 52 – Structure of Delete_RequestPDU body 69
Table 53 – Structure of Delete_ResponsePDU body 70
Table 54 – Structure of Get_Attribute_Single_ResponsePDU body 70
Table 55 – Structure of Set_Attribute_Single_RequestPDU body 70
Table 56 – Structure of Set_Attribute_Single_ResponsePDU body 70
Table 57 – Structure of Find_Next_Object_Instance_RequestPDU body 71
Table 58 – Structure of Find_Next_Object_Instance_ResponsePDU body 71
Table 59 – Structure of Apply_Attributes_RequestPDU body 71
Table 60 – Structure of Apply_Attributes_ResponsePDU body 71
Table 61 – Structure of Save_RequestPDU body 71
Table 62 – Structure of Save_ResponsePDU body 72
Table 63 – Structure of Restore_RequestPDU body 72
Table 64 – Structure of Restore_ResponsePDU body 72
Table 65 – Structure of Get_Member_ResponsePDU body 72
Table 66 – Structure of Set_Member_RequestPDU body 72
Table 67 – Structure of Set_Member_ResponsePDU body 73
Table 68 – Structure of Insert_Member_RequestPDU body 73
Table 69 – Structure of Insert_Member_ResponsePDU body 73
Table 70 – Structure of Remove_Member_ResponsePDU body 73
Table 71 – Common structure of _Member_RequestPDU body (basic format) 74

Table 72 – Common structure of _Member_ResponsePDU body (basic format) 75
Table 73 – Common structure of _Member_RequestPDU body (extended format) 75
Table 74 – Common structure of _Member_ResponsePDU body (extended format) 75
Table 75 – Extended Protocol ID 76
Table 76 – Structure of _Member_RequestPDU body (Multiple Sequential Members) 76
Table 77 – Structure of _Member_ResponsePDU body (Multiple Sequential Members) 76
Table 78 – Structure of _Member_RequestPDU body (International String Selection) 77
Table 79 – Structure of _Member_ResponsePDU body (International String Selection) 77
Table 80 – Structure of Group_Sync_RequestPDU body 77
Table 81 – Structure of Group_Sync_ResponsePDU body 78
Table 82 – Structure of Multiple_Service_Packet_RequestPDU body 78
Table 83 – Structure of Multiple_Service_Packet_ResponsePDU body 78
Table 84 – Structure of Get_Connection_Point_Member_List_ResponsePDU body 79
Table 85 – Identity object class attributes 80
Table 86 – Identity object instance attributes 80
Table 87 – Identity object Vendor ID ranges 83
Table 88 – Identity object bit definitions for status instance attribute 83
Table 89 – Default values for extended device status field (bits 4 to 7) of status instance attribute 83
Table 90 – Identity object bit definitions for protection mode instance attribute 84
Table 91 – Identity object bit definitions for features supported attribute 84
Table 92 – Class level object/service specific response data of Get_Attributes_All 84
Table 93 – Instance level object/service specific response data of Get_Attributes_All 85
Table 94 – Object-specific request parameter for Reset 86
Table 95 – Reset service parameter values 86
Table 96 – Communication link attributes that shall be preserved 86
Table 97 – Structure of Flash_LEDs_RequestPDU body 87
Table 98 – Message Router object class attributes 87
Table 99 – Message Router object instance attributes 87
Table 100 – Class level object/service specific response data of Get_Attributes_All 88
Table 101 – Instance level object/service specific response data of Get_Attributes_All 88
Table 102 – Structure of Symbolic_Translation_RequestPDU body 88
Table 103 – Structure of Symbolic_Translation_ResponsePDU body 88
Table 104 – Object specific status for Symbolic_Translation service 89
Table 105 – Structure of Send_Receive_Fragment_RequestPDU body – Phase 1 89
Table 106 – Structure of Send_Receive_Fragment_RequestPDU body – Phase 2 89
Table 107 – Structure of Send_Receive_Fragment_ResponsePDU body – Phase 2 90
Table 108 – Request/Response Fragmentation Flags 90
Table 109 – Fragmentation Flags Usage 90
Table 110 – Object specific status for Send_Receive_Fragment service 91
Table 111 – Assembly object class attributes 92
Table 112 – Assembly object instance attributes 92
Table 113 – Assembly Instance ID ranges 93

Table 114 – Standard Network Diagnostic assembly content and ordering 94
Table 115 – Object-specific request parameter for Create 94
Table 116 – Object-specific response parameter for Create 95
Table 117 – Acknowledge Handler object class attributes 95
Table 118 – Acknowledge Handler object instance attributes 95
Table 119 – Structure of Add_AckData_Path_RequestPDU body 96
Table 120 – Structure of Remove_AckData_Path_RequestPDU body 96
Table 121 – Time Sync object class attributes 96
Table 122 – Time Sync object instance attributes 97
Table 123 – ClockIdentity encoding for different network implementations 101
Table 124 – ClockClass values 101
Table 125 – TimeAccuracy values 102
Table 126 – TimePropertyFlags bit values 102
Table 127 – TimeSource values 103
Table 128 – Types of Clock 103
Table 129 – Network protocol to PortPhysicalAddressInfo mapping 103
Table 130 – Time Sync connection point 1, Standard Network Diagnostics 104
Table 131 – Class level object/service specific response data of Get_Attributes_All 104
Table 132 – Parameter object class attributes 105
Table 133 – Parameter Class Descriptor bit values 105
Table 134 – Parameter object instance attributes 106
Table 135 – Semantics of Descriptor Instance attribute 107
Table 136 – Descriptor Scaling bits usage 107
Table 137 – Minimum and Maximum Value semantics 108
Table 138 – Scaling Formula attributes 109
Table 139 – Scaling links 109
Table 140 – Class level object/service specific response data of Get_Attributes_All 110
Table 141 – Instance level object/service specific response data of Get_Attributes_All (Parameter object stub) 110
Table 142 – Instance level object/service specific response data of Get_Attributes_All (full Parameter object) 111
Table 143 – Structure of Get_Enum_String_RequestPDU body 112
Table 144 – Structure of Get_Enum_String_ResponsePDU body 112
Table 145 – Enumerated strings Type versus Parameter data type 112
Table 146 – Connection Manager object class attributes 113
Table 147 – Connection Manager object instance attributes 113
Table 148 – Connection Manager connection point 1, Standard Network Diagnostics 114
Table 149 – Class level object/service specific response data of Get_Attributes_All 114
Table 150 – Instance level object/service specific response data of Get_Attributes_All 115
Table 151 – Instance level object/service specific request data of Set_Attributes_All 115
Table 152 – Connection object class attributes 116
Table 153 – Connection object instance attributes 116
Table 154 – Values assigned to the state attribute 117
Table 155 – Values assigned to the instance_type attribute 118

Table 156 – Possible values within Direction Bit 119
Table 157 – Possible values within Production Trigger Bits 119
Table 158 – Possible values within Transport Class Bits 120
Table 159 – TransportClass_Trigger attribute values summary 120
Table 160 – Transport Class 0 client behavior summary 121
Table 161 – Transport Class 1, 2 and 3 client behavior summary 121
Table 162 – Values defined for the DN_produced_connection_id attribute 121
Table 163 – Values defined for the DN_consumed_connection_id attribute 122
Table 164 – Values for the Initial Production Characteristics nibble 123
Table 165 – Values for the Initial Consumption Characteristics nibble 124
Table 166 – Values for the watchdog_timeout_action 127
Table 167 – Object-specific response parameters for Apply_Attributes 129
Table 168 – Object-specific response parameter for Set_Attribute_Single 129
Table 169 – Structure of Connection_Bind_RequestPDU body 129
Table 170 – Object specific status for Connection_Bind service 129
Table 171 – Structure of Producing_Application_Lookup_RequestPDU body 130
Table 172 – Structure of Producing_Application_Lookup_ResponsePDU body 130
Table 173 – Producing_Application_Lookup Service status codes 130
Table 174 – Possible port segment examples 133
Table 175 – TCP/IP link address examples 134
Table 176 – Extended Logical Type 135
Table 177 – Electronic key segment format 136
Table 178 – Key Format Table (key type 4) 137
Table 179 – Serial Number Key Format Table (key type 5) 137
Table 180 – Logical segments examples 138
Table 181 – Network segments 139
Table 182 – Extended network segment subtype definitions 141
Table 183 – Symbolic segment examples 143
Table 184 – Data segment 143
Table 185 – ANSI_Extended_Symbol segment 144
Table 186 – Addressing categories 146
Table 187 – Class code ID ranges 147
Table 188 – Class Attribute ID ranges 147
Table 189 – Instance Attribute ID ranges 147
Table 190 – Connection Point ranges 148
Table 191 – Service code ranges 148
Table 192 – Class codes 149
Table 193 – Reserved class attributes for all object class definitions 150
Table 194 – Common services list 151
Table 195 – Identity object specific services list 151
Table 196 – Message Router object specific services list 152
Table 197 – Acknowledge Handler object specific services list 152
Table 198 – Parameter object specific services list 152

Table 199 – Services specific to Connection Manager 152
Table 200 – Services specific to Connection object 153
Table 201 – Device type numbering 153
Table 202 – Implementation profile numbering 154
Table 203 – Connection Manager service request error codes 155
Table 204 – General status codes 165
Table 205 – Extended status code for a general status of "Key Failure in path 167
Table 206 – Identity object status codes 168
Table 207 – TCP port numbers 174
Table 208 – UDP port numbers 175
Table 209 – Encapsulation header 175
Table 210 – Encapsulation command codes 176
Table 211 – Encapsulation status codes 177
Table 212 – Nop request encapsulation header 178
Table 213 – RegisterSession request encapsulation header 179
Table 214 – RegisterSession request data portion 179
Table 215 – RegisterSession reply encapsulation header 180
Table 216 – RegisterSession reply data portion (successful) 180
Table 217 – UnRegisterSession request encapsulation header 181
Table 218 – ListServices request encapsulation header 182
Table 219 – ListServices reply encapsulation header 182
Table 220 – ListServices reply data portion (successful) 182
Table 221 – Communications capability flags 183
Table 222 – ListIdentity request encapsulation header 184
Table 223 – ListIdentity reply encapsulation header 185
Table 224 – ListIdentity reply data portion (successful) 185
Table 225 – Type 2 identity item 186
Table 226 – Type 2 Ethernet Capability item 186
Table 227 – ListInterfaces request encapsulation header 187
Table 228 – ListInterfaces reply encapsulation header 187
Table 229 – SendRRData request encapsulation header 188
Table 230 – SendRRData request data portion 188
Table 231 – SendRRData reply encapsulation header 189
Table 232 – SendUnitData request encapsulation header 189
Table 233 – SendUnitData request data portion 190
Table 234 – Common packet format 190
Table 235 – CPF item format 190
Table 236 – Item Type ID numbers 191
Table 237 – Null address item 191
Table 238 – Connected address item 192
Table 239 – Sequenced address item 192
Table 240 – Unconnected data item 192
Table 241 – Connected data item 193

Table 242 – Sockaddr info items 193
Table 243 – Usage of CPF items 194
Table 244 – BOOLEAN encoding 195
Table 245 – Example compact encoding of a BOOL value 195
Table 246 – Encoding of SignedInteger values 196
Table 247 – Example compact encoding of a SignedInteger value 196
Table 248 – UnsignedInteger values 196
Table 249 – Example compact encoding of an UnsignedInteger 196
Table 250 – FixedLengthReal values 196
Table 251 – Example compact encoding of a REAL value 197
Table 252 – Example compact encoding of a LREAL value 197
Table 253 – FixedLengthReal values 197
Table 254 – STRING value 198
Table 255 – STRING2 value 198
Table 256 – STRINGN value 198
Table 257 – SHORT_STRING value 198
Table 258 – Example compact encoding of a STRING value 198
Table 259 – Example compact encoding of STRING2 value 199
Table 260 – SHORT_STRING type 199
Table 261 – Example compact encoding of a single dimensional ARRAY 200
Table 262 – Example compact encoding of a multi-dimensional ARRAY 201
Table 263 – Example compact encoding of a STRUCTURE 201
Table 264 – Identification codes and descriptions of elementary data types 203
Table 265 – Identification codes and descriptions of constructed data types 204
Table 266 – Formal structure encoding definition 204
Table 267 – Formal structure with handles encoding definition 205
Table 268 – Abbreviated structure encoding definition 206
Table 269 – Formal array encoding definition 207
Table 270 – Abbreviated array encoding definition 208
Table 271 – I/O Connection state event matrix 211
Table 272 – Bridged Connection state event matrix 216
Table 273 – Explicit Messaging Connection state event matrix 217
Table 274 – Primitives issued by FAL user to FSPM 220
Table 275 – Primitives issued by FAL user to FSPM 221
Table 276 – Primitives issued by FSPM to FAL user 223
Table 277 – Parameters used with primitives exchanged between FAL user and FSPM 225
Table 278 – Primitives issued by FSPM to ARPM 227
Table 279 – Primitives issued by ARPM to FSPM 227
Table 280 – Parameters used with primitives exchanged between FSPM and ARPM 228
Table 281 – UCMM client states 228
Table 282 – State event matrix of UCMM client 229
Table 283 – High-end UCMM server states 230
Table 284 – State event matrix of high-end UCMM server 231

Table 285 – Low-end UCMM server states 232
Table 286 – State event matrix of low–end UCMM server 233
Table 287 – Notification 236
Table 288 – Transport classes 237
Table 289 – Primitives issued by FSPM to ARPM 237
Table 290 – Primitives issued by ARPM to FSPM 238
Table 291 – Parameters used with primitives exchanged between FSPM and ARPM 238
Table 292 – Class 0 transport client states 240
Table 293 – Class 0 client SEM 240
Table 294 – Class 0 transport server states 241
Table 295 – Class 0 server SEM 241
Table 296 – Class 1 transport client states 244
Table 297 – Class 1 client SEM 245
Table 298 – Class 1 transport server states 246
Table 299 – Class 1 server SEM 247
Table 300 – Class 2 transport client states 251
Table 301 – Class 2 client SEM 252
Table 302 – Class 2 transport server states 253
Table 303 – Class 2 server SEM 254
Table 304 – Class 3 transport client states 259
Table 305 – Class 3 client SEM 260
Table 306 – Class 3 transport server states 262
Table 307 – Class 3 server SEM 264
Table 308 – Primitives issued by ARPM to DMPM 266
Table 309 – Primitives issued by DMPM to ARPM 266
Table 310 – Parameters used with primitives exchanged between ARPM and DMPM 266
Table 311 – Primitives exchanged between data-link layer and DMPM 267
Table 312 – Parameters used with primitives exchanged between DMPM and Data-link 267
Table 313 – Selection of connection ID 268
Table 314 – Link producer states 268
Table 315 – State event matrix of link producer 269
Table 316 – Link consumer states 269
Table 317 – State event matrix of link consumer 270
Table 318 – UCMM request 271
Table 319 – UCMM reply 272
Table 320 – Network Connection ID selection 273
Table 321 – Sockaddr Info usage 275
Table 322 – Example multicast assignments 278
Table 323 – UDP data format for class 0 and class 1 279
Table 324 – Transport class 2 and class 3 connected data 281
Table 325 – Default DSCP and IEEE Std 802.1Q-2018 mapping 285

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 6-2: Application layer protocol specification – Type 2 elements

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

Attention is drawn to the fact that the use of the associated protocol type is restricted by its intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a layer protocol type to be used with other layer protocols of the same type, or in other type combinations explicitly authorized by its intellectual-property-right holders.

NOTE Combinations of protocol types are specified in the IEC 61784-1 series and the IEC 61784-2 series.

IEC 61158-6-2 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation. It is an International Standard.

This fifth edition cancels and replaces the fourth edition published in 2019. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) update of normative and bibliographic references;
b) review of Get/Set_Attributes_All parameter format in 3.5.3;
c) new services in 4.1.2.1, 4.1.8.1 and 8.2, 8.3;
d) clarifications of services in 4.1.5;
e) definition of specific connection path in 4.1.6.12;
f) clarifications and updates of Get/Set_attribute_list services in 4.1.8.1;
g) clarifications, new attributes for the Identity object in 4.1.8.2;
h) new attributes, service parameters and service for the Message Router object in 4.1.8.3;
i) clarifications, new attribute and other extensions for the Assembly object in 4.1.8.4;
j) clarifications, new attributes, service parameters, services and diagnostics connection points for the Time Sync object in 4.1.8.6;
k) clarifications, new services and addition of diagnostics connection points for the Connection Manager object in 4.1.8.9;
l) clarifications and extensions of Path Segments in 4.1.9;
m) updates and extensions of class, attribute and service codes in 4.1.10;
n) clarifications and additions of error codes in 4.1.11;
o) update of STIME, UTIME and NTIME data types in 4.2.3 and 5.1.3.5;
p) updates of encapsulation protocol in 4.3.1;
q) addition of internal services in 7.1;
r) removal of obsoleted transport options and related services in Clause 9 and Clause 11;
s) updates of DMPM2 in Clause 11;
t) removal of all references to CPF and CPs (material moved to profile documents);
u) miscellaneous editorial corrections.

The text of this International Standard is based on the following documents:

Draft	Report on voting
65C/1204/FDIS	65C/1245/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts of the IEC 61158 series, published under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the "three-layer" fieldbus reference model described in IEC 61158-1.

The application protocol provides the application service by making use of the services available from the data-link or other immediately lower layer. The primary aim of this document is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer application entities (AEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- as a guide for implementers and designers;
- for use in the testing and procurement of equipment;
- as part of an agreement for the admittance of systems into the open systems environment;
- as a refinement to the understanding of time-critical communications within OSI.

This document is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this document together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems can work together in any combination.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 6-2: Application layer protocol specification – Type 2 elements

1 Scope

1.1 General

The Fieldbus Application Layer (FAL) provides user programs with a means to access the fieldbus communication environment. In this respect, the FAL can be viewed as a "window between corresponding application programs."

This part of IEC 61158 provides common elements for basic time-critical and non-time-critical messaging communications between application programs in an automation environment and material specific to Type 2 fieldbus. The term "time-critical" is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This document specifies interactions between remote applications and defines the externally visible behavior provided by the Type 2 fieldbus application layer in terms of

- the formal abstract syntax defining the application layer protocol data units conveyed between communicating application entities;
- the transfer syntax defining encoding rules that are applied to the application layer protocol data units;
- the application context state machine defining the application service behavior visible between communicating application entities;
- the application relationship state machines defining the communication behavior visible between communicating application entities.

The purpose of this document is to define the protocol provided to

- define the wire-representation of the service primitives defined in IEC 61158-5-2, and
- define the externally visible behavior associated with their transfer.

This document specifies the protocol of the Type 2 fieldbus application layer, in conformance with the OSI Basic Reference Model (ISO/IEC 7498-1) and the OSI application layer structure (ISO/IEC 9545).

1.2 Specifications

The principal objective of this document is to specify the syntax and behavior of the application layer protocol that conveys the application layer services defined in IEC 61158-5-2.

A secondary objective is to provide migration paths from previously-existing industrial communications protocols.

1.3 Conformance

This document does not specify individual implementations or products, nor does it constrain the implementations of application layer entities within industrial automation systems. Conformance is achieved through implementation of this application layer protocol specification.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE All parts of the IEC 61158 series, as well as the IEC 61784-1 series and the IEC 61784-2 series are maintained simultaneously. Cross-references to these documents within the text therefore refer to the editions as dated in this list of normative references.

IEC 61158-1:2023, *Industrial communication networks – Fieldbus specifications – Part 1: Overview and guidance for the IEC 61158 and IEC 61784 series*

IEC 61158-3-2:2023, *Industrial communication networks – Fieldbus specifications – Part 3-2: Data-link layer service definition – Type 2 elements*

IEC 61158-4-2:2023, *Industrial communication networks – Fieldbus specifications – Part 4-2: Data-link layer protocol specification – Type 2 elements*

IEC 61158-5-2:2023, *Industrial communication networks – Fieldbus specifications – Part 5-2: Application layer service definition – Type 2 elements*

IEC 61588:2021, *Precision clock synchronization protocol for networked measurement and control systems*

IEC 61784-3-2, *Industrial communication networks – Profiles – Part 3-2: Functional safety fieldbuses – Additional specifications for CPF 2*

IEC 61800-7-202, *Adjustable speed electrical power drive systems – Part 7-202: Generic interface and use of profiles for power drive systems – Profile type 2 specification*

IEC 62026-3:2014, *Low-voltage switchgear and controlgear – Controller-device interfaces (CDIs) – Part 3: DeviceNet*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*

ISO/IEC/IEEE 8802-3, *Telecommunications and exchange between information technology systems – Requirements for local and metropolitan area networks – Part 3: Standard for Ethernet*

ISO/IEC 8824-1, *Information technology – Abstract Syntax Notation One (ASN.1) – Part 1: Specification of basic notation*

ISO/IEC 8825-1, *Information technology – ASN.1 encoding rules – Part 1: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)*

ISO/IEC 9545, *Information technology – Open Systems Interconnection – Application Layer structure*

ISO/IEC 10646, *Information technology – Universal Coded Character Set (UCS)*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*

ISO 639-2, *Codes for the representation of names of languages – Part 2: Alpha-3 code*

ISO 11898-1:2015, *Road vehicles – Controller area network (CAN) – Part 1: Data link layer and physical signalling*

IEEE Std 802.1Q-2018, *IEEE standard for local and metropolitan area networks – Bridges and bridged networks*

IEEE Std 802.3-2018, *IEEE Standard for Ethernet*

IETF RFC 791, J. Postel, *Internet Protocol*, September 1981, available at https://www.rfc-editor.org/info/rfc791 [viewed 2022-02-18]

IETF RFC 1035, P.V. Mockapetris, *Domain Names – Implementation and Specification*, November 1987, available at https://www.rfc-editor.org/info/rfc1035 [viewed 2022-02-18]

IETF RFC 1112, S.E. Deering, *Host Extensions for IP Multicasting*, August 1989, available at https://www.rfc-editor.org/info/rfc1112 [viewed 2022-02-18]

IETF RFC 1117, S. Romano, M.K. Stahl, M. Recker, *Internet Numbers*, August 1989, available at https://www.rfc-editor.org/info/rfc1117 [viewed 2022-02-18]

IETF RFC 1122, R. Braden, *Requirements for Internet Hosts – Communication Layers,* October 1989, available at https://www.rfc-editor.org/info/rfc1122 [viewed 2022-02-18]

IETF RFC 1759, R. Smith, F. Wright, T. Hastings, S. Zilles, J. Gyllenskog, *Printer MIB*, March 1995, available at https://www.rfc-editor.org/info/rfc1759 [viewed 2022-02-18]

IETF RFC 2236, W. Fenner, *Internet Group Management Protocol, Version 2*, November 1997, available at https://www.rfc-editor.org/info/rfc2236 [viewed 2022-02-18]

IETF RFC 2474, K. Nichols, S. Blake, F. Baker, D. Black, *Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers*, December 1998, available at https://www.rfc-editor.org/info/rfc2474 [viewed 2022-02-18]

IETF RFC 2475, S. Blake, D. Black, M. Carlson, E. Davies, Z. Wang, W. Weiss, *An Architecture for Differentiated Services*, December 1998, available at https://www.rfc-editor.org/info/rfc2475 [viewed 2022-02-18]

IETF RFC 2597, J. Heinanen, F. Baker, W. Weiss, J. Wroclawski, *Assured Forwarding PHB Group*, June 1999, available at https://www.rfc-editor.org/info/rfc2597 [viewed 2022-02-18]

IETF RFC 2873, X. Xiao, A. Hannan, V. Paxson, E. Crabbe, *TCP Processing of the IPv4 Precedence Field*, June 2000, available at https://www.rfc-editor.org/info/rfc2873 [viewed 2022-02-18]

IETF RFC 3140, D. Black, S. Brim, B. Carpenter, F. Le Faucheur, *Per Hop Behavior Identification Codes*, June 2001, available at https://www.rfc-editor.org/info/rfc3140 [viewed 2022-02-18]

IETF RFC 3246, B. Davie, A. Charny, J.C.R. Bennet, K. Benson, J.Y. Le Boudec, W. Courtney, S. Davari, V. Firoiu, D. Stiliadis, *An Expedited Forwarding PHB (Per-Hop Behavior)*, March 2002, available at https://www.rfc-editor.org/info/rfc3246 [viewed 2022-02-18]

IETF RFC 3376, B. Cain, S. Deering, I. Kouvelas, B. Fenner, A. Thyagarajan, *Internet Group Management Protocol, Version 3*, October 2002, available at https://www.rfc-editor.org/info/rfc3376 [viewed 2022-02-18]

IETF RFC 4594, J. Babiarz, K. Chan, F. Baker, *Configuration Guidelines for DiffServ Service Classes*, August 2006, available at https://www.rfc-editor.org/info/rfc4594 [viewed 2022-02-18]