IEC 61174

Edition 4.0 2015-08

REDLINE VERSION

colour inside

Maritime navigation and radiocommunication equipment and systems – Electronic chart display and information system (ECDIS) – Operational and performance requirements, methods of testing and required test results

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 47.020.70

ISBN 978-2-8322-2865-4

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 12
1 Scope 14
2 Normative references 14
3 Terms, definitions and abbreviations 16
3.1 Terms and definitions 16
3.2 Abbreviations 22
4 Minimum operational and performance requirements 23
4.1 General 23
4.2 ECDIS definitions 24
4.3 Display of SENC information 24
4.3.1 SENC 24
4.3.2 ~~Warning~~ Indication about use of non-HO source 24
4.3.3 Categories of display 24
4.3.4 Safety contour 26
4.3.5 Safety depth 26
4.3.6 Information content 26
4.3.7 Verification and updates 26
4.3.8 Information about chart objects 26
4.3.9 Display scale 26
4.4 Provision and updating of chart information 26
4.4.1 Contents of the SENC 26
4.4.2 Updates 27
4.5 Scale 28
4.6 Display of other navigational information 28
4.6.1 ~~Common refrence system~~ General for all overlays 28
4.6.2 Radar ~~and plotting~~ information 28
4.6.3 AIS information 31
4.6.4 AIS target data 34
4.6.5 AIS voyage-related data 34
4.6.6 AIS CPA/TCPA alarms 35
4.6.7 AIS lost target warning 35
4.6.8 Anchor watch 36
4.7 Display mode and generation of the neighbouring area 36
4.8 Colours and symbols 37
4.9 Display requirements 37
4.9.1 Route planning and monitoring 37
4.9.2 Chart presentation size 37
4.9.3 Colour and resolution 37
4.9.4 Presentation 38
4.9.5 Removal of information categories 38
4.10 Route planning, monitoring and voyage recording 38
4.10.1 General 38
4.10.2 Route planning 38
4.10.3 Route monitoring 40
4.10.4 Position integration 42
4.10.5 Object information 42

4.10.6 LOP position fix 42
4.10.7 Voyage recording 43
4.11 Calculations and accuracy 43
4.12 Connections with other equipment (interfaces) 44
4.12.1 Connection with navigation equipment 44
4.12.2 Connection with BAM 44
4.12.3 Connection with VDR 45
4.12.4 Connection with BNWAS 46
4.12.5 Connection for SENC information 46
4.12.6 Connection with NAVTEX or SafetyNET for MSI 46
4.12.7 Connection for transfer of route information 47
4.12.8 Connection with INS 47
4.13 Performance tests, malfunction ~~alarms~~ alerts and indications 47
4.14 Back-up arrangements 48
4.15 Power supply 48
4.16 Software maintenance 48
4.17 Quality management requirements 48
4.18 Default control setting and saved user control settings 49
5 Requirements contained in IHO ~~special~~ publications 52
~~5.1 Content and structure of chart data ..... 52~~
5.1 Priority of chart display 52
5.2 Display of chart information 52
5.2.1 Scale and navigation purpose 52
~~5.2.2 Text ..... 53~~
5.2.2 Units and legend 53
5.2.3 Terminology 54
5.3 Display functions 54
5.3.1 ~~Object information~~ Cursor pick 54
5.3.2 Navigational information 55
~~5.3.2 Safety contour ..... 55~~
~~5.3.3 Navigational calculations ..... 56~~
5.3.3 Date-dependant ENC objects 55
5.4 Supplementary display functions 56
5.4.1 Additional mariner's information 56
5.4.2 Additional non-HO information 56
5.4.3 Tidal adjustment 57
5.5 Use of the presentation library 57
5.5.1 Presentation library 57
5.5.2 Test diagrams 58
5.6 Display characteristics 58
~~5.6.1 Display base ..... 58~~
~~5.6.2 Navigators notes ..... 58~~
5.7 Performance requirements 58
5.7.1 Redraw 58
5.7.2 Resolution 59
5.7.3 Symbols 59
5.7.4 Number of colours 59
5.7.5 Brightness and contrast 59
5.8 Ergonomic requirements 60

5.8.1 Mode and orientation 60
5.8.2 Windows 60
~~5.8.3 Mariner's information panel~~ .....
5.9 Update of chart information 60
5.9.1 General 60
5.9.2 Manual update 62
5.9.3 Semi-automatic update 63
5.9.4 Reception of updates 63
5.9.5 Sequence check 63
5.9.6 Consistency check 63
5.9.7 Geographic applicability 64
5.9.8 Summary report 64
5.9.9 Review of ENC updates 64
5.9.10 Modification of updates 64
5.10 Operational area 64
5.11 External removable media 65
6 Methods of testing and required test results 65
6.1 EUT installation, technical documentation, and test requirements 65
6.2 Interfaces 65
6.2.1 General 65
6.2.2 BAM interface 66
6.2.3 VDR interface 67
6.2.4 BNWAS interface 68
6.3 General requirements and presentation requirements 68
6.3.1 General requirements 68
6.3.2 Presentation requirements 68
6.4 Preparation 69
6.4.1 Power-up 69
6.4.2 Initial ship parameters 69
6.4.3 Required test items 69
6.5 ~~Initial data tests~~ Requirements related to ENC chart 70
6.5.1 General 70
6.5.2 Presentation library 71
6.5.3 ENC 71
6.5.4 Encrypted ENC 71
6.6 Accuracy 72
6.7 Visual requirements 72
6.7.1 Symbols 72
6.7.2 Terminology, units and legend 73
6.7.3 Colour table 73
6.7.4 Resolution 74
6.7.5 Display characteristics 74
6.8 Functional requirements 74
6.8.1 Methods of testing 74
6.8.2 Standard display 75
6.8.3 Display base 75
6.8.4 All other information 75
6.8.5 Viewing group layers and text group layers 75
6.8.6 Display priorities 76

6.8.7 Additional display functions 76
6.8.8 Scale and navigation purpose 77
6.8.9 Mode and orientation 77
6.8.10 Safety contour 78
6.8.11 Safety depth 78
6.8.12 ~~Object information~~ Cursor pick 80
6.8.13 Navigation related functions 81
6.8.14 Position integration 81
6.8.15 Radar and ~~plotting~~ other navigational information 81
6.8.16 Loading of corrupted data 84
6.8.17 Automatic updates 84
6.8.18 Manual updates 86
6.8.19 Self-tests of major functions 86
6.8.20 Operational area 87
6.8.21 External removable media 88
6.9 Operational requirements 88
6.9.1 Ergonomic principles 88
6.9.2 Route planning 88
6.9.3 Route monitoring 90
6.9.4 Twelve-hour log 91
6.9.5 Voyage record 92
6.9.6 Power supply 92
6.9.7 LOP position fix 92
6.10 Software maintenance 93
6.11 Quality management 93
6.12 Default control setting and saved operator control settings 93
6.13 AIS information and AIS target data 94
6.13.1 General 94
6.13.2 AIS targets and data report capacity 94
6.13.3 AIS target filtering 94
6.13.4 Activation and deactivation of AIS targets 95
6.13.5 AIS functionality and presentation 95
6.13.6 AIS target data 96
6.13.7 AIS CPA/TCPA alarm 97
6.13.8 AIS lost target warning 97
6.14 AIS Voyage-related data 98
6.15 Anchor watch 98
6.16 NAVTEX and SafetyNET for MSI 98
6.17 Interface for transfer of route information 99
6.18 Interface with INS 100
Annex A (normative) SENC information to be displayed during route planning and route monitoring 101
Annex B (normative) Navigational elements and parameters 102
Annex C (normative) Areas for which special conditions exist 103
Annex D (normative) ~~Alarms and indicators~~ Alerts and indications 104
Annex E (normative) ~~ENC test data set~~ Mandatory terminology and abbreviations 109
Annex F (normative) Back-up arrangements 115
F.1 ~~Introduction~~ Overview 115

F.2 Purpose 115
F.3 Functional requirements 115
F.3.1 Required functions and their availability 115
F.3.2 Reliability and accuracy 119
F.3.3 Malfunctions, warnings, ~~alarms~~ alerts and indications 119
F.4 Operational requirements 119
F.4.1 Ergonomics 119
F.4.2 Presentation of information 119
F.5 Power supply 120
F.6 ~~Connections with other equipment~~ Other requirement 120
F.6.1 ~~Back-up~~ Connection with other systems 120
F.6.2 Route transfer interface 121
F.6.3 Radar as back-up system 121
F.6.4 Operational area 121
F.6.5 Software maintenance 122
F.6.6 Quality management 122
F.6.7 Default Control Settings and Saved User Control Settings 122
F.6.8 External removable media 122
F.7 Methods of testing and required test results 122
F.7.1 EUT installation and technical documentation 122
F.7.2 Interfaces 122
F.7.3 General requirements and presentation requirements 122
F.7.4 Preparation 122
F.7.5 Initial data tests – Chart 123
F.7.6 Accuracy 123
F.7.7 Visual requirements 124
F.7.8 Functional requirements 124
F.7.9 Operational requirements 126
Annex G (normative) ECDIS in the RCDS mode of operation 130
G.1 ~~Introduction~~ Overview 130
G.2 RCDS definitions 130
G.3 Display of SRNC information 131
G.3.1 SRNC 131
G.3.2 Categories of display 131
G.3.3 Power failure 131
G.3.4 Information content 131
G.3.5 Verification and updates 131
G.3.6 Indication 132
G.4 Provision and updating of chart information 132
G.4.1 Contents of the RNC 132
G.4.2 Updates 132
G.5 Scale 133
G.6 Display of other navigational information 133
G.6.1 ~~Common reference system~~ General for all overlays 133
G.6.2 Radar ~~and plotting~~ information 133
G.6.3 AS information 134
G.6.4 AIS Target Data 134
G.6.5 AIS Voyage Related Data 134
G.6.6 AIS CPA/TCPA alarms 134

G.6.7 AIS lost target warning 134
G.6.8 Anchor watch 134
G.7 Display mode and generation of the neighbouring area 134
G.8 Colours and symbols 135
G.9 Display requirements 135
G.9.1 Route planning and monitoring 135
G.9.2 Display characteristics 135
G.9.3 Chart notes 136
G.10 Route planning, monitoring and voyage recording 136
G.10.1 General 136
G.10.2 Route planning 136
G.10.3 Route monitoring 136
G.10.4 Position integration 137
G.10.5 Object information 138
G.10.6 LOP position fix 138
G.10.7 Voyage recording 139
G.11 Calculations and accuracy 139
G.12 Connections with other equipment (interfaces) 139
G.13 Performance tests, malfunction ~~alarms~~ alerts and indications 140
G.14 Back-up arrangements for RCDS mode of operation 140
G.15 Power supply for RCDS mode of operation 140
G.16 Requirements contained in IHO ~~special~~ publications 141
G.16.1 Structure of RNC data 141
G.16.2 RNC data resolution and accuracy 141
G.16.3 RNC meta-data 141
G.16.4 RNC colours 141
G.16.5 RNC notes, diagrams, etc 142
G.16.6 Operational area 142
G.16.7 External removable media 142
G.17 Methods of testing and required test results 142
G.17.1 Preparation – Required test items 142
G.17.2 Initial data tests 143
G.17.3 Accuracy 144
G.17.4 Visual requirements 144
G.17.5 Functional requirements 145
G.17.6 Operational requirement 151
G.18 RNC test data set 154
Annex H (normative) ~~Alarms ans indicators~~ Alerts and indications in the RCDS mode of operation 155
Annex I (normative) Scenario definitions and plots 156
I.1 Overview 156
I.2 Scenario 1: 157
I.3 Scenario 2: 160
I.4 Scenario 3: 163
I.5 Scenario 4: 166
~~Annex J (informative) Tests required for encrypted ENC .....~~
Annex J (informative) Guidance on geodetic calculations 172
J.1 Overview 172

J.2 Distance deviations between Great Circle (orthodrome) and Rhumb Line (loxodrome) 172
J.3 Bearing deviations at start point between Great Circle (orthodrome) and Rhumb Line (loxodrome) 173
Annex K (informative) Guidance for testing 175
K.1 Methods of test derived from ISO 9241-12 175
K.2 Observation 175
K.3 Inspection of documented evidence 175
K.4 Measurement 175
K.5 Analytical evaluation 176
~~Annex L (normative) Testing for colours and intensity ..... ~~
Annex L (informative) Examples of ENC Update Status Report 180
L.1 Overview 180
L.2 ENC Update Status Report – Summary 180
L.3 ENC Update Status Report – Full 181
L.4 ENC Management Report – Route Filtered 183
Annex M (~~informative~~ normative) Elements of an electronic chart database 184
M.1 General 184
M.2 ECDIS implementation 184
M.3 Display base category 185
M.3.1 Coastline layer 185
M.3.2 Safety contour layer 186
M.3.3 Isolated underwater dangers layer 186
M.3.4 Isolated above-water dangers layer 186
M.4 Standard display category 187
M.4.1 Display base layer 187
M.4.2 Additional aids to navigation and fixed structures layer 187
M.4.3 Fairways layer 188
M.4.4 Conspicuous features layer 188
M.4.5 Prohibited and restricted areas layer 188
M.4.6 Ferry routes layer 188
M.4.7 Archipelagic sea lanes layer 188
M.4.8 Buoys and beacons layer 188
M.4.9 Traffic routeing layer 189
M.5 All other information category 189
M.5.1 Information about the chart display layer 189
M.5.2 Natural and man-made features, Port features layer 189
M.5.3 Depth, currents, etc. layer 191
M.5.4 Seabed, obstructions, pipelines layer 191
M.5.5 Traffic routes layer 192
M.5.6 Special areas layer 192
M.5.7 Service and small craft facilities layer 192
M.6 Text grouping 192
M.6.1 Important Text group layer 192
M.6.2 Other Text group layer 192
~~Annex N (informative) Cross-references between IEC 61174 editions and MSC.232(82) ..... ~~
Annex N (informative) Use cases for safety contour and safety depth 196
Annex O (informative) Guidelines on use of electronic chart systems in polar waters 198

O.1 Projection and coordinate system 198
O.2 Consistency 199
Annex P (normative) Scenarios for polar areas above 85° North 200
Annex Q (normative) IEC 61162 interfaces 206
Q.1 General 206
Q.2 VDR interface 208
Q.3 AIS interface and interrogation 209
Q.4 Route transfer interface 209
Q.5 BAM interface 209
Annex R (informative) Conversion between IEC 61162-1 sentences and IEC 61162-3 parameter group numbers 214
Annex S (normative) Route plan exchange format – RTZ 216
S.1 General 216
S.2 RTP Data container 217
S.3 High-level description of the RTZ format 218
S.4 Adaptation to third-party extensions 218
S.4.1 Generic idea 218
S.4.2 Unique identification of a waypoint 218
S.4.3 Creation of new waypoints 219
S.4.4 Change of geographic data for a waypoint 219
S.4.5 Waypoint removal 219
S.5 Detailed RTZ format description 219
S.5.1 File components 219
S.5.2 Route node description 219
S.5.3 RouteInfo node description 220
S.5.4 Waypoints node description 221
S.5.5 DefaultWaypoint node description 221
S.5.6 Waypoint node description 222
S.5.7 Storing date and time for legs 223
S.5.8 Schedules node description 223
S.5.9 Schedule node description 223
S.5.10 Extensions node description 225
S.5.11 Extension node description 226
S.6 XML schema to be met by RTZ route files 226
S.7 Basic RTZ route example 238
S.8 Example of the RTZ route with embedded extensions 239
S.9 UML model of the Route exchange format 240
Annex T (normative) Interface for reporting route transfer 242
T.1 Route encapsulation format for transmitting RTZ over IEC 61162-450 242
T.2 RRT – Report route transfer 243
Annex U (normative) Sentences used by SafetyNET 244
U.1 General 244
U.2 SM1 – SafetyNET Message, All Ships/NavArea 244
U.3 SM2 – SafetyNET Message, Coastal Warning Area 246
U.4 SM3 – SafetyNET Message, Circular Area Address 248
U.5 SM4 – SafetyNET Message, Rectangular Area Address 250
U.6 SMB – IMO SafetyNET Message Body 253
U.7 An example of use 254

Annex V (normative) Extension of TTD sentence, Protocol version 1 255
V.1 General 255
V.2 TTD – Tracked target data, Protocol version 1 255
Annex W (normative) Symbols 256
Bibliography 257

Figure F.1 – Backup system logical interfaces 121
Figure I.1 – Definition of elements of route 156
Figure I.2 – Route for scenario 1 159
Figure I.3 – Route for scenario 2 162
Figure I.4 – Route for scenario 3 165
Figure I.5 – Route for scenario 4 168
Figure J.1 – Distance deviations between Great Circle and Rhumb Line 172
Figure J.2 – Bearing deviations at start point between Great Circle and Rhumb Line 174
Figure N.1 – Original situation 196
Figure N.2 – New situation 197
Figure P.1 – Examples of use of the tables 200
Figure Q.1 – ECDIS logical interfaces 206
Figure Q.2 – Alert reporting by ECDIS without escalation of a warning 210
Figure Q.3 – Alert reporting by ECDIS with escalation of a warning as alarm 210
Figure Q.4 – Alert reporting by ECDIS in case of remote acknowledge 211
Figure Q.5 – Alert reporting by ECDIS in case of remote silence 212
Figure Q.6 – Alert reporting by ECDIS in case of remote silence 213
Figure Q.7 – Alert reporting by ECDIS in case of remote silence 213
Figure S.1 – Description of route plan – Distance between WP 2 and WP 3 217
Figure S.2 – Description of route plan – Leg parameters belonging to WP 3 217
Figure S.3 – UML diagram 241
Figure T.1 – Examples of timing for route transfer 242

~~Table 1 – Mandatory IEC 61162-1 .....~~
Table 1 – Tracked target display capacity 29
~~Table 2 – Area, line and point objects .....~~
Table 2 – AIS display capacity 32
Table 3 – Control settings configured in response to ‘Default’ selection 50
Table D.1 – Alerts and indications resulting from IMO requirements 104
Table D.2 – Alerts and indications defined in this standard 105
Table E.1 – Chart display terminology 109
Table E.2 – Main function terminology 111
Table E.3 – Database terminology 112
Table E.4 – Route, route monitoring or route plan related terminology 113
Table H.1 – Alerts and indications in the RCDS mode of operation 155
Table J.1 – Rhumb Line distances 173
Table J.2 – Deviations from Great Circle distances 174

~~Table L.1 – Ambient light conditions~~
Table M.1 – Minimum ECDIS mariner viewing group layer selectors 185
Table M.2 – Minimum ECDIS mariner text group layer selectors 185
Table P.1 – Spatial control points from 85°N, 0°E as origin 201
Table P.2 – Spatial control points from 87°N, 0°E as origin 202
Table P.3 – Spatial control points from 89°N, 0°E as origin 203
Table P.4 – Spatial control points from 90°N, 0°E as origin, 180°E as origin of relative bearings 204
Table Q.1 – Mandatory sentences received by ECDIS 207
Table Q.2 – Optional sentences received by ECDIS 207
Table Q.3 – Mandatory sentences transmitted by the ECDIS 208
Table Q.4 – Optional sentences transmitted by the ECDIS 208
Table Q.5 – Mandatory information transmitted to the VDR 208
Table Q.6 – Information between the ECDIS and an ECDIS backup system 209
Table R.1 – Conversion from IEC 61162-1 to IEC 61162-3 214
Table R.2 – Conversion from IEC 61162-3 to IEC 61162-1 215
Table W.1 – Anchor watch symbol 256

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS –

Electronic chart display and information system (ECDIS) – Operational and performance requirements, methods of testing and required test results

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

DISCLAIMER
This Redline version is not an official IEC Standard and is intended only to provide the user with an indication of what changes have been made to the previous version. Only the current version of the standard is to be considered the official document.

This Redline version provides you with a quick and easy way to compare all the changes between this standard and its previous edition. A vertical bar appears in the margin wherever a change has been made. Additions and deletions are displayed in red, with deletions being struck through.

International Standard IEC 61174 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This fourth edition of IEC 61174 cancels and replaces the third edition published in 2008, of which it constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- updated references are provided to IHO publications and test methods are updated to IHO test data sets;
- requirements have been added for display of radar and AIS information;
- new interface requirements have been added for BNWAS, VDR, BAM, MSI, INS and route transfer;
- a requirement for an anchor watch has been added;
- additional test methods are specified for operation of ECDIS beyond the normal range between 85 degrees South latitude and 85 degrees North latitude.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/761/FDIS	80/767/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS –

Electronic chart display and information system (ECDIS) – Operational and performance requirements, methods of testing and required test results

1 Scope

This International Standard specifies the performance requirements, methods of testing and required test results of equipment conforming to performance standards not inferior to those adopted by the IMO in resolution MSC.232(82).

This standard is based upon the performance standards of IMO resolution MSC.232(82), and is also associated with IMO resolution A.694(17) and IEC 60945. Reference is made, where appropriate, to IMO resolution MSC.232(82), and all subclauses whose wording is identical to that in the resolution are printed in italics.

In association with the above IMO resolution MSC.232(82), are the International Hydrographic Organization (IHO) ~~special~~ publications[1] IHO S-32, IHO S-52, IHO S-57, IHO S-61, IHO S-63 and IHO S-64. This standard has included extracts from the above publications where they are applicable to this equipment. Where reference is made, all subclauses whose wording is identical to that in the publications, are printed in italics.

(232/A2.1) *These performance standards should apply to all ECDIS equipment carried on all ships as follows:*

– *dedicated standalone workstation.*

– *a multifunction workstation as part of an INS.*

(232/A2.2) These performance standards apply to ECDIS mode of operation, ECDIS in RCDS mode of operation as specified in Annex G *and ECDIS backup arrangements as specified in* Annex F*.*

(232/A2.3) Requirements for structure and format of the chart data, encryption of chart data as well as the presentation of chart data are within the scope of relevant IHO standards, including those listed in the normative references.

The requirements of this standard are not intended to prevent the use of new techniques in equipment and systems, provided the facilities offered are not inferior to those stated.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

_____

[1] IHO publications are available from http://www.iho.int, together with any supplementary information.

~~IEC 61162 (all parts), *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*~~

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

IEC 61162-450:2011 *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 450: Multiple talkers and multiple listeners – Ethernet interconnection*

IEC 61924-2:2012, *Maritime navigation and radiocommunication equipment and systems – Integrated navigation systems – Part 2: Modular structure for INS – Operational and performance requirements, methods of testing and required test results*

IEC 61996-1:2013, *Maritime navigation and radiocommunication equipment and systems – Shipborne voyage data recorder (VDR) – Part 1: Performance requirements, methods of testing and required test results*

IEC 62288:2014, *Maritime navigation and radiocommunication equipment and systems – Presentation of navigation-related information on shipborne navigational displays – General requirements – Methods of testing and required test results*

IEC 62388:2013, *Maritime navigation and radiocommunication equipment and systems – Shipborne radar – Performance requirements – Methods of testing and required test results*

ISO 8601, *Data elements and interchange formats – Information interchange – Representation of dates and times*

IHO M-3:2007, *Resolutions of the IHO, Chapter A, Section 3, Technical Resolution 3.11*

IHO S-52:2014, *Specifications for chart content and display aspects of ECDIS edition 6.1*

IHO S-52, appendix 1:2012, *Guidance on Updating the Electronic Navigational Chart edition 4.0*

IHO S-52, Annex A:2014, *Presentation library edition 4.0*

IHO S-57, *IHO transfer standard for digital hydrographic data*

IHO S-57, appendix B.1, *ENC product specification*

IHO S-61:1999, *Product specification for raster navigational charts (RNC)*

IHO S-63, *IHO data protection scheme*

IHO S-64, *Test data sets for ECDIS*

IMO, *International Convention for the safety of life at sea (SOLAS) 1974 (as amended)*

~~IMO A.424(XI):1979, *Performance standards for gyro-compasses*~~

IMO A.694(17):1991, *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

~~IMO A.821(19):1995, *Performance standards for gyro-compasses for high-speed craft*~~

~~IMO A.823(19):1995, *Performance standards for automatic radar plotting aids*~~

~~IMO A.824(19):1995, *Performance standards for devices to indicate speed and distance*~~

~~IMO A.830(19):1995, Code on Alarms and Indicators~~

IMO MSC.191(79):2004, *Performance standards for the presentation of navigation-related information on shipborne navigational displays*

~~IMO MSC.192(79), *Revised performance standards for radar equipment*~~

IMO MSC.232(82):2006, *Revised Performance standards for electronic chart display and information systems (ECDIS)*

IMO MSC.252(83), *Performance standards for integrated navigation systems (INS)*

IMO MSC/Circ.982:2000, *Guidelines on ergonomic criteria for bridge equipment and layout*

~~IMO SN/Circ.243 (2004), *Guidelines for the Presentation of Navigation-related Symbols, Terms and Abbreviations*~~

IMO SN.1/Circ.266:2007, *Maintenance of electronic chart display and information system (ECDIS) software*

~~IHO M-3:2007, *Resolutions of the IHO, Chapter A, Section 3, Technical Resolution 3.11*~~

~~IHO S-32, appendix 1, *Hydrographic dictionary – Glossary of ECDIS related terms*~~

~~IHO S-52:1996, *Specifications for chart content and display aspects of ECDIS*~~

~~IHO S-52, appendix 1:1996, *Guidance on updating the electronic navigational chart*~~

~~IHO S-52, appendix 2:2004 *Colour and symbol specifications for ECDIS*~~

~~IHO S-57, appendix B.1: 2000, ENC product specification~~

~~IHO S-61:1999, Product specification for raster navigational charts (RNC)~~

~~IHO S-63:2008, IHO data protection scheme~~

~~IHO S-64, *Test data sets for ECDIS*~~

IEC 61174

Edition 4.0 2015-08

INTERNATIONAL STANDARD

colour inside

Maritime navigation and radiocommunication equipment and systems – Electronic chart display and information system (ECDIS) – Operational and performance requirements, methods of testing and required test results



IEC 61174:2015-08(en)

CONTENTS

FOREWORD 12
1 Scope 14
2 Normative references 14
3 Terms, definitions and abbreviations 16
3.1 Terms and definitions 16
3.2 Abbreviations 21
4 Minimum operational and performance requirements 22
4.1 General 22
4.2 ECDIS definitions 23
4.3 Display of SENC information 23
4.3.1 SENC 23
4.3.2 Indication about use of non-HO source 23
4.3.3 Categories of display 23
4.3.4 Safety contour 24
4.3.5 Safety depth 25
4.3.6 Information content 25
4.3.7 Verification and updates 25
4.3.8 Information about chart objects 25
4.3.9 Display scale 25
4.4 Provision and updating of chart information 25
4.4.1 Contents of the SENC 25
4.4.2 Updates 26
4.5 Scale 26
4.6 Display of other navigational information 26
4.6.1 General for all overlays 26
4.6.2 Radar information 27
4.6.3 AIS information 30
4.6.4 AIS target data 32
4.6.5 AIS voyage-related data 33
4.6.6 AIS CPA/TCPA alarms 33
4.6.7 AIS lost target warning 34
4.6.8 Anchor watch 34
4.7 Display mode and generation of the neighbouring area 35
4.8 Colours and symbols 35
4.9 Display requirements 36
4.9.1 Route planning and monitoring 36
4.9.2 Chart presentation size 36
4.9.3 Colour and resolution 36
4.9.4 Presentation 36
4.9.5 Removal of information categories 36
4.10 Route planning, monitoring and voyage recording 36
4.10.1 General 36
4.10.2 Route planning 37
4.10.3 Route monitoring 38
4.10.4 Position integration 40
4.10.5 Object information 41

4.10.6 LOP position fix 41
4.10.7 Voyage recording 41
4.11 Calculations and accuracy 42
4.12 Connections with other equipment (interfaces) 42
4.12.1 Connection with navigation equipment 42
4.12.2 Connection with BAM 42
4.12.3 Connection with VDR 43
4.12.4 Connection with BNWAS 44
4.12.5 Connection for SENC information 44
4.12.6 Connection with NAVTEX or SafetyNET for MSI 44
4.12.7 Connection for transfer of route information 45
4.12.8 Connection with INS 46
4.13 Performance tests, malfunction alerts and indications 46
4.14 Back-up arrangements 46
4.15 Power supply 46
4.16 Software maintenance 46
4.17 Quality management requirements 47
4.18 Default control setting and saved user control settings 47
5 Requirements contained in IHO publications 49
5.1 Priority of chart display 49
5.2 Display of chart information 50
5.2.1 Scale and navigation purpose 50
5.2.2 Units and legend 50
5.2.3 Terminology 51
5.3 Display functions 51
5.3.1 Cursor pick 51
5.3.2 Navigational information 51
5.3.3 Date-dependant ENC objects 52
5.4 Supplementary display functions 52
5.4.1 Additional mariner’s information 52
5.4.2 Additional non-HO information 52
5.4.3 Tidal adjustment 53
5.5 Use of the presentation library 53
5.5.1 Presentation library 53
5.5.2 Test diagrams 53
5.6 Display characteristics 53
5.7 Performance requirements 54
5.7.1 Redraw 54
5.7.2 Resolution 54
5.7.3 Symbols 54
5.7.4 Number of colours 55
5.7.5 Brightness and contrast 55
5.8 Ergonomic requirements 55
5.8.1 Mode and orientation 55
5.8.2 Windows 55
5.9 Update of chart information 56
5.9.1 General 56
5.9.2 Manual update 57
5.9.3 Semi-automatic update 58

5.9.4 Reception of updates 58
5.9.5 Sequence check 58
5.9.6 Consistency check 59
5.9.7 Geographic applicability 59
5.9.8 Summary report 59
5.9.9 Review of ENC updates 59
5.9.10 Modification of updates 59
5.10 Operational area 59
5.11 External removable media 60
6 Methods of testing and required test results 60
6.1 EUT installation, technical documentation, and test requirements 60
6.2 Interfaces 60
6.2.1 General 60
6.2.2 BAM interface 61
6.2.3 VDR interface 62
6.2.4 BNWAS interface 63
6.3 General requirements and presentation requirements 63
6.3.1 General requirements 63
6.3.2 Presentation requirements 63
6.4 Preparation 63
6.4.1 Power-up 63
6.4.2 Initial ship parameters 64
6.4.3 Required test items 64
6.5 Requirements related to ENC chart 64
6.5.1 General 64
6.5.2 Presentation library 65
6.5.3 ENC 65
6.5.4 Encrypted ENC 65
6.6 Accuracy 65
6.7 Visual requirements 65
6.7.1 Symbols 65
6.7.2 Terminology, units and legend 65
6.7.3 Colour table 65
6.7.4 Resolution 66
6.7.5 Display characteristics 66
6.8 Functional requirements 66
6.8.1 Methods of testing 66
6.8.2 Standard display 66
6.8.3 Display base 66
6.8.4 All other information 67
6.8.5 Viewing group layers and text group layers 67
6.8.6 Display priorities 67
6.8.7 Additional display functions 67
6.8.8 Scale and navigation purpose 67
6.8.9 Mode and orientation 68
6.8.10 Safety contour 68
6.8.11 Safety depth 68
6.8.12 Cursor pick 68
6.8.13 Navigation related functions 68

6.8.14 Position integration 69
6.8.15 Radar and other navigational information 69
6.8.16 Loading of corrupted data 72
6.8.17 Automatic updates 72
6.8.18 Manual updates 73
6.8.19 Self-tests of major functions 73
6.8.20 Operational area 73
6.8.21 External removable media 74
6.9 Operational requirements 74
6.9.1 Ergonomic principles 74
6.9.2 Route planning 74
6.9.3 Route monitoring 76
6.9.4 Twelve hour log 78
6.9.5 Voyage record 78
6.9.6 Power supply 78
6.9.7 LOP position fix 78
6.10 Software maintenance 79
6.11 Quality management 79
6.12 Default control setting and saved operator control settings 80
6.13 AIS information and AIS target data 80
6.13.1 General 80
6.13.2 AIS targets and data report capacity 80
6.13.3 AIS target filtering 80
6.13.4 Activation and deactivation of AIS targets 81
6.13.5 AIS functionality and presentation 81
6.13.6 AIS target data 82
6.13.7 AIS CPA/TCPA alarm 83
6.13.8 AIS lost target warning 83
6.14 AIS Voyage-related data 84
6.15 Anchor watch 84
6.16 NAVTEX and SafetyNET for MSI 85
6.17 Interface for transfer of route information 85
6.18 Interface with INS 86
Annex A (normative) SENC information to be displayed during route planning and route monitoring 87
Annex B (normative) Navigational elements and parameters 88
Annex C (normative) Areas for which special conditions exist 89
Annex D (normative) Alerts and indications 90
Annex E (normative) Mandatory terminology and abbreviations 92
Annex F (normative) Back-up arrangements 98
F.1 Overview 98
F.2 Purpose 98
F.3 Functional requirements 98
F.3.1 Required functions and their availability 98
F.3.2 Reliability and accuracy 102
F.3.3 Malfunctions, warnings, alerts and indications 102
F.4 Operational requirements 102
F.4.1 Ergonomics 102

F.4.2 Presentation of information 102
F.5 Power supply 103
F.6 Other requirement 103
F.6.1 Connection with other systems 103
F.6.2 Route transfer interface 104
F.6.3 Radar as back-up system 104
F.6.4 Operational area 104
F.6.5 Software maintenance 104
F.6.6 Quality management 104
F.6.7 Default Control Settings and Saved User Control Settings 104
F.6.8 External removable media 104
F.7 Methods of testing and required test results 105
F.7.1 EUT installation and technical documentation 105
F.7.2 Interfaces 105
F.7.3 General requirements and presentation requirements 105
F.7.4 Preparation 105
F.7.5 Initial data tests – Chart 106
F.7.6 Accuracy 106
F.7.7 Visual requirements 106
F.7.8 Functional requirements 106
F.7.9 Operational requirements 108
Annex G (normative) ECDIS in the RCDS mode of operation 111
G.1 Overview 111
G.2 RCDS definitions 111
G.3 Display of SRNC information 112
G.3.1 SRNC 112
G.3.2 Categories of display 112
G.3.3 Power failure 112
G.3.4 Information content 112
G.3.5 Verification and updates 112
G.3.6 Indication 113
G.4 Provision and updating of chart information 113
G.4.1 Contents of the RNC 113
G.4.2 Updates 113
G.5 Scale 114
G.6 Display of other navigational information 114
G.6.1 General for all overlays 114
G.6.2 Radar information 114
G.6.3 AS information 115
G.6.4 AIS Target Data 115
G.6.5 AIS Voyage Related Data 115
G.6.6 AIS CPA/TCPA alarms 115
G.6.7 AIS lost target warning 115
G.6.8 Anchor watch 115
G.7 Display mode and generation of the neighbouring area 115
G.8 Colours and symbols 116
G.9 Display requirements 116
G.9.1 Route planning and monitoring 116
G.9.2 Display characteristics 116

G.9.3 Chart notes 117
G.10 Route planning, monitoring and voyage recording 117
G.10.1 General 117
G.10.2 Route planning 117
G.10.3 Route monitoring 117
G.10.4 Position integration 118
G.10.5 Object information 119
G.10.6 LOP position fix 119
G.10.7 Voyage recording 119
G.11 Calculations and accuracy 120
G.12 Connections with other equipment (interfaces) 120
G.13 Performance tests, malfunction alerts and indications 121
G.14 Back-up arrangements for RCDS mode of operation 121
G.15 Power supply for RCDS mode of operation 121
G.16 Requirements contained in IHO publications 122
G.16.1 Structure of RNC data 122
G.16.2 RNC data resolution and accuracy 122
G.16.3 RNC meta-data 122
G.16.4 RNC colours 122
G.16.5 RNC notes, diagrams, etc 123
G.16.6 Operational area 123
G.16.7 External removable media 123
G.17 Methods of testing and required test results 123
G.17.1 Preparation – Required test items 123
G.17.2 Initial data tests 124
G.17.3 Accuracy 124
G.17.4 Visual requirements 125
G.17.5 Functional requirements 126
G.17.6 Operational requirement 131
G.18 RNC test data set 134
Annex H (normative) Alerts and indications in the RCDS mode of operation 135
Annex I (normative) Scenario definitions and plots 136
I.1 Overview 136
I.2 Scenario 1: 137
I.3 Scenario 2: 138
I.4 Scenario 3: 140
I.5 Scenario 4: 141
Annex J (informative) Guidance on geodetic calculations 144
J.1 Overview 144
J.2 Distance deviations between Great Circle (orthodrome) and Rhumb Line (loxodrome) 144
J.3 Bearing deviations at start point between Great Circle (orthodrome) and Rhumb Line (loxodrome) 145
Annex K (informative) Guidance for testing 147
K.1 Methods of test derived from ISO 9241-12 147
K.2 Observation 147
K.3 Inspection of documented evidence 147
K.4 Measurement 147
K.5 Analytical evaluation 148

Annex L (informative) Examples of ENC Update Status Report 149
L.1 Overview 149
L.2 ENC Update Status Report – Summary 149
L.3 ENC Update Status Report – Full 150
L.4 ENC Management Report – Route Filtered 152
Annex M (normative) Elements of an electronic chart database 153
M.1 General 153
M.2 ECDIS implementation 153
M.3 Display base category 154
M.3.1 Coastline layer 154
M.3.2 Safety contour layer 155
M.3.3 Isolated underwater dangers layer 155
M.3.4 Isolated above-water dangers layer 155
M.4 Standard display category 156
M.4.1 Display base layer 156
M.4.2 Additional aids to navigation and fixed structures layer 156
M.4.3 Fairways layer 156
M.4.4 Conspicuous features layer 156
M.4.5 Prohibited and restricted areas layer 157
M.4.6 Ferry routes layer 157
M.4.7 Archipelagic sea lanes layer 157
M.4.8 Buoys and beacons layer 157
M.4.9 Traffic routeing layer 157
M.5 All other information category 158
M.5.1 Information about the chart display layer 158
M.5.2 Natural and man-made features, Port features layer 158
M.5.3 Depth, currents, etc. layer 159
M.5.4 Seabed, obstructions, pipelines layer 160
M.5.5 Traffic routes layer 160
M.5.6 Special areas layer 160
M.5.7 Service and small craft facilities layer 161
M.6 Text grouping 161
M.6.1 Important Text group layer 161
M.6.2 Other Text group layer 161
Annex N (informative) Use cases for safety contour and safety depth 163
Annex O (informative) Guidelines on use of electronic chart systems in polar waters 165
O.1 Projection and coordinate system 165
O.2 Consistency 166
Annex P (normative) Scenarios for polar areas above 85° North 167
Annex Q (normative) IEC 61162 interfaces 173
Q.1 General 173
Q.2 VDR interface 176
Q.3 AIS interface and interrogation 176
Q.4 Route transfer interface 177
Q.5 BAM interface 177
Annex R (informative) Conversion between IEC 61162-1 sentences and IEC 61162-3 parameter group numbers 181
Annex S (normative) Route plan exchange format – RTZ 183

S.1 General ... 183
S.2 RTP Data container ... 184
S.3 High-level description of the RTZ format ... 185
S.4 Adaptation to third-party extensions ... 185
S.4.1 Generic idea ... 185
S.4.2 Unique identification of a waypoint ... 185
S.4.3 Creation of new waypoints ... 186
S.4.4 Change of geographic data for a waypoint ... 186
S.4.5 Waypoint removal ... 186
S.5 Detailed RTZ format description ... 186
S.5.1 File components ... 186
S.5.2 Route node description ... 186
S.5.3 RouteInfo node description ... 187
S.5.4 Waypoints node description ... 188
S.5.5 DefaultWaypoint node description ... 188
S.5.6 Waypoint node description ... 189
S.5.7 Storing date and time for legs ... 190
S.5.8 Schedules node description ... 190
S.5.9 Schedule node description ... 190
S.5.10 Extensions node description ... 192
S.5.11 Extension node description ... 193
S.6 XML schema to be met by RTZ route files ... 193
S.7 Basic RTZ route example ... 205
S.8 Example of the RTZ route with embedded extensions ... 206
S.9 UML model of the Route exchange format ... 207
Annex T (normative) Interface for reporting route transfer ... 209
T.1 Route encapsulation format for transmitting RTZ over IEC 61162-450 ... 209
T.2 RRT – Report route transfer ... 210
Annex U (normative) Sentences used by SafetyNET ... 211
U.1 General ... 211
U.2 SM1 – SafetyNET Message, All Ships/NavArea ... 211
U.3 SM2 – SafetyNET Message, Coastal Warning Area ... 213
U.4 SM3 – SafetyNET Message, Circular Area Address ... 215
U.5 SM4 – SafetyNET Message, Rectangular Area Address ... 217
U.6 SMB – IMO SafetyNET Message Body ... 220
U.7 An example of use ... 221
Annex V (normative) Extension of TTD sentence, Protocol version 1 ... 222
V.1 General ... 222
V.2 TTD – Tracked target data, Protocol version 1 ... 222
Annex W (normative) Symbols ... 223
Bibliography ... 224

Figure F.1 – Backup system logical interfaces ... 103
Figure I.1 – Definition of elements of route ... 136
Figure I.2 – Route for scenario 1 ... 138
Figure I.3 – Route for scenario 2 ... 139
Figure I.4 – Route for scenario 3 ... 140

Figure I.5 – Route for scenario 4 143
Figure J.1 – Distance deviations between Great Circle and Rhumb Line 144
Figure J.2 – Bearing deviations at start point between Great Circle and Rhumb Line 146
Figure N.1 – Original situation 163
Figure N.2 – New situation 164
Figure P.1 – Examples of use of the tables 167
Figure Q.1 – ECDIS logical interfaces 173
Figure Q.2 – Alert reporting by ECDIS without escalation of a warning 177
Figure Q.3 – Alert reporting by ECDIS with escalation of a warning as alarm 178
Figure Q.4 – Alert reporting by ECDIS in case of remote acknowledge 178
Figure Q.5 – Alert reporting by ECDIS in case of remote silence 179
Figure Q.6 – Alert reporting by ECDIS in case of remote silence 180
Figure Q.7 – Alert reporting by ECDIS in case of remote silence 180
Figure S.1 – Description of route plan – Distance between WP 2 and WP 3 184
Figure S.2 – Description of route plan – Leg parameters belonging to WP 3 184
Figure S.3 – UML diagram 208
Figure T.1 – Examples of timing for route transfer 209

Table 1 – Tracked target display capacity 28
Table 2 – AIS display capacity 30
Table 3 – Control settings configured in response to ‘Default’ selection 47
Table D.1 – Alerts and indications resulting from IMO requirements 90
Table D.2 – Alerts and indications defined in this standard 91
Table E.1 – Chart display terminology 92
Table E.2 – Main function terminology 94
Table E.3 – Database terminology 95
Table E.4 – Route, route monitoring or route plan related terminology 96
Table H.1 – Alerts and indications in the RCDS mode of operation 135
Table J.1 – Rhumb Line distances 145
Table J.2 – Deviations from Great Circle distances 146
Table M.1 – Minimum ECDIS mariner viewing group layer selectors 153
Table M.2 – Minimum ECDIS mariner text group layer selectors 154
Table P.1 – Spatial control points from 85°N, 0°E as origin 168
Table P.2 – Spatial control points from 87°N, 0°E as origin 169
Table P.3 – Spatial control points from 89°N, 0°E as origin 170
Table P.4 – Spatial control points from 90°N, 0°E as origin, 180°E as origin of relative bearings 171
Table Q.1 – Mandatory sentences received by ECDIS 174
Table Q.2 – Optional sentences received by ECDIS 175
Table Q.3 – Mandatory sentences transmitted by the ECDIS 175
Table Q.4 – Optional sentences transmitted by the ECDIS 176
Table Q.5 – Mandatory information transmitted to the VDR 176
Table Q.6 – Information between the ECDIS and an ECDIS backup system 177

Table R.1 – Conversion from IEC 61162-1 to IEC 61162-3 181
Table R.2 – Conversion from IEC 61162-3 to IEC 61162-1 182
Table W.1 – Anchor watch symbol 223

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS –

Electronic chart display and information system (ECDIS) – Operational and performance requirements, methods of testing and required test results

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61174 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This fourth edition of IEC 61174 cancels and replaces the third edition published in 2008, of which it constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- updated references are provided to IHO publications and test methods are updated to IHO test data sets;
- requirements have been added for display of radar and AIS information;

- new interface requirements have been added for BNWAS, VDR, BAM, MSI, INS and route transfer;
- a requirement for an anchor watch has been added;
- additional test methods are specified for operation of ECDIS beyond the normal range between 85 degrees South latitude and 85 degrees North latitude.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/761/FDIS	80/767/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS –

Electronic chart display and information system (ECDIS) – Operational and performance requirements, methods of testing and required test results

1 Scope

This International Standard specifies the performance requirements, methods of testing and required test results of equipment conforming to performance standards not inferior to those adopted by the IMO in resolution MSC.232(82).

This standard is based upon the performance standards of IMO resolution MSC.232(82), and is also associated with IMO resolution A.694(17) and IEC 60945. Reference is made, where appropriate, to IMO resolution MSC.232(82), and all subclauses whose wording is identical to that in the resolution are printed in italics.

In association with the above IMO resolution MSC.232(82), are the International Hydrographic Organization (IHO) publications[1]. IHO S-32, IHO S-52, IHO S-57, IHO S-61, IHO S-63 and IHO S-64. This standard has included extracts from the above publications where they are applicable to this equipment. Where reference is made, all subclauses whose wording is identical to that in the publications, are printed in italics.

(232/A2.1) *These performance standards should apply to all ECDIS equipment carried on all ships as follows:*

– *dedicated standalone workstation.*

– *a multifunction workstation as part of an INS.*

(232/A2.2) These performance standards apply to ECDIS mode of operation, ECDIS in RCDS mode of operation as specified in Annex G *and ECDIS backup arrangements as specified in* Annex F*.*

(232/A2.3) Requirements for structure and format of the chart data, encryption of chart data as well as the presentation of chart data are within the scope of relevant IHO standards, including those listed in the normative references.

The requirements of this standard are not intended to prevent the use of new techniques in equipment and systems, provided the facilities offered are not inferior to those stated.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

_____

[1] IHO publications are available from http://www.iho.int, together with any supplementary information.

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

IEC 61162-450:2011 *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 450: Multiple talkers and multiple listeners – Ethernet interconnection*

IEC 61924-2:2012, *Maritime navigation and radiocommunication equipment and systems – Integrated navigation systems – Part 2: Modular structure for INS – Operational and performance requirements, methods of testing and required test results*

IEC 61996-1:2013, *Maritime navigation and radiocommunication equipment and systems – Shipborne voyage data recorder (VDR) – Part 1: Performance requirements, methods of testing and required test results*

IEC 62288:2014, *Maritime navigation and radiocommunication equipment and systems – Presentation of navigation-related information on shipborne navigational displays – General requirements – Methods of testing and required test results*

IEC 62388:2013, *Maritime navigation and radiocommunication equipment and systems – Shipborne radar – Performance requirements – Methods of testing and required test results*

ISO 8601, *Data elements and interchange formats – Information interchange – Representation of dates and times*

IHO M-3:2007, *Resolutions of the IHO, Chapter A, Section 3, Technical Resolution 3.11*

IHO S-52:2014, *Specifications for chart content and display aspects of ECDIS edition 6.1*

IHO S-52, appendix 1:2012, *Guidance on Updating the Electronic Navigational Chart edition 4.0*

IHO S-52, Annex A:2014, *Presentation library edition 4.0*

IHO S-57, *IHO transfer standard for digital hydrographic data*

IHO S-57, appendix B.1, *ENC product specification*

IHO S-61:1999, *Product specification for raster navigational charts (RNC)*

IHO S-63, *IHO data protection scheme*

IHO S-64, *Test data sets for ECDIS*

IMO, *International Convention for the safety of life at sea (SOLAS) 1974 (as amended)*

IMO A.694(17):1991, *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO MSC.191(79):2004, *Performance standards for the presentation of navigation-related information on shipborne navigational displays*

IMO MSC.232(82):2006, *Revised Performance standards for electronic chart display and information systems (ECDIS)*

IMO MSC.252(83), *Performance standards for integrated navigation systems (INS)*

IMO MSC/Circ.982:2000, *Guidelines on ergonomic criteria for bridge equipment and layout*

IMO SN.1/Circ.266:2007, *Maintenance of electronic chart display and information system (ECDIS) software*