IEC 61400-50-1

Edition 1.0 2022-11

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

Wind energy generation systems – Part 50-1: Wind measurement – Application of meteorological mast, nacelle and spinner mounted instruments

Systèmes de génération d'énergie éolienne Partie 50-1: Mesurages du vent – Application d'instruments météorologiques montés sur mât, nacelle et nez de rotor



IEC 61400-50-1:2022-11 (en-fr)



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2022 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC
La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC
Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC - webstore.iec.ch/advsearchform
La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, …). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished
Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc
Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org
Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 300 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 19 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

IEC 61400-50-1

Edition 1.0 2022-11

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

Wind energy generation systems – Part 50-1: Wind measurement – Application of meteorological mast, nacelle and spinner mounted instruments

Systèmes de génération d'énergie éolienne Partie 50-1: Mesurages du vent – Application d'instruments météorologiques montés sur mât, nacelle et nez de rotor

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 27.180

ISBN 978-2-8322-5937-5

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

® Registered trademark of the International Electrotechnical Commission
Marque déposée de la Commission Electrotechnique Internationale

CONTENTS

FOREWORD 6
INTRODUCTION 8
1 Scope 9
2 Normative references 9
3 Terms and definitions 10
4 Symbols, units and abbreviated terms 11
5 General 16
6 Classification of cup and sonic anemometry 16
6.1 General 16
6.2 Classification classes 17
6.3 Influence parameter ranges 17
6.4 Classification of cup and sonic anemometers 17
6.5 Reporting format 19
7 Assessment of cup and sonic anemometry 19
7.1 General 19
7.2 Measurements of anemometer characteristics 19
7.2.1 Measurements in a wind tunnel for tilt angular response characteristics of cup anemometers 19
7.2.2 Wind tunnel measurements of directional characteristics of cup anemometers 21
7.2.3 Wind tunnel measurements of cup anemometer rotor torque characteristics 21
7.2.4 Wind tunnel measurements of step responses of cup anemometers 22
7.2.5 Measurement of temperature induced effects on anemometer performance 23
7.2.6 Wind tunnel measurements of directional characteristics of sonic anemometers 24
7.3 A cup anemometer classification method based on wind tunnel and laboratory tests and cup anemometer modelling 25
7.3.1 Method 25
7.3.2 Example of a cup anemometer model 25
7.4 A sonic anemometer classification method based on wind tunnel tests and sonic anemometer modelling 32
7.5 Free field comparison measurements 32
8 Wind tunnel calibration procedure for anemometers 32
8.1 General requirements 32
8.2 Requirements for the wind tunnel 33
8.3 Instrumentation and calibration setup requirements 35
8.4 Calibration procedure 35
8.4.1 General procedure for cup and sonic anemometers 35
8.4.2 Procedure for the calibration of sonic anemometers 36
8.4.3 Determination of the wind speed at the anemometer position 36
8.5 Data analysis 37
8.6 Uncertainty analysis 37
8.7 Reporting format 38
8.8 Example uncertainty calculation 39

9 In-situ comparison of anemometers 42
9.1 General 42
9.2 Prerequisite 42
9.3 Analysis method 42
9.4 Evaluation criteria 43
10 Mounting of instruments on the meteorological mast 45
10.1 General 45
10.2 Single top-mounted anemometer 46
10.3 Side-by-side top-mounted anemometers 47
10.4 Side-mounted instruments 49
10.4.1 General 49
10.4.2 Tubular meteorological masts 49
10.4.3 Lattice meteorological masts 51
10.4.4 Flow distortion correction of side-mounted anemometers 56
10.5 Lightning protection 56
10.6 Mounting of other meteorological instruments 56
10.7 Data acquisition system 57
11 Uncertainty of wind speed measurement 57
11.1 Category B uncertainties: Wind speed – Introduction 57
11.2 Category B uncertainties: Wind speed – Hardware 57
11.3 Category B uncertainties: Wind speed – Meteorological mast mounted sensors 57
11.3.1 General 57
11.3.2 Pre-calibration 58
11.3.3 Post-calibration 58
11.3.4 Classification 58
11.3.5 Mounting 59
11.3.6 Lightning finial 60
11.3.7 Data acquisition 60
11.4 Category B uncertainties: Method – Cold climate 60
11.5 Combining uncertainties 60
11.5.1 General 60
11.5.2 Combining uncertainties in the wind speed measurement ($u_{V,i}$) 61
11.5.3 Combining uncertainties in the wind speed measurement from cup or sonic anemometer ($u_{VS,i}$) 61
12 Reporting 61
Annex A (informative) Wind tunnel calibration procedure for wind direction sensors 63
A.1 General requirements 63
A.2 Requirements of the wind tunnel 63
A.3 Instrumentation and calibration setup requirements 64
A.4 Calibration procedure 65
A.5 Data analysis 66
A.6 Uncertainty analysis 66
A.7 Reporting format 67
A.8 Example of uncertainty calculation 68
A.8.1 General 68
A.8.2 Measurement uncertainties generated by determination of the flow direction in the wind tunnel 68

A.8.3 Uncertainty contribution by uncertainties in the determination of the geometrical centreline α_{CL} (wind tunnel centreline) 68
A.8.4 Contribution by uncertainties in the determination of flow direction α_{dir} 68
Annex B (informative) Mast flow distortion correction for lattice masts 73
Annex C (informative) Nacelle instrument mounting 76
C.1 General 76
C.2 Preferred method of anemometer's mounting 76
C.3 Preferred position of anemometer 76
Annex D (informative) Spinner anemometers 78
Bibliography 79

Figure 1 – Tilt angular response $V_\alpha/V_{\alpha=0}$ of a cup anemometer as a function of flow angle α compared to cosine response 21
Figure 2 – Wind tunnel torque measurements $Q_A - Q_F$ as a function of angular speed ω of a cup anemometer rotor at 8 m/s 22
Figure 3 – Example of bearing friction torque Q_F as function of temperature for a range of angular speeds ω 24
Figure 4 – Example of rotor torque coefficient C_{QA} as a function of speed ratio λ derived from step responses with κ_{low} equal to −5,5 and κ_{high} equal to −6,5 27
Figure 5 – Classification deviations of example cup anemometer showing a class 1,69A (upper) and a class 6,56B (lower) 30
Figure 6 – Classification deviations of example cup anemometer showing a class 8,01C (upper) and a class 9,94D (lower) 31
Figure 7 – Definition of volume for flow uniformity test 34
Figure 8 – Example valid control anemometer direction sector for a single top-mounted anemometer on a triangular lattice meteorological mast 44
Figure 9 – Example valid control anemometer direction sector for a single top-mounted anemometer on a tubular meteorological mast 45
Figure 10 – Example of a top-mounted anemometer and requirements for mounting 47
Figure 11 – Example of alternative top-mounted primary and control anemometers positioned side-by-side and wind vane and other instruments on the boom 48
Figure 12 – Iso-speed plot of local flow speed around a cylindrical meteorological mast 50
Figure 13 – Centreline relative wind speed as a function of distance R_d from the centre of a tubular meteorological mast and meteorological mast diameter d 51
Figure 14 – Representation of a three-legged lattice meteorological mast 51
Figure 15 – Iso-speed plot of local flow speed around a triangular lattice meteorological mast with a C_T of 0,5 52
Figure 16 – Centreline relative wind speed as a function of distance R_d from the centre of a triangular lattice meteorological mast of leg distance L_m for various C_T values 53
Figure 17 – 3D CFD derived flow distortion for two different wind directions around a triangular lattice meteorological mast (C_T = 0,27) 55
Figure A.1 – Example of calibration setup of a wind direction sensor in a wind tunnel 65
Figure B.1 – Example of mast flow distortion 73
Figure B.2 – Flow distortion residuals versus wind direction 75
Figure C.1 – Mounting of anemometer on top of nacelle 77

Table 1 – Influence parameter ranges (10 min averages) of classes A, B, C, D and S.....18
Table 2 – Tilt angle response of example cup anemometer.....28
Table 3 – Friction coefficients of example cup anemometer.....29
Table 4 – Miscellaneous data related to classification of example cup anemometer.....29
Table 5 – Example of evaluation of anemometer calibration uncertainty.....39
Table 6 – Estimation method for C_T for various types of lattice mast.....54
Table A.1 – Uncertainty contributions in wind directions sensor calibration.....71
Table A.2 – Uncertainty contributions and total standard uncertainty in wind direction sensor calibration.....72

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

WIND ENERGY GENERATION SYSTEMS –

Part 50-1: Wind measurement – Application of meteorological mast, nacelle and spinner mounted instruments

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61400-50-1 has been prepared by IEC technical committee 88: Wind energy generation systems. It is an International Standard.

This first edition of IEC 61400-50-1 is part of a structural revision that cancels and replaces the performance standards IEC 61400-12-1:2017 and IEC 61400-12-2:2013. The structural revision contains no technical changes with respect to IEC 61400-12-1:2017 and IEC 61400-12-2:2013, but the parts that relate to wind measurements, measurement of site calibration and assessment of obstacle and terrain have been extracted into separate standards.

The purpose of the re-structure was to allow the future management and revision of the power performance standards to be carried out more efficiently in terms of time and cost and to provide a more logical division of the wind measurement requirements into a series of separate standards which could be referred to by other use case standards in the IEC 61400 series and subsequently maintained and developed by appropriate experts.

The text of this International Standard is based on the following documents:

Draft	Report on voting
88/902/FDIS	88/916/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 61400 series, published under the general title *Wind energy generation systems*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of IEC 61400 specifies procedures and methods which ensure that wind measurements using cup or sonic anemometers mounted on meteorological masts or wind turbine nacelles/spinners are carried out and reported consistently and in accordance with best practice. This document does not define the purpose or use case of the wind measurements. However, as this document forms part of the IEC 61400 series of standards, it is anticipated that the wind measurements carried out in accordance with this standard will be used in relation to some form of wind energy testing or resource assessment.

The main clauses of this document are not mutually dependent. Therefore, it is possible that a user will refer to only certain of the main clauses rather than all clauses to adapt this document to their specific use case. However, the main clauses are presented in a logical sequence that could be applied in practice.

The technical content of this document could previously be found in IEC 61400-12-1:2017 and IEC 61400-12-2:2013.

NOTE A technical correction to the value of the tolerance of the anemometer mounting tube has been made in 10.2.

Due to the increasing complexity of these source documents, IEC TC 88 decided that a re-structuring of the IEC 61400-12 series of standards into a number of more specific parts would allow more efficient management and maintenance going forward. This document has been created as part of that re-structuring process. The requirements on wind measurement specific to the use cases described in IEC 61400-12-1:2017 and IEC 61400-12-2:2013 (for example, the required location of the meteorological mast relative to the test turbine and the height of wind measurement relative to hub height) remain within the new editions of IEC 61400-12-1 and IEC 61400-12-2.

WIND ENERGY GENERATION SYSTEMS –

Part 50-1: Wind measurement – Application of meteorological mast, nacelle and spinner mounted instruments

1 Scope

IEC 61400-50 specifies methods and requirements for the application of instruments to measure wind speed (and related parameters, e.g. wind direction, turbulence intensity). Such measurements are required as an input to some of the evaluation and testing procedures for wind energy and wind turbine technology (e.g. resource evaluation and turbine performance testing) described by other standards in the IEC 61400 series. This document is applicable specifically to the use of wind measurement instruments mounted on meteorological masts, turbine nacelles or turbine spinners which measure the wind at the location at which the instruments are mounted. This document excludes remote sensing devices which measure the wind at some location distant from the location at which the instrument is mounted (e.g. vertical profile or forward facing lidars). This document specifies the following:

a) the classification parameters for cup and sonic anemometers such that the uncertainty in wind speed measurement for a specific type and model of anemometer exposed to a certain class of environmental conditions can be assessed;

b) the procedure and requirements for classifying cup and sonic anemometers as, for example, part of the type testing of a specific anemometer model and type;

c) the procedures and requirements for wind tunnel calibration of anemometers;

d) an additional or alternative method of checking the consistency of the calibration of an anemometer in the field by carrying out an in-situ comparison with another anemometer;

e) the requirements for the mounting of anemometers and other instruments on meteorological masts;

f) the assessment of wind speed measurement uncertainty;

g) reporting requirements.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2533:1975, *Standard atmosphere*

ISO 3966, *Measurement of fluid flow in closed conduits – Velocity area method using Pitot static tubes*

ISO/IEC Guide 98-3:2008, *Uncertainty of measurement – Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1
accuracy
closeness of the agreement between the result of a measurement and a true value of the measurand

3.2
data set
collection of data sampled over a continuous period

3.3
distance constant
indication of the response time of an anemometer, defined as the length of air that shall pass the instrument for it to indicate 63 % of the final value for a step input in wind speed

3.4
flow distortion
change in air flow caused by obstacles, topographical variations, or other wind turbines that results in the wind speed at the measurement location being different from the wind speed at the wind turbine location

3.5
hub height
<of a wind turbine> height of the centre of the swept area of the wind turbine rotor above the ground at the tower

Note 1 to entry: For a vertical axis wind turbine the hub height is defined as the height of the centroid of the swept area of the rotor above the ground at the tower.

3.6
measurement period
period during which a statistically significant database has been collected for the use case

Note 1 to entry: A power performance test is an example of a use case.

3.7
measurement sector
sector of wind directions from which data are selected for the use case

Note 1 to entry: A measured power curve is an example of a use case.

3.8
obstacle
obstruction that blocks the wind and creates distortion of the flow

Note 1 to entry: Buildings and trees are examples of obstacles.

3.9
power performance
measure of the capability of a wind turbine to produce electric power and energy

3.10
standard uncertainty
uncertainty of the result of a measurement expressed as a standard deviation

3.11
wind measurement equipment
meteorological mast-mounted instruments or remote sensing device

3.12
wind shear
change of wind speed with height

3.13
wind shear exponent
α
exponent of the power law defining the variation of wind speed with height

Note 1 to entry: This parameter is used as a measure of the magnitude of wind shear and can be otherwise useful. The power law equation is:

$$v_{zi} = v_h \left(\frac{z_i}{H} \right)^{\alpha} \quad (1)$$

where

v_h is the hub height wind speed;

H is the hub height (m);

v_{zi} is the wind speed at height z_i;

α is the wind shear exponent.

4 Symbols, units and abbreviated terms

Symbol	Description	Unit
A	swept area of the wind turbine rotor	m^2
B	barometric pressure	Pa
B_{10min}	measured air pressure averaged over 10 min	Pa
C_h	pitot tube head coefficient	
C_{QA}	generalized aerodynamic torque coefficient	
C_T	thrust coefficient	
c	sensitivity factor of a parameter (the partial differential)	
$c_{B,i}$	sensitivity factor of air pressure in bin i	W/Pa
$c_{d,i}$	sensitivity factor of data acquisition system in bin i	
c_{index}	sensitivity factor of index parameter	
$c_{k,i}$	sensitivity factor of component k in bin i	
$c_{T,i}$	sensitivity factor of air temperature in bin i	W/K
$c_{V,i}$	sensitivity factor of wind speed in bin i	Ws/m
$c_{\rho,i}$	sensitivity factor of air density correction in bin i	Wm^3/kg