IEC 61850-7-1

Edition 2.1 2020-08
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

colour inside

Communication networks and systems for power utility automation – Part 7-1: Basic communication structure – Principles and models

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.200

ISBN 978-2-8322-8823-8

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 11
INTRODUCTION 13
1 Scope 14
2 Normative references 14
3 Terms and definitions 15
4 Abbreviated terms 16
5 Overview of the IEC 61850 series concepts 17
5.1 Objective 17
5.2 Topology and communication functions of substation automation systems 18
5.3 The information models of substation automation systems 19
5.4 Applications modelled by logical nodes defined in IEC 61850-7-4 21
5.5 The semantic is attached to data 24
5.6 The services to exchange information 26
5.7 Services mapped to concrete communication protocols 28
5.8 The configuration of the automation system 28
5.9 Summary 29
6 Modelling approach of the IEC 61850 series 30
6.1 Decomposition of application functions and information 30
6.2 Creating information models by stepwise composition 32
6.3 Example of an IED composition 34
6.4 Information exchange models 35
6.4.1 General 35
6.4.2 Output model 36
6.4.3 Input model 40
6.4.4 Model for statistical and historical statistical data 50
6.4.5 Model for system functions 53
7 Application view 55
7.1 General 55
7.2 First modelling step – Logical nodes and data 57
7.3 Mode and behaviour of a logical node 60
7.4 Use of measurement ranges and alarms for supervision functions 60
7.5 Data used for limiting the access to control actions 61
7.6 Data used for blocking functions described by logical nodes 61
7.7 Data used for logical node inputs/outputs blocking (operational blocking) 61
7.7.1 General 61
7.7.2 Blocking incoming commands 62
7.7.3 Blocking process outputs 62
7.7.4 Blocking the communication of status outputs updates 62
7.8 Data used for testing 63
7.8.1 General 63
7.8.2 Multicast signals used for simulation 63
7.8.3 Input signals used for testing 64
7.8.4 Test mode 66
7.9 Logical node used for extended logging functions 66
8 Device view 67

8.1 General....67
8.2 Second modelling step – logical device model....68
8.2.1 The logical device concept....68
8.2.2 The device nameplate....69
8.2.3 Gateways and proxies....70
8.2.4 Logical devices for monitoring external device health....74
8.2.5 Logical devices management hierarchy....74
9 Communication view....76
9.1 General....76
9.2 The service models of the IEC 61850 series....76
9.3 The virtualisation....78
9.4 Basic information exchange mechanisms....79
9.5 The client-server building blocks....81
9.5.1 Server....81
9.5.2 Client-server roles....82
9.6 Logical nodes communicate with logical nodes....83
9.7 Interfaces inside and between devices....84
10 Where physical devices, application models and communication meet....85
11 Relationships between IEC 61850-7-2, IEC 61850-7-3 and IEC 61850-7-4....86
11.1 Refinements of class definitions....86
11.2 Example 1 – Logical node and data object class....87
11.3 Example 2 – Relationship of IEC 61850-7-2, IEC 61850-7-3, and IEC 61850-7-4....91
12 Formal specification method....93
12.1 Notation of ACSI classes....93
12.2 Class modelling....93
12.2.1 Overview....93
12.2.2 Common data class....95
12.2.3 Logical node class....99
12.3 Service parameters tables....101
12.4 Referencing instances....102
13 Namespaces....105
13.1 General....105
13.2 Namespaces defined in the IEC 61850-7-x series....106
13.3 Namespaces dependencies....110
13.3.1 General....110
13.3.2 Basic namespaces dependencies....110
13.3.3 Other namespaces dependencies....112
13.4 Specification of namespaces....113
13.5 Attributes for references to namespaces....113
13.5.1 General....113
13.5.2 Attribute for logical device namespace (ldNs)....114
13.5.3 Attribute for logical device basic namespace (LLN0.NamPlt.lnNs)....114
13.5.4 Attribute for logical node namespace (lnNs)....115
13.5.5 Attribute for data namespace (dataNs)....115
13.5.6 Attribute for common data class namespace (cdcNs)....115
13.5.7 Attribute for naming a common data class name (cdcName)....115
13.6 Deprecation of namespaces....116
14 Common rules for new version of classes and for extension of object classes....116

14.1 General ... 116
14.2 Basic rules ... 116
14.2.1 General ... 116
14.2.2 Use of optional information ... 119
14.2.3 General rules for enumerations types and enumeration-based data objects and attributes ... 119
14.3 Rules for extensions within private namespace ... 119
14.3.1 Rules for LN classes ... 119
14.3.2 New LN classes ... 120
14.3.3 Rules for Common Data Classes ... 120
14.3.4 Rules for enumeration types and enumeration-based data objects and attributes ... 121
14.4 Extensions made within product standard namespaces ... 121
14.5 Extensions made within transitional namespaces ... 121
14.6 Extensions made within basic and domain namespaces ... 121
14.7 Multiple instances of LN classes for dedicated and complex functions ... 122
14.7.1 Example for time overcurrent ... 122
14.7.2 Example for PDIS ... 122
14.7.3 Example for power transformer ... 122
14.7.4 Example for auxiliary network ... 122
14.8 Specialisation of data by use of number extensions ... 123
14.9 Examples for new LNs ... 123
14.10 Example for new Data ... 123
15 Compatibility between different versions of the standard ... 124
Annex A (informative) Overview of logical nodes and data ... 125
A.1 Compatible logical node classes and data classes (IEC 61850-7-4) ... 125
A.1.1 List of LN groups (IEC 61850-7-4) ... 125
A.1.2 LN classes (IEC 61850-7-4) ... 125
A.1.3 Data object classes (IEC 61850-7-4) ... 125
A.2 Common data class specifications (IEC 61850-7-3) ... 125
Annex B (informative) Allocation of data to logical nodes ... 127
Annex C (informative) Use of the substation configuration language (SCL) ... 130
C.1 General ... 130
C.2 SCL and options in logical nodes ... 130
C.3 SCL and options in data ... 131
Annex D (xxx) ... 132
Annex E (informative) Relation between logical nodes and PICOMs ... 133
Annex F (informative) Mapping the ACSI to real communication systems ... 134
F.1 General ... 134
F.1.1 Mapping example (IEC 61850-8-1) ... 136
Annex G (normative) LGOS/LSVS engineering ... 142
G.1 General ... 142
G.2 LGOS/LSVS engineering by the ICT ... 143
G.3 LGOS/LSVS engineering by the SCT ... 144
Annex H (normative) GOOSE/SMV Subscription Configuration ... 146
H.1 General ... 146
H.2 SCT supplied input binding workflow ... 147
H.3 ICT supplied input binding (for later binding) ... 148

Annex I (informative) Specification of namespaces for Edition 3 149
I.1 Namespaces dependencies 149
I.1.1 General 149
I.1.2 Namespaces dependencies 149
I.2 Example 2 – Standardized data objects used in standardized LNs 150
I.3 Example 3 – Edition 2 device: standardized data object introduced in IEC61850-7-4:2007B 151
I.4 Example 4 – Edition 2 device: standardized LN introduced in IEC61850-7-4:2007B 152
I.5 Example 5 – Edition 1 device: Logical nodes in technical reports 153
I.6 Example 6- Edition 2.1 device: Logical nodes in technical reports defining new CDCs 155
I.7 Example 7- Edition 2.1 device: devices for product family standards 156
I.8 Example 8 – Standardized logical nodes introduced by other domain applications 157
I.9 Example 9 – Standardized logical nodes introduced by other domain applications than moved to IEC 61850-7-4 159
Annex J (normative) Use case scenarios examples for clarifying the common rules of Clause 14 162
J.1 General 162
J.2 Example 1 – Private LN using standardized DOs 162
J.3 Example 2 – Standardized data objects used in standardized LNs 163
J.4 Example 3 – Edition 2 device: standardized data object introduced in IEC61850-7-4:2007B 163
J.5 Example 4 – Edition 2 device: standardized LN introduced in IEC61850-7-4:2007B 164
J.6 Example 5 – Edition 1 device: Logical nodes in technical reports 165
J.7 Example 6- Edition 2.1 device: Logical nodes in technical reports defining new CDCs 167
J.8 Example 7- Edition 2.1 device: devices for product family standards 168
J.9 Example 8 – Standardized logical nodes introduced by other domain applications 169
J.10 Example 9 – Standardized logical nodes introduced by other domain applications than moved to IEC 61850-7-4 171
Annex K (normative) General requirements and recommendations regarding compatibility issues between different versions of IEC 61850 174
K.1 Overview 174
K.1.1 General 174
K.1.2 Definitions (to go to part 2): 174
K.1.3 Introduction to compatibility discussion 175
K.1.4 Assumptions 175
K.1.5 Generic rules 176
K.1.6 Overview on use cases 177
K.2 Use cases related to the data model 181
K.2.1 Use case 1: Add new type 181
K.2.2 Use case 2: Add new FC 181
K.2.3 Use case 3: Extend CDC with elements of existing types and FCs 182
K.2.4 Use case 4: Add a new DataObject (DO) based on new CDCs 183
K.2.5 Use case 5: Add a new DO based on existing CDCs 184
K.2.6 Use case 6: Rename a DO 184
K.2.7 Use case 7: Rename a DA, subDO or subDA 184

K.2.8 Use case 8: Deprecation of a FC 185
K.2.9 Use case 9: Deprecation of a DA 186
K.2.10 Use case 10: Removal of a DA 186
K.2.11 Use case 11: Deprecation of a DO 187
K.2.12 Use case 12: Use a weaker presence condition 187
K.2.13 Use case 13: Use a stronger presence condition 188
K.2.14 Use case 14: Extend Enumeration List with an enumerated value 188
K.2.15 Use case 15: Modification of an Enumerated value 189
K.2.16 Use case 16: Deprecation of an Enumerated value 190
K.2.17 Use case 17: Extension of a PACKED LIST 190
K.2.18 Use case 18: Extend Name Length 190
K.3 Use cases related to the services I 191
K.3.1 Use case 30: Add new type 191
K.3.2 Use case 31: Using new control block class 192
K.3.3 Use case 32: Using new services 192
K.3.4 Use case 33: Extending control block class with an attribute of existing type 193
K.3.5 Use case 34: Rename a service parameter not associated with a control block attribute 193
K.3.6 Use case 35: Removing / Deprecating Control Block Classes 193
K.3.7 Use case 36: Using a stronger presence condition 194
Bibliography 195

Figure 1 – Relations between modelling and mapping parts of the IEC 61850 series 17
Figure 2 – Sample substation automation topology 19
Figure 3 – Modelling approach (conceptual) 20
Figure 4 – Logical node information categories 23
Figure 5 – Build-up of devices (principle) 23
Figure 6 – Position information depicted as a tree (conceptual) 24
Figure 7 – Service excerpt 27
Figure 8 – Example of communication mapping 28
Figure 9 – Summary 30
Figure 10 – Decomposition and composition process (conceptual) 31
Figure 11 – XCBR1 information depicted as a tree 33
Figure 12 – Example of IED composition 35
Figure 13 – Output and input model (principle) 36
Figure 14 – Output model (step 1) (conceptual) 37
Figure 15 – Output model (step 2) (conceptual) 38
Figure 16 – GSE output model (conceptual) 38
Figure 17 – Setting data (conceptual) 39
Figure 18 – Input model for analogue values (step 1) (conceptual) 41
Figure 19 – Range and deadbanded value (conceptual) 42
Figure 20 – Input model for analogue values (step 2) (conceptual) 43
Figure 21 – Reporting and logging model (conceptual) 44
Figure 22 – Data set members and reporting 45
Figure 23 – Buffered report control block (conceptual) 46

Figure 24 – Buffer time 47
Figure 25 – Data set members and inclusion-bitstring 48
Figure 26 – Log control block (conceptual) 48
Figure 27 – Peer-to-peer data value publishing model (conceptual) 49
Figure 28 – Conceptual model of statistical and historical statistical data (1) 51
Figure 29 – Conceptual model of statistical and historical statistical data (2) 53
Figure 30 – Concept of the service tracking model – Example: control service tracking 55
Figure 31 – Real world devices 56
Figure 32 – Logical nodes and data (IEC 61850-7-2) 57
Figure 33 – Simple example of modelling 58
Figure 34 – Basic building blocks 58
Figure 35 – Logical nodes and PICOM 59
Figure 36 – Logical nodes connected (outside view in IEC 61850-7-x series) 59
Figure 37 – Mode and behaviour data (IEC 61850-7-4) 60
Figure 38 – Data used for limiting the access to control actions (IEC 61850-7-4) 61
Figure 39 – Data used for logical node inputs/outputs blocking (IEC 61850-7-4) 62
Figure 40 – Data used for receiving simulation signals 63
Figure 80 – GOOSE subscription supervision state machine 64
Figure 81 – SV subscription supervision state machine 64
Figure 41 – Example of input signals used for testing 65
Figure 42 – Test mode example 66
Figure 43 – Logical node used for extended logging functions (GLOG) 67
Figure 44 – Logical device building block 68
Figure 45 – Logical devices and LLN0/LPHD 69
Figure 46 – The common data class DPL 70
Figure 47 – Logical devices in proxies or gateways 72
Figure 79 – Logical devices in proxies or gateways (functional naming) 73
Figure 48 – Logical devices for monitoring external device health 74
Figure 49 – Logical devices management hierarchy 75
Figure 50 – ACSI communication methods 77
Figure 51 – Virtualisation 79
Figure 52 – Virtualisation and usage 79
Figure 53 – Information flow and modelling 80
Figure 54 – Application of the GSE model 80
Figure 55 – Server building blocks 81
Figure 56 – Interaction between application process and application layer (client/server) 82
Figure 57 – Example for a service 82
Figure 58 – Client/server and logical nodes 82
Figure 59 – Client and server roles 83
Figure 60 – Logical nodes communicate with logical nodes 84
Figure 61 – Interfaces inside and between devices 85
Figure 62 – Component hierarchy of different views (excerpt) 86

Figure 63 – Refinement of the DATA class 87
Figure 64 – Instances of a Data object class (conceptual) 91
Figure 65 – Relation between parts of the IEC 61850 series 92
Figure 66 – Abstract data model example for IEC 61850-7-x 94
Figure 67 – Relation of TrgOp and Reporting 99
Figure 68 – Sequence diagram 102
Figure 69 – References 102
Figure 70 – Use of FCD and FCDA 103
Figure 71 – Object names and object reference 105
Figure 72 – Definition of names and semantics 106
Figure 73 – Name space as class repository 107
Figure 74 – All instances derived from classes in a single name space 108
Figure 75 – Instances derived from multiple namespaces 109
Figure 76 – Inherited namespaces 109
Figure 77 – Basic namespaces dependencies 111
Figure 78 – Other namespaces dependencies 112
Figure 78 – Basic extension rules diagram 117
Figure B.1 – Example for control and protection LNs combined in one physical device 127
Figure B.2 – Merging unit and sampled value exchange (topology) 128
Figure B.3 – Merging unit and sampled value exchange (data) 128
Figure C.1 – Application of SCL for LNs (conceptual) 130
Figure C.2 – Application of SCL for data (conceptual) 131
Figure E.1 – Exchanged data between subfunctions (logical nodes) 133
Figure E.2 – Relationship between PICOMS and client/server model 133
Figure F.1 – ACSI mapping to an application layer 134
Figure F.2 – ACSI mappings (conceptual) 135
Figure F.3 – ACSI mapping to communication stacks/profiles 136
Figure F.4 – Mapping to MMS (conceptual) 136
Figure F.5 – Mapping approach 137
Figure F.6 – Mapping detail of mapping to a MMS named variable 138
Figure F.7 – Example of MMS named variable (process values) 138
Figure F.8 – Use of MMS named variables and named variable list 139
Figure F.9 – MMS information report message 140
Figure F.10 – Mapping example 141
Figure G.1 – LGOS/LSVS engineering 143
Figure G.2 – LGOS/LSVS engineering by ICT 144
Figure G.3 – LGOS/LSVS engineering by the SCT 145
Figure H.1 – GOOSE/SMV subscription engineering workflow 146
Figure H.2 – SCT supplied input binding 147
Figure H.3 – ICT supplied input binding (for later binding) 148
Figure I.1 – Private LN using standardized DOs (Edition 2) 150
Figure I.2 –Standardized data objects used in standardized LNs 151

Figure I.3 – Edition 2 device: standardized data object introduced in IEC61850-7-4:2007B 152
Figure I.4 – Edition 2 device: standardized LN introduced in IEC61850-7-4:2007B 153
Figure I.5 – Edition 1 device: Logical nodes in technical reports 154
Figure I.6 – Edition 2 device: Logical nodes in technical reports 155
Figure I.7 – Edition 2.1 device: Logical nodes in technical reports defining new CDCs 156
Figure I.8 – Edition 2.1 device: standardized LNs extended by other domains 157
Figure I.9 – Edition 2 device: standardized LN introduced in IEC 61850-7-420:2009 158
Figure I.10 – Edition 2.1 device: standardized LN introduced in IEC 61850-7-420:2015 159
Figure I.11 – Edition 2 device: standardized LN moved from introduced in IEC 61850-7-420:2009 to IEC 61850-7-4:2007 160
Figure I.12 – Edition 2.1 device: standardized LN moved from introduced in IEC 61850-7-420:2009 to IEC 61850-7-4:2007 161
Figure J.1 – Private LN using standardized DOs (Edition 2) 162
Figure J.2 –Standardized data objects used in standardized LNs 163
Figure J.3 – Edition 2 device: standardized data object introduced in IEC61850-7-4:2007B 164
Figure J.4 – Edition 2 device: standardized LN introduced in IEC61850-7-4:2007B 165
Figure J.5 – Edition 1 device: Logical nodes in technical reports 166
Figure J.6 – Edition 2 device: Logical nodes in technical reports 167
Figure J.7 – Edition 2.1 device: Logical nodes in technical reports defining new CDCs 168
Figure J.8 – Edition 2.1 device: standardized LNs extended by other domains 169
Figure J.9 – Edition 2 device: standardized LN introduced in IEC 61850-7-420:2009 170
Figure J.10 – Edition 2.1 device: standardized LN introduced in IEC 61850-7-420:2015 171
Figure J.11 – Edition 2 device: standardized LN moved from introduced in IEC 61850-7-420:2009 to IEC 61850-7-4:2007 172
Figure J.12 – Edition 2.1 device: standardized LN moved from introduced in IEC 61850-7-420:2009 to IEC 61850-7-4:2007 173

Table 1 – LN groups 21
Table 2 – Logical node class XCBR (conceptual) 32
Table 3 – Excerpt of integer status setting 40
Table 4 – Comparison of the data access methods 45
Table 5 – ACSI models and services 77
Table 6 – Logical node circuit breaker 88
Table 7 – Controllable double point (DPC) 90
Table 8 – ACSI class definition 93
Table 9 – Single point status common data class (SPS) 95
Table 10 – Quality components attribute definition 96
Table 16 – Attributes of DetailQual 97
Table 11– Functional constraints (excerpt) 98
Table 12– Trigger option 98
Table 13 – GenLogicalNodeClass definition 100
Table 14 – Excerpt of logical node name plate common data class (LPL) 114
Table 15 – Excerpt of the abstract common data class BasePrimitiveCDC 114

Table A.2 – List of common data classes (excerpt) 125
Table K.1 – Information users and information providers 175
Table K.2 – Data model use cases 177
Table K.3 – Services use cases 179
Table K.4 – Data Forbidden cases 180
Table K.5 – Add new basic type 181
Table K.6 – Extend CDC with DA of new FC 182
Table K.7 – Add new DA using existing type and FCs 182
Table K.8 – Add a new DO based on new CDC using existing types and FCs 183
Table K.9 – Adding a new DO based on existing CDC 184
Table K.10 – Renaming a DO 184
Table K.11 – Renaming a DA, subDO or subDA 185
Table K.12 – Deprecation of a FC 186
Table K.13 – Deprecation of a DA 186
Table K.14 – Removal of a DA 187
Table K.15 – Deprecation of a DO 187
Table K.16 – Use of a weaker presence condition 188
Table K.17 – Use of a stronger presence condition 188
Table K.18 – Extend an enumeration with an enumerated value 189
Table K.19 – Modification of an enumerated value from an enumeration list 189
Table K.20 – Deprecate an enumerated value from an enumeration list 190
Table K.21 – Extension of a PACKED LIST 190
Table K.22 – Extend size of names / references 191
Table K.23 – Add new basic type 191
Table K.24 – Adding new Control Blocks 192
Table K.25 – Adding new services 192
Table K.26 – Add new attributes in control block 193
Table K.27 – Deprecating control block class 193
Table K.28 – Using a stronger presence condition 194

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

COMMUNICATION NETWORKS AND SYSTEMS FOR POWER UTILITY AUTOMATION –

Part 7-1: Basic communication structure – Principles and models

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 61850-7-1 edition 2.1 contains the second edition (2011-07) [documents 57/1121/FDIS and 57/1145/RVD] and its amendment 1 (2020-08) [documents 57/2201/FDIS and 57/2221/RVD].

International Standard IEC 61850-7-1 has been prepared by IEC technical committee 57: Power systems management and associated information exchange.

This second edition edition constitutes a technical revision.

Compared to the first edition, this second edition introduces:

- the model for statistical and historical statistical data,
- the concepts of proxies, gateways, LD hierarchy and LN inputs,
- the model for time synchronisation,
- the concepts behind different testing facilities,
- the extended logging function.

It also clarifies the following points:

- the use of numbers for data extension,
- the use of namespaces,
- the mode and behaviour of a logical node,
- the use of range and deadbanded values,
- the access to control actions and others.

Compared to the second edition, this first revision of the second edition:

- provides clarifications and corrections to the second edition of IEC 61850-7-1, based 55 on the tissues = {828, 874, 948, 1060, 1072, 1129, 1151, 1196, 1251, 1268, 1312, 1396, 1437, 1468, 1491};
- re-edit the Clause 8.2.3 on gateways and proxies;
- re-edit the complete Clauses 13 and 14 about namespaces and rules for extension of object classes;
- include three new normative annexes respectively for LGOS/LSVS engineering (G), GOOSE/SMV Subscription Configuration (H) and use case scenarios examples for clarifying the common rules of Clause 14 (J);
- introduces in the informative annex I, the concept of decoupling domain namespaces from basic namespaces in edition 3 of this document;

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61850 series, under the general title: *Communication networks and systems for power utility automation*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of the IEC 61850 series provides an overview of the architecture for communication and interactions between systems for power utility automation such as protection devices, breakers, transformers, substation hosts etc.

This document is part of a set of specifications which details a layered communication architecture for power utility automation. This architecture has been chosen to provide abstract definitions of classes (representing hierarchical information models) and services such that the specifications are independent of specific protocol stacks, implementations, and operating systems.

The goal of the IEC 61850 series is to provide interoperability between the IEDs from different suppliers or, more precisely, between functions to be performed by systems for power utility automation but residing in equipment (physical devices) from different suppliers. Interoperable functions may be those functions that represent interfaces to the process (for example, circuit breakers) or substation automation functions such as protection functions. This part of the IEC 61850 series uses simple examples of functions to describe the concepts and methods applied in the IEC 61850 series.

This part of the IEC 61850 series describes the relationships between other parts of the IEC 61850 series. Finally this part defines how interoperability is reached.

NOTE Interchangeability is the ability to replace a device from the same vendor, or from different vendors, utilising the same communication interface and as a minimum, providing the same functionality, with no impact on the rest of the system. If differences in functionality are accepted, the exchange may also require some changes somewhere else in the system. Interchangeability implies a standardisation of functions and, in a strong sense, of devices which are outside the scope of this standard. Interchangeability is outside the scope, but it will be supported following this standard for interoperability.

This part of the IEC 61850 series is intended for all stakeholders of standardised communication and standardised systems in the utility industry. It provides an overview of and an introduction to IEC 61850-7-4, IEC 61850-7-3, IEC 61850-7-2, IEC 61850-6, and IEC 61850-8-1.

COMMUNICATION NETWORKS AND SYSTEMS FOR POWER UTILITY AUTOMATION –

Part 7-1: Basic communication structure – Principles and models

1 Scope

This part of the IEC 61850 series introduces the modelling methods, communication principles, and information models that are used in the various parts of the IEC 61850-7-x series. The purpose of this part of the IEC 61850 series is to provide – from a conceptual point of view – assistance to understand the basic modelling concepts and description methods for:

– substation-specific information models for power utility automation systems,

– device functions used for power utility automation purposes, and

– communication systems to provide interoperability within power utility facilities.

Furthermore, this part of the IEC 61850 series provides explanations and provides detailed requirements relating to the relation between IEC 61850-7-4, IEC 61850-7-3, IEC 61850-7-2 and IEC 61850-5. This part explains how the abstract services and models of the IEC 61850-7-x series are mapped to concrete communication protocols as defined in IEC 61850-8-1.

The concepts and models provided in this part of the IEC 61850 series may also be applied to describe, among others, information models and functions for:

– hydroelectric power plants,

– substation to substation information exchange,

– information exchange for distributed automation,

– substation to control centre information exchange,

– information exchange for metering,

– condition monitoring and diagnosis, and

– information exchange with engineering systems for device configuration.

NOTE 1 This part of IEC 61850 uses examples and excerpts from other parts of the IEC 61850 series. These excerpts are used to explain concepts and methods. These examples and excerpts are informative in this part of IEC 61850.

NOTE 2 Examples in this part use names of classes (e.g. XCBR for a class of a logical node) defined in IEC 61850-7-4, IEC 61850-7-3, and service names defined in IEC 61850-7-2. The normative names are defined in IEC 61850-7-4, IEC 61850-7-3, and IEC 61850-7-2 only.

NOTE 3 This part of IEC 61850 does not provide a comprehensive tutorial. It is recommended that this part be read first – in conjunction with IEC 61850-7-4, IEC 61850-7-3, and IEC 61850-7-2. In addition, it is recommended that IEC 61850-1 and IEC 61850-5 also be read.

NOTE 4 This part of IEC 61850 does not discuss implementation issues.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61850-2, *Communication networks and systems in substations – Part 2: Glossary*

IEC 61850-3, *Communication networks and systems in substations – Part 3: General requirements*

IEC 61850-4, *Communication networks and systems for power utility automation – Part 4: System and project management*

IEC 61850-5, *Communication networks and systems in substations – Part 5: Communication requirements for functions and device models*

IEC 61850-6, *Communication networks and systems for power utility automation – Part 6: Configuration description language for communication in electrical substations related to IEDs*

IEC 61850-7-2, *Communication networks and systems for power utility automation – Part 7-2: Basic information and communication structure – Abstract communication service interface (ACSI)*

IEC 61850-7-3, *Communication networks and systems for power utility automation – Part 7-3: Basic communication structure – Common data classes*

IEC 61850-7-4, *Communication networks and systems for power utility automation – Part 7-4: Basic communication structure – Compatible logical node classes and data object classes*

IEC 61850-8-1, *Communication networks and systems for power utility automation – Part 8-1: Specific Communication Service Mapping (SCSM) – Mappings to MMS (ISO 9506-1 and ISO 9506-2) and to ISO/IEC 8802-3*

IEC 61850-9-2, *Communication networks and systems in substations – Part 9-2: Specific Communication Service Mapping (SCSM) – Sampled values over ISO/IEC 8802-3*

IEC 61850-10, *Communication networks and systems in substations – Part 10: Conformance testing*

ISO/IEC 8802-3, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*

ISO/IEC 8825 (all parts), *Information technology – ASN.1 encoding rules*

ISO 9506-1, *Industrial automation systems – Manufacturing Message Specification – Part 1: Service definition*

ISO 9506-2, *Industrial automation systems – Manufacturing Message Specification – Part 2: Protocol specification*