IEC 62106-10

Edition 1.0 2021-11

INTERNATIONAL STANDARD

Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz – Part 10: UECP – Universal Encoder Communication Protocol

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.060.01; 33.160.20; 33.170

ISBN 978-2-8322-1042-4

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 6
INTRODUCTION 8
1 Scope 9
2 Normative references 9
3 Terms, definitions and abbreviated terms 9
3.1 Terms and definitions 9
3.2 Abbreviated terms 10
4 RDS encoder hardware model 10
5 RDS encoder software model 12
6 Destination addressing method 13
6.1 General 13
6.2 Site address 14
6.3 Encoder address 15
7 Transmission modes 15
7.1 General 15
7.2 Uni-directional mode 15
7.3 Bi-directional mode, requested response 15
7.4 Bi-directional mode, spontaneous response 15
8 Protocol description 15
8.1 Data format 15
8.2 Data link layer 15
8.2.1 General 15
8.2.2 Data-frame 16
8.2.3 Byte-stuffing method 19
8.2.4 Message field format 19
8.3 Message codes 21
8.3.1 General 21
8.3.2 Remote and configuration commands 21
8.3.3 RDS messages 21
8.3.4 Handling of RDS message bits declared "rfu" 21
8.3.5 Status messages 21
8.3.6 Specific messages 21
8.4 Description of data handling 21
8.5 Group sequence configuration 22
8.5.1 Basic principles used 22
8.5.2 Group sequence determination 22
8.5.3 Extended group sequence command 22
8.5.4 Relative priority group sequence command 22
8.5.5 Special transmission conditions 22
8.6 Handling of ODA data 23
8.6.1 Using ODAs on data-stream 0 23
8.6.2 Using ODAs on the upper data-streams 1 to 3 23
Annex A (normative) UECP message command repertoire 26
A.1 Message command format 26
A.2 Commands for A or B-type groups on data-stream 0 26
A.2.1 PI / MEC 0x01 26

A.2.2 PS / MEC 0x02 27
A.2.3 Long PS / MEC 0x21 28
A.2.4 Data group for PTYI / MEC 0x04 28
A.2.5 TP – TA / MEC 0x03 29
A.2.6 PTY / MEC 0x07 29
A.2.7 PTYN / MEC 0x3E 30
A.2.8 RT / MEC 0x0A 30
A.2.9 AF / MEC 0x13 33
A.2.10 EON-AF / MEC 0x14 34
A.2.11 ECC and other slow label settings / MEC 0x1A 35
A.2.12 Linkage information / MEC 0x2E 36
A.2.13 Free-format data in type A or B group / MEC 0x24 36
A.3 Commands for ODAs on data-stream 0 37
A.3.1 Group type 3A ODA configuration and short message command / MEC 0x40 37
A.3.2 ODA assignment group usage sequence signalling / MEC 0x41 39
A.3.3 ODA relative priority group sequence / MEC 0x43 40
A.3.4 ODA data group repetitions and burst mode / MEC 0x44 40
A.3.5 ODA "spinning wheel" timing control / MEC 0x45 41
A.3.6 ODA data / MEC 0x46 42
A.3.7 ODA data command access right / MEC 0x47 44
A.4 Commands for clock setting and control for data-stream 0 45
A.4.1 Real time clock for CT / MEC 0x0D 45
A.4.2 Real time clock correction for CT / MEC 0x09 46
A.4.3 CT on-off command / MEC 0x19 46
A.5 Commands for RDS signal alignment and control on data-stream 0 47
A.5.1 RDS on-off command data-stream 0 / MEC 0x1E 47
A.5.2 RDS phase for subcarrier 0 / MEC 0x22 47
A.5.3 RDS level for subcarrier 0 / MEC 0x0E 48
A.6 Message name commands control and set-up commands on data-stream 0 49
A.6.1 Site address / MEC 0x23 49
A.6.2 Encoder address / MEC 0x27 49
A.6.3 Make PSN list / MEC 0x28 50
A.6.4 PSN enable-disable / MEC 0x0B 50
A.6.5 EON elements enable-disable / MEC 0x3F 51
A.6.6 Communication mode / MEC 0x2C 52
A.6.7 TA control / MEC 0x2A 53
A.6.8 EON-TA control / MEC 0x15 53
A.6.9 Reference input select / MEC 0x1D 54
A.6.10 Data set select / MEC 0x1C 54
A.6.11 Group sequence determination for data-stream 0 / MEC 0x16 54
A.6.12 Extended group sequence for data-stream 0 / MEC 0x38 55
A.6.13 Group variant code sequence for data-stream 0 / MEC 0x29 57
A.6.14 Encoder access right / MEC: 0x3A 58
A.6.15 Communications port configuration – Mode / MEC 0x3B 59
A.6.16 Communications port configuration – Speed / MEC 0x3C 60
A.6.17 Communications port configuration – Timeout /MEC 0x3D 62
A.6.18 Message acknowledgment / MEC 0x18 63
A.6.19 Request message / MEC 0x17 64

A.7 Manufacturers' and transmission operators' specific command / MEC 0x2D 65
A.8 Commands for the C-type groups used on data-streams 1 to 3 66
A.8.1 ODA-AID channel assignment for AS group type C (Alternative 1)/MEC 0x50 66
A.8.2 ODA-AID channel assignment for AS group type C (Alternative 2) / MEC 0x51 68
A.8.3 Relative priority group sequence / MEC 0x53 71
A.8.4 Burst mode control for ODA group type C / MEC 0x54 71
A.8.5 RFT file data transfer (Alternative 2)/MEC 0x55 72
A.8.6 ODA data group command / MEC 0x56 73
A.8.7 RFT file data transfer and associated data for the assignment group(s) variants 0 and 1 (Alternative 1) / MEC 0x57 75
A.8.8 File associated data for AS group variants 2 to 7 (Alternative 1)/MEC 0x58 76
A.8.9 Define in the RFT a file sequence for the AID/MEC 0x59 78
A.8.10 Define the group sequence / MEC 0x61 79
A.8.11 Extended group sequence for group type C/MEC 0x83 80
A.8.12 Upper data-stream level / MEC 0xE0 82
A.8.13 Upper data-streams on – off/MEC 0xE1 82
Annex B (normative) UECP transmission over IP networks 84
Annex C (informative) Transport of UECP data within DVB-S radio 85
Annex D (informative) Manufacturer and transmission operator command code registration 86
Annex E (informative) Listing of Message Element Codes 87
Annex F (informative) Special optional ODA transmission mode on RDS data-stream 0 with group type A or B 89
F.1 "Burst mode" transmission 89
F.2 "Spinning wheel" mode transmission 89
Annex G (normative) Message Element Codes kept for backwards compatibility on data-stream 0 90
G.1 General 90
G.2 ODA data group/MEC 0x42 90
G.3 EWS / MEC 0x2B 91
G.4 TDC/MEC 0x26 92
G.5 TMC / MEC 0x30 93
G.6 DAB Dynamic label message – DL/MEC 0xAA 93
G.7 DAB Dynamic label command/MEC 0x48 94
Annex H (informative) Example for defining the group sequence for data-stream 0 including ODA groups 96
Annex I (informative) Example of how to send a logo with two different resolutions using RFT 97
I.1 Send files to the encoder 97
I.1.1 General 97
I.1.2 Alternative 1: using MECs 0x50 and 0x57 97
I.1.3 Alternative 2: using MECs 0x51 and 0x55 98
I.2 Data-stream number setting 100
I.3 File sequence setting 100
Bibliography 101

Figure 1 – RDS encoder hardware model 11
Figure 2 – RDS encoder software model 13
Figure 3 – Fictitious example of site addressing 14
Figure 4 – UECP data-frame format 16
Figure 5 – UECP data frame with the CRC-16 for example 1 being 0x25F4 18
Figure 6 – UECP data frame with the CRC-16 for example 2 being 0x800C 19
Figure A.1 – Message transmission cycle diagram 32
Figure F.1 – "Spinning wheel" mode – one minute transmission cycle that starts with a 4A group 89

Table 1 – UECP data-frame description 16
Table 2 – Byte-stuffing method 19
Table 3 – Message structure 20
Table 4 – Data set number 20
Table 5 – Programme Service Number 21
Table A.1 – Message command format 26

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

RADIO DATA SYSTEM (RDS) – VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 64,0 MHz TO 108,0 MHz –

Part 10: UECP – Universal Encoder Communication Protocol

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62106-10 has been prepared by technical area 1: Terminals for audio, video and data services and content, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This first edition, together with IEC 62106-1, IEC 62106-2, IEC 62106-3, IEC 62106-4, IEC 62106-5, IEC 62106-6 and IEC 62106-9, cancels and replaces IEC 62106:2015, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62106:2015:

- The Universal Encoder Communication protocol UECP adapted to support optional RDS2 is new.
- The section dealing with legacy RDS using data-stream 0 only is a transcription of an RDS Forum technical specification which was initially developed by the EBU and which was already in its 7th version [1]. Full backwards compatibility with previous versions was maintained, but RDS features no longer specified in IEC 62106-2 were deleted.

The text of this International Standard is based on the following documents:

Draft	Report on voting
100/3643/FDIS	100/3688/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 62106 series, published under the general title *Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz)*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

Since the mid-1980s a fascinating development has taken place. Most of the multimedia applications and standards have been created or redefined significantly. Hardware has become extremely powerful with dedicated software and middleware. In the mid-1980s, Internet as well as its protocols did not exist. Navigation systems became affordable in the late 1990s, and a full range of attractive smartphones now exist. The computing power of all these new products is comparable with that of the mainframe installations in that era.

Listener expectations have grown faster than the technology. Visual experience is now very important, like the Internet look and feel. Scrolling text or delivering just audio is nowadays perceived as insufficient for FM radio, specifically for smartphone users. New types of radio receivers with added value features are therefore required. RDS has so far proven to be very successful.

FM radio with RDS is an analogue-digital hybrid system, which is still a valid data transmission technology and only the applications need adaptation. Now the time has come to solve the only disadvantage, the lack of sufficient data capacity. With RDS2, the need to increase the data capacity can be fulfilled.

RDS was introduced in the early 1980s. During the introductory phase in Europe, the car industry became very involved and that was the start of an extremely successful roll-out. Shortly afterwards, RDS (RBDS) was launched in the USA [2, 3, 4, 5, 6].[1]

The RDS Forum has investigated a solution to the issue of limited data capacity. For RDS2, both sidebands around the RDS 57 kHz subcarrier can be repeated a few times, up to three, centred on additional subcarriers higher up in the FM multiplex still remaining compatible with the ITU Recommendations.

The core elements of RDS2 are the additional subcarriers, which will enable a significant increase of RDS data capacity to be achieved, and then only new additional data applications will have to be created, using the RDS-ODA feature, which has been part of the RDS standard IEC 62106 for many years.

In order to update IEC 62106:2015 to the specifications of RDS2, IEC 62106 has been restructured as follows:

Part 1: Modulation characteristics and baseband coding

Part 2: RDS message format, coding and definition of RDS features

Part 3: Usage and registration of Open Data Applications ODAs

Part 4: Registered code tables

Part 5: Marking of RDS and RDS2 devices

Part 6: Compilation of technical specifications for Open Data Applications in the public domain

Part 9: RBDS – RDS variant used in North America

Part 10: Universal Encoder Communication Protocol UECP

NOTE 1 The Part numbers 7 and 8 will not be used.

The original specifications of the RDS system have been maintained and the extra functionalities of RDS2 have been added.

Obsolete or unused functions from the original RDS standard have been deleted.

---

1 Numbers in square brackets refer to the Bibliography.

RADIO DATA SYSTEM (RDS) – VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 64,0 MHz TO 108,0 MHz –

Part 10: UECP – Universal Encoder Communication Protocol

1 Scope

This part of IEC 62106 describes the Universal Encoder Communication Protocol – UECP. The UECP has as its primary objectives to satisfy the need for harmonized RDS encoder communication protocols and to facilitate the interworking of various RDS systems components, such as RDS servers, data bridges and encoders, regardless of the supplier. Furthermore, a harmonised network environment and encoder model is being maintained to facilitate the interchange of component parts of RDS network systems. These harmonized models and a universal layered protocol are specified, based on the ISO/OSI recommendation. The UECP encompasses all current RDS features including any new developments using the ODA protocol.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62106-1, *Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz – Part 1: Modulation characteristics and baseband coding*

IEC 62106-2:2021, *Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz – Part 2: Message format: Coding and definition of RDS features*

IEC 62106-4, *Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz – Part 4: Registered code tables*

ETSI EN 300 401, *Radio Broadcasting Systems; Digital Audio Broadcasting (DAB) to mobile, portable and fixed receivers*

ETSI TS 101 756, *Digital Audio Broadcasting (DAB); Registered Tables*

ETSI TS 102 980, *Digital Audio Broadcasting (DAB); Dynamic Label Plus (DL Plus); Application specification*