IEC 62106-2

Edition 2.0 2021-02
REDLINE VERSION

INTERNATIONAL STANDARD

colour inside

Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz –
Part 2: Message format: coding and definitions of RDS features

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.160.40

ISBN 978-2-8322-9484-0

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 6
INTRODUCTION 2
1 Scope 10
2 Normative references 10
3 Terms, definitions, abbreviated terms and conventions 10
3.1 Terms and definitions 10
3.2 Abbreviated terms 10
3.3 Notation and conventions 12
4 Message format 12
4.1 Design principles 12
4.2 Group structure 13
4.2.1 Group type A structure 13
4.2.2 Group type B structure 14
4.2.3 Group type C structure 14
4.2.4 RFT ODA pipe/channel 15
4.3 Group type A and B usage 16
4.4 Group type C usage 17
4.4.1 Transmitting legacy data using data-streams 1, 2 and 3 17
4.4.2 Transmitting group type C ODA data 17
4.4.3 AID and channel number assignment for group type C ODAs 18
5 Description of the RDS features 19
5.1 Alternative Frequencies list (AFs) 19
5.2 Clock Time and date (CT) 19
5.3 Dynamic PTY Indicator (PTYI) using DI 19
5.4 Extended Country Code (ECC) 19
5.5 Enhanced Other Networks information (EON) 19
5.6 Linkage information 20
5.7 Open Data Applications (ODAs) 20
5.8 Programme Identification (PI) 20
5.9 Programme Service name – (PS) 21
5.10 Long Programme Service name – (LPS) 21
5.11 Programme Type (PTY) 21
5.12 Programme Type Name (PTYN) 21
5.13 RadioText (RT) 22
5.14 enhanced RadioText (eRT) 22
5.15 RadioText Plus (RT+ and eRT+) 22
5.16 Traffic Programme identification (TP) 22
5.17 Traffic Announcement identification (TA) 22
5.18 Traffic Message Channel (TMC) 23
6 Coding of the group types 23
6.1 Groups of type 0A and 0B: Basic tuning and switching information with PS name 23
6.2 Group type 1A: Slow labelling codes 24
6.3 Group type 2A and 2B: RadioText 25
6.4 Group type 3A: Application identification for any specific ODA using groups of type A or B 26

6.5 Group type 4A: Clock-Time and date 26
6.6 Group type 10A: Programme Type Name PTYN 27
6.7 Group type 14A and B: Enhanced Other Networks information (EON) 28
6.8 Group type 15A: Long Programme Service name – 32 bytes with UTF-8 coding 28
6.9 Group type 15B: Fast basic tuning and switching information 29
7 Coding of RDS features for control 30
7.1 Programme Identification (PI) codes and Extended Country Codes (ECC) 30
7.1.1 PI structure 30
7.1.2 Country Identifier (CI) codes: 'Nibble 1' 30
7.1.3 Extended Country Codes (ECC) 30
7.1.4 Programme service in terms of area coverage (codes for fixed location transmitters only): 'Nibble 2' 31
7.1.5 Programme reference number: 'Nibbles 3 and 4' 31
7.1.6 PI codes for low-power short range transmitting devices 31
7.2 Programme Type (PTY) codes 32
7.3 Traffic Programme (TP) and Traffic Announcement (TA) codes 32
7.4 Decoder Identification (DI) and dynamic PTY Indicator (PTYI) codes 32
7.5 Coding of Alternative Frequencies (AFs) 33
7.5.1 AF code tables 33
7.5.2 Use of Alternative Frequencies in group type 0A 35
7.5.3 Use of AF codes in group type 14A 37
7.6 Coding of Enhanced Other Networks information (EON) 38
7.6.1 General 38
7.6.2 Coding of frequencies for cross-referenced programme services in EON 39
7.6.3 Use of the TP and TA features with EON 39
7.6.4 Use of PTY with EON 40
8 Required main RDS feature repetition rates on data-stream 0 40
Annex A (normative) Method for linking RDS programme services – Linkage information – Group type 1A and 14A 45
A.1 General 45
A.2 LA – Linkage Actuator 46
A.3 EG – Extended Generic indicator 46
A.4 ILS – International Linkage Set indicator 46
A.5 LSN – Linkage Set Number 46
Annex B (informative) Conversion between time and date conventions 48
Annex C (normative) RDS2 File Transfer protocol RFT for files up to 163 kB 50
C.1 Group coding of the ODA-AID assignment groups 50
C.1.1 General principles 50
C.1.2 Variant 0 50
C.1.3 Variant 1 51
C.1.4 Variants 2 to 15 52
C.2 Coding of the RFT data group used to carry the file data bytes 52
Annex D (informative) CRC-16 ITU-T/CCITT checkword calculation 54
D.1 General 54
D.2 PASCAL listing of CRC-16-calculation routine 54
D.3 C listing of the CRC-16 calculation routine 54
D.4 Fictitious example 55
Bibliography 56

Figure 1 – Group type A structure 13
Figure 2 – Group type B structure 14
Figure 3 – Group type C structure 14
Figure 4 – Tunnelling structure for group types A and B 17
Figure 5 – Basic tuning and switching information – Group type 0A 23
Figure 6 – Basic tuning and switching information – Group type 0B 24
Figure 7 – Slow labelling codes – Group type 1A 24
Figure 8 – RadioText – Group type 2A 25
Figure 9 – RadioText – Group type 2B 26
Figure 10 – Application identification for any specific ODA – Group type 3A 26
Figure 11 – Clock-Time and date transmission – Group type 4A 27
Figure 12 – Programme Type Name PTYN – Group type 10A 27
Figure 13 – Enhanced Other Networks information – Group type 14A 28
Figure 14 – Enhanced Other Networks information – Group type 14B 28
Figure 15 – Long PS, UTF-8 coded – Group type 15A 29
Figure 16 – Fast basic tuning and switching information – Group type 15B 29
Figure 17 – PI code structure 30
Figure A.1 – Structure of group type 1A, block 3 45
Figure A.2 – Structure of group type 14A variant 12, block 3 (Linkage information) – National link 46
Figure A.3 – Structure of group type 14A variant 12, block 3 (Linkage information) – International link 47
Figure B.1 – Conversion routes between Modified Julian Date (MJD) and Coordinated Universal Time (UTC) 48
Figure C.1 – AID assignment group coding for variant 0 50
Figure C.2 – AID assignment group coding for variant 1 52
Figure C.3 – AID assignment group coding for variant 2 to 15 52
Figure C.4 – RFT data group 53

Table 1 – Group type C Function Header definition 15
Table 2 – Group type A and B usage 16
Table 3 – Group type C assignment methods used to connect channel numbers with one or more AIDs 18
Table 4 – Assignment of up to three successive channel numbers to multiple AIDs 19
Table 5 – Area coverage codes 31
Table 6 – Programme service reference number codes 31
Table 7 – PI codes for short range transmitting devices 32
Table 8 – Codes for TP and TA 32
Table 9 – Meaning of bits d_0 to d_3 33
Table 10 – VHF frequencies 87,6 MHz to 107,9 MHz code table 33
Table 11 – Special meanings AF code table 34
Table 12 – LF/MF code table – ITU regions 1 and 3 (9 kHz spacing) 34
Table 13 – MF code table – ITU region 2 (10 kHz spacing) 35

Table 14 – Example including AFs for the extended FM Band 38
Table 15 – Data-stream 0 group repetition rates: Transmitter not part of a multi-programme service network: no TMC and only 'basic' RDS features 41
Table 16 – Data-stream 0 group repetition rates: Transmitter part of a multi-programme service network: no TMC 41
Table 17 – Data-stream 0 group repetition rates: Transmitter not part of a multi-programme service network: with TMC 42
Table 18 – Data-stream 0 group repetition rates: Transmitter not part of a multi-programme service network: no TMC and with support for UTF-8 coded characters 43
Table 19 – Data-stream 0 group repetition rates: Transmitter part of a multi-programme service network: with TMC 44
Table B.1 – Symbols used for time and date calculation 48
Table C.2 – Relation between chunk size, max. file size and max.chunk address 51

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

RADIO DATA SYSTEM (RDS) – VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 64,0 MHz TO 108,0 MHz –

Part 2: Message format: coding and definitions of RDS features

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 62106-2:2018. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

IEC 62106-2 has been prepared by technical area 1: Terminals for audio, video and data services and contents, of IEC technical committee 100: Audio, video and multimedia systems and equipment. It is an International Standard.

This second edition cancels and replaces the first edition published in 2018. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62106-2:2018:

a) Subclause 4.2.4 has been added;

b) Tables 1 and 13 have been modified;

c) The new function RDS2 file transfer has been added and it is detailed in Annex C; this uses a CRC-16, which is specified in Annex D.

The text of this International Standard is based on the following documents:

CDV	Report on voting
100/3464/CDV	100/3547/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 62106 series, published under the general title *Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*, can be found on the IEC website.

The language used for the development of this International Standard is English,

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Since the mid-1980s, a fascinating development has taken place. Most of the multimedia applications and standards have been created or redefined significantly. Hardware has become extremely powerful with dedicated software and middleware. In the mid-1980s, Internet as well as its protocols did not exist. Navigation systems became affordable in the late 1990s, and a full range of attractive smartphones now exist. The computing power of all these new products is comparable with that of the mainframe installations in that era.

Listener expectations have grown faster than the technology. Visual experience is now very important, like the Internet look and feel. Scrolling text or delivering just audio is nowadays perceived as insufficient for FM radio, ~~specifically~~ especially for smartphone users. New types of radio receivers with added value features are therefore required. RDS has so far proven to be very successful.

FM radio with RDS is an analogue-digital hybrid system, which is still a valid data transmission technology and only the applications need adaptation. Now the time has come to solve the only disadvantage, the lack of sufficient data capacity. With RDS2, the need to increase the data capacity can be fulfilled.

RDS was introduced in the early 1980s. During the introductory phase in Europe, the car industry became very involved and that was the start of an extremely successful roll-out. Shortly afterwards, RDS (RBDS) was launched in the USA [1, 2, 3, 4, 5][1] .

The RDS Forum has investigated a solution to the issue of limited data capacity. For RDS2, both sidebands around the RDS 57 kHz subcarrier can be repeated a few times, up to three, centred on additional subcarriers higher up in the FM multiplex while still remaining compatible with the ITU Recommendations.

The core elements of RDS2 are the additional subcarriers, which will enable a significant increase of RDS data capacity to be achieved, and then only new additional data applications will have to be created, using the RDS-ODA feature, which has been part of the RDS standard IEC 62106 for many years.

In order to update IEC 62106:2015 to the specifications of RDS2, IEC 62106 has been restructured as follows:

Part 1: Modulation characteristics and baseband coding

Part 2: RDS message format, coding and definition of RDS features

Part 3: Usage and registration of Open Data Applications ODAs

Part 4: Registered code tables

Part 5: Marking of RDS and RDS2 devices

Part 6: Compilation of technical specifications for Open Data Applications in the public domain

~~The following future parts are planned:~~

Part ~~7~~9: RBDS – RDS variant used in North America

Part ~~8~~10: Universal Encoder Communication Protocol UECP

The original specifications of the RDS system have been maintained and the extra functionalities of RDS2 have been added.

---

1 Numbers in square brackets refer to the Bibliography.

~~Obsolete or unused functions from the original RDS standard IEC 62106:2015 have been deleted.~~ The presentation in Parts 1, 2 and 3 follows the OSI basic reference model for information processing systems [6].

RADIO DATA SYSTEM (RDS) – VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 64,0 MHz TO 108,0 MHz –

Part 2: Message format: coding and definitions of RDS features

1 Scope

This part of IEC 62106 defines the coding and definition of features for the Radio Data System (RDS).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62106 (all parts), *Radio Data System (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*

ISO/IEC 10646, *Information technology – Universal Coded Character Set (UCS)*

ISO 14819 (all parts), *Intelligent transport systems – Traffic and travel information messages via traffic message coding*

IEC 62106-2

Edition 2.0 2021-02

INTERNATIONAL STANDARD

Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz –
Part 2: Message format: coding and definitions of RDS features



IEC 62106-2:2021-02(en)

CONTENTS

FOREWORD 6
INTRODUCTION 8
1 Scope 9
2 Normative references 9
3 Terms, definitions, abbreviated terms and conventions 9
3.1 Terms and definitions 9
3.2 Abbreviated terms 9
3.3 Notation and conventions 11
4 Message format 11
4.1 Design principles 11
4.2 Group structure 12
4.2.1 Group type A structure 12
4.2.2 Group type B structure 13
4.2.3 Group type C structure 13
4.2.4 RFT ODA pipe/channel 14
4.3 Group type A and B usage 15
4.4 Group type C usage 16
4.4.1 Transmitting legacy data using data-streams 1, 2 and 3 16
4.4.2 Transmitting group type C ODA data 16
4.4.3 AID and channel number assignment for group type C ODAs 17
5 Description of the RDS features 18
5.1 Alternative Frequencies list (AFs) 18
5.2 Clock Time and date (CT) 18
5.3 Dynamic PTY Indicator (PTYI) using DI 18
5.4 Extended Country Code (ECC) 18
5.5 Enhanced Other Networks information (EON) 18
5.6 Linkage information 19
5.7 Open Data Applications (ODAs) 19
5.8 Programme Identification (PI) 19
5.9 Programme Service name – (PS) 20
5.10 Long Programme Service name – (LPS) 20
5.11 Programme Type (PTY) 20
5.12 Programme Type Name (PTYN) 20
5.13 RadioText (RT) 21
5.14 enhanced RadioText (eRT) 21
5.15 RadioText Plus (RT+ and eRT+) 21
5.16 Traffic Programme identification (TP) 21
5.17 Traffic Announcement identification (TA) 21
5.18 Traffic Message Channel (TMC) 22
6 Coding of the group types 22
6.1 Groups of type 0A and 0B: Basic tuning and switching information with PS name 22
6.2 Group type 1A: Slow labelling codes 23
6.3 Group type 2A and 2B: RadioText 24
6.4 Group type 3A: Application identification for any specific ODA using groups of type A or B 25

6.5 Group type 4A: Clock-Time and date 25
6.6 Group type 10A: Programme Type Name PTYN 26
6.7 Group type 14A and B: Enhanced Other Networks information (EON) 27
6.8 Group type 15A: Long Programme Service name – 32 bytes with UTF-8 coding 27
6.9 Group type 15B: Fast basic tuning and switching information 28
7 Coding of RDS features for control 29
7.1 Programme Identification (PI) codes and Extended Country Codes (ECC) 29
7.1.1 PI structure 29
7.1.2 Country Identifier (CI) codes: 'Nibble 1' 29
7.1.3 Extended Country Codes (ECC) 29
7.1.4 Programme service in terms of area coverage (codes for fixed location transmitters only): 'Nibble 2' 30
7.1.5 Programme reference number: 'Nibbles 3 and 4' 30
7.1.6 PI codes for low-power short range transmitting devices 30
7.2 Programme Type (PTY) codes 31
7.3 Traffic Programme (TP) and Traffic Announcement (TA) codes 31
7.4 Decoder Identification (DI) and dynamic PTY Indicator (PTYI) codes 31
7.5 Coding of Alternative Frequencies (AFs) 32
7.5.1 AF code tables 32
7.5.2 Use of Alternative Frequencies in group type 0A 34
7.5.3 Use of AF codes in group type 14A 36
7.6 Coding of Enhanced Other Networks information (EON) 37
7.6.1 General 37
7.6.2 Coding of frequencies for cross-referenced programme services in EON 38
7.6.3 Use of the TP and TA features with EON 38
7.6.4 Use of PTY with EON 38
8 Required main RDS feature repetition rates on data-stream 0 39
Annex A (normative) Method for linking RDS programme services – Linkage information – Group type 1A and 14A 44
A.1 General 44
A.2 LA – Linkage Actuator 45
A.3 EG – Extended Generic indicator 45
A.4 ILS – International Linkage Set indicator 45
A.5 LSN – Linkage Set Number 45
Annex B (informative) Conversion between time and date conventions 47
Annex C (normative) RDS2 File Transfer protocol RFT for files up to 163 kB 49
C.1 Group coding of the ODA-AID assignment groups 49
C.1.1 General principles 49
C.1.2 Variant 0 49
C.1.3 Variant 1 50
C.1.4 Variants 2 to 15 51
C.2 Coding of the RFT data group used to carry the file data bytes 51
Annex D (informative) CRC-16 ITU-T/CCITT checkword calculation 53
D.1 General 53
D.2 PASCAL listing of CRC-16-calculation routine 53
D.3 C listing of the CRC-16 calculation routine 53
D.4 Fictitious example 54
Bibliography 55

Figure 1 – Group type A structure 12
Figure 2 – Group type B structure 13
Figure 3 – Group type C structure 13
Figure 4 – Tunnelling structure for group types A and B 16
Figure 5 – Basic tuning and switching information – Group type 0A 22
Figure 6 – Basic tuning and switching information – Group type 0B 23
Figure 7 – Slow labelling codes – Group type 1A 23
Figure 8 – RadioText – Group type 2A 24
Figure 9 – RadioText – Group type 2B 25
Figure 10 – Application identification for any specific ODA – Group type 3A 25
Figure 11 – Clock-Time and date transmission – Group type 4A 26
Figure 12 – Programme Type Name PTYN – Group type 10A 26
Figure 13 – Enhanced Other Networks information – Group type 14A 27
Figure 14 – Enhanced Other Networks information – Group type 14B 27
Figure 15 – Long PS, UTF-8 coded – Group type 15A 28
Figure 16 – Fast basic tuning and switching information – Group type 15B 28
Figure 17 – PI code structure 29
Figure A.1 – Structure of group type 1A, block 3 44
Figure A.2 – Structure of group type 14A variant 12, block 3 (Linkage information) – National link 45
Figure A.3 – Structure of group type 14A variant 12, block 3 (Linkage information) – International link 46
Figure B.1 – Conversion routes between Modified Julian Date (MJD) and Coordinated Universal Time (UTC) 47
Figure C.1 – AID assignment group coding for variant 0 49
Figure C.2 – AID assignment group coding for variant 1 51
Figure C.3 – AID assignment group coding for variant 2 to 15 51
Figure C.4 – RFT data group 52

Table 1 – Group type C Function Header definition 14
Table 2 – Group type A and B usage 15
Table 3 – Group type C assignment methods used to connect channel numbers with one or more AIDs 17
Table 4 – Assignment of up to three successive channel numbers to multiple AIDs 18
Table 5 – Area coverage codes 30
Table 6 – Programme service reference number codes 30
Table 7 – PI codes for short range transmitting devices 31
Table 8 – Codes for TP and TA 31
Table 9 – Meaning of bits d_0 to d_3 32
Table 10 – VHF frequencies 87,6 MHz to 107,9 MHz code table 32
Table 11 – Special meanings AF code table 33
Table 12 – LF/MF code table – ITU regions 1 and 3 (9 kHz spacing) 33
Table 13 – MF code table – ITU region 2 (10 kHz spacing) 33

Table 14 – Example including AFs for the extended FM Band 37
Table 15 – Data-stream 0 group repetition rates: Transmitter not part of a multi-programme service network: no TMC and only 'basic' RDS features 39
Table 16 – Data-stream 0 group repetition rates: Transmitter part of a multi-programme service network: no TMC 40
Table 17 – Data-stream 0 group repetition rates: Transmitter not part of a multi-programme service network: with TMC 41
Table 18 – Data-stream 0 group repetition rates: Transmitter not part of a multi-programme service network: no TMC and with support for UTF-8 coded characters 42
Table 19 – Data-stream 0 group repetition rates: Transmitter part of a multi-programme service network: with TMC 43
Table B.1 – Symbols used for time and date calculation 47
Table C.2 – Relation between chunk size, max. file size and max.chunk address 50

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

RADIO DATA SYSTEM (RDS) – VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 64,0 MHz TO 108,0 MHz –

Part 2: Message format: coding and definitions of RDS features

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62106-2 has been prepared by technical area 1: Terminals for audio, video and data services and contents, of IEC technical committee 100: Audio, video and multimedia systems and equipment. It is an International Standard.

This second edition cancels and replaces the first edition published in 2018. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62106-2:2018:

a) Subclause 4.2.4 has been added;
b) Tables 1 and 13 have been modified;
c) The new function RDS2 file transfer has been added and it is detailed in Annex C; this uses a CRC-16, which is specified in Annex D.

The text of this International Standard is based on the following documents:

CDV	Report on voting
100/3464/CDV	100/3547/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 62106 series, published under the general title *Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*, can be found on the IEC website.

The language used for the development of this International Standard is English,

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

Since the mid-1980s, a fascinating development has taken place. Most of the multimedia applications and standards have been created or redefined significantly. Hardware has become extremely powerful with dedicated software and middleware. In the mid-1980s, Internet as well as its protocols did not exist. Navigation systems became affordable in the late 1990s, and a full range of attractive smartphones now exist. The computing power of all these new products is comparable with that of the mainframe installations in that era.

Listener expectations have grown faster than the technology. Visual experience is now very important, like the Internet look and feel. Scrolling text or delivering just audio is nowadays perceived as insufficient for FM radio, especially for smartphone users. New types of radio receivers with added value features are therefore required. RDS has so far proven to be very successful.

FM radio with RDS is an analogue-digital hybrid system, which is still a valid data transmission technology and only the applications need adaptation. Now the time has come to solve the only disadvantage, the lack of sufficient data capacity. With RDS2, the need to increase the data capacity can be fulfilled.

RDS was introduced in the early 1980s. During the introductory phase in Europe, the car industry became very involved and that was the start of an extremely successful roll-out. Shortly afterwards, RDS (RBDS) was launched in the USA [1, 2, 3, 4, 5][1] .

The RDS Forum has investigated a solution to the issue of limited data capacity. For RDS2, both sidebands around the RDS 57 kHz subcarrier can be repeated a few times, up to three, centred on additional subcarriers higher up in the FM multiplex while still remaining compatible with the ITU Recommendations.

The core elements of RDS2 are the additional subcarriers, which will enable a significant increase of RDS data capacity to be achieved, and then only new additional data applications will have to be created, using the RDS-ODA feature, which has been part of the RDS standard IEC 62106 for many years.

In order to update IEC 62106:2015 to the specifications of RDS2, IEC 62106 has been restructured as follows:

Part 1: Modulation characteristics and baseband coding

Part 2: RDS message format, coding and definition of RDS features

Part 3: Usage and registration of Open Data Applications ODAs

Part 4: Registered code tables

Part 5: Marking of RDS and RDS2 devices

Part 6: Compilation of technical specifications for Open Data Applications in the public domain

Part 9: RBDS – RDS variant used in North America

Part 10: Universal Encoder Communication Protocol UECP

The original specifications of the RDS system have been maintained and the extra functionalities of RDS2 have been added.

The presentation in Parts 1, 2 and 3 follows the OSI basic reference model for information processing systems [6].

---

1 Numbers in square brackets refer to the Bibliography.

RADIO DATA SYSTEM (RDS) – VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 64,0 MHz TO 108,0 MHz –

Part 2: Message format: coding and definitions of RDS features

1 Scope

This part of IEC 62106 defines the coding and definition of features for the Radio Data System (RDS).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62106 (all parts), *Radio Data System (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*

ISO/IEC 10646, *Information technology – Universal Coded Character Set (UCS)*

ISO 14819 (all parts), *Intelligent transport systems – Traffic and travel information messages via traffic message coding*