IEC 62288

Edition 3.1 2024-11
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

colour inside

Maritime navigation and radiocommunication equipment and systems – Presentation of navigation-related information on shipborne navigational displays – General requirements, methods of testing and required test results

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 47.020.70

ISBN 978-2-8327-0021-1

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 9
INTRODUCTION to Amendment 1 11
1 Scope 12
2 Normative references 12
3 Terms, definitions and abbreviated terms 13
3.1 Terms and definitions 13
3.2 Abbreviated terms 20
4 General requirements for all displays on the bridge of a ship 20
4.1 Relationship to IMO standards 20
4.2 Application of IEC 60945 22
4.2.1 Remark 22
4.2.2 General requirements 22
4.3 Arrangement of information 22
4.3.1 Consistency of layout and logical grouping 22
4.3.2 Consistent presentation of information 23
4.3.3 Separation of operational display area 23
4.4 Readability 23
4.4.1 Readability under all ambient light conditions 23
4.4.2 Legibility of alphanumeric data and text 26
4.4.3 Presentation of text and icons 26
4.5 Colours and intensity 27
4.5.1 Discrimination of colours – Requirement 27
4.5.2 Methods of test and required results 28
4.6 Symbols 28
4.6.1 Operational information 28
4.6.2 Electronic chart information 29
4.7 Colour coding 30
4.7.1 Colour coding for discrimination 30
4.7.2 Colour coding of information 30
4.7.3 Colour coding in combination with other attributes 30
4.7.4 Flashing of information 30
4.8 Integrity marking 31
4.8.1 Indication of source, validity and integrity status 31
4.8.2 Colour coding of validity and integrity 31
4.8.3 Indication of presentation failure 31
4.9 Alerts and indications 32
4.9.1 Operational status 32
4.9.2 List of alerts 32
4.9.3 Alert related information from multiple sources 32
4.9.4 Speech output for alarms and warnings 32
4.10 Presentation mode 32
4.10.1 Requirement 32
4.10.2 Methods of test and required results 33
4.11 User manuals, instructions and reference guides 33
4.11.1 Requirement 33
4.11.2 Methods of test and required results 33
5 Presentation of operational information 33

5.1 Application 33
5.2 Presentation of own ship information 33
5.2.1 Graphical representation of own ship – Requirement 33
5.2.2 Methods of test and required results 34
5.3 Presentation of chart information 34
5.3.1 Alteration of chart information 34
5.3.2 Colours and symbols for charted information 34
5.4 Presentation of radar information 35
5.4.1 Radar video images 35
5.4.2 Target trails 36
5.5 Presentation of target information 36
5.5.1 Providing target information 36
5.5.2 Consistent user interface for target information 37
5.5.3 Indication of exceeding target capacity 37
5.5.4 Presentation of repeated AIS reports 38
5.5.5 Filtering sleeping AIS targets 39
5.5.6 Activation of AIS targets 39
5.5.7 Graphical presentation of targets 40
5.5.8 Target selection 41
5.5.9 Indication of target derivation 42
5.5.10 Presentation of tracked radar target information 42
5.5.11 Presentation of reported AIS target information 43
5.5.12 Continual update of target information 44
5.5.13 Own ship’s AIS information 44
5.5.14 Obscuring the operational display area 45
5.6 Operational alerts 45
5.6.1 Alert status 45
5.6.2 CPA/TCPA alarms 45
5.6.3 Acquisition/activation zones warnings 46
5.6.4 Lost target warnings 46
5.7 AIS and radar target association 47
5.7.1 Requirement 47
5.7.2 Methods of test and required results 47
5.8 AIS presentation user selectors and their status indications 48
5.8.1 Requirement 48
5.8.2 Methods of test and required results 49
5.9 Trial manoeuvre 50
5.9.1 Requirement 50
5.9.2 Methods of test and required results 50
5.10 Measurement 50
5.10.1 Measurement from own ship 50
5.10.2 Bearing and range measurements 50
5.11 Navigation tools 51
5.11.1 General requirements 51
5.11.2 Range rings 51
5.11.3 Variable range marker (VRM) 51
5.11.4 Bearing scale 52
5.11.5 Electronic bearing line (EBL) 53
5.11.6 Parallel index lines (PI) 54

5.11.7 Offset measurement of range and bearing 55
5.11.8 User cursor 56
5.12 AIS data link message processing capacity 57
5.12.1 General 57
5.12.2 Requirements 57
5.12.3 Methods of test and required results 57
5.13 AIS data report 57
5.13.1 General 57
5.13.2 AIS data report capacity 57
5.13.3 AIS data report display 58
5.13.4 Graphical presentation of AIS AtoN dimensions 61
5.14 AIS locating device 61
5.14.1 General 61
5.14.2 AIS locating device capacity 62
5.14.3 AIS locating device display 62
5.15 AIS ASM 64
5.15.1 General 64
5.15.2 Categories 65
5.15.3 AIS ASM capacity 67
5.15.4 AIS ASM display 69
5.16 Presentation of AIS synthetic target 71
5.16.1 Requirement 71
5.16.2 Methods of test and required results 72
5.17 Presentation of association of DSC received call with a displayed AIS object 73
5.17.1 Requirement 73
5.17.2 Methods of test and required results 73
5.18 AIS ASM information extending reported AIS target information 74
5.19 Received AIS safety related messages 75
5.19.1 Requirements 75
5.19.2 Methods of test and required results 76
5.20 Sent AIS safety related messages 77
5.20.1 Requirements 77
5.20.2 Methods of test and required results 77
6 INS, radar and chart displays 77
6.1 General 77
6.1.1 Application 77
6.1.2 Multifunction displays 77
6.1.3 Simultaneous display of radar and chart data 78
6.1.4 Range scales 78
6.1.5 Operational display area 79
6.1.6 Motion display modes 79
6.1.7 Orientation modes 79
6.1.8 Off-centring 80
6.1.9 Stabilisation modes 80
6.2 Radar displays 81
6.2.1 Application 81
6.2.2 Radar video image 81
6.2.3 Brightness of radar information 82
6.2.4 Display of chart information on radar 82

6.2.5 Priority of radar information 83
6.2.6 Display of map graphics 83
6.3 Chart displays 84
6.3.1 Application 84
6.3.2 Display of chart information 84
6.3.3 IMO ECDIS display categories 85
6.3.4 Adding or removing information from the display 85
6.3.5 Safety contour 86
6.3.6 Safety depth 86
6.3.7 Chart scale 86
6.3.8 Display of radar and target information 87
6.3.9 Display of additional information 87
6.4 Composite task-oriented presentations 88
6.4.1 User-configured presentations 88
6.4.2 Information associated with the task-at-hand 88
6.5 Single and simple operator actions 88
6.5.1 Applicability 88
6.5.2 Requirement 89
6.5.3 Methods of test and required results 89
6.6 User and default settings 89
6.6.1 General 89
6.6.2 User-settings 89
6.6.3 Default settings 90
7 Physical requirements 90
7.1 General 90
7.2 Display adjustment 90
7.2.1 Contrast and brightness 90
7.2.2 Magnetic interference 91
7.2.3 Temporal stability 91
7.2.4 Physical controls and status indicators 92
7.3 Screen size 92
7.3.1 Requirement 92
7.3.2 Method of test and required results 93
7.4 Multicoloured display equipment 93
7.4.1 Requirement 93
7.4.2 Method of test and required results 93
7.5 Screen resolution 94
7.5.1 Requirement 94
7.5.2 Method of test and required results 94
7.6 Screen viewing angle 94
7.6.1 Requirement 94
7.6.2 Methods of test and required results 94
Annex A (normative) Presentation colours and symbols 95
A.1 Overview 95
A.2 Purpose 95
A.3 Use 95
A.4 Application 95
A.5 Navigation-related symbols 95

Annex B (normative) Guidelines for the presentation of navigation-related terminology and abbreviations 131
B.1 Overview 131
B.2 Purpose 131
B.3 Use of these guidelines 131
B.4 Application 131
B.5 Navigation related terminology and abbreviations 131
Annex C (informative) Guidance on display and dialogue design in IMO MSC/Circ.982 138
C.1 Overview 138
C.2 General 138
C.3 Requirements in IMO MSC/Circ.982 related to the display design 138
Annex D (informative) Guidance on testing 140
D.1 Methods of test 140
D.1.1 General 140
D.1.2 Observation 140
D.1.3 Inspection of documented evidence 140
D.1.4 Measurement 141
D.1.5 Analytical evaluation 141
D.2 Application of IEC 60945 141
D.2.1 Display equipment category 141
D.2.2 Technical performance 141
D.2.3 Pre-conditioning for environmental tests 142
D.2.4 Methods of test applied for IEC 60945 142
D.3 Compliance with requirements 143
D.4 Simulation 144
D.5 Electronic chart data 144
Annex E (normative) Operational controls and logical grouping 145
E.1 Overview 145
E.2 Logical grouping of data and control functions 145
E.3 Navigation related terminology and icons for common function controls (hot keys and shortcuts) 147
Annex F (normative) Icons for presentation of the state of an alert 161
Annex G (normative) Testing for colours, intensity and flicker 162
G.1 Testing for colours and intensity 162
G.1.1 General 162
G.1.2 Test personnel 163
G.1.3 Method of test 163
G.2 Testing for flicker 164
G.2.1 Overview 164
G.2.2 Analytic model 164
G.2.3 Decision criteria 166
Annex H (normative) Single and simple operator actions 168
H.1 General 168
H.2 Tables for single and simple operator actions 168
Annex I (normative) Default settings 170
I.1 General 170
I.2 ECDIS default settings 170
I.3 Radar default settings 172

Annex J (normative) Implementation details of AIS ASM 173
J.1 General 173
J.2 AIS ASM 173
Annex K (informative) Overview of AIS Messages 182
K.1 General 182
K.2 Use case guidance on AIS ASM 184
Annex L (informative) Overview of the use AIS AtoN status field bits 185
Bibliography 186

Table 1 – Ambient light conditions 24
Table 2 – Operational status of indications 32
Table 3 – User selectors for AIS presentation 48
Table 4 – AIS status indications 49
Table 5 – AIS data report capacity 58
Table 6 – AIS locating devices capacity 62
Table 7 – AIS ASM object capacity 67
Table 8 – Extended reported AIS target information from AIS ASM 74
Table A.1 – Own ship symbols 96
Table A.2 – Radar and AIS symbols 100
Table A.3 – Navigation symbols 116
Table A.4 – Navigation tools 121
Table A.5 – Other symbols 122
Table A.6 – Example of possible colour scheme 130
Table B.1 – List of standard terms and abbreviations 132
Table B.2 – List of standard units of measurement and abbreviations 137
Table C.1 – Paragraphs in MSC/Circ.982 associated with IEC 60945 requirements 138
Table C.2 – Other paragraphs in MSC/Circ.982 related to display design 139
Table C.3 – Other paragraphs in MSC/Circ.982 partially related to display design 139
Table D.1 – Methods of test applied for IEC 60945 142
Table E.1 – Logical grouping for radar, ECDIS and INS applications (based on MSC.1/Circ.1609) 146
Table E.2 – Examples of logical grouping for voluntary implementation 147
Table E.3 – General controls 148
Table E.4 – General navigation functions (based on MSC.1/Circ.1609) 149
Table E.5 – Radar specific controls 152
Table E.6 – Control of chart display functions (based on MSC.1/Circ.1609) 153
Table E.7 – Control of chart functionality (based on MSC.1/Circ.1609) 158
Table E.8 – Database functions (based on MSC.1/Circ.1609) 158
Table E.9 – Route plan and monitoring functions (based on MSC.1/Circ.1609) 159
Table E.10 – Groups of functions (based on MSC.1/Circ.1609) 159
Table G.1 – Values of predicted energy and special coefficients 167
Table H.1 – Access to functions, as defined before June 2019 (based on MSC.1/Circ.1609) 168
Table H.2 – Access to functions (based on MSC.1/Circ.1609) 169

Table H.3 – Access to group of functions (based on MSC.1/Circ.1609) 169
Table I.1 – ECDIS settings configured in response to "Default" selection (based on MSC.1/Circ.1609) 170
Table I.2 – Radar control settings configured in response to "Default" selection (based on MSC.1/Circ.1609) 172
Table J.1 – Details of AIS ASM 173
Table K.1 – AIS Messages 182
Table K.2 – AIS ASM Messages 183
Table L.1 – AIS AtoN status field 185

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – PRESENTATION OF NAVIGATION-RELATED INFORMATION ON SHIPBORNE NAVIGATIONAL DISPLAYS – GENERAL REQUIREMENTS, METHODS OF TESTING AND REQUIRED TEST RESULTS

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 62288 edition 3.1 contains the third edition (2021-12) [documents 80/1013/FDIS and 80/1017/RVD] and its amendment 1 (2024-11) [documents 80/1117/CDV and 80/1128/RVC].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

IEC 62288 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems. It is an International Standard.

This third edition cancels and replaces the second edition published in 2014. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) Clause 4 has been revised to remove requirements for indications of alerts which are now given in IEC 62923-1;
b) Clause 5 has been extensively revised to add new requirements for AIS, ASM and DSC presentation together with three new supporting annexes, Annex J, Annex K, Annex L;
c) Annex A and Annex B have been revised to incorporate changes to IMO circular SN.1/Circ.243;
d) Annex E has been revised to incorporate changes to IMO resolution MSC.191(79) and renamed as "Operational controls and logical grouping".
e) two new annexes have been added, Annex H on operator actions and Annex I on default settings in support of IMO circular MSC.1/Circ.1609.

The text of this International Standard is based on the following documents:

Draft	Report on voting
80/1013/FDIS	80/1017/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION to Amendment 1

This amendment updates the interpretation of the bit encoding for reporting various cases of AtoN errors or failures to be compliant with the notes available in the IALA R-0126 Ed.2 published in December 2021. The amendment further corrects an inconsistency between Table L.1 of IEC 62288:2021 and Figure 4 section 4.8.4 of IALA Rec.R-0126:2021.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – PRESENTATION OF NAVIGATION-RELATED INFORMATION ON SHIPBORNE NAVIGATIONAL DISPLAYS – GENERAL REQUIREMENTS, METHODS OF TESTING AND REQUIRED TEST RESULTS

1 Scope

This document specifies the general requirements, methods of testing, and required test results, for the presentation of navigation-related information on shipborne navigational displays in support of IMO resolutions MSC.191(79) as amended by MSC.466(101) in June 2019, and where applicable MSC.302(87).

This document also supports the guidelines included in the related IMO Circulars MSC.1/Circ.1609 on the standardization of user interface design for navigation equipment and SN.1/Circ.243 as revised in June 2019 on the presentation of navigation related symbols, terms and abbreviations.

This document also specifies the presentation of AIS data reports and the AIS Application Specific Messages defined for international use in IMO SN.1/Circ.289 and intended to be received by a ship for display onboard.

NOTE All text in this document whose wording is identical to text contained in an IMO document is printed in *italics*. Reference to the document is noted at the beginning of the paragraph. The notation contains a prefix referring to the document and a suffix with the paragraph number from the document (for example, (MSC191/1); (SN243/1), etc.).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945:2002, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61174, *Maritime navigation and radiocommunication equipment and systems – Electronic chart display and information system (ECDIS) – Operational and performance requirements, methods of testing and required test results*

IEC 61966-4, *Multimedia systems and equipment – Colour measurement and management – Part 4: Equipment using liquid crystal display panels*

IEC 62388, *Maritime navigation and radiocommunication equipment and systems – Shipborne radar – Performance requirements, methods of testing and required test results*

IEC 62923-1, *Maritime navigation and radiocommunication equipment and systems – Bridge alert management – Part 1: Operational and performance requirements, methods of testing and required test results*

IHO S-52, *Specifications for chart content and display aspects of ECDIS*

IMO, *Seafarers' Training, Certification and Watchkeeping Code (STCW Code)*

IMO A.694(17):1991, *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO MSC.191(79):2004, *Performance standards for the presentation of navigation related information on shipborne navigational displays*

IMO MSC.192(79):2004, *Performance standards for radar equipment*

IMO MSC.232(82):2006, *Revised performance standards for electronic chart display and information systems (ECDIS)*

IMO SN.1/Circ.243/Rev.2:2019+Corr.1, *Guidelines for the presentation of navigation related symbols, terms and abbreviations*

IMO SN.1/Circ.289:2010, *Guidance on the use of AIS application-specific messages*

IMO MSC.302(87):2010, *Performance standards for bridge alert management (BAM)*

IMO MSC.1/Circ.1609:2019, *Guidelines for the standardization of user interface design for navigation equipment*

IMO A.1021(26):2009, *Code on Alerts and Indications*

VESA-2001-6, *Flat Panel Display Measurements* (*FPDM*)

CONTENTS

FOREWORD 9
INTRODUCTION to Amendment 1 11
1 Scope 12
2 Normative references 12
3 Terms, definitions and abbreviated terms 13
3.1 Terms and definitions 13
3.2 Abbreviated terms 20
4 General requirements for all displays on the bridge of a ship 20
4.1 Relationship to IMO standards 20
4.2 Application of IEC 60945 22
4.2.1 Remark 22
4.2.2 General requirements 22
4.3 Arrangement of information 22
4.3.1 Consistency of layout and logical grouping 22
4.3.2 Consistent presentation of information 23
4.3.3 Separation of operational display area 23
4.4 Readability 23
4.4.1 Readability under all ambient light conditions 23
4.4.2 Legibility of alphanumeric data and text 26
4.4.3 Presentation of text and icons 26
4.5 Colours and intensity 27
4.5.1 Discrimination of colours – Requirement 27
4.5.2 Methods of test and required results 28
4.6 Symbols 28
4.6.1 Operational information 28
4.6.2 Electronic chart information 29
4.7 Colour coding 30
4.7.1 Colour coding for discrimination 30
4.7.2 Colour coding of information 30
4.7.3 Colour coding in combination with other attributes 30
4.7.4 Flashing of information 30
4.8 Integrity marking 31
4.8.1 Indication of source, validity and integrity status 31
4.8.2 Colour coding of validity and integrity 31
4.8.3 Indication of presentation failure 31
4.9 Alerts and indications 32
4.9.1 Operational status 32
4.9.2 List of alerts 32
4.9.3 Alert related information from multiple sources 32
4.9.4 Speech output for alarms and warnings 32
4.10 Presentation mode 32
4.10.1 Requirement 32
4.10.2 Methods of test and required results 33
4.11 User manuals, instructions and reference guides 33
4.11.1 Requirement 33
4.11.2 Methods of test and required results 33
5 Presentation of operational information 33

5.1 Application 33
5.2 Presentation of own ship information 33
5.2.1 Graphical representation of own ship – Requirement 33
5.2.2 Methods of test and required results 34
5.3 Presentation of chart information 34
5.3.1 Alteration of chart information 34
5.3.2 Colours and symbols for charted information 34
5.4 Presentation of radar information 35
5.4.1 Radar video images 35
5.4.2 Target trails 36
5.5 Presentation of target information 36
5.5.1 Providing target information 36
5.5.2 Consistent user interface for target information 37
5.5.3 Indication of exceeding target capacity 37
5.5.4 Presentation of repeated AIS reports 38
5.5.5 Filtering sleeping AIS targets 39
5.5.6 Activation of AIS targets 39
5.5.7 Graphical presentation of targets 40
5.5.8 Target selection 41
5.5.9 Indication of target derivation 42
5.5.10 Presentation of tracked radar target information 42
5.5.11 Presentation of reported AIS target information 43
5.5.12 Continual update of target information 44
5.5.13 Own ship’s AIS information 44
5.5.14 Obscuring the operational display area 45
5.6 Operational alerts 45
5.6.1 Alert status 45
5.6.2 CPA/TCPA alarms 45
5.6.3 Acquisition/activation zones warnings 46
5.6.4 Lost target warnings 46
5.7 AIS and radar target association 47
5.7.1 Requirement 47
5.7.2 Methods of test and required results 47
5.8 AIS presentation user selectors and their status indications 48
5.8.1 Requirement 48
5.8.2 Methods of test and required results 49
5.9 Trial manoeuvre 50
5.9.1 Requirement 50
5.9.2 Methods of test and required results 50
5.10 Measurement 50
5.10.1 Measurement from own ship 50
5.10.2 Bearing and range measurements 50
5.11 Navigation tools 51
5.11.1 General requirements 51
5.11.2 Range rings 51
5.11.3 Variable range marker (VRM) 51
5.11.4 Bearing scale 52
5.11.5 Electronic bearing line (EBL) 53
5.11.6 Parallel index lines (PI) 54

5.11.7 Offset measurement of range and bearing 55
5.11.8 User cursor 56
5.12 AIS data link message processing capacity 57
5.12.1 General 57
5.12.2 Requirements 57
5.12.3 Methods of test and required results 57
5.13 AIS data report 57
5.13.1 General 57
5.13.2 AIS data report capacity 57
5.13.3 AIS data report display 58
5.13.4 Graphical presentation of AIS AtoN dimensions 61
5.14 AIS locating device 61
5.14.1 General 61
5.14.2 AIS locating device capacity 62
5.14.3 AIS locating device display 62
5.15 AIS ASM 64
5.15.1 General 64
5.15.2 Categories 65
5.15.3 AIS ASM capacity 67
5.15.4 AIS ASM display 69
5.16 Presentation of AIS synthetic target 71
5.16.1 Requirement 71
5.16.2 Methods of test and required results 72
5.17 Presentation of association of DSC received call with a displayed AIS object 73
5.17.1 Requirement 73
5.17.2 Methods of test and required results 73
5.18 AIS ASM information extending reported AIS target information 74
5.19 Received AIS safety related messages 75
5.19.1 Requirements 75
5.19.2 Methods of test and required results 76
5.20 Sent AIS safety related messages 77
5.20.1 Requirements 77
5.20.2 Methods of test and required results 77
6 INS, radar and chart displays 77
6.1 General 77
6.1.1 Application 77
6.1.2 Multifunction displays 77
6.1.3 Simultaneous display of radar and chart data 78
6.1.4 Range scales 78
6.1.5 Operational display area 79
6.1.6 Motion display modes 79
6.1.7 Orientation modes 79
6.1.8 Off-centring 80
6.1.9 Stabilisation modes 80
6.2 Radar displays 81
6.2.1 Application 81
6.2.2 Radar video image 81
6.2.3 Brightness of radar information 82
6.2.4 Display of chart information on radar 82

6.2.5 Priority of radar information 83
6.2.6 Display of map graphics 83
6.3 Chart displays 84
6.3.1 Application 84
6.3.2 Display of chart information 84
6.3.3 IMO ECDIS display categories 85
6.3.4 Adding or removing information from the display 85
6.3.5 Safety contour 86
6.3.6 Safety depth 86
6.3.7 Chart scale 86
6.3.8 Display of radar and target information 87
6.3.9 Display of additional information 87
6.4 Composite task-oriented presentations 88
6.4.1 User-configured presentations 88
6.4.2 Information associated with the task-at-hand 88
6.5 Single and simple operator actions 88
6.5.1 Applicability 88
6.5.2 Requirement 89
6.5.3 Methods of test and required results 89
6.6 User and default settings 89
6.6.1 General 89
6.6.2 User-settings 89
6.6.3 Default settings 90
7 Physical requirements 90
7.1 General 90
7.2 Display adjustment 90
7.2.1 Contrast and brightness 90
7.2.2 Magnetic interference 91
7.2.3 Temporal stability 91
7.2.4 Physical controls and status indicators 92
7.3 Screen size 92
7.3.1 Requirement 92
7.3.2 Method of test and required results 93
7.4 Multicoloured display equipment 93
7.4.1 Requirement 93
7.4.2 Method of test and required results 93
7.5 Screen resolution 94
7.5.1 Requirement 94
7.5.2 Method of test and required results 94
7.6 Screen viewing angle 94
7.6.1 Requirement 94
7.6.2 Methods of test and required results 94
Annex A (normative) Presentation colours and symbols 95
A.1 Overview 95
A.2 Purpose 95
A.3 Use 95
A.4 Application 95
A.5 Navigation-related symbols 95

Annex B (normative) Guidelines for the presentation of navigation-related terminology and abbreviations 131
B.1 Overview 131
B.2 Purpose 131
B.3 Use of these guidelines 131
B.4 Application 131
B.5 Navigation related terminology and abbreviations 131
Annex C (informative) Guidance on display and dialogue design in IMO MSC/Circ.982 138
C.1 Overview 138
C.2 General 138
C.3 Requirements in IMO MSC/Circ.982 related to the display design 138
Annex D (informative) Guidance on testing 140
D.1 Methods of test 140
D.1.1 General 140
D.1.2 Observation 140
D.1.3 Inspection of documented evidence 140
D.1.4 Measurement 141
D.1.5 Analytical evaluation 141
D.2 Application of IEC 60945 141
D.2.1 Display equipment category 141
D.2.2 Technical performance 141
D.2.3 Pre-conditioning for environmental tests 142
D.2.4 Methods of test applied for IEC 60945 142
D.3 Compliance with requirements 143
D.4 Simulation 144
D.5 Electronic chart data 144
Annex E (normative) Operational controls and logical grouping 145
E.1 Overview 145
E.2 Logical grouping of data and control functions 145
E.3 Navigation related terminology and icons for common function controls (hot keys and shortcuts) 147
Annex F (normative) Icons for presentation of the state of an alert 161
Annex G (normative) Testing for colours, intensity and flicker 162
G.1 Testing for colours and intensity 162
G.1.1 General 162
G.1.2 Test personnel 163
G.1.3 Method of test 163
G.2 Testing for flicker 164
G.2.1 Overview 164
G.2.2 Analytic model 164
G.2.3 Decision criteria 166
Annex H (normative) Single and simple operator actions 168
H.1 General 168
H.2 Tables for single and simple operator actions 168
Annex I (normative) Default settings 170
I.1 General 170
I.2 ECDIS default settings 170
I.3 Radar default settings 172

Annex J (normative) Implementation details of AIS ASM 173
J.1 General 173
J.2 AIS ASM 173
Annex K (informative) Overview of AIS Messages 182
K.1 General 182
K.2 Use case guidance on AIS ASM 184
Annex L (informative) Overview of the use AIS AtoN status field bits 185
Bibliography 186

Table 1 – Ambient light conditions 24
Table 2 – Operational status of indications 32
Table 3 – User selectors for AIS presentation 48
Table 4 – AIS status indications 49
Table 5 – AIS data report capacity 58
Table 6 – AIS locating devices capacity 62
Table 7 – AIS ASM object capacity 67
Table 8 – Extended reported AIS target information from AIS ASM 74
Table A.1 – Own ship symbols 96
Table A.2 – Radar and AIS symbols 100
Table A.3 – Navigation symbols 116
Table A.4 – Navigation tools 121
Table A.5 – Other symbols 122
Table A.6 – Example of possible colour scheme 130
Table B.1 – List of standard terms and abbreviations 132
Table B.2 – List of standard units of measurement and abbreviations 137
Table C.1 – Paragraphs in MSC/Circ.982 associated with IEC 60945 requirements 138
Table C.2 – Other paragraphs in MSC/Circ.982 related to display design 139
Table C.3 – Other paragraphs in MSC/Circ.982 partially related to display design 139
Table D.1 – Methods of test applied for IEC 60945 142
Table E.1 – Logical grouping for radar, ECDIS and INS applications (based on MSC.1/Circ.1609) 146
Table E.2 – Examples of logical grouping for voluntary implementation 147
Table E.3 – General controls 148
Table E.4 – General navigation functions (based on MSC.1/Circ.1609) 149
Table E.5 – Radar specific controls 152
Table E.6 – Control of chart display functions (based on MSC.1/Circ.1609) 153
Table E.7 – Control of chart functionality (based on MSC.1/Circ.1609) 158
Table E.8 – Database functions (based on MSC.1/Circ.1609) 158
Table E.9 – Route plan and monitoring functions (based on MSC.1/Circ.1609) 159
Table E.10 – Groups of functions (based on MSC.1/Circ.1609) 159
Table G.1 – Values of predicted energy and special coefficients 167
Table H.1 – Access to functions, as defined before June 2019 (based on MSC.1/Circ.1609) 168
Table H.2 – Access to functions (based on MSC.1/Circ.1609) 169

Table H.3 – Access to group of functions (based on MSC.1/Circ.1609) 169
Table I.1 – ECDIS settings configured in response to "Default" selection (based on MSC.1/Circ.1609) 170
Table I.2 – Radar control settings configured in response to "Default" selection (based on MSC.1/Circ.1609) 172
Table J.1 – Details of AIS ASM 173
Table K.1 – AIS Messages 182
Table K.2 – AIS ASM Messages 183
Table L.1 – AIS AtoN status field 185

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – PRESENTATION OF NAVIGATION-RELATED INFORMATION ON SHIPBORNE NAVIGATIONAL DISPLAYS – GENERAL REQUIREMENTS, METHODS OF TESTING AND REQUIRED TEST RESULTS

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 62288 edition 3.1 contains the third edition (2021-12) [documents 80/1013/FDIS and 80/1017/RVD] and its amendment 1 (2024-11) [documents 80/1117/CDV and 80/1128/RVC].

This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.

IEC 62288 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems. It is an International Standard.

This third edition cancels and replaces the second edition published in 2014. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) Clause 4 has been revised to remove requirements for indications of alerts which are now given in IEC 62923-1;
b) Clause 5 has been extensively revised to add new requirements for AIS, ASM and DSC presentation together with three new supporting annexes, Annex J, Annex K, Annex L;
c) Annex A and Annex B have been revised to incorporate changes to IMO circular SN.1/Circ.243;
d) Annex E has been revised to incorporate changes to IMO resolution MSC.191(79) and renamed as "Operational controls and logical grouping".
e) two new annexes have been added, Annex H on operator actions and Annex I on default settings in support of IMO circular MSC.1/Circ.1609.

The text of this International Standard is based on the following documents:

Draft	Report on voting
80/1013/FDIS	80/1017/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION to Amendment 1

This amendment updates the interpretation of the bit encoding for reporting various cases of AtoN errors or failures to be compliant with the notes available in the IALA R-0126 Ed.2 published in December 2021. The amendment further corrects an inconsistency between Table L.1 of IEC 62288:2021 and Figure 4 section 4.8.4 of IALA Rec.R-0126:2021.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – PRESENTATION OF NAVIGATION-RELATED INFORMATION ON SHIPBORNE NAVIGATIONAL DISPLAYS – GENERAL REQUIREMENTS, METHODS OF TESTING AND REQUIRED TEST RESULTS

1 Scope

This document specifies the general requirements, methods of testing, and required test results, for the presentation of navigation-related information on shipborne navigational displays in support of IMO resolutions MSC.191(79) as amended by MSC.466(101) in June 2019, and where applicable MSC.302(87).

This document also supports the guidelines included in the related IMO Circulars MSC.1/Circ.1609 on the standardization of user interface design for navigation equipment and SN.1/Circ.243 as revised in June 2019 on the presentation of navigation related symbols, terms and abbreviations.

This document also specifies the presentation of AIS data reports and the AIS Application Specific Messages defined for international use in IMO SN.1/Circ.289 and intended to be received by a ship for display onboard.

NOTE All text in this document whose wording is identical to text contained in an IMO document is printed in *italics*. Reference to the document is noted at the beginning of the paragraph. The notation contains a prefix referring to the document and a suffix with the paragraph number from the document (for example, (MSC191/1); (SN243/1), etc.).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945:2002, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61174, *Maritime navigation and radiocommunication equipment and systems – Electronic chart display and information system (ECDIS) – Operational and performance requirements, methods of testing and required test results*

IEC 61966-4, *Multimedia systems and equipment – Colour measurement and management – Part 4: Equipment using liquid crystal display panels*

IEC 62388, *Maritime navigation and radiocommunication equipment and systems – Shipborne radar – Performance requirements, methods of testing and required test results*

IEC 62923-1, *Maritime navigation and radiocommunication equipment and systems – Bridge alert management – Part 1: Operational and performance requirements, methods of testing and required test results*

IHO S-52, *Specifications for chart content and display aspects of ECDIS*

IMO, *Seafarers' Training, Certification and Watchkeeping Code (STCW Code)*

IMO A.694(17):1991, *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO MSC.191(79):2004, *Performance standards for the presentation of navigation related information on shipborne navigational displays*

IMO MSC.192(79):2004, *Performance standards for radar equipment*

IMO MSC.232(82):2006, *Revised performance standards for electronic chart display and information systems (ECDIS)*

IMO SN.1/Circ.243/Rev.2:2019+Corr.1, *Guidelines for the presentation of navigation related symbols, terms and abbreviations*

IMO SN.1/Circ.289:2010, *Guidance on the use of AIS application-specific messages*

IMO MSC.302(87):2010, *Performance standards for bridge alert management (BAM)*

IMO MSC.1/Circ.1609:2019, *Guidelines for the standardization of user interface design for navigation equipment*

IMO A.1021(26):2009, *Code on Alerts and Indications*

VESA-2001-6, *Flat Panel Display Measurements* (*FPDM*)