IEC 62391-2

Edition 2.0 2025-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Fixed electric double-layer capacitors for use in electric and electronic equipment –
Part 2: Sectional specification – Electric double-layer capacitors for power application

Condensateurs électriques fixes à double couche utilisés dans les équipements électriques et électroniques –
Partie 2: Spécification intermédiaire – Condensateurs électriques à double couche pour application de puissance



IEC 62391-2:2025-02(en-fr)



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2025 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC
La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC
Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC - webstore.iec.ch/advsearchform
La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, …). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished
Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc
Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications, symboles graphiques et le glossaire. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org
Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 500 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 25 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

IEC 62391-2

Edition 2.0 2025-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Fixed electric double-layer capacitors for use in electric and electronic equipment – Part 2: Sectional specification – Electric double-layer capacitors for power application

Condensateurs électriques fixes à double couche utilisés dans les équipements électriques et électroniques – Partie 2: Spécification intermédiaire – Condensateurs électriques à double couche pour application de puissance

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 31.060.10

ISBN 978-2-8327-0153-9

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

® Registered trademark of the International Electrotechnical Commission
Marque déposée de la Commission Electrotechnique Internationale

CONTENTS

FOREWORD 5
1 Scope 7
2 Normative references 7
3 Terms and definitions 8
4 Preferred ratings and characteristics 8
4.1 Preferred characteristics 8
4.2 Preferred values of ratings 9
4.2.1 Nominal capacitance (C_N) 9
4.2.2 Tolerance on nominal capacitance 9
4.2.3 Rated voltage (U_R) 9
4.2.4 Rated temperature 9
4.2.5 Internal resistance 9
5 Test and measurement procedures, and performance requirements 9
5.1 General 9
5.2 Preliminary drying 9
5.3 Test conditions and measurement conditions 9
5.4 Visual examination and check of dimensions 10
5.4.1 General 10
5.4.2 Visual examination 10
5.4.3 Requirements 10
5.5 Electrical tests 10
5.5.1 Capacitance 10
5.5.2 Internal resistance 10
5.5.3 Leakage current 11
5.6 Robustness of terminations 11
5.6.1 General 11
5.6.2 Initial measurement 11
5.6.3 Final inspection, measurements and requirements 11
5.7 Resistance to soldering heat 11
5.7.1 General 11
5.7.2 Initial measurement 11
5.7.3 Conditions 12
5.7.4 Final inspection, measurements and requirements 12
5.8 Solderability 12
5.8.1 General 12
5.8.2 Final inspection, measurements and requirements 12
5.9 Rapid change of temperature 12
5.9.1 General 12
5.9.2 Initial measurement 12
5.9.3 Conditioning 12
5.9.4 Final inspection, measurements and requirements 12
5.10 Vibration 13
5.10.1 General 13
5.10.2 Initial measurement 13
5.10.3 Test conditions 13
5.10.4 Final inspection, measurements and requirements 13

5.11 Maintain voltage 13
5.11.1 General 13
5.11.2 Test conditions 13
5.11.3 Final inspection, measurements and requirements 13
5.12 Storage at high temperature 13
5.12.1 General 13
5.12.2 Initial measurement 13
5.12.3 Test conditions 14
5.12.4 Final inspection, measurements and requirements 14
5.13 Damp heat, steady state 14
5.13.1 General 14
5.13.2 Initial measurement 14
5.13.3 Conditioning of test 14
5.13.4 Final inspection, measurements and requirements 14
5.14 Endurance 14
5.14.1 General 14
5.14.2 Initial measurement 14
5.14.3 Test conditions 14
5.14.4 Final inspection, measurements and requirements 14
5.15 Characteristics at high and low temperature 15
5.15.1 General 15
5.15.2 Measurements and requirements 15
5.16 Passive flammability (if applicable) 15
5.16.1 General 15
5.16.2 Requirements 15
5.17 Pressure relief (if applicable) 15
5.17.1 General 15
5.17.2 Requirements 15
6 Marking 15
6.1 General 15
6.2 Information for marking 15
6.3 Marking on the capacitors 16
6.4 Marking of the packaging 16
6.5 Additional marking 16
7 Information to be given in a detail specification 16
7.1 General 16
7.2 Outline drawing and dimensions 16
7.3 Mounting 17
7.4 Rating and characteristics 17
7.4.1 General 17
7.4.2 Nominal capacitance range 17
7.4.3 Particular characteristics 17
7.4.4 Soldering 17
7.5 Marking 17
8 Quality assessment procedures 17
8.1 Primary stage of manufacture 17
8.2 Structurally similar components 17
8.3 Certified test records of released lots 17
8.4 Qualification approval procedures 18

8.4.1 General 18
8.4.2 Qualification approval on the basis of the fixed sample size procedures 18
8.5 Quality conformance inspection 23
8.5.1 Formation of inspection lots 23
8.5.2 Test schedule 23
8.5.3 Delayed delivery 23
8.5.4 Assessment levels 23
Annex A (informative) Calculation procedure for power density 25
A.1 General 25
A.2 Calculation procedure for power density 25
A.2.1 Calculation method of power density per mass 25
A.2.2 Calculation method of power density per volume 25
Annex X (informative) Cross-references to IEC 62391-2:2006 27
Bibliography 28

Figure A.1 – Voltage characteristics between capacitor terminals 26

Table 1 – Fixed sample size test plan for qualification approval – Assessment level EZ 19
Table 2 – Test schedule for qualification approval 20
Table 3 – Lot-by-lot inspection 24
Table 4 – Periodic test 24
Table X.1 – Cross-references to the previous edition 27

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

FIXED ELECTRIC DOUBLE-LAYER CAPACITORS FOR USE IN ELECTRIC AND ELECTRONIC EQUIPMENT –

Part 2: Sectional specification – Electric double-layer capacitors for power application

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62391-2 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment. It is an International Standard.

This International Standard is to be used in conjunction with IEC 62391-1:2022.

This second edition cancels and replaces the first edition published in 2006. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) the document has been completely restructured to comply with the ISO/IEC Directives, Part 2;

b) introduction of a new technical categorization for the test methods;

c) reorganization of the test methods according to these new categories;

d) revision of the tables, figures and references according to changes.

The text of this International Standard is based on the following documents:

Draft	Report on voting
40/3193/FDIS	40/3199/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 62391 series, published under the general title *Fixed electric double-layer capacitors for use in electric and electronic equipment*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

FIXED ELECTRIC DOUBLE-LAYER CAPACITORS FOR USE IN ELECTRIC AND ELECTRONIC EQUIPMENT –

Part 2: Sectional specification – Electric double-layer capacitors for power application

1 Scope

This part of IEC 62391 applies to electric double-layer capacitors for power application.

Electric double-layer capacitors for power are intended for applications that require discharge currents in the range from mA to A. The characteristics of the capacitors include such performance as relatively high capacitance and low internal resistance, which is applicable to Class 3 and Class 5 of the measurement classification specified in IEC 62391-1:2022.

The object of this document is to specify preferred ratings and characteristics and to select from IEC 62391-1:2022 the appropriate quality assessment procedures, tests and measuring methods and to give general performance requirements for this type of capacitor. Test severities and requirements specified in detail specifications referring to this document provide specific test severities and requirements of an equal or higher performance level.

The definition of power density and its calculating procedure can be found in Annex A.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-6:2007, *Environmental testing – Part 2-6: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60068-2-14:2023, *Environmental testing – Part 2-14: Tests – Test N: Change of temperature*

IEC 60068-2-20:2021, *Environmental testing – Part 2-20: Tests – Test Ta and Tb: Test methods for solderability and resistance to soldering heat of devices with leads*

IEC 60417, *Graphical symbols for use on equipment,* available at http://www.graphical-symbols.info/equipment

IEC 61193-2:2007, *Quality assessment systems – Part 2: Selection and use of sampling plans for inspection of electronic components and packages*

IEC 62391-1:2022, *Fixed electric double-layer capacitors for use in electric and electronic equipment – Part 1: Generic specification*

IEC 62391-2-1:2006, *Fixed electric double-layer capacitors for use in electronic equipment – Part 2-1: Blank detail specification – Electric double-layer capacitors for power application – Assessment level EZ*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62391-1 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1
surface mount capacitor
capacitor whose small dimensions and nature or shape of terminations make it suitable for surface mounting

3.2
electric double-layer capacitor for power application
capacitor with relatively high capacitance and low internal resistance characteristics

Note 1 to entry: Capacitors are intended for applications that require discharge currents in the range from milliamps to amps and are applicable to Class 3 and Class 5 of the measurement classification specified in IEC 62391-1:2022.

3.3
power density
P_d
electric power that can be taken out per mass (W/kg) or volume (W/l) of a capacitor

Note 1 to entry: Refer to Annex A.

Note 2 to entry: The higher the power density is, the higher the current can be taken efficiently.

4 Preferred ratings and characteristics

4.1 Preferred characteristics

The values given in the detail specification should be selected from the following:

The surface mount capacitors covered by this document are classified into climatic categories in accordance with the general rules given in IEC 60068-1:2013, Annex A.

The lower and upper category temperatures and the duration of the damp-heat, steady-state test shall be chosen from the following unless otherwise agreed between the manufacturer and the customer.

Lower category temperature:	−25 °C or −40 °C
Upper category temperature:	+60 °C or +70 °C
Duration of the damp-heat, steady-state test:	10 days

The severities of the cold and dry heat tests are the lower and upper category temperatures respectively.

For the damp-heat steady-state test, the atmospheric conditions shall be as follows:

- temperature: 40 °C ± 2 °C;
- relative humidity: 93 % ± 3 %.

4.2 Preferred values of ratings

4.2.1 Nominal capacitance (C_N)

The nominal capacitance shall be expressed in farads (F) and agreed between the manufacturer and the customer. Preferred values of rated capacitance are the values from the E24 series of IEC 60063 and their decimal multiples.

4.2.2 Tolerance on nominal capacitance

The preferred values of tolerance on nominal capacitance are:

±20 % or −20 % / +80 %.

4.2.3 Rated voltage (U_R)

The rated voltage shall be as agreed between the manufacturer and the customer. The preferred values of the rated direct voltages are the values of the R20 series of ISO 3 and their decimal multiples.

4.2.4 Rated temperature

The rated temperature value is 60 °C or 70 °C, unless otherwise agreed between the manufacturer and the customer.

4.2.5 Internal resistance

The internal resistance shall be as agreed between the manufacturer and the customer. The internal resistance shall be measured with the DC resistance method. However, if a coefficient can be obtained from both DC and AC resistance methods, the AC resistance method may be used for measurement.

5 Test and measurement procedures, and performance requirements

5.1 General

Test severities and requirements specified in detail specifications and referring to this document are of equal or higher performance level, because lower performance levels are not permitted.

This clause supplements information given in IEC 62391-1:2022, Clause 5 to Clause 10.

5.2 Preliminary drying

If specified in the detail specification, the conditions shall be as given in IEC 62391-1:2022, 5.3.

5.3 Test conditions and measurement conditions

Test conditions: IEC 62391-1:2022, 5.2.1 applies.

Measurement conditions: IEC 62391-1:2022, 5.2.2 applies.

5.4 Visual examination and check of dimensions

5.4.1 General

IEC 62391-1:2022, 7.1, applies with the following details.

5.4.2 Visual examination

A visual examination shall be carried out with suitable equipment with approximately 10× magnification and lighting appropriate to the specimen under test and the quality level required.

The operator should have available facilities for incident or transmitted illumination as well as an appropriate measuring facility.

5.4.3 Requirements

The capacitors shall be examined to verify that the materials, design, construction, physical dimensions and workmanship are in accordance with the applicable requirements given in the detail specification.

5.5 Electrical tests

5.5.1 Capacitance

5.5.1.1 General

IEC 62391-1:2022, 6.1, applies with the following details:

5.5.1.2 Measurement conditions

The ambient temperature shall be 20 °C ± 2 °C.

The measurement shall be made under the conditions specified in IEC 62391-1:2022, 6.1.3.3.

5.5.1.3 Requirements

The capacitance shall correspond with the rated value taking into account the specified tolerance.

5.5.2 Internal resistance

5.5.2.1 General

IEC 62391-1:2022, 6.1, applies with the following details.

The AC resistance method may be used when a correlation is found with the results of the DC measurement method. The measurement method should be in accordance with IEC 62391-1:2022, 6.2.2.

5.5.2.2 Measurement conditions

The ambient temperature shall be 20 °C ± 2 °C.

The measurement shall be made under the conditions specified in IEC 62391-1:2022, 6.1.3.3.

5.5.2.3 Requirements

The internal resistance shall meet the requirements of the detail specification.

5.5.3 Leakage current

5.5.3.1 General

IEC 62391-1:2022, 6.3, applies with the following details.

5.5.3.2 Measurement conditions

The ambient temperature shall be 20 °C ± 2 °C.

The rated voltage shall be applied across the capacitor and its protective resistor.

The protective resistor shall have a value of 1 000 Ω or less.

The discharge time before the test shall be at least 12 h, unless otherwise agreed between the manufacturer and the customer.

The electrification time shall be 24 h unless otherwise agreed between the manufacturer and the customer.

5.5.3.3 Requirements

The leakage current (at 20 °C ± 2 °C) shall meet the requirements of the detail specification.

5.6 Robustness of terminations

5.6.1 General

IEC 62391-1:2022, 7.2, applies with the following details.

The detail specification shall specify the test method and degree of severity to be used.

5.6.2 Initial measurement

The capacitance shall be measured in accordance with 5.5.1.

5.6.3 Final inspection, measurements and requirements

The capacitors shall be visually examined and shall meet the requirements shown in Table 2.

5.7 Resistance to soldering heat

5.7.1 General

IEC 62391-1:2022, 9.1, applies with the following details.

NOTE Not applicable to capacitors with screw terminations or other terminations not designed to be soldered, as stated in the detail specification.

5.7.2 Initial measurement

The capacitance shall be measured in accordance with 5.5.1.

5.7.3 Conditions

No pre-drying.

The capacitors shall be tested in accordance with IEC 60068-2-20:2021, 5.2, method 1 of Test Tb.

Immersion time shall be 5 s ± 0,5 s.

5.7.4 Final inspection, measurements and requirements

The capacitors shall be visually examined, electrically measured and shall meet the requirements shown in Table 2.

5.8 Solderability

5.8.1 General

IEC 62391-1:2022, 9.2, applies with the following details.

NOTE Not applicable to capacitors with screw terminations or other terminations not designed to be soldered, as stated in the detail specification.

5.8.2 Final inspection, measurements and requirements

The capacitors shall be visually examined and shall meet the requirements shown in Table 2.

5.9 Rapid change of temperature

5.9.1 General

IEC 62391-1:2022, 8.1, applies with the following details.

5.9.2 Initial measurement

The capacitance shall be measured in accordance with 5.5.1.

5.9.3 Conditioning

The capacitance shall be tested in accordance with IEC 60068-2-14:2023, Clause 7, test Na for 5 cycles.

The exposure time at each temperature limit shall be 30 min to 3 h as specified in the detail specification.

The recovery period shall be 16 h.

5.9.4 Final inspection, measurements and requirements

After recovery, the capacitors shall be visually examined, electrically measured and shall meet the requirements shown in Table 2.