IEC 62620

Edition 1.1 2023-05
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

Secondary cells and batteries containing alkaline or other non-acid electrolytes – Secondary lithium cells and batteries for use in industrial applications

Accumulateurs alcalins et autres accumulateurs à électrolyte non acide – Eléments et batteries d'accumulateurs au lithium pour utilisation dans les applications industrielles



IEC 62620:2014-11+AMD1:2023-05 CSV(en-fr)



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC
La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC
Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC - webstore.iec.ch/advsearchform
La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, …). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished
Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc
Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org
Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 300 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 19 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

IEC 62620

Edition 1.1 2023-05
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

Secondary cells and batteries containing alkaline or other non-acid electrolytes – Secondary lithium cells and batteries for use in industrial applications

Accumulateurs alcalins et autres accumulateurs à électrolyte non acide – Eléments et batteries d'accumulateurs au lithium pour utilisation dans les applications industrielles

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.220.30

ISBN 978-2-8322-7030-1

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

® Registered trademark of the International Electrotechnical Commission
Marque déposée de la Commission Electrotechnique Internationale

IEC 62620

Edition 1.1 2023-05
CONSOLIDATED VERSION

REDLINE VERSION

VERSION REDLINE

colour inside

Secondary cells and batteries containing alkaline or other non-acid electrolytes – Secondary lithium cells and batteries for use in industrial applications

Accumulateurs alcalins et autres accumulateurs à électrolyte non acide – Eléments et batteries d'accumulateurs au lithium pour utilisation dans les applications industrielles



IEC 62620:2014-11+AMD1:2023-05 CSV(en-fr)

CONTENTS

FOREWORD 4
1 Scope 6
2 Normative references 6
3 Terms and definitions 6
4 Parameters measurement tolerances 8
5 Marking and designation 8
5.1 Marking 8
5.2 Cell designation 10
5.3 Battery designation 12
5.3.1 General 12
5.3.2 Battery structure formulation 13
5.4 Cell or battery termination 13
6 Electrical tests 13
6.1 General 13
6.2 Charging procedure for test purposes 14
6.3 Discharge performance 14
6.3.1 Discharge performance at +25 °C 14
6.3.2 Discharge performance at low temperature 15
6.3.3 High rate permissible current 15
6.4 Charge (capacity) retention and recovery 16
6.4.1 General 16
6.4.2 Test method 16
6.4.3 Acceptance criterion 16
6.5 Cell and battery internal resistance 17
6.5.1 General 17
6.5.2 Measurement of the internal a.c. resistance 17
6.5.3 Measurement of the internal d.c. resistance 17
6.6 Endurance 18
6.6.1 Endurance in cycles 18
6.6.2 Endurance in storage at constant voltage (permanent charge life) 19
7 Type test conditions 20
7.1 General 20
7.2 Sample size 20
7.3 Conditions for type approval 21
7.3.1 Dimensions 21
7.3.2 Electrical tests 22
Annex A (informative) Battery structure information 23
A.1 Example 1 23
A.2 Example 2 23
A.3 Example 3 23
A.4 Example 4 23
A.5 Example 5 24
A.6 Example 6 24
A.7 Example 7 25
A.8 Example 8 25
A.9 Example 9 26

Bibliography 27

Figure 1 – Test sequence 21
Figure A.1 – Structure 3S 23
Figure A.2 – Structure 2P 23
Figure A.3 – Structure 3S2P 23
Figure A.4 – Structure 2P4S 24
Figure A.5 – Structure 2P4S3P 24
Figure A.6 – Structure (2P4S)3P 25
Figure A.7 – Structure (3S2P)3P 25
Figure A.8 – Structure (5S)4S 26
Figure A.9 – Structure ((3S2P)3P)2S 26

Table 1 – Marking 10
Table 2 – Discharge performance at +25 °C ± 5 °C 14
Table 3 – Discharge performance at low temperature 15
Table 4 – Discharge current values for high rate permissible test 16
Table 5 – Constant discharge current used for measurement of the internal d.c. resistance 18
Table 6 – Type test 20
Table 7 – Severe conditions 22

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

SECONDARY CELLS AND BATTERIES CONTAINING ALKALINE OR OTHER NON-ACID ELECTROLYTES – SECONDARY LITHIUM CELLS AND BATTERIES FOR USE IN INDUSTRIAL APPLICATIONS

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 62620 edition 1.1 contains the first edition (2014-11) [documents 21A/561/FDIS and 21A/572/RVD] and its amendment 1 (2023-05) [documents 21A/795/CDV and 21A/812/RVC].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 62620 has been prepared by subcommittee 21A: Secondary cells and batteries containing alkaline or other non-acid electrolytes, of IEC technical committee 21: Secondary cells and batteries.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under webstore.iec.ch in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The *'colour inside'* logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

SECONDARY CELLS AND BATTERIES CONTAINING ALKALINE OR OTHER NON-ACID ELECTROLYTES – SECONDARY LITHIUM CELLS AND BATTERIES FOR USE IN INDUSTRIAL APPLICATIONS

1 Scope

This International Standard specifies marking, tests and requirements for lithium secondary cells and batteries used in industrial applications including stationary applications.

When there exists an IEC standard specifying test conditions and requirements for cells used in special applications and which is in conflict with this standard, the former takes precedence. (e.g. IEC 62660 series on road vehicles).

The following are some examples of applications that utilize the cells and batteries under the scope of this standard.

- Stationary applications: telecom, uninterruptible power supplies (UPS), electrical energy storage system, utility switching, emergency power and similar applications.
- Motive applications: fork-lift truck, golf cart, AGV, railway, and marine, excluding road vehicles.

Since this standard covers batteries for various industrial applications, it includes those requirements, which are common and minimum to the various applications.

This standard applies to cells and batteries. If the battery is divided into smaller units, the smaller unit can be tested as the representative of the battery. The manufacturer clearly declares the tested unit. The manufacturer may add functions, which are present in the final battery, to the tested unit.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-482:2004, *International Electrotechnical Vocabulary (IEV) – Part 482: Primary and secondary cells and batteries*

ISO/IEC Guide 51*, Safety aspects – Guidelines for their inclusion in standards*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-482 and ISO/IEC Guide 51 as well as the following apply.

3.1
charge recovery
capacity recovery
capacity that a cell or battery can deliver after the charge following the charge retention test

Note 1 to entry: Charge retention is defined in 3.2.

3.2
charge retention
capacity retention
capacity that a cell or battery can deliver after storage, at a specific temperature, for a specific time without subsequent recharge as a percentage of the rated capacity

3.3
final voltage
end-of-discharge voltage
specified closed circuit voltage at which the discharge of a cell or battery is terminated

3.4
nominal voltage
suitable approximate value of the voltage used to designate or identify a cell or a battery

Note 1 to entry: The cell or battery manufacturer may provide the nominal voltage.

Note 2 to entry: The nominal voltage of a battery of n series connected cells is equal to n times the nominal voltage of a single cell.

[SOURCE: IEC 60050-482:2004, 482-03-31, modified – Addition of Notes 1 and 2 to entry.]

3.5
rated capacity
capacity value of a cell or battery determined under specified conditions and declared by the manufacturer

Note 1 to entry: The rated capacity is the quantity of electricity Cn Ah (ampere-hours) declared by the manufacturer which a single cell or battery can deliver during a n h period when charging, storing and discharging under the conditions specified in 6.3.1. n is 5 for an E, M and H discharge rate type cell or battery. n is 8, 10, 20 or 240 for an S discharge rate type battery.

[SOURCE: IEC 60050-482:2004, 482-03-15, modified – Addition of Note 1 to entry.]

3.6
cell
secondary lithium cell
secondary cell where electrical energy is derived from the insertion/extraction reactions of lithium ions or oxidation/reduction reaction of lithium between the negative electrode and the positive electrode

Note 1 to entry: The cell typically has an electrolyte that consists of a lithium salt and organic solvent compound in liquid, gel or solid form and has a metal or a laminate film casing. It is not ready for use in an application because it is not yet fitted with its final housing, terminal arrangement and electronic control device.

3.7
cell block
group of cells connected together in parallel configuration with or without protective devices (e.g. fuse or PTC) and monitoring circuitry

Note 1 to entry: It is not ready for use in an application because it is not yet fitted with its final housing, terminal arrangement and electronic control device.

3.8
module
group of cells connected together either in a series and/or parallel configuration with or without protective devices (e.g. fuse or PTC) and monitoring circuitry

3.9
battery pack
energy storage device, which is comprised of one or more cells or modules electrically connected

Note 1 to entry: It may incorporate a protective housing and be provided with terminals or other interconnection arrangement. It may include protective devices and control and monitoring, which provides information (e.g. cell voltage) to a battery system.

3.10
battery system
battery
system which incorporates one or more cells, modules or battery packs; it has a battery management system

Note 1 to entry: It may have cooling or heating units.

3.11
battery management system
BMS
electronic system associated with a battery which monitors and/or manages its state, calculates secondary data, reports that data and/or controls its environment to influence the battery's safety, performance and/or service life and has the functions to cut off in case of over charging, over current and over heating

Note 1 to entry: The function of the BMS can be assigned to the battery pack or to equipment that uses the battery.

Note 2 to entry: A BMS is sometimes also referred to as a BMU (battery management unit).

4 Parameters measurement tolerances

The overall accuracy of controlled or measured values, relative to the specified or actual values, shall be within the following tolerances:

a) ±0,5 % for voltage;

b) ±1 % for current;

c) ±2 °C for temperature;

d) ±0,1 % for time;

e) ±1 % for dimensions.

These tolerances comprise the combined accuracy of the measuring instruments, the measurement techniques used, and all other sources of error in the test procedure.

The details of the instrumentation used shall be provided in any report of results.

5 Marking and designation

5.1 Marking

The marking items shown in Table 1 are indicated on the cell, battery system or instruction manual. When marked on the cell or battery system, each cell or battery system that is installed or maintained shall carry clear and durable markings giving the information.

The following options are allowed:

- if there are designations on a battery system, designations are not necessary on the battery pack, module or cell;

- if there are designations on a battery pack, designations are not necessary on the module and cell;
- if there are designations on a module, designations are not necessary on the cell.

However, for a transportable unit (i.e. a unit that is being shipped), it is necessary to provide the marking information on the main transportable unit or in its instruction manual. Furthermore, if there is a marking matter of arrangement between the purchaser and the manufacturer, it shall comply with the agreement.

See Table 1.

Each cell or battery that is installed or maintained shall carry clear and durable markings giving the following information:

- secondary (rechargeable) Li or Li-ion;
- polarity (can be deleted if there is an agreement between cell and pack manufacturer);
- date of manufacture (which may be in code);
- name or identification of manufacturer or supplier;
- rated capacity;
- nominal voltage;
- appropriate caution statement.

The model name and manufacturing traceability shall be marked on the cell and battery surface. The other items listed above can be marked on the smallest package or supplied with the cell or the battery.

The following information shall be marked on or supplied with the cell or the battery:

- disposal instructions;
- recommended charge instructions.

The following information shall be marked on the cell or when there is no marking place on the cell, it shall be marked in the manual.

- cell designation as specified in 5.2.