IEC 62629-52-1

Edition 1.0 2024-01

INTERNATIONAL STANDARD

colour inside

3D displays –
Part 52-1: Fundamental measurement methods of aerial display – Optical



IEC 62629-52-1:2024-01 (en)



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC 62629-52-1

Edition 1.0 2024-01

INTERNATIONAL STANDARD

colour inside

3D displays –
Part 52-1: Fundamental measurement methods of aerial display – Optical

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.120; 31.260

ISBN 978-2-8322-8174-1

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 4
1 Scope 6
2 Normative references 6
3 Terms, definitions, abbreviated terms and letter symbols 6
3.1 Terms and definitions 6
3.2 Abbreviated terms 7
3.3 Letter symbols (quantity symbols and units) 8
4 Standard measurement conditions 8
4.1 Standard environmental conditions 8
4.2 Power supply 8
4.3 Warm-up time 8
4.4 Darkroom condition 8
5 Measurement systems 9
5.1 Measurement equipment 9
5.1.1 Goniometer 9
5.1.2 Light measuring device (LMD) 9
5.2 Test patterns 10
5.2.1 General 10
5.2.2 Geometrical test pattern 10
5.2.3 Solid colour patterns 11
5.3 Measuring points 11
5.4 Standard coordinate system 11
6 Measurement methods for optical characteristics 14
6.1 General 14
6.2 Preparations 15
6.3 Position and size of aerial image area and floating distance 15
6.3.1 General 15
6.3.2 Measurement procedure 15
6.3.3 Calculation 15
6.3.4 Report 16
6.4 Luminance and luminance non-uniformity 17
6.4.1 General 17
6.4.2 Measurement procedure 17
6.4.3 Calculation 18
6.4.4 Report 18
6.5 Contrast ratio 19
6.5.1 General 19
6.5.2 Measurement procedure 19
6.5.3 Calculation 20
6.5.4 Report 20
6.6 Chromaticity and white chromaticity 20
6.6.1 General 20
6.6.2 Measuring procedures 20
6.6.3 Calculation 21
6.6.4 Reports 21

6.7 Image luminance variation within the design viewing space 21
6.7.1 General 21
6.7.2 Measurement procedure 21
6.7.3 Calculation 22
6.7.4 Report 22
Bibliography 24

Figure 1 – Geometrical test pattern with vertical, horizontal and diagonal lines 10
Figure 2 – Measuring points for the centre and multi-point measurement 11
Figure 3 – Relation between the spherical coordinate system and the Cartesian coordinate system 12
Figure 4 – Definition of floating distance and end points of design viewing space of aerial display 14
Figure 5 – Measuring the aerial image positions 17

Table 1 – Letter symbols (quantity symbols and units) 8
Table 2 – Example of measurement results of luminance and luminance non-uniformity 19
Table 3 – Example of measurement results of luminance and luminance non-uniformity within the design viewing space 23

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

3D DISPLAYS –

Part 52-1: Fundamental measurement methods of aerial display – Optical

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62629-52-1 has been prepared by IEC technical committee 110: Electronic displays. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
110/1593/FDIS	110/1616/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 62629 series, published under the general title *3D displays*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

3D DISPLAYS –

Part 52-1: Fundamental measurement methods of aerial display – Optical

1 Scope

This part of IEC 62629 specifies the standard measurement methods and measurement conditions for determining the optical properties of aerial displays. This document excludes image quality of aerial displays, such as modulation transfer function (MTF) and resolution measurements.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62629-1-2:2021, *3D display devices – Part 1-2: Generic – Terminology and letter symbols*

ISO/CIE 19476, *Characterization of the performance of illuminance meters and luminance meters*

3 Terms, definitions, abbreviated terms and letter symbols

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in 62629-1-2 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1.1
aerial display
display that forms a real image in mid-air by use of an incoherent light-source and a passive optical component to converge diverging light from the light-source

Note 1 to entry: Details of aerial display, including the principles and typical optical components to form a real image, are given in IEC TR 62629-51-1 [1].

[SOURCE: IEC 62629-1-2:2021, 3.1.20, modified – in the definition, the term "display" is removed from the light source description because the light source is not limited to display, and Note 1 has been expanded.]

3.1.2
aerial image area
two-dimensional area in mid-air where the aerial display exhibits information via electrically generated images

3.1.3
design viewing space
three-dimensional space within which the user places both eyes and can see the entire aerial image area

Note 1 to entry: Unlike the eye box of the eyewear display, the design viewing space of the aerial display usually has no upper limit in the viewing distance; the width and height are quite larger than the interpupillary distance. Both eyes of the viewer in the design viewing space will see the entire aerial image area meet a specified performance metric.

3.1.4
design viewing position
design location at which the midpoint of both eyes is placed to achieve the optimal performance when using an aerial display

Note 1 to entry: The design viewing position is not limited to the front centre of the aerial image area.

3.1.5
hardware reference point
design location on the aerial display hardware that is used for the origin of the coordinates

Note 1 to entry: The hardware reference point serves as the origin location of the measurement.

Note 2 to entry: The design viewing position is located along the line from the hardware reference point to the centre of the aerial image area.

3.1.6
floating distance
distance from the centre of the aerial image area to the hardware reference point

3.1.7
design viewing distance
<aerial display> distance from the design viewing position to the centre of the aerial image area

Note 1 to entry: The summation of the design viewing distance and the floating distance becomes the distance between the hardware reference point and the design viewing position.

3.2 Abbreviated terms

AIA aerial image area
CCD charge-coupled device
DUT device under test
DVP design viewing position
DVS design viewing space
HRP hardware reference point
LMD light measuring device
MTF modulation transfer function

3.3 Letter symbols (quantity symbols and units)

The letter symbols for aerial displays are shown in Table 1.

Table 1 – Letter symbols (quantity symbols and units)

Quantities	Symbols	Units
Measuring point (i = 0: centre)	P_i	
Luminance	L_v	cd/m^2
Maximum luminance	L_{max}	cd/m^2
Minimum luminance	L_{min}	cd/m^2
Average luminance (spatial)	L_{va}	cd/m^2
Luminance non-uniformity	NU	
Contrast ratio	CR	

4 Standard measurement conditions

4.1 Standard environmental conditions

Unless otherwise specified, all tests and measurements for aerial displays shall be carried out after sufficient warm-up time for the illumination sources and DUT (see 4.3), under the standard environmental conditions as follows:

– temperature 25 °C ± 3 °C,
– relative humidity 25 % to 85 %, and
– atmospheric pressure 86 kPa to 106 kPa.

When different environmental conditions are used, they shall be noted in the report.

4.2 Power supply

In order to stabilize the performances of the DUT, the power supply for driving the DUT shall be adjusted in accordance with the specification of the DUT.

NOTE When the DUT is driven by the battery, it is less susceptible to power supply fluctuations.

4.3 Warm-up time

The optical performances of the DUT can be affected by the temperature. It takes a certain time for the luminance output of the DUT to achieve a steady state. If the luminance output is not within ±3 % variation, it shall be reported. All measuring conditions shall be kept constant during the measurements.

NOTE If the measuring result does not become steady state, it might be influenced by the output fluctuation of the DUT or fluctuation of the LMD such as noise, or both.

4.4 Darkroom condition

The luminance contribution from the background in the test room reflected off the measurement space shall be less than 1/20 of minimum luminance output from the DUT. If the condition is not satisfied, then background subtraction is required, and it shall be noted in the report.