IEC 62885-2

Edition 3.0 2026-07

INTERNATIONAL STANDARD

COMMENTED VERSION

Surface cleaning appliances -
Part 2: Dry vacuum cleaners for household or similar use - Methods for measuring the performance

ICS 97.080

ISBN 978-2-8327-1389-1

IEC 62885-2:2026-07 CMV(en)

THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD 7
1 Scope 9
2 Normative references 9
3 Terms and definitions 10
4 General conditions for testing 13
4.1 Atmospheric conditions 13
4.2 Test equipment and materials 14
4.2.1 General 14
4.2.2 Pile direction 14
4.3 Voltage and frequency 14
4.4 Running-in of dry vacuum cleaner 14
4.5 Equipment of the dry vacuum cleaner 15
4.6 Operation of the dry vacuum cleaner 15
4.6.1 General 15
4.6.2 Operation of water filter vacuum cleaners, additional requirements 16
4.7 Conditioning prior to each test 17
4.8 Mechanical operator 17
4.9 Number of samples 17
4.10 Carpets for testing 17
4.11 Stroke length and test area 18
4.12 Stroke speed 18
5 Dry vacuum cleaning test 19
5.1 Dust removal from hard flat floors 19
5.1.1 Test equipment 19
5.1.2 Test area and stroke length 19
5.1.3 Removal of remaining dust 19
5.1.4 Distribution of test dust 19
5.1.5 Preconditioning of dust receptacle 19
5.1.6 Determination of dust removal ability 19
5.2 Dust removal from hard floors with crevices 20
5.2.1 General 20
5.2.2 Test surface and crevice 21
5.2.3 Distribution of test dust 21
5.2.4 Determination of dust removal ability 21
5.3 Debris removal from hard floors 22
5.3.1 Test equipment 22
5.3.2 Test surface 22
5.3.3 Distribution of debris 22
5.3.4 Determination of debris removal ability 23
5.4 Dust removal from carpets 24
5.4.1 General 24
5.4.2 Test carpet and equipment 24
5.4.3 Test area and stroke length 24
5.4.4 Conditioning of test carpet 24
5.4.5 Distribution of test dust 25
5.4.6 Embedding of dust into carpet 25
5.4.7 Preconditioning of dust receptacle 25

5.4.8 Determination of dust removal ability 25
5.5 Debris removal from carpet 27
5.5.1 Test equipment 27
5.5.2 Distribution of debris 27
5.5.3 Determination of debris removal ability 27
5.6 Dust removal along walls 29
5.6.1 Test equipment and materials 29
5.6.2 Distribution of test dust 29
5.6.3 Determination of dust removal ability along walls 29
5.7 Fibre removal from carpets 30
5.7.1 General 30
5.7.2 Test carpet 30
5.7.3 Distribution of fibres 30
5.7.4 Determination of fibre removal ability from carpets 31
5.8 Fibre removal from upholstery 33
5.8.1 General 33
5.8.2 Test cushion 33
5.8.3 Distribution of fibres 33
5.8.4 Determination of fibre removal ability from upholstery 34
5.9 Thread removal from carpets 35
5.9.1 Test carpet 35
5.9.2 Distribution of threads 35
5.9.3 Determination of thread removal ability 36
5.10 Maximum usable volume of the dust receptacle 36
5.10.1 General 36
5.10.2 Conditions for test 36
5.10.3 Introduction of moulding granules 37
5.10.4 Determination of maximum usable volume of dust receptacle 37
5.11 Air data 38
5.11.1 ~~Purpose~~General 38
5.11.2 Test conditions 38
5.11.3 Test equipment and apparatus 38
5.11.4 Test procedure 39
5.11.5 Reporting 43
5.12 Performance with loaded dust receptacle 43
5.12.1 ~~Purpose~~General 43
5.12.2 Determination of suction pressure change with loaded dust receptacle 44
5.12.3 Throttling to simulate loaded dust receptacle 46
5.12.4 Determination of performance with loaded dust receptacle 46
5.13 Total emissions while vacuum cleaning 46
5.13.1 ~~Purpose~~General 46
5.13.2 Test conditions 47
5.13.3 Test equipment 47
5.13.4 Test carpet 47
5.13.5 Test chamber setup and conditioning 47
5.13.6 Test sample and material setup 47
5.13.7 Positioning the test (unit) 47
5.13.8 Test procedure 48
5.13.9 Reporting 48

5.14 Dust re-emission and fractional filtration efficiency of the dry vacuum cleaner 48
5.14.1 General 48
5.14.2 Test conditions 49
5.14.3 Determining the test dust quantity 49
5.14.4 Dust re-emission for the entire range of particle size 49
5.14.5 Fractional filtration efficiency 55
6 Miscellaneous tests 58
6.1 General 58
6.2 Motion resistance 58
6.2.1 Purpose 58
6.2.2 Test carpet, hard floor surface, and test equipment 58
6.2.3 Determination of motion resistance 58
6.3 Cleaning under furniture 59
6.3.1 Purpose 59
6.3.2 Distribution of test dust 59
6.3.3 Determination of free furniture height 59
6.4 Radius of operation 59
6.4.1 Purpose 59
6.4.2 Conditions for measurement 60
6.4.3 Determination of radius of operation 60
6.5 Impact resistance for detachable cleaning heads 60
6.5.1 Purpose 60
6.5.2 Test equipment 60
6.5.3 Determination of impact resistance 60
6.6 Deformation of hose and connecting tubes 60
6.6.1 Purpose 60
6.6.2 Test equipment 60
6.6.3 Determination of permanent deformation 61
6.7 Bump test 61
6.7.1 Purpose 61
6.7.2 Test equipment 61
6.7.3 Test cycle 63
6.7.4 Test procedure 63
6.8 Flexibility of the hose 63
6.8.1 Purpose 63
6.8.2 Preparation of test object 63
6.8.3 Determination of the flexibility of the hose 64
6.9 Durability of suction hoses 64
6.9.1 Primary hose testing 64
6.9.2 Secondary hose testing 67
6.10 Ability to maintain air flow performance 67
6.10.1 Purpose 67
6.10.2 Test dust 68
6.10.3 Procedure 68
6.11 Mass 68
6.12 Weight in hand 68
6.13 Specific cleaning time 69
6.14 Dimensions 69
6.15 Airborne acoustical noise 69

6.16 Energy consumption 69
6.16.1 General 69
6.16.2 Energy consumption when vacuuming carpets 70
6.16.3 Energy consumption with vacuuming of hard floors and hard floors with crevices 72
6.16.4 Energy consumption of cordless active dry nozzles for use with mains-powered dry vacuum cleaners 73
6.17 Operational motor lifetime test 74
6.17.1 ~~Purpose~~General 74
6.17.2 Procedure 75
7 Test material and equipment 75
7.1 General 75
~~7.2 Material for tests ..... 76~~
7.2 Test carpets 76
7.2.1 General 76
7.2.2 Quantity and size of carpets 76
~~7.2.2 Mineral dust – Type 4 ..... 77~~
~~7.2.3 Fibre material ..... 77~~
~~7.2.4 Thread material ..... 77~~
~~7.2.5 Moulding granules ..... 77~~
~~7.2.6 Test cushion ..... 77~~
~~7.2.7 Debris ..... 77~~
7.3 Equipment for tests 77
7.3.1 Floor test plate 77
~~7.3.2 Test plate with crevice ..... 78~~
~~7.3.3 Carpet beating machine ..... 78~~
~~7.3.4 Hold-downs and guides ..... 78~~
~~7.3.5 Mechanical dust spreader (optional) ..... 78~~
~~7.3.6 Rollers for embedding ..... 78~~
~~7.3.7 Equipment for air data test ..... 78~~
~~7.3.8 Test equipment for determining the fractional filtration efficiency and dust re-emission of the dry vacuum cleaner ..... 79~~
~~7.3.9 Device for motion resistance test ..... 80~~
~~7.3.10 Device for impact test ..... 80~~
~~7.3.11 Device for determination of deformation of hoses and connecting tubes ..... 81~~
~~7.3.12 Mechanical operator ..... 82~~
7.3.2 Weighing machine 95
7.3.3 Total emissions test 95
7.3.4 Dust collection box 96
~~7.3.16 Secondary hose test equipment ..... 96~~
8 Instructions for use 98
Annex A (informative) Information on materials 99
Annex B (informative) Information at the point of sale 100
~~Annex C (informative) Reference vacuum cleaner system RSB ..... 101~~
~~Annex D (informative) Maintenance of the RSB ..... 104~~
~~Annex E (normative) Hard floorboard realization, floor support and floor pattern ..... 105~~
~~Annex F (informative) Maximum operational power ..... 107~~
Annex C (informative) Maximum operational power (Not applicable to cordless dry vacuum cleaners) 111

Annex D (normative) Cordless dry vacuum cleaners for household or similar use - Additional requirements 112
Bibliography 116
List of comments 119

Figure 1 – Right-angled T 29
Figure 2 – Determination of cleaning area 30
Figure 3 – Stencil for distribution of fibres on test carpets 31
Figure 4 – Zigzag stroke pattern 32
Figure 5 – Frame for test cushion 33
Figure 6 – Stencil for distribution of fibres on upholstery 34
Figure 7 – Arrangement of threads in the thread removal test 35
Figure 8 – Stroke length in tests 36
Figure 9 – Air data curves 40
Figure 10 – Connecting tube opening 44
Figure 11 – Test dust for loading dust receptacle 45
Figure 12 – Insertion depth 59
Figure 13 – Position of test object and cross-section for measurement of deformation 61
Figure 14 – Profile of threshold 62
Figure 15 – Arrangements for bump test 62
~~Figure 16 – Preparation of hoses for testing flexibility ..... 65~~
Figure 16 – Configurations of vacuum cleaners with primary or secondary hoses 65
Figure 17 – Interconnecting hose 66
~~Figure 19 – Equipment for repeated bending of hoses ..... 97~~
Figure 18 – Dust collection box 97
~~Figure 20 – Test plate with crevice ..... 98~~
~~Figure 21 – Carpet-beating machine ..... 99~~
~~Figure 22 – Carpet hold-downs and guides ..... 100~~
~~Figure 23 – Dust spreader and roller for embedding dust into carpets ..... 101~~
~~Figure 24 – Alternative A equipment for air data tests ..... 102~~
~~Figure 25 – Measuring box for alternative A ..... 103~~
~~Figure 26 – Alternative B equipment for air data tests ..... 104~~
~~Figure 27 – Test hood ..... 105~~
~~Figure 28 – Intake aerosol channel with sampling probe ..... 106~~
~~Figure 29 – Exhaust channel with sampling probe ..... 107~~
~~Figure 30 – Equipment diagram for filtration / dust re-emission testing ..... 108~~
~~Figure 31 – Modified test hood ..... 109~~
~~Figure 32 – Drum for impact test ..... 110~~
~~Figure 33 – Device for testing deformation of hoses and connecting tubes ..... 111~~
~~Figure 34 – Mechanical operator for the measurement of dust removal from carpets and of motion resistance ..... 112~~
~~Figure 36 – Equipment for durability testing of secondary hoses ..... 113~~
~~Figure C.1 – RSB with passive and active nozzle and vacuum measuring box ..... 114~~
~~Figure E.1 – Dimensions of the floorboard and mounting on a test rig ..... 115~~

~~Figure E.2 – Pattern of hard floor planks~~
Figure D.1 – Air data curves 115

Table 1 – Confidence limits of a Poisson distribution for 95 % confidence range 54
~~Table 2 – Nominal diameters of orifices~~
~~Table 3 – Graduation of eight size classes for particle sizes 0,3 µm to 10 µm~~
Table D.1 – Modifications to the text of this document 112

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

Surface cleaning appliances - Part 2: Dry vacuum cleaners for household or similar use - Methods for measuring the performance

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

This commented version (CMV) of the official standard IEC 62885-2:2026 edition 3.0 allows the user to identify the changes made to the previous IEC 62885-2:2021 edition 2.0. Furthermore, comments from IEC SC 59F experts are provided to explain the reasons of the most relevant changes, or to clarify any part of the content.

A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text. Experts' comments are identified by a blue-background number. Mouse over a number to display a pop-up note with the comment.

This publication contains the CMV and the official standard. The full list of comments is available at the end of the CMV.

IEC 62885-2 has been prepared by subcommittee 59F: Surface cleaning appliances, of IEC technical committee 59: Performance of household and similar electrical appliances. It is an International Standard.

This third edition of IEC 62885-2 cancels and replaces the second edition published in 2021. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) relocation of RSB annexes to IEC TS 62885-1 [1];
b) relocation of remaining test materials, test dust, and equipment to IEC TS 62885-1 [1];
c) reduced number of test strokes from 5 double strokes to 3 double strokes except as specifically required;
d) relocated requirements for cordless products, except for battery-related items, from IEC 62885-4 [2] to a new Annex D;
e) added definition and instructions for a universal dry nozzle;
f) relocated air data equipment to IEC TS 62885-1 [1], relocated formulae to 5.11, and made revisions to air data requirements;
g) relocated dust re-emission equipment to IEC TS 62885-1 [1].

The text of this International Standard is based on the following documents:

Draft	Report on voting
59F/569/FDIS	59F/576/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all the parts in the IEC 62885 series, under the general title *Surface cleaning appliances*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

– reconfirmed,
– withdrawn, or
– revised.

1 Scope

This part of IEC 62885 is applicable for measurements of the performance of mains-operated and cordless dry vacuum cleaners, including water filter vacuum cleaners for household or similar use.

Table D.1 of Annex D is applicable to measurements of the performance of cordless dry vacuum cleaners for household use or under conditions similar to those in households. The results obtained under this annex are intended to be comparable to the results obtained for mains-operated vacuum cleaners. The purpose of Annex D is to specify additional requirements for measurements of cordless dry vacuum cleaners. **1**

NOTE 1 Annex D is not intended for mains-operated vacuum cleaners or cleaning robots.

NOTE 2 Cleaning robots are evaluated to IEC/ASTM 62885-7 [3].

NOTE 3 Handheld dry vacuum cleaners are excluded, except for 5.10.2 and 5.11.

NOTE 4 Measurements of the performance of mains-operated commercial dry vacuum cleaners are found in IEC 62885-8 [4].

The purpose of this document is to specify essential performance characteristics of dry vacuum cleaners which are of interest to users and to describe methods for measuring these characteristics.

NOTE 5 Due to the influence of environmental conditions, variations in time, origin of test materials and proficiency of the operator, some of the described test methods will give more reliable results when applied for comparative testing of a number of appliances at the same time, in the same laboratory and by the same operator.

NOTE 6 The methods here can be applied with modifications for surface-cleaning product types or technologies not currently covered within the scope.

For safety requirements, reference is made to IEC 60335-1:2020 [5] and IEC 60335-2-2 [6].

A recommendation on information for the consumer at the point of sale is given in Annex B.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

~~IEC 60688, *Electrical measuring transducers for converting A.C. and D.C. electrical quantities to analogue or digital signals*~~

IEC 60704-2-1, *Household and similar electrical appliances - Test code for the determination of airborne acoustical noise - Part 2-1: Particular requirements for dry vacuum cleaners*

IEC 62301:2011, *Household electrical appliances - Measurement of standby power*

IEC TS 62885-1:~~2020~~2026, *Surface cleaning appliances - Part 1: General requirements on test material and test equipment*

~~ISO 5167-1, *Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full – Part 1: General principles and* requirements~~

~~ISO 12103-1, *Road vehicles – Test dust for* filter *evaluation* – Part 1: *Arizona test dust*~~

ISO 29463-1, *High efficiency filters and filter media for removing particles in air — Part 1: Classification, performance, testing and marking*

EN 1822-1, *High efficiency air filters (EPA, HEPA, and ULPA) - Part 1: Classification, performance testing, marking.*

IEC 60335-2-2:2019, Household and similar electrical appliances - Safety - Part 2-2: Particular requirements for vacuum cleaners and water-suction cleaning appliances

IEST-RP-CC001, HEPA and ULPA Filters

ISO 29643-1, High efficiency filters and filter media for removing particles in air — Part 1: Classification, performance, testing and marking

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

– IEC Electropedia: available at https://www.electropedia.org/
– ISO Online browsing platform: available at https://www.iso.org/obp

3.1
active depth of the dry 2 cleaning head
distance from the front edge of the dry cleaning head (3.3) to its rear edge or a line 10 mm behind the rear edge of the suction opening on the underside of the dry cleaning head (3.3), whichever is the shortest

3.2
active dry nozzle
dry cleaning head (3.3) provided with a driven agitation device to assist dirt removal

Note 1 to entry: The agitation device can be driven by an incorporated electric motor (motorized nozzle), an incorporated turbine powered by the air flow (air-turbine nozzle), or an incorporated friction or gear mechanism actuated by moving the dry cleaning head (3.3) over the surface to be cleaned (mechanical nozzle).

3.3
dry cleaning head
plain nozzle or brush attached to a connecting tube (3.23), or a power nozzle, separate or part of the cleaner housing, and that part of a dry vacuum cleaner (3.8) which is applied to a surface to be cleaned

3.4
dry cleaning head width
B
external maximum width of the dry cleaning head (3.3), in metres

3.5
cordless active dry nozzle
dry cleaning head (3.3) provided on a mains-operated machine with an agitation device to assist dirt removal driven by a battery-operated motor

3.6
cylinder dry vacuum cleaner
portable dry vacuum cleaner (3.8) having a nozzle separated from the cleaner housing by a hose