IEC PAS 61980-6

Edition 1.0 2025-03

PUBLICLY AVAILABLE SPECIFICATION

Electric vehicle wireless power transfer (WPT) systems – Part 6: Specific requirements for magnetic field dynamic power transfer (MF-D-WPT) system communication and activities

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 43.120; 29.240.99

ISBN 978-2-8327-0323-6

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 7
INTRODUCTION 9
1 Scope 10
2 Normative references 10
3 Terms and definitions 11
4 Abbreviated terms 12
5 General system structure and interoperability concept 12
5.1 System structure 12
5.2 Interoperability concept 13
6 General communication requirements 14
6.1 General 14
6.2 Communication and signalling for power management 14
6.2.1 General 14
6.2.2 Bidirectional wireless communication 14
6.2.3 Unidirectional wireless signalling (P2PS) 15
6.2.4 Bidirectional wireless signalling (P2PS) 15
7 Communication procedure during an MF-D-WPT session 16
7.1 General 16
7.2 Activities 17
7.2.1 Preparation (supply device) 17
7.2.2 Preparation (EV device) 17
7.2.3 Communication setup/Request D-WPT service 17
7.2.4 Compatibility check/Service authentication 18
7.2.5 Pairing 19
7.2.6 Alignment check (lateral direction) 19
7.2.7 Magnetic coupling check 19
7.2.8 Power transfer 19
7.2.9 Inter-inverter segment switching 21
7.2.10 Stand-by 21
7.2.11 Power transfer terminate 22
7.2.12 Terminate D-WPT service session 23
7.2.13 Parameters definition between EV device and supply device 23
7.2.14 Safety monitoring and diagnostics 24
7.2.15 Wake-up after power outage 24
7.3 Exception handling 24
7.3.1 General 24
7.3.2 Exception descriptions 25
7.3.3 Supply device exceptions 27
7.3.4 EV device exceptions 27
Annex A (informative) System architecture 28
A.1 General 28
A.2 One supply power electronics drives multiple primary devices 28
A.2.1 Parallel connection of primary devices 28
A.2.2 P2PS with magnetic coupling check 29
A.3 DC (direct current) power distribution 30

A.4 Corresponding states to each step in passing D-WPT charging area (included sections and segments) 31
Annex B (informative) P2PS sensors 33
B.1 General 33
B.2 Methods 33
B.3 P2PS paring sensors 34
Annex C (informative) Communication of dynamic wireless power transfer for electric vehicles 35
C.1 General overview 35
C.2 Message sequence in the communication for D-WPT 36
C.3 State transitions in the communication for D-WPT 37
C.3.1 State transition diagram at D-SECC (in supply device) 37
C.3.2 State transition diagram at D-EVCC (in EV device) 38
C.3.3 State transition in D-SECC (supply device) 39
C.3.4 State transition in D-EVCC (EV device) 40
Annex D (informative) Communication of dynamic wireless power transfer for electric vehicles 41
D.1 General overview 41
D.2 Communication architecture 41
D.2.1 Overview 41
D.2.2 Infrastructure operation strategy 43
D.3 Detailed communication description 43
D.3.1 Bidirectional communication: vehicle <-> cloud 43
D.3.2 Bidirectional communication: management unit <-> cloud 43
D.3.3 Unidirectional communication: vehicle -> management unit 44
Annex E (informative) Segment switching based on vehicle detection using bidirectional P2PS 45
E.1 General 45
E.2 Vehicle detection 46
E.2.1 General 46
E.2.2 Coupling/decoupling 47
E.3 Segment switching 48
E.3.1 General 48
E.3.2 Group segment switching 48
E.3.3 Group segment switching with superposition 49
E.3.4 Calculating the speed of a vehicle 50
Annex F (informative) Use cases 51
F.1 General 51
F.2 Use case descriptions 51
Annex G (informative) State diagrams of MF-D-WPT process 55
G.1 General 55
G.2 Supply device state definitions 55
G.2.1 Supply device state diagram 55
G.2.2 System On (DWPT_S_ON) 56
G.2.3 Session initiated (DWPT_S_SI) 56
G.2.4 Idle (DWPT_S_IDLE) 56
G.2.5 Power transfer active (DWPT_S_PTA) 56
G.2.6 Power transfer (DWPT_S_PT) 56
G.2.7 Inter-inverter segment switching (DWPT_S_CH) 56

G.2.8 System off (DWPT_S_OFF) 57
G.2.9 Service terminated occupied (DWPT_S_STO) 57
G.2.10 StandBy (DWPT_S_STBY) 57
G.2.11 Sleep (DWPT_S_SLP) 57
G.3 Supply device state transitions 57
G.3.1 General 57
G.3.2 TS_03 and TS_10 58
G.3.3 TS_04 and TS_05 58
G.3.4 TS_06, TS_08 and TS_12 59
G.3.5 TS_07, TS_13 and TS_15 60
G.3.6 TS_11 61
G.3.7 TS_08 62
G.3.8 TS_09 62
G.3.9 TS_16 63
G.3.10 TS_14 64
G.4 Vehicle device state definitions 65
G.4.1 Vehicle device state diagram 65
G.4.2 System off (DWPT_V_OFF) 65
G.4.3 System on (DWPT_V_ON) 65
G.4.4 System initialized (DWPT_V_SI) 65
G.4.5 Sleep (DWPT_V_SLEEP) 66
G.4.6 Power transfer active (DWPT_V_PTA) 66
G.4.7 Power transfer (DWPT_V_PT) 66
G.4.8 Standby (DWPT_V_STBY) 66
G.4.9 System off (DWPT_V_OFF) 67
G.4.10 Inter-inverter segment switching (DWPT_V_CH) 67
G.5 Vehicle device state transitions 67
G.5.1 General 67
G.5.2 TV_03 68
G.5.3 TV_04 and TV_05 69
G.5.4 TV_07 and TV_15 70
G.5.5 TV_08, TV_14 and TV_16 71
G.5.6 TV_09 72
G.5.7 TV_10 72
G.5.8 TV_11 73
G.5.9 TV_17 74
G.5.10 TV_18 74
G.5.11 TV_19 75
Bibliography 76

Figure 1 – Example of an MF-D-WPT system 13
Figure 2 – Chain of activities 17
Figure 3 – Communication system 20
Figure 4 – Example of controlled power transfer trajectory 21
Figure 5 – Classification of system events 25
Figure A.1 – Configuration of primary device parallel connection to supply power electronics 29
Figure A.2 – Configuration of P2PS with coupling check 30

Figure A.3 – Configuration of P2PS with coupling check 31
Figure A.4 – Corresponding states to each step in passing D-WPT charging area 32
Figure B.1 – Example of auxiliary signal transmitters/receivers arrangements for the EV device (left) and the supply device (right) 34
Figure C.1 – Structure of communication in D-WPT 35
Figure C.2 – Message sequence in D-WPT during inter-inverter segment switching 37
Figure C.3 – State transition diagram in D-SECC 38
Figure C.4 – State transition diagram in D-EVCC 39
Figure D.1 – General overview 41
Figure D.2 – Components of the system 42
Figure D.3 – Control strategy of the infrastructure 43
Figure E.1 – Configuration of VD for dynamic WPT 45
Figure E.2 – Example of bidirectional P2PS procedure 47
Figure E.3 – Example of segment switching 48
Figure E.4 – Example of group segment switching 49
Figure E.5 – Example of group segment switching with superposition 49
Figure F.1 – Use cases particularly for dynamic wireless power transfer 51
Figure G.1 – Supply device state diagram 55
Figure G.2 – Transition TS_03 and TS_10 58
Figure G.3 – Transition TS_04 and TS_05 59
Figure G.4 – Transition TS_06, TS_08 and TS_12 60
Figure G.5 – Transition TS_07, TS_13 and TS_15 61
Figure G.6 – Transition TS_11 61
Figure G.7 – Transition TS_08 62
Figure G.8 – Transition TS_09 63
Figure G.9 – Transition TS_16 63
Figure G.10 – Transition TS_14 64
Figure G.11 – Vehicle device state diagram 65
Figure G.12 – Transition TV_03 69
Figure G.13 – Transition TV_04 and TV_05 70
Figure G.14 – Transition TV_07 and TV_15 71
Figure G.15 – Transition TV_08, TV_14 and TV_16 72
Figure G.16 – Transition TV_09 72
Figure G.17 – Transition TV_10 73
Figure G.18 – Transition TV_11 73
Figure G.19 – Transition TV_17 74
Figure G.20 – Transition TV_18 74
Figure G.21 – Transition TV_19 75

Table 1 – Requirement for the communication interface between one SECC and one EVCC 15
Table 2 – Requirement for P2PS system in unidirectional P2PS 15
Table 3 – Specification of P2PS system in unidirectional P2PS 15
Table 4 – Requirement for P2PS system in bidirectional P2PS 16

Table 5 – Specification of P2PS system in bidirectional P2PS 16
Table 6 – Communication information for Communication setup/Request D-WPT service 18
Table 7 – Communication information for compatibility check 18
Table 8 – Communication information for power transfer 21
Table 9 – Communication information for power transfer stand-by 22
Table 10 – Communication information for power transfer terminated 22
Table 11 – Communication information for power transfer service session 23
Table 12 – Parameters sent from EV device to supply device 23
Table 13 – Parameters sent from supply device to EV device 24
Table 14 – Exception handling 25
Table B.1 – Communication information for pairing 33
Table C.1 – State transition in D-SECC 39
Table C.2 – State transition in D-EVCC 40
Table E.1 – Communication information for vehicle detecting 48
Table F.1 – UC Checking adjacent D-SECC 52
Table F.2 – UC Perform power transfer 52
Table F.3 – UC Checking vehicle on segment 52
Table F.4 – UC Perform Inter-inverter_segment_siwtching 53
Table F.5 – UC Compatibility check 54
Table G.1 – Supply device state transitions 57
Table G.2 – Vehicle device state transitions 67

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

ELECTRIC VEHICLE WIRELESS POWER TRANSFER (WPT) SYSTEMS –

Part 6: Specific requirements for magnetic field dynamic power transfer (MF-D-WPT) system communication and activities

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch [and/or] www.iso.org/patents. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61980-6 has been prepared by IEC technical committee 69: Electrical power/energy transfer systems for electrically propelled road vehicles and industrial trucks. It is a Publicly Available Specification.

The text of this Publicly Available Specification is based on the following documents:

Draft	Report on voting
69/1022/DPAS	69/1040/RVDPAS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

This PAS shall remain valid for an initial maximum period of 2 years starting from the publication date. The validity may be extended for a single period up to a maximum of 2 years, at the end of which it shall be transformed, with or without changes, into another type of normative document, or shall be withdrawn.

The language used for the development of this Publicly Available Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

NOTE In accordance with ISO/IEC Directives, Part 1, IEC PASs are automatically withdrawn after 4 years.

INTRODUCTION

The IEC 61980 series is published in separate parts according to the following structure:

– IEC 61980-1 covers general requirements for electric road vehicle (EV) wireless power transfer (WPT) systems including general background and definitions (e.g. efficiency, electrical safety, EMC, EMF);

– IEC 61980-2 specifically applies to magnetic field wireless power transfer (MF-WPT) for electric road vehicles and covers specific requirements for system activities and communication between the electric road vehicle side and the off-board side, including general background and definitions;

– IEC 61980-3 covers specific power transfer requirements for the off-board side of magnetic field wireless power transfer systems for electric road vehicles (e.g. efficiency, electrical safety, EMC, EMF);

– IEC 61980-4[1] covers specific power transfer requirements for the off-board side of magnetic field high power wireless power transfer (H-WPT) systems for electric vehicles electric road vehicles (e.g. efficiency, electrical safety, EMC, EMF);

– IEC PAS 61980-5 covers specific power transfer requirements for the off-board side of magnetic field dynamic wireless power transfer (MF-D-WPT) systems for electric vehicles electric road vehicles (e.g. efficiency, electrical safety, EMC, EMF);

– IEC 61980-6 specifically applies to magnetic field dynamic wireless power transfer for electric road vehicles and covers specific requirements for system activities and communication between the electric road vehicle side and the off-board side, including general background and definitions.

Requirements for the on-board side of MF-WPT and MF-D-WPT for electric road vehicles are covered in ISO 5474-6.

---

[1] Under preparation. Stage at the time of publication: IEC/CD 61980-4:2024.

ELECTRIC VEHICLE WIRELESS POWER TRANSFER (WPT) SYSTEMS –

Part 6: Specific requirements for magnetic field dynamic power transfer (MF-D-WPT) system communication and activities

1 Scope

This part of IEC 61980 addresses communication and activities of magnetic field dynamic wireless power transfer (MF-D-WPT) systems. The power transfer takes place while the electric vehicle (EV) is in motion.

NOTE 1 "In motion" includes a temporally stop on the road.

The requirements in this document are intended to be applied for MF-D-WPT systems according to IEC PAS 61980-5 and ISO 5474-6.

Supply device fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements described in ISO 5474-6.

The aspects covered in this document include:

– operational and functional characteristics of the MF-D-WPT communication system and related activities
– operational and functional characteristics of the positioning system

The following aspects are under consideration for future documents:

– requirements for two- and three-wheel vehicles,
– requirements for bidirectional power transfer

NOTE 2 Any internal communication at supply device or EV device is not in the scope of this document

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61980-1:2020, *Electric vehicle wireless power transfer (WPT) systems – Part 1: General requirements*

IEC 61980-2:2023, *Electric vehicle wireless power transfer (WPT) systems – Part 2: Specific requirements for MF-WPT system communication and activities*

IEC 61980-3:2022, *Electric vehicle wireless power transfer (WPT) systems – Part 3: Specific requirements for magnetic field wireless power transfer systems*

ISO PAS CD 5474-6:2023, *Electrically propelled road vehicles — Functional requirements and safety requirements for power transfer — Part 6: Magnetic field wireless power transfer — Safety and interoperability requirements for heavy-duty vehicles*

ISO 15118-20, *Road vehicles – Vehicle to grid communication interface – Part 20: 2nd generation network layer and application layer requirements*