IEC PAS 63151

Edition 1.0 2018-01

PUBLICLY AVAILABLE SPECIFICATION

PRE-STANDARD

colour inside

Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Vector measurement-based systems (Frequency range of 30 MHz to 6 GHz)

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 17.220.20, 17.240

ISBN 978-2-8322-5178-2

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 7
INTRODUCTION 9
1 Scope 10
2 Normative references 10
3 Terms and definitions 11
4 Symbols and abbreviated terms 11
5 Overview of the measurement procedure 11
6 Measurement system specifications 13
6.1 General requirements 13
6.2 Phantom specifications 15
6.2.1 Head Phantom specifications – shell 15
6.2.2 Body Phantom specifications – shell 15
6.2.3 Tissue-equivalent medium material properties 15
6.3 Hand and Device holder considerations 16
6.4 Measurement system requirements 16
6.4.1 General 16
6.4.2 Single probe measurement system specifications 16
6.4.3 Array measurement system specifications 16
6.5 Device holder specification 17
6.6 Reconstruction algorithm and peak spatial-averaging specifications 18
7 Protocol for SAR assessment 18
7.1 Measurement preparation 18
7.1.1 Preparation of tissue-equivalent medium 18
7.1.2 System check 19
7.1.3 Preparation of the device under test 19
7.1.4 Operating modes 19
7.1.5 Position of the DUT in relation to the phantom 19
7.1.6 Positions of the DUT in relation to the flat phantom for large DUT 19
7.1.7 Test frequencies for DUT 20
7.2 Tests to be performed 21
7.3 General measurement procedure 22
7.3.1 Measurement procedure for single probe systems 22
7.3.2 Measurement procedure for array systems 22
7.4 SAR measurements for simultaneous transmission 22
7.4.1 SAR measurements for non-correlated signals 22
7.4.2 SAR measurements for correlated signals 23
8 Uncertainty estimation 24
8.1 General 24
8.2 Requirements on the uncertainty evaluation 25
8.3 Description of uncertainty models 25
9 Measurement report 30
Annex A (normative) Phantom specifications 31
A.1 SAM phantom specifications 31
A.1.1 SAM phantom geometry 31
A.1.2 SAM Phantom shell 35
A.1.3 Tissue Equivalent Medium 36

A.2 Flat phantom specifications 37
A.3 Specific phantoms 38
A.4 Tissue-equivalent medium 39
Annex B (normative) Calibration and characterization of dosimetric probes 40
B.1 Introduction 40
B.2 Types of calibration 40
B.2.1 Amplitude calibration with analytical fields 40
B.2.2 Amplitude and phase calibration by transfer calibration 41
B.2.3 Amplitude and phase calibration using numerical reference 42
Annex C (informative) Field Reconstruction Techniques 45
C.1 Introduction 45
C.2 Objective of Field Reconstruction Techniques 45
C.3 Background 45
C.4 Reconstruction Techniques 47
C.4.1 Expansion Techniques 47
C.4.2 Source Reconstruction Techniques 48
C.4.3 Source Base Function Decomposition 48
C.4.4 Phase Reconstruction 48
C.4.5 Other Approaches 48
C.5 Source reconstruction and SAR estimation from fields measured outside the phantom 49
Annex D (normative) SAR measurement system verification and validation 50
D.1 Introduction 50
D.1.1 Objectives and purpose of *system check* 50
D.1.2 Objectives of *system validation* 50
D.2 SAR measurement setup and procedure for *system check* and *system validation* 51
D.2.1 General 51
D.2.2 Power measurement setups 52
D.2.3 Procedure to normalize the measured SAR 53
D.2.4 Power measurement uncertainty 55
D.3 *System check* 56
D.3.1 *System check* antennas and test conditions 56
D.3.2 System check acceptance criteria 56
D.4 *System validation* 57
D.4.1 Requirements for *system validation* antennas and test conditions 57
D.4.2 Test positions for *system validation* 58
D.4.3 *System validation* procedure based on peak spatial-average SAR 61
D.4.4 Validation acceptance criteria 70
Annex E (informative) Interlaboratory comparisons 71
E.1 Purpose 71
E.2 Monitor laboratory 71
E.3 Phantom set-up 71
E.4 Reference devices 71
E.5 Power set-up 71
E.6 Interlaboratory comparison – Procedure 72
Annex F (normative) Validation antennas 73
F.1 Introduction 73
F.2 Standard dipole antenna 73

F.3 VPIFA 75
F.4 2-PEAK CPIFA 80
F.5 Additional antennas 83
Annex G (normative) Calibration of Reference Antennas 85
G.1 Introduction 85
G.2 Parameters or quantities and ranges to be determined by calibration method 86
G.3 Reference Antenna Calibration Setup 86
G.4 Reference Antenna Calibration procedure 87
G.4.1 Verification of Return Loss 87
G.4.2 Calibration of Reference Antennas: Step-by-Step Procedure 87
G.4.3 Uncertainty Budget of Reference Antenna Calibration 88
Annex H (normative) General considerations on uncertainty estimation 93
H.1 Concept of uncertainty estimation 93
H.2 Type A and Type B evaluation 94
H.3 Degrees of freedom and coverage factor 94
H.4 Combined and expanded uncertainties 95
H.5 Analytical reference functions 96
Annex I (normative) Evaluation of the measurement system uncertainty 99
I.1 Measuring system uncertainties to be specified by the manufacturer 99
I.1.1 Calibration CF 99
I.1.2 Vector probe or vector probe-array isotropy ISO 99
I.1.3 Mutual sensor coupling MSC 100
I.1.4 Scattering within the array AS 100
I.1.5 System linearity LIN 102
I.1.6 Sensitivity limit SL 102
I.1.7 Boundary effect BE 102
I.1.8 Readout electronics RE 103
I.1.9 Response time RT 103
I.1.10 Probe positioning PP 103
I.1.11 Sampling error SE 104
I.1.12 Array boundaries AB 105
I.1.13 Phantom shell PS 105
I.1.14 Tissue-equivalent material parameters MAT 106
I.1.15 Phantom Homogeneity HOM 108
I.2 Uncertainty of post-processing algorithms 108
I.2.1 Introduction 108
I.2.2 Evaluation of uncertainty due to reconstruction REC 108
I.2.3 Impact of noise on interpolation and extrapolation POL 109
I.2.4 SAR Averaging SAV 109
I.2.5 SAR scaling $SARS$ 109
I.2.6 SAR correction for deviations in permittivity and conductivity SC 109
I.3 Measuring system errors which are dependent on the DUT 111
I.3.1 Introduction 111
I.3.2 Probe or probe-array coupling with the DUT PAC 111
I.3.3 Modulation Response MOD 112
I.3.4 Integration time IT 112
I.3.5 Measurement system drift and noise DN 112
I.4 DUT-related errors or validation antenna related errors and environmental factors 114

I.4.1 Device holder DH 114
I.4.2 Device Positioning DP 115
I.4.3 Measured SAR drift SD 115
I.4.4 RF ambient conditions AC 115
I.4.5 Measurement system immunity/secondary reception MSI 115
I.4.6 Deviation of experimental antennas DEX 116
I.4.7 Other uncertainty contributions when using validation antennas OVS 116
Bibliography 117

Figure 1 – Evaluation plan checklist 12
Figure 2 – Illustration of the shape and orientation relative to a curved phantom surface of the distorted cubic volume for computing peak spatial-average SAR 18
Figure 3 – Measurements performed by shifting a large device over the efficient measurement area of the system including overlapping areas – in this case: 6 tests performed 20
Figure A.1 – Illustration of dimensions in Table A.1 and Table A.2 32
Figure A.2 – Close up side view of phantom showing the ear region 34
Figure A.3 – Side view of the phantom showing relevant markings, dimensions are in mm 34
Figure A.4 – Cross-sectional view of SAM at the reference plane 36
Figure A.5 – Sagittally bisected phantom with extended perimeter, used for single probe systems 37
Figure A.6 – Dimensions of the elliptical phantom 38
Figure C.1 – Coordinate system for 2D planar measurement-system 46
Figure C.2 – Generic configuration of SAR measurement system 46
Figure C.3 – Schematic representation of 2D planar measurement-based SAR system and its coordinate system 48
Figure C.4 – Source Reconstruction outside the phantom 49
Figure D.1 – A Recommended power measurement setup for system check and system validation 52
Figure D.2 – Equipment setup for measurement of forward power P_{fc} 53
Figure D.3 – Equipment setup for measuring the shorted reverse coupled power P_{rcs} 54
Figure D.4 – Equipment setup for measuring the power with the Reference antenna connected 54
Figure D.5 – *System check* and validation locations for the flat phantom for minimal device specs (the minimal L and W shall be 160 mm x 80 mm) 59
Figure D.6 – *System check* and validation locations for the head phantom 60
Figure D.7 – Definition of rotation angles for dipoles 61
Figure F.1 – Mechanical details of the standard dipole 75
Figure F.2 – VPIFA validation antenna 77
Figure F.3 – Masks for positioning VPIFAs 78
Figure F.4 – Peak CPIFA at 2450 MHz 82
Figure F.5 – Tuning structure and matching structure 82
Figure G.1 – Measurement setup for waveguide calibration of dosimetric probe, and similar setup (same tissue-equivalent liquid, dielectric spacer, power sensors and coupler) for antenna calibration 86
Figure G.2 – Setup for calibration of a reference antenna 87

Figure I.1 – Illustration of the SAR measurements during 8 hours and the centered moving average 113

Table 1 – Evaluation plan checklist 13

Table 2 – Uncertainty budget template for the evaluation of the measurement system uncertainty of the 1 g or 10 g psSAR to be carried out by the system manufacturer (N = normal, R = rectangular) 27

Table 3 – Uncertainty budget template for evaluating the uncertainty in the measured value of 1 g SAR or 10 g SAR from a DUT (N = normal, R = rectangular) 28

Table 4 – Uncertainty budget template for evaluating the uncertainty in the measured value of 1 g SAR or 10 g SAR from a validation antenna (N = normal, R = rectangular) 29

Table 5 – Uncertainty budget template for evaluating the uncertainty in the measured value of 1 g SAR or 10 g SAR from the *system check* (N = normal, R = rectangular) 30

Table A.1 – Dimensions used in deriving SAM phantom from the ARMY 90th percentile male head data (Gordon et al.[61]) 33

Table A.2 – Additional SAM dimensions compared with selected dimensions from the ARMY 90th-percentile male head data (Gordon et al. [61]) – Specialist head measurement section 33

Table A.3 – Dielectric properties of the tissue-equivalent medium 39

Table B.1 – Uncertainty analysis of single-probe calibration in waveguide 41

Table B.2 – Uncertainty analysis of transfer calibration of array systems 42

Table B.3 – Uncertainty analysis of transfer calibration of array systems 44

Table D.1 – Modulations and multiplexing methods used by radio systems 58

Table D.2a – Peak spatial SAR (psSAR) averaged over 1g and 10g values for the flat phantom filled with tissue simulating material for the antennas defined in Annex F. Modulations are as defined in Table D.1 62

Table D.2b – Peak spatial SAR (psSAR) averaged over 1g and 10g values for antenna generating two peaks on the flat phantom filled with tissue simulating material for the antennas defined in Annex F. Modulations are as defined in Table D.1 64

Table D.3a – Peak spatial SAR (psSAR) averaged over 1g and 10g values on the head left and right phantom for the antennas defined in Annex F. Modulations are as defined in Table D.1 65

Table D.3b – Peak spatial SAR (psSAR) averaged over 1g and 10g values for antenna generating two peaks on the head left and right phantom for the antennas defined in Annex F. Modulations are as defined in Table D.1 69

Table F.1 – Mechanical dimensions of the reference dipoles 74

Table F.2 – Dimensions for VPIFA antennas at different frequencies 79

Table F.3 – Electric properties for the dielectric layers for VPIFA antennas 79

Table F.4 – Thickness of substrates and planar metallization 83

Table F.5 – Dielectric properties for FR4 83

Table F.6 – Lengths for the different components 83

Table G.1 – Example uncertainty budget for reference antenna (DIPOLE) calibration for 1g and 10g averaged SAR (750 MHz – 3 GHz) 90

Table G.2 – Example uncertainty budget for reference antenna calibration (PIFA) for 1 g and 10 g averaged SAR (750 MHz – 3 GHz) 91

Table G.3 – Example uncertainty budget for reference antenna (DIPOLE) calibration for 1g and 10g averaged SAR (3 – 6 GHz) 92

Table H.1 – Parameters of analytical reference functions and associated reference peak 10g SAR value. Reference peak 1g SAR value is 1 W/kg for every function 98

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

MEASUREMENT PROCEDURE FOR THE ASSESSMENT OF SPECIFIC ABSORPTION RATE OF HUMAN EXPOSURE TO RADIO FREQUENCY FIELDS FROM HAND-HELD AND BODY-MOUNTED WIRELESS COMMUNICATION DEVICES –

Vector measurement-based systems (Frequency range of 30 MHz to 6 GHz)

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is a technical specification not fulfilling the requirements for a standard, but made available to the public.

IEC PAS 63151 has been prepared by IEC technical committee 106: Methods for the assessment of electric, magnetic and electromagnetic fields associated with human exposure.

The text of this PAS is based on the following document:	This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document
Draft PAS	**Report on voting**
106/410/DPAS	106/420/RVDPAS

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

This PAS shall remain valid for an initial maximum period of 3 years starting from the publication date. The validity may be extended for a single period up to a maximum of 3 years, at the end of which it shall be published as another type of normative document, or shall be withdrawn.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This Publicly Available Specification (PAS) specifies the requirements for vector measurement-based systems to measure the Specific Absorption Rate (SAR) of devices that are used in close proximity to the human body or head.

This PAS is published in order to make available the current state of the technology. It is planned to publish a standard as Part 3 of the IEC 62209 series. When IEC 62209-3 is published this PAS will be withdrawn.

This PAS acknowledges the need for fast and accurate systems to determine the human exposure to radio frequency fields from hand-held and body mounted wireless communication devices.

As SAR measurement systems are used for showing compliance with national and international exposure limits the test procedures have to be standardized. The standardization is necessary to achieve comparable results for the approval process.

Vector measurement-based systems and protocols can differ from traditional SAR measurement systems and protocols. These systems use more advanced field reconstruction methods, allowing the application of indirect measurement approaches in which the SAR is evaluated in three dimensions from a limited number of measurement points which may be located in a limited part of the volume of interest, or even outside this volume. Such new SAR assessment approaches result in significantly reduced SAR measurement times.

MEASUREMENT PROCEDURE FOR THE ASSESSMENT OF SPECIFIC ABSORPTION RATE OF HUMAN EXPOSURE TO RADIO FREQUENCY FIELDS FROM HAND-HELD AND BODY-MOUNTED WIRELESS COMMUNICATION DEVICES –

Vector measurement-based systems (Frequency range of 30 MHz to 6 GHz)

1 Scope

This Publicly Available Specification (PAS) specifies protocols and test procedures for the reproducible measurement of the peak spatial-average specific absorption rate (psSAR) induced inside a simplified model of the head or the body by radio-frequency (RF) transmitting devices, with a defined uncertainty. It provides requirements for systems using vector measurement-based systems. Such systems determine the psSAR by 3D field reconstruction within the volume of interest by specifying the requirements for the measurement system, calibration, uncertainty assessment and validation methods. The protocols and procedures apply for a significant majority of people including children during use of hand-held and body-worn wireless communication devices.

This PAS is applicable to any wireless communication device intended to be used at a position near the human head or body at distances up to and including 200 mm. This PAS can be employed to evaluate SAR compliance of different types of wireless communication devices used next to the ear, in front of the face, mounted on the body, combined with other RF-transmitting or non-transmitting devices or accessories (e.g. belt-clip), or embedded in garments. The overall applicable frequency range is from 30 MHz to 6 GHz.

The system validation procedures provided within this PAS cover frequencies from 600 MHz to 6 GHz.

NOTE Some specifications (e.g., validation antennas and other procedures or requirements) are not yet defined over the full frequency range within the scope of this document but will be included in a future revision.

The device categories covered include but are not limited to mobile telephones, cordless microphones, auxiliary broadcast devices and radio transmitters in personal computers, desktop, laptop devices, multi-band, multi-antenna, and push-to-talk devices.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC Guide 98-3, *Uncertainty of measurement – Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

ISO/IEC 17025, *General requirements for the competence of testing and calibration laboratories*

IEC 62209-1:2016, *Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz)*

IEC 62209-2*, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)*

IEC 62479, *Assessment of the compliance of low-power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)*

IEC TR 62630:2010, *Guidance for evaluating exposure from multiple electromagnetic sources*

IEC/IEEE 62704 (all parts), *Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communications devices, 30 MHz to 6 GHz*