IEC TR 60919-3

Edition 2.2 2021-10
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

colour inside

Performance of high-voltage direct current (HVDC) systems with line-commutated converters –
Part 3: Dynamic conditions

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.200; 29.240.99

ISBN 978-2-8322-1044-2

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

IEC TR 60919-3

Edition 2.2 2021-10
CONSOLIDATED VERSION

REDLINE VERSION

colour inside

Performance of high-voltage direct current (HVDC) systems with line-commutated converters –
Part 3: Dynamic conditions



IEC TR 60919-3:2009-10+AMD1:2016-03+AMD2:2021-10 CSV(en)

CONTENTS

1 Scope 7
2 Normative references 7
3 Outline of HVDC dynamic performance specifications 8
3.1 Dynamic performance specification 8
3.2 General comments 9
4 AC system power flow and frequency control 9
4.1 General 9
4.2 Power flow control 9
4.2.1 Steady-state power control requirements 9
4.2.2 Step change power requirement 10
4.3 Frequency control 12
5 AC dynamic voltage control and interaction with reactive power sources 13
5.1 General 13
5.2 Voltage and reactive power characteristics of an HVDC substation and other reactive power sources 13
5.2.1 General 13
5.2.2 Converter as active/reactive power source 14
5.2.3 Voltage characteristics of a.c. networks depending on the power loading at the busbar of the HVDC substation 16
5.2.4 Voltage characteristics of a.c. filters, capacitor banks and shunt reactors for power compensation at the HVDC substation 18
5.2.5 Voltage characteristics of static var compensator (SVC) 18
5.2.6 Voltage characteristics of synchronous compensator (SC) 19
5.2.7 Voltage characteristics of static synchronous compensator (STATCOM) 19
5.3 Voltage deviations on the busbar of an HVDC substation 19
5.4 Voltage and reactive power interaction of the substation and other reactive power sources 20
5.4.1 HVDC converters, switchable a.c. filters, capacitor banks and shunt reactors 20
5.4.2 HVDC converters, switchable reactive power sources, SVC 21
5.4.3 HVDC converters, switchable reactive power sources and synchronous compensators 21
5.4.4 HVDC converters, switchable reactive power sources, STATCOM 22
6 AC system transient and steady-state stability 23
6.1 General 23
6.2 Characteristics of active and reactive power modulation 23
6.2.1 General 23
6.2.2 Large signal modulation 24
6.2.3 Small signal modulation 25
6.2.4 Reactive power modulation 25
6.3 Classification of network situations 26
6.4 AC network in parallel with the HVDC link 26
6.5 Improvement of the stability within one of the connected a.c. networks 30
6.6 Determination of the damping control characteristics 30
6.7 Implementation of the damping controller and telecommunication requirements 31

7 Dynamics of the HVDC system at higher frequencies 31
7.1 General 31
7.2 Types of instability 32
7.2.1 Loop instability (harmonic instability) 32
7.2.2 Current loop instability 32
7.2.3 Core saturation instability 32
7.2.4 Harmonic interactions 32
7.3 Information required for design purposes 33
7.4 Means available for preventing instabilities 34
7.5 Damping of low order harmonics by control action 34
7.6 Demonstration of satisfactory performance at higher frequencies 34
8 Subsynchronous oscillations 35
8.1 General 35
8.2 Criteria for subsynchronous torsional interaction with an HVDC system 36
8.3 Screening criteria for identifying generator units susceptible to torsional interactions 37
8.4 Performance considerations for utilizing subsynchronous damping ~~controls~~ controllers (SSDCs) 38
8.5 Performance testing 38
8.6 Turbine generator protection 38
9 Power plant interaction 39
9.1 General 39
9.2 Specific interactions 39
9.2.1 General 39
9.2.2 Frequency variation effects 39
9.2.3 Frequency controls interactions 40
9.2.4 Overvoltage effects 40
9.2.5 Harmonics 40
9.2.6 Subsynchronous and shaft impact effects 40
9.2.7 Resonance 41
9.2.8 Overvoltages 41
9.2.9 Stresses in a.c. switching equipment 41
9.2.10 Under-frequency 41
9.2.11 Starting procedure for an HVDC converter 41
9.3 Special considerations for a nuclear plant 41

Figure 1 – Elements for reactive power compensation at an HVDC substation 14
Figure 2 – *P/Q* diagram of a converter 15
Figure 3 – Reactive power requirements of a weak a.c. system depending on the active power loading for various constant voltage characteristics at the a.c. bus of an HVDC substation 17
Figure 4 – Representation of the a.c. network 17
Figure 5 – Example of voltage – current characteristic showing possible current modulation range in the absence of telecommunication between rectifier and inverter 25
Figure 6 – Reactive power modulation in an HVDC transmission operating at minimum extinction angle γ_{min} 27
Figure 7 – Reactive power modulation in an HVDC transmission operating at extinction angle $\gamma > \gamma_{min}$ 28

Figure 8 – Stability improvement of an a.c. link or network 29
Figure 9 – Principle arrangements of a damping controller 29

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

PERFORMANCE OF HIGH-VOLTAGE DIRECT CURRENT (HVDC) SYSTEMS WITH LINE-COMMUTATED CONVERTERS –

Part 3: Dynamic conditions

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendments has been prepared for user convenience.

IEC TR 60919-3 edition 2.2 contains the second edition (2009-10) [documents 22F/183/DTR and 22F/192/RVC], its amendment 1 (2016-03) [documents 22F/376/DTR and 22F/382A/RVC] and its amendment 2 (2021-10) [documents 22F/634/DTR and 22F/654/RVDTR].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendments 1 and 2. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 60919-3, which is a technical report, has been prepared by subcommittee 22F: Power electronics for electrical transmission and distribution systems, of IEC technical committee 22: Power electronic systems and equipment.

This edition includes the following significant technical changes with respect to the previous edition:

a) this report concerns only line-commutated converters;
b) significant changes have been made to the control system technology;
c) some environmental constraints, for example audible noise limits, have been added;
d) the capacitor coupled converters (CCC) and controlled series capacitor converters (CSCC) have been included.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60919 series, under the general title: *Performance of high-voltage direct current (HVDC) systems with line-commutated converters*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under webstore.iec.ch in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

A bilingual version of this publication may be issued at a later date.

PERFORMANCE OF HIGH-VOLTAGE DIRECT CURRENT (HVDC) SYSTEMS WITH LINE-COMMUTATED CONVERTERS –

Part 3: Dynamic conditions

1 Scope

This Technical Report provides general guidance on the dynamic performance of high-voltage direct current (HVDC) systems. Dynamic performance, as used in this specification, is meant to include those events and phenomena whose characteristic frequencies or time domain cover the range between transient conditions and steady state. It is concerned with the dynamic performance due to interactions between two-terminal HVDC systems and related a.c. systems or their elements such as power plants, a.c. lines and buses, reactive power sources, etc. at steady-state or transient conditions. The two-terminal HVDC systems are assumed to utilize 12-pulse converter units comprised of three-phase bridge (double way) connections. The converters are assumed to use thyristor valves as bridge arms, with gapless metal oxide arresters for insulation coordination and to have power flow capability in both directions. Diode valves are not considered in this specification. While multi-terminal HVDC transmission systems are not expressly considered, much of the information in this specification is equally applicable to such systems.

Only line-commutated converters are covered in this report, which includes capacitor commutated converter circuit configurations. General requirements for semiconductor line-commutated converters are given in IEC 60146-1-1, IEC 60146-1-2 and IEC 60146-1-3. Voltage-sourced converters are not considered.

This report (IEC 60919-3) which covers dynamic performance, is accompanied by publications for steady-state (IEC 60919-1) and transient (IEC 60919-2) performance. All three aspects should be considered when preparing two-terminal HVDC system specifications.

A difference exists between system performance specifications and equipment design specifications for individual components of a system. While equipment specifications and testing requirements are not defined herein, attention is drawn to those which would affect performance specifications for a system. There are many possible variations between different HVDC systems, therefore these are not considered in detail. This report should not be used directly as a specification for a specific project, but rather to provide the basis for an appropriate specification tailored to fit actual system requirements for a particular electric power transmission scheme. This report does not intend to discriminate between the responsibility of users and manufacturers for the work specified.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60146-1-1, *Semiconductor converters – General requirements and line commutated converters – Part 1-1: Specification of basic requirements*

IEC/TR 60146-1-2, *Semiconductor convertors – General requirements and line commutated convertors – Part 1-2: Application guide*

IEC 60146-1-3, *Semiconductor convertors – General requirements and line commutated convertors – Part 1-3: Transformers and reactors*

IEC TR 60919-1:~~2005~~2020, *Performance of high-voltage direct current (HVDC) systems with line-commutated converters – Part 1: Steady-state conditions*

IEC TR 60919-2:2008, *Performance of high-voltage direct current (HVDC) systems with line-commutated converters – Part 2: Faults and switching*
IEC TR 60919-2:2008/AMD1:2015
IEC TR 60919-2:2008AMD2:2020

IEC TR 60919-3

Edition 2.2 2021-10
CONSOLIDATED VERSION

FINAL VERSION

Performance of high-voltage direct current (HVDC) systems with line-commutated converters –
Part 3: Dynamic conditions



IEC TR 60919-3:2009-10+AMD1:2016-03+AMD2:2021-10 CSV(en)

CONTENTS

1 Scope 7
2 Normative references 7
3 Outline of HVDC dynamic performance specifications 8
3.1 Dynamic performance specification 8
3.2 General comments 9
4 AC system power flow and frequency control 9
4.1 General 9
4.2 Power flow control 9
4.2.1 Steady-state power control requirements 9
4.2.2 Step change power requirement 10
4.3 Frequency control 12
5 AC dynamic voltage control and interaction with reactive power sources 13
5.1 General 13
5.2 Voltage and reactive power characteristics of an HVDC substation and other reactive power sources 13
5.2.1 General 13
5.2.2 Converter as active/reactive power source 14
5.2.3 Voltage characteristics of a.c. networks depending on the power loading at the busbar of the HVDC substation 16
5.2.4 Voltage characteristics of a.c. filters, capacitor banks and shunt reactors for power compensation at the HVDC substation 18
5.2.5 Voltage characteristics of static var compensator (SVC) 18
5.2.6 Voltage characteristics of synchronous compensator (SC) 18
5.2.7 Voltage characteristics of static synchronous compensator (STATCOM) 19
5.3 Voltage deviations on the busbar of an HVDC substation 19
5.4 Voltage and reactive power interaction of the substation and other reactive power sources 20
5.4.1 HVDC converters, switchable a.c. filters, capacitor banks and shunt reactors 20
5.4.2 HVDC converters, switchable reactive power sources, SVC 21
5.4.3 HVDC converters, switchable reactive power sources and synchronous compensators 21
5.4.4 HVDC converters, switchable reactive power sources, STATCOM 22
6 AC system transient and steady-state stability 22
6.1 General 22
6.2 Characteristics of active and reactive power modulation 23
6.2.1 General 23
6.2.2 Large signal modulation 23
6.2.3 Small signal modulation 25
6.2.4 Reactive power modulation 25
6.3 Classification of network situations 26
6.4 AC network in parallel with the HVDC link 26
6.5 Improvement of the stability within one of the connected a.c. networks 30
6.6 Determination of the damping control characteristics 30
6.7 Implementation of the damping controller and telecommunication requirements 31

7 Dynamics of the HVDC system at higher frequencies 31
7.1 General 31
7.2 Types of instability 32
7.2.1 Loop instability (harmonic instability) 32
7.2.2 Current loop instability 32
7.2.3 Core saturation instability 32
7.2.4 Harmonic interactions 32
7.3 Information required for design purposes 33
7.4 Means available for preventing instabilities 34
7.5 Damping of low order harmonics by control action 34
7.6 Demonstration of satisfactory performance at higher frequencies 34
8 Subsynchronous oscillations 35
8.1 General 35
8.2 Criteria for subsynchronous torsional interaction with an HVDC system 36
8.3 Screening criteria for identifying generator units susceptible to torsional interactions 37
8.4 Performance considerations for utilizing subsynchronous damping controllers (SSDCs) 38
8.5 Performance testing 38
8.6 Turbine generator protection 38
9 Power plant interaction 39
9.1 General 39
9.2 Specific interactions 39
9.2.1 General 39
9.2.2 Frequency variation effects 39
9.2.3 Frequency controls interactions 39
9.2.4 Overvoltage effects 40
9.2.5 Harmonics 40
9.2.6 Subsynchronous and shaft impact effects 40
9.2.7 Resonance 41
9.2.8 Overvoltages 41
9.2.9 Stresses in a.c. switching equipment 41
9.2.10 Under-frequency 41
9.2.11 Starting procedure for an HVDC converter 41
9.3 Special considerations for a nuclear plant 41

Figure 1 – Elements for reactive power compensation at an HVDC substation 14
Figure 2 – *P/Q* diagram of a converter 15
Figure 3 – Reactive power requirements of a weak a.c. system depending on the active power loading for various constant voltage characteristics at the a.c. bus of an HVDC substation 17
Figure 4 – Representation of the a.c. network 17
Figure 5 – Example of voltage – current characteristic showing possible current modulation range in the absence of telecommunication between rectifier and inverter 25
Figure 6 – Reactive power modulation in an HVDC transmission operating at minimum extinction angle γ_{min} 27
Figure 7 – Reactive power modulation in an HVDC transmission operating at extinction angle $\gamma > \gamma_{min}$ 28

Figure 8 – Stability improvement of an a.c. link or network 29
Figure 9 – Principle arrangements of a damping controller 29

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

PERFORMANCE OF HIGH-VOLTAGE DIRECT CURRENT (HVDC) SYSTEMS WITH LINE-COMMUTATED CONVERTERS –

Part 3: Dynamic conditions

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendments has been prepared for user convenience.

IEC TR 60919-3 edition 2.2 contains the second edition (2009-10) [documents 22F/183/DTR and 22F/192/RVC], its amendment 1 (2016-03) [documents 22F/376/DTR and 22F/382A/RVC] and its amendment 2 (2021-10) [documents 22F/634/DTR and 22F/654/RVDTR].

This Final version does not show where the technical content is modified by amendments 1 and 2. A separate Redline version with all changes highlighted is available in this publication.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 60919-3, which is a technical report, has been prepared by subcommittee 22F: Power electronics for electrical transmission and distribution systems, of IEC technical committee 22: Power electronic systems and equipment.

This edition includes the following significant technical changes with respect to the previous edition:

a) this report concerns only line-commutated converters;
b) significant changes have been made to the control system technology;
c) some environmental constraints, for example audible noise limits, have been added;
d) the capacitor coupled converters (CCC) and controlled series capacitor converters (CSCC) have been included.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60919 series, under the general title: *Performance of high-voltage direct current (HVDC) systems with line-commutated converters*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under webstore.iec.ch in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

PERFORMANCE OF HIGH-VOLTAGE DIRECT CURRENT (HVDC) SYSTEMS WITH LINE-COMMUTATED CONVERTERS –

Part 3: Dynamic conditions

1 Scope

This Technical Report provides general guidance on the dynamic performance of high-voltage direct current (HVDC) systems. Dynamic performance, as used in this specification, is meant to include those events and phenomena whose characteristic frequencies or time domain cover the range between transient conditions and steady state. It is concerned with the dynamic performance due to interactions between two-terminal HVDC systems and related a.c. systems or their elements such as power plants, a.c. lines and buses, reactive power sources, etc. at steady-state or transient conditions. The two-terminal HVDC systems are assumed to utilize 12-pulse converter units comprised of three-phase bridge (double way) connections. The converters are assumed to use thyristor valves as bridge arms, with gapless metal oxide arresters for insulation coordination and to have power flow capability in both directions. Diode valves are not considered in this specification. While multi-terminal HVDC transmission systems are not expressly considered, much of the information in this specification is equally applicable to such systems.

Only line-commutated converters are covered in this report, which includes capacitor commutated converter circuit configurations. General requirements for semiconductor line-commutated converters are given in IEC 60146-1-1, IEC 60146-1-2 and IEC 60146-1-3. Voltage-sourced converters are not considered.

This report (IEC 60919-3) which covers dynamic performance, is accompanied by publications for steady-state (IEC 60919-1) and transient (IEC 60919-2) performance. All three aspects should be considered when preparing two-terminal HVDC system specifications.

A difference exists between system performance specifications and equipment design specifications for individual components of a system. While equipment specifications and testing requirements are not defined herein, attention is drawn to those which would affect performance specifications for a system. There are many possible variations between different HVDC systems, therefore these are not considered in detail. This report should not be used directly as a specification for a specific project, but rather to provide the basis for an appropriate specification tailored to fit actual system requirements for a particular electric power transmission scheme. This report does not intend to discriminate between the responsibility of users and manufacturers for the work specified.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60146-1-1, *Semiconductor converters – General requirements and line commutated converters – Part 1-1: Specification of basic requirements*

IEC/TR 60146-1-2, *Semiconductor convertors – General requirements and line commutated convertors – Part 1-2: Application guide*

IEC 60146-1-3, *Semiconductor convertors – General requirements and line commutated convertors – Part 1-3: Transformers and reactors*

IEC TR 60919-1:2020, *Performance of high-voltage direct current (HVDC) systems with line-commutated converters – Part 1: Steady-state conditions*

IEC TR 60919-2:2008, *Performance of high-voltage direct current (HVDC) systems with line-commutated converters – Part 2: Faults and switching*
IEC TR 60919-2:2008/AMD1:2015
IEC TR 60919-2:2008AMD2:2020