IEC TR 61850-90-30

Edition 1.0 2025-03

TECHNICAL REPORT

Communication networks and systems for power utility automation – Part 90-30: IEC 61850 Function Modelling in SCL

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.200

ISBN 978-2-8327-0068-6

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 11
INTRODUCTION 13
1 Scope 14
1.1 General 14
1.2 Published versions of this standard and related namespace name 14
1.3 Identification of the Code Components 15
1.3.1 IEC 61850-6-100 XML namespace compliant with IEC 61850-6:2018 edition 2 amendment 1 15
1.3.2 IEC 61850-6-100 XML namespace compliant with IEC 61850-6:2024 edition 2 amendment 2 16
1.3.3 IEC/TR 61850-90-30 SSD example 16
1.4 Code Component Distribution 16
1.4.1 General 16
1.4.2 SCL extension namespace code component 17
1.4.3 SSD example code component 17
2 Normative references 17
3 Terms and definitions 18
4 Functions and Applications 19
4.1 General 19
4.2 Functions 19
4.3 Application Schemes 19
4.4 Examples of Functions and Applications 21
4.4.1 General 21
4.4.2 1 ½ Breaker Control Application 21
4.4.3 Breaker Failure Application 21
4.4.4 Power Measurement Application 22
4.4.5 Power Transformer Applications 23
5 SCL extension representation concepts 26
5.1 General 26
5.2 PathName 26
5.3 SCL Location 27
5.4 Condition for attribute presence 27
6 Data Flow inside and between Functions 28
6.1 General 28
6.2 Data Flow 28
6.2.1 General 28
6.2.2 SCL Location 28
6.2.3 SourceRef 28
6.2.4 ControlRef 31
6.2.5 SourceRef and ControlRef connection 32
6.3 Data flow resolution 35
6.3.1 General 35
6.3.2 SCL Location 37
6.3.3 SubscriberLNode 37
6.3.4 ControllingLNode 37
6.4 Service-related Elements 38
6.4.1 SpecServiceType 38

6.4.2 ServiceSpecifications 40
7 LNode Data specification 53
7.1 SCL Location 53
7.2 General 53
7.3 Specification of Data Objects and Attributes 53
7.3.1 General 53
7.3.2 DOS/SDS/DAS Definition 53
7.4 LNode Mapping Documentation 57
8 LNodeSpecNaming 58
8.1 SCL Location 58
8.2 Definition 58
9 ProcessResource 60
9.1 SCL Location 60
9.2 Definition 60
9.3 SCL representation 67
9.3.1 General 67
9.3.2 ProcessResources 67
9.3.3 ProcessResource 67
9.3.4 Resource 68
10 PowerSystemRelation 70
10.1 SCL Location 70
10.2 Definition 70
10.3 SCL representation 72
10.3.1 General 72
10.3.2 PowerSystemRelations 72
10.3.3 PowerSystemRelation 72
11 SCL elements reference and categorisation 73
11.1 General 73
11.2 Function Reference 73
11.2.1 General 73
11.2.2 FunctionRef 73
11.2.3 FunctionCatRef 74
11.3 FunctionCategory 74
11.3.1 SCL Location 74
11.3.2 General 74
11.3.3 SCL representation 75
11.4 Allocation Role 76
11.4.1 SCL Location 76
11.4.2 Definition 76
11.4.3 Example 1 77
11.4.4 Example 2 79
11.4.5 Example 3 81
12 Variables 82
12.1 SCL Location 82
12.2 Definition 82
12.3 SCL representation 84
12.3.1 General 84
12.3.2 Variable 84

12.3.3 VariableApplyTo 85
13 Behavior description 88
13.1 SCL Location 88
13.2 Definition 88
13.3 SCL representation 89
13.3.1 General 89
13.3.2 BehaviorDescription 89
13.3.3 InputVar and OutputVar 91
13.3.4 IEC 61131 BehaviorDescription use cases 93
14 Process Echo 95
14.1 SCL location 95
14.2 Definition and rules 95
14.3 Use cases 96
14.3.1 Use case 1: circuit breaker position transmission 96
14.3.2 Use case 2: measurement transmission 97
15 Bay Type 98
15.1 SCL location 98
15.2 Definition 98
16 Specification Workflow, tools and file types 98
16.1 FSD 98
16.1.1 Definition and rules 98
16.1.2 SCL content 99
16.1.3 FunctionTemplate 99
16.1.4 Usage 100
16.2 SSD Template 101
16.3 S-IED 101
16.3.1 General 101
16.3.2 Logical Node and Function Allocation 101
16.3.3 S-IED as formal Specification 102
16.3.4 S-IEDs for Testing and Simulation 102
16.3.5 S-IED identification inside an SCL file 103
16.3.6 From Functional Specification to the S-IED 103
16.3.7 ISD 104
16.4 Process SCL files 107
16.4.1 General 107
16.4.2 Process ICD 107
16.4.3 Process IID 110
16.4.4 Instantiating a process ICD/IID in an SCD – Implementation rules 112
16.4.5 Documenting the implementation of the IED to the specification 114
16.5 Engineering Rights applied to functions 131
16.5.1 Definition 131
16.5.2 Rules from IEC 61850-6 131
16.5.3 The SCC file format 132
16.5.4 The project ID 133
16.5.5 The checkout ID 134
16.5.6 Combining SCC and SED workflows 143
16.5.7 Additional example adding SCL references 144
16.5.8 Use cases 146

16.5.9 Rules regarding engineering rights on process section elements 150
16.6 Information flow between tools 151
16.6.1 General 151
16.6.2 Response of a process ICD to a system specification or IED specification template 151
16.6.3 Response of a process IID to a project SCD 151
16.6.4 Response of a process IID to a project specific ISD/SSD 152
16.6.5 Response of a process ICD to an SSD with allocation roles 152
16.6.6 Global overview of tools and interfaces 152
17 SclFileReferences extension 153
17.1 General 153
17.2 Use of the SclFileReference for FSD 154
17.3 Use of SclFileReference for ASD 154
17.4 Use of other references 155
17.4.1 General 155
17.4.2 SclFileReference for SSD in ISD 155
17.4.3 SclFileReference for ISD in ICD 156
17.4.4 SclFileReference for ISD in SCD 156
17.4.5 SclFileReference for ISD in IID 156
17.4.6 SclFileReference for ICD in IID 156
17.4.7 SclFileReference for ICD in SCD 156
17.4.8 SclFileReference for IID in SCD 157
17.4.9 SclFileReference for SCD in IID 157
17.4.10 SclFileReference for SSD in SCD 157
17.4.11 SclFileReference for SCD in SED/SCC 157
17.4.12 CheckoutID from SED/SCC in SCD/SED/SCC 157
17.4.13 SclFileReference for SSD in ICD 157
17.4.14 SclFileReference for IID in SSD 158
17.4.15 SclFileReference for SSD in SSD 158
18 UUIDs 158
18.1 General 158
18.2 Scenario 1: 160
18.2.1 General 160
18.2.2 Subscenario 1: zoom on ASD 160
18.2.3 Subscenario 2: creating the project SSD 162
18.2.4 Subscenario 3: creating the process ICD 163
18.2.5 Subscenario 4: creating SCD 164
18.3 Other examples 165
18.3.1 General 165
18.3.2 Scenario 2 166
18.3.3 Scenario 3 166
Annex A (informative) Predefined Function classifications 167
A.1 Overview 167
A.2 Basic Function Categories 167
A.3 Protection 167
A.4 Automation 168
A.5 Extended Function Categories 169
A.6 Function scope 169

Annex B (informative) Service section rules for ISD files service section rules for ISD files 170
Annex C (informative) Management of different Schema version 180
C.1 General 180
C.2 Upgrading rules from 2019B9 to 2019C1 180
C.3 Downgrading rules from 2019C1 to 2019B9 181
Annex D (informative) Example SCL File 183
Bibliography 184

Figure 1 – Breaker Failure Protection from IEC TR 61850-7-500 20
Figure 2 – Breaker Failure Application 20
Figure 3 – 1 ½ Breaker Functions 21
Figure 4 – Breaker Failure Application 22
Figure 5 – Power Measurement Application 23
Figure 6 – 3 Transformer Differential Protection 24
Figure 7 – 3 Transformer Winding Overcurrent Protection 25
Figure 8 – 3 Transformer Voltage Control 26
Figure 9 – Absolute PathName Examples with Object Reference 27
Figure 10 – Data Flow specification with SourceRefs inside a Function 29
Figure 11 – Data Flow specification for data exchange between Functions 29
Figure 12 – Example of a SourceRef and ControlRef connection 33
Figure 13 – Example of open SourceRef and ControlRef 33
Figure 14 – Example of a connected SourceRef and ControlRef (source and controlled are set) 34
Figure 15 – Example of an implemented SourceRef and ControlRef (extRefAddr and extCtrlAddr are set) 35
Figure 16 – SubscriberLNode and ControllingLNode definition example 36
Figure 17 – SubscriberLNode and ControllingLNode selection example 36
Figure 18 – SubscriberLNode and ControllingLNode resolution example 36
Figure 19 – Example of service specification within a SourceRef element 38
Figure 20 – Example of service specification within a SubscriberLN element 39
Figure 21 – Example of a GooseParameters specification 43
Figure 22 – Example for referencing a GooseParameters 43
Figure 23 – Specification of a binary Wired oriented connection 46
Figure 24 – Specification of a binary Wired oriented connection (visual representation) 46
Figure 25 – Implementation of the LPDI/LPDO 47
Figure 26 – Example of BinaryWiringParameters 48
Figure 27 – Example of Wired Input and Output specification for XCBR 49
Figure 28 – Example of the implementation of the XCBR wiring specification 50
Figure 29 – Specification of an analogue Wired oriented connection 51
Figure 30 – Specification of an analogue Wired oriented connection (visual representation) 51
Figure 31 – Implementation of an analogue Wired oriented connection specification 52
Figure 32 – Example of AnalogueWiringParameters 53
Figure 33 – Example of Control Model specification 55

Figure 34 – Example of PTOC Setting Groups specification 56
Figure 35 – Example of array values specification 57
Figure 36 – Example LNodeSpecNaming 59
Figure 37 – Application Template definition with ProcessResource 61
Figure 38 – Application instance with ProcessResource resolution 62
Figure 39 – CB interlocking equation 63
Figure 40 – Application template 63
Figure 41 – Example Application with ProcessResource 64
Figure 42 – Using ProcessResource for SourceRef parameterization 65
Figure 43 – ProcessResource resolution to set SourceRef source 65
Figure 44 – Using ProcessResource with SubscriberLNode 66
Figure 45 – ProcessResource resolution with SubscriberLNode 67
Figure 46 – Example of ProcessResource usage for CBR usage 69
Figure 47 – Example of ProcessResource usage for CT usage 70
Figure 48 – Function and SubFunctions related to the Process Section 71
Figure 49 – 1 1/2 breaker control and protection application 72
Figure 50 – SCL support for Function classification (example) 75
Figure 51 – Example of Function Classification in SCL 76
Figure 52 – Example of Allocation roles with PIU 78
Figure 53 – Example of Allocation roles without Bay Controller CB Interface 79
Figure 54 – Allocation variant use case 80
Figure 55 – Allocation Variant use case representation in XML 81
Figure 56 – Auto recloser multiple allocation example 82
Figure 57 – Variables in the Process Section 83
Figure 58 – Example of variable to manage XCBR prefix 83
Figure 59 – Example of variable to manage specification of functional name 83
Figure 60 – Example of variable to manage DA value 84
Figure 61 – Example of Variable setting directly the Circuit Breaker prefix 86
Figure 62 – Example of Variable value set by an XPath expression. 87
Figure 63 – Example of Variables used for Setting Group definition 87
Figure 64 – Behavior description in a Bay 89
Figure 65 – Behavior description location 89
Figure 66 – Example of BehaviorDescription in a single LNode 93
Figure 67 – Example of floating BehaviorDescription 94
Figure 68 – Example P21 BehaviorDescription 95
Figure 69 – Example of ProcessEcho for XCBR.Pos transmission 97
Figure 70 – Example of ProcessEcho for measurement transmission 98
Figure 71 – FSD usage in specification process 100
Figure 72 – SSD Template 101
Figure 73 – IED Allocation 102
Figure 74 – Function Structure mapped to S-IEDs 102
Figure 75 – Process IID workflow 112
Figure 76 – Process ICD with ISD workflow 113

Figure 77 – Process ICD without ISD workflow 113
Figure 78 – Process ICD with ISD from SSD template workflow 113
Figure 79 – BehaviorDescription implementation documentation 114
Figure 80 – Multiple LNodes instantiation by one LN 115
Figure 81 – specification of binary inputs function 116
Figure 82 – Process ICD content with mapping documentation 117
Figure 83 – Single LNode implemented by multiple LN 118
Figure 84 – SourceRef implementation in same LN documentation 119
Figure 85 – SourceRef implementation in a GGIO documentation 120
Figure 86 – SourceRef implementation in a TCTR documentation 120
Figure 87 – Example of SourceRef mapping to real IED 121
Figure 88 – Example of real IED used to implement SourceRef 122
Figure 89 – Concept of mapping SourceRef to ExtRef 123
Figure 90 – SourceRef definition based on DO 124
Figure 91 – Using granularity for better SourceRef creation 124
Figure 92 – SourceRef definition for same DO at DA level 125
Figure 93 – SourceRef definition at DO level for reporting communication 125
Figure 94 – 1 to 1 implementation of SourceRef 126
Figure 95 – Using intAddr for mapping SourceRef to ExtRef 127
Figure 96 – Match documentation between ExtRef and SourceRef 127
Figure 97 – Choosing position ExtRef as mapping of SourceRef 128
Figure 98 – Example of same intAddr 129
Figure 99 – Using extRefAddr for SMV mapping 129
Figure 100 – Use of extCtrlAddr example 130
Figure 101 – Deviating DO/DA mapping documentation 131
Figure 102 – SED exchange 131
Figure 103 – Engineering rights rules from IEC 61850-6:2009+AMD2:2024 132
Figure 104 – SCC/SED concept 132
Figure 105 – SCC concept 133
Figure 106 – project UUID 134
Figure 107 – SCC workflow example 139
Figure 108 – use of UUIDs to handle SED flows 141
Figure 109 – use of UUIDs to handle SCC flows 142
Figure 110 – Handling of minRequestSCDFileVersion/Revision example 143
Figure 111 – Combining SCC and SED workflows 144
Figure 112 – Example of exchange between main/fork project and other system 145
Figure 113 – Combined example SCC/SED 146
Figure 114 – Use of SCC for extension engineering 147
Figure 115 – Single line of project process example 148
Figure 116 – Project execution flow 148
Figure 117 – interaction between main and for projects 149
Figure 118 – Use of SCC for exchange between main and fork project 149
Figure 119 – example of project flow between engineering and commissioning 150

Figure 120 – Example of SCC process 150
Figure 121 – Response of a process ICD to a system specification or IED specification template 151
Figure 122 – Response of a process IID to a project SCD 151
Figure 123 – Response of a process IID to an ISD/SSD 152
Figure 124 – Response of a process ICD to an SSD with allocation roles 152
Figure 125 – Global overview 153
Figure 126 – Reference to FSD 154
Figure 127 – Reference to ASD 155
Figure 128 – Use of references 155
Figure 129 – UUID example 1 159
Figure 130 – UUID example 2 159
Figure 131 – UUID example 3 160
Figure 132 – Scenario 1 160
Figure 133 – Zoom on ASD 161
Figure 134 – Subscenario 1 162
Figure 135 – Zoom on SSD Template 163
Figure 136 – Subscenario 2 163
Figure 137 – Zoom on ISD 164
Figure 138 – Subscenario 3 164
Figure 139 – Zoom on SCD 165
Figure 140 – Subscenario 4 165
Figure 141 – Scenario 2 166
Figure 142 – Scenario 3 166

Table 1 – Reference between published versions of the standard and related namespace name 15
Table 2 – Attributes of the IEC 61850-6-100:2019B9 XML namespace 15
Table 3 – Attributes of the IEC 61850-6-100:2019C1 XML namespace 16
Table 4 – Attributes of the IEC/TR 61850-90-30 SSD example 16
Table 5 – Conditions for presence of attributes within a context 27
Table 6 – Attributes of the SourceRef element 30
Table 7 – Management of the ExtRef with SourceRef 31
Table 8 – Attributes of the ControlRef element 31
Table 9 – Attributes of SubscriberLNode 37
Table 10 – Attributes of ControllingLNode 37
Table 11 – SpecServiceType 38
Table 12 – Attributes of the L2CommParameter element 41
Table 13 – Attributes of the L3IPv4CommParameter element 41
Table 14 – Attributes of the L3IPv6CommParameter element 42
Table 15 – Attributes of the GooseParameters element 42
Table 16 – Attributes of the SMVParameters element 44
Table 17 – Attributes of the ReportParameters element 44
Table 18 – Attributes of the LogParameters element 45

Table 19 – Attributes of the BinaryWiringParameters element 48
Table 20 – Attributes of the AnalogueWiringParameters element 52
Table 21 – DOS element attributes 54
Table 22 – SDS element attributes 54
Table 23 – DAS element attributes 54
Table 24 – LNodeSpecNaming element attributes 59
Table 25 – Attributes of the ProcessResource element 68
Table 26 – Attributes of the Resource element 68
Table 27 – Attributes of the PowerSystemRelation element 73
Table 28 – Attributes of the FunctionRef element 74
Table 29 – Attributes of the FunctionCatRef element 74
Table 30 – Attributes of the FunctionCategory and SubCategory element 75
Table 31 – Attributes of the AllocationRole element 77
Table 32 – Attributes of the Variable element 84
Table 33 – Attributes of the VariableApplyTo element 85
Table 34 – Attributes of the BehaviorDescription element 90
Table 35 – isSpecification and isSimulation attributes usage 90
Table 36 – Attributes of the BehaviorReference element 90
Table 37 – Attributes of the InputVar element 92
Table 38 – Attributes of the OutputVar element 92
Table 39 – Attributes of the ProcessEcho element 96
Table 40 – Attributes of the FunctionTemplate and SubFunctionTemplate element 100
Table 41 – ISD file content 104
Table 42 – Process ICD file content 108
Table 43 – Process IID file content 110
Table 44 – Attributes of the Project element 134
Table 45 – Attributes of the ProjectProcessReference element 134
Table 46 – Attributes of the CheckoutID element 135
Table 47 – Rules for SCC scenarios 137
Table 48 – Rules for SED scenarios 140
Table B.1 – Service section of ISD File 170

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

COMMUNICATION NETWORKS AND SYSTEMS FOR POWER UTILITY AUTOMATION –

Part 90-30: IEC 61850 Function Modelling in SCL

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 61850 has been prepared by subcommittee 10: Guidelines for IEC 61850 Function Modelling in SCL, of IEC technical committee TC 57: WG10. It is a Technical Report.

The text of this Technical Report is based on the following documents:

Draft	Report on voting
57/2693/DTR	57/2734/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61850 series, published under the general title *Communication networks and systems for power utility automation*, can be found on the IEC website.

NOTE The following print types are used:

- *SCL attributes and elements: in italic type.*

This IEC technical report includes Code Components i.e. components that are intended to be directly processed by a computer. Such content is any text found between the markers <CODE BEGINS> and <CODE ENDS>, or otherwise is clearly labelled in this standard as a Code Component.

The purchase of this IEC technical report carries a copyright license for the purchaser to sell software containing Code Components from this standard to end users either directly or via distributors, subject to IEC software licensing conditions, which can be found at: http://www.iec.ch/CCv1.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

The notion of Function is omnipresent in IEC 61850. Here are some examples:

- IEC 61850-1 introduces Functions on page 16 together with Logical Nodes and physical devices as core elements of the IEC 61850 reference architecture.
- IEC 61850-5 contains a comprehensive list of Functions in the Substation Domain and their relationship to Logical Nodes and PICOMs.
- IEC 61850-7-500 describes the use of the information model for devices and Functions of IEC 61850 in applications in substation automation systems.
- Functions play a central role in Logic Modelling.
- Basic Application Profiles (BAP) (IEC TR 61850-7-6) defines "Application Functions" as the chosen context for defining a profile.

The Function element requires an appropriate embedding in the formal SCL model and additional Guidelines on how to use it for the formalized, SCL based specification and description of power automation systems.

In Edition 1 of IEC 61850-6 the SCL element Function was limited to the Station Level and intended to be a container for information outside the immediate substation control & protection domain. E.g. "Door Alarm".

Since Edition 2 of IEC 61850-6, Functions are essential elements of the Substation and or Process Section. They serve as containers for Logical Nodes and can have internal structures (SubFunctions).

COMMUNICATION NETWORKS AND SYSTEMS FOR POWER UTILITY AUTOMATION –

Part 90-30: IEC 61850 Function Modelling in SCL

1 Scope

1.1 General

This part of IEC 61850, which is a Technical Report, describes extensions of the SCL Substation/Process Section allowing the creation of a comprehensive, IED and hardware independent specification of an IEC 61850 based power system.

It addresses how to:

- decompose functions in SCL
- show function classifications in SCL
- relate functions with the SCL Substation and Process Section
- relate functions to Logical Nodes and IEDs/Specification IEDs
- present information flow between functions in a hardware/implementation independent way
- position Functions in relation to "Application Schemes", "Distributed Functions", "Protection Schemes"
- consider the relationship to Basic Application Profiles (BAP) defined in IEC TR 61850-7-6

The document addresses the engineering process as far as it is related to the specification of Functions and their instantiation in IEC 61850 based power system. This includes the impact on the SCL Process Section during system configuration.

The engineering process related to the definition of Applications and their instantiation is addressed in the Basic Application Profile Document (BAP) in IEC TR 61850-7-6.

The System Configuration process is described in IEC 61850-6.

Modifications and extensions of SCL are done in a way to guarantee backwards compatibility.

In addition, this document introduces:

- Some further elements to SCL that improve the content and usefulness of SSD files and facilitate the handling of SCL files for engineering purposes,
- New variants of SCL files: ISD (IED Specification Description) and FSD (Function Specification Description),
- Evolution of the engineering rights management, to first improve the usage of SED and add a new concept of System Configuration Collaboration (SCC file) which allows collaboration on the same project with different engineers.

1.2 Published versions of this standard and related namespace name

This technical report defines an SCL namespace extension. This allows adding these extensions to existing SCL files without requiring a new SCL schema release. They will be included in a future SCL release.

This technical report also defines SSD examples of files showing the possibilities offered by this new document. The content of the examples is defined in IEC_61850-90-30.SSD.2024A2.Full.

The SCL namespace extension is defined under IEC 61850-6-100 identifier which is a common extension between this document and IEC TR 61850-7-6:2024 (Edition 2).

The SCL namespace extension is proposed in two versions based on:

– IEC 61850-6:2018 edition 2 amendment 1 which has already been used by some experimentation
– IEC 61850-6:2024 edition 2 amendment 2 which defines UUID (Universal Unique IDentifier) used in some proposed extension in this document.

The differences and the management of the two versions is described in Annex C.

Table 1 provides an overview of the references between the published versions of this standard and the related namespace name.

Table 1 – Reference between published versions of the standard and related namespace name

Edition	Publication date	Webstore	Namespace
Edition 1.0	2024-03	IEC 61850-90-30:2023	IEC 61850-6-100:2019B9 for SCL 2.1
Edition 1.0	2024-03	IEC 61850-90-30:2023	IEC 61850-6-100:2019C1 for SCL 2.2

1.3 Identification of the Code Components

1.3.1 IEC 61850-6-100 XML namespace compliant with IEC 61850-6:2018 edition 2 amendment 1

The example associated with this document is an SCL file (SSD) example based on IEC 61850-6-100 2019C1 and IEC 61850-6 2007C5. The content of these examples is defined in Annex D. The parameters which identify the namespace are provided in Table 2:

Table 2 – Attributes of the IEC 61850-6-100:2019B9 XML namespace

Attribute	Content
Namespace nameplate	
Namespace Identifier (xmlns)	http://www.iec.ch/61850/2019/SCL/6-100
Version	2019
Revision	B
Release	9
XSD version header attribute	2019B9
Recommended reference name	eIEC61850-6-100
Code Component Name	IEC_61850-6-100.XSD.2019B9.Full
Namespace dependencies	
includes	http://www.iec.ch/61850/2003/SCL version: 2007 revision: B release: 4

1.3.2 IEC 61850-6-100 XML namespace compliant with IEC 61850-6:2024 edition 2 amendment 2

The namespace associated with this document is an XML schema (XSD) for an extension to the System Configuration Language (SCL) as defined in IEC 61850-6. The parameters which identify the namespace are provided in Table 3:

Table 3 – Attributes of the IEC 61850-6-100:2019C1 XML namespace

Attribute	Content
Namespace nameplate	
Namespace Identifier (xmlns)	http://www.iec.ch/61850/2019/SCL/6-100
Version	2019
Revision	C
Release	1
XSD version header attribute	2019C1
Recommended reference name	eIEC61850-6-100
CodeComponentName	IEC_61850-6-100.XSD.2019C1.Full
Namespace dependencies	
includes	http://www.iec.ch/61850/2003/SCL version: 2007 revision: C release: 5

1.3.3 IEC/TR 61850-90-30 SSD example

The example associated with this document is an SCL file (SSD) example based on IEC 61850-6-100 2019C1 and IEC 61850-6 2007C5. The parameters which identify the namespace are provided in Table 4:

Table 4 – Attributes of the IEC TR 61850-90-30 SSD example

Attribute	Content
Example nameplate	
Version	2024
Revision	A
Release	1
Code Component Name	IEC_61850-90-30.SSD.2024A1.Full
Example dependencies	
includes	http://www.iec.ch/61850/2003/SCL version: 2007 revision: C release: 5
includes	http://www.iec.ch/61850/2019/SCL/6-100 version: 2019 revision: C release: 1

1.4 Code Component Distribution

1.4.1 General

This document is associated with code components.

Each Code Component is a ZIP package containing at least the electronic representation of the Code Component itself and a file describing the content of the package (IECManifest.xml).

The life cycle of a code component is not restricted to the life cycle of the related publication. The publication life cycle goes through two stages, Version (corresponding to an edition) and Revision (corresponding to an amendment). A third publication stage (Release) allows publication of Code Component in case of urgent fixes of InterOp Tissues, thus without need to publish an amendment.

Consequently, new release(s) of the Code Component may be released, which supersede(s) the previous release, and will be distributed through the IEC TC 57 web site at:

http://www.iec.ch/tc57/supportingdocuments

1.4.2 SCL extension namespace code component

The latest version/release of the document will be found by selecting the file for the code component with the highest value for VersionStateInfo, e.g. IEC_61850-6-100.XSD.{VersionStateInfo}.full.zip.

The SCL extension namespace is available in two version, for compatibility with SCL edition 2.1 or SCL edition 2.2. The VersionStateInfo will differ for both version:

– The version compatible with SCL edition 2.1 will be following 2019Bx where x is the latest release,
– The version compatible with SCL edition 2.2 will be following 2019Cx where x is the latest release.

The Code Component associated with this document is reflecting the XML schema specified in this document formatted in XSD files. It also contains example of IEC 618580-6-100 usage in the context of IEC TR 61850-90-30 and IEC TR 61850-7-6. The list of examples is detailed in the IECManifest.xml file.

The full version is freely accessible on the IEC website for download at http://www.iec.ch/tc57/supportingdocuments but the usage remains under the licensing conditions.

In case of any differences between the downloadable code and the IEC pdf published content, the downloadable code(s) is(are) the valid one; it may be subject to updates. See history files.

1.4.3 SSD example code component

The latest version/release of the SSD examples will be found by selecting the file for the code component with the highest value for VersionStateInfo, e.g. IEC_61850-90-30.SSD.{VersionStateInfo}.full.zip.

The code component associated to this TR is a list of examples packages as ZIP file used as informative. It is available as a full version only. It is freely accessible on the IEC website for download at http://www.iec.ch/tc57/supportdocuments, but the usage remains under the licensing conditions.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61850-6:2009, *Communication networks and systems for power utility automation – Part 6: Configuration description language for communication in electrical substations related to IEDs*
IEC 61850-6:2009/AMD2:2024

IEC 61850-7-2:2010, *Communication networks and systems for power utility automation – Part 7-2: Basic information and communication structure – Abstract communication service interface (ACSI)*
IEC 61850-7-2:2010/AMD1:2020

IEC 61850-7-4:2010, *Communication networks and systems for power utility automation – Part 7-4: Basic communication structure – Compatible logical node classes and data object classes*

IEC 61850-7-4:2010/AMD1:2020

IEC TR 61850-7-6:2024, *Communication networks and systems for power utility automation – Part 7-6: Guideline for definition of Basic Application Profiles (BAPs) using IEC 61850*

IEC TR 61850-7-500, *Communication networks and systems for power utility automation – Part 7-500: Basic information and communication structure – Use of logical nodes for modeling application functions and related concepts and guidelines for substations*

IEC 61131 (all parts), *Programmable controllers*