IEC TR 63079

Edition 1.2 2020-04

CONSOLIDATED VERSION

colour inside

Code of practice for hearing-loop systems (HLS)

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 17.140.50

ISBN 978-2-8322-8141-3

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

IEC TR 63079

Edition 1.2 2020-04

REDLINE VERSION

colour inside

Code of practice for hearing-loop systems (HLS)



IEC TR 63079:2017-04+AMD1:2018-09+AMD2:2020-04 CSV(en)

CONTENTS

FOREWORD 7
INTRODUCTION 9
1 Scope 10
2 Normative references 10
3 Terms, definitions, signs and symbols 10
3.1 Terms and definitions 10
3.2 Signs and symbols 12
3.2.1 Symbol for an induction-loop 12
3.2.2 Symbol for multiple loops 13
3.2.3 Sign for display in premises where an HLS is installed and for HLS equipment identification 13
3.2.4 Identification of areas where reception of the HLS is not satisfactory 14
4 General 14
4.1 How to use this document 14
4.1.1 Persons addressed 14
4.1.2 Objectives 14
4.2 Specialist advice 15
4.3 Safety aspects 15
4.4 Conforming to existing performance documents 15
5 Technical advice 15
5.1 Complying with this document 15
5.2 Seeking technical advice 16
5.3 The nature of the advice 16
5.4 Professional (consultancy) advice 16
6 Purpose of the system 16
7 Choosing the system supplier 17
7.1 General 17
7.2 Approaching a contractor 17
7.3 Approaching a manufacturer of HLS equipment 17
7.4 Approaching a specialist consultant 17
8 Contractual provisions 18
8.1 Performance specification 18
8.2 Verifying that the completed system delivers its intended performance 18
8.3 Arbitration 18
9 Classification of systems 19
10 Design 20
10.1 General 20
10.2 Symbols 21
10.3 Basic theory 21
10.3.1 Production of a magnetic field 21
10.3.2 Directional pattern of the magnetic field 23
10.3.3 Uniformity of the magnetic field strength 27
10.3.4 Reference points for magnetic field strength 27
10.3.5 Relationship between the requirements of IEC 60118-4 and the characteristics of hearing aids and speech signals 28

10.3.6 Impedance of the loop 29
10.3.7 Selection of the method of driving the loop 30
10.3.8 Current-driven loop 30
10.3.9 Voltage-driven loop 31
10.3.10 Voltage-driven loop with high-level equalization 32
10.3.11 Voltage-driven loop with low-level equalization 34
10.3.12 Use of transformers 34
10.3.13 Effects of building construction 35
10.3.14 Electromagnetic compatibility (EMC) 36
10.3.15 Tone signals 38
10.3.16 Equalization, other than for compensating loop impedance characteristics 38
10.3.17 Multiple loops 38
10.3.18 Protection of loop conductors 41
10.3.19 Automatic gain control (AGC), compression, limiting, noise gating and voice control 42
10.3.20 Signal-to-noise ratio 42
10.3.21 HLS for purposes other than assisted hearing 43
10.3.22 Time-differences between related information streams 44
10.4 System components 44
10.4.1 Final amplifiers 44
10.4.2 Preamplifiers and mixers 44
10.4.3 Signal sources 45
10.5 Objective measurement of intelligibility 52
10.6 Safety and reliability considerations 53
10.7 Designing for monitoring and maintenance 53
10.8 External factors 53
10.8.1 Magnetic noise interference 53
10.8.2 Effect of metal in the building 54
10.9 Magnetic field overspill 54
10.10 The role of the system designer in commissioning 54
11 Responsibility of the installer 54
12 Installation practices and workmanship 56
13 Inspection and testing of wiring 57
14 Commissioning 58
15 Documentation 60
16 Certification 60
17 Acceptance 61
18 Verification 62
19 Owner responsibilities 63
19.1 Signage 63
19.2 User feedback 63
19.3 Staff training 63
20 Operation and maintenance 63
20.1 General 63
20.2 Routine testing 63
20.3 Inspection and servicing 64
20.4 Non-routine attention 65

20.5 Special inspection on appointment of a new maintenance organization 65
20.6 Arrangements for repair of faults or damage 65
20.7 Modifications to the system 66
21 User responsibilities 66
21.1 Responsible person 66
21.2 Logbook 67
Annex A (informative) HLS monitoring receivers 68
A.1 General 68
A.2 Recommendations for fixed receivers 68
A.3 Recommendations for portable receivers 69
Annex B (informative) What is a hearing-loop system (HLS) and how does it work? 70
B.1 General 70
B.2 Benefits of HLS (for hearing enhancement) 70
B.3 Limitations of HLS 71
Annex C (informative) Explanations of the basis of the design formulas 72
C.1 Magnetic field strength 72
C.1.1 Magnetic field strength produced by an element of conductor 72
C.1.2 Field strength produced by a circular loop at a point on its axis 73
C.2 Magnetic field strength at the centre of a rectangular loop 74
C.3 Magnetic field strength at an arbitrary point 76
C.4 Loop conductor sizes and resistances 80
C.4.1 General 80
C.4.2 Resistance of the loop conductor and relation between conductor size and cut-off frequency for a voltage-driven loop 80
C.4.3 Quick reference tables (derived from IEC 60228) 82
C.4.4 Inductance of two parallel wires, leading to the inductance of a rectangular loop 82
C.4.5 Variation of the impedance of a loop of fixed dimensions with conductor resistance 84
C.4.6 High-level equalizer 85
Annex D (informative) Explanation of the specification and measurement of magnetic field strength of induction-loop systems 88
Annex E (normative) Specification of the PPM-based field strength meter 90
E.1 General 90
E.2 Checking magnetic field strength meters 91
Annex F (informative) Magnetic field direction near the loop conductor 92
Annex G (informative) Direct-to-reverberant sound pressure ratio 95
Annex H (informative) Model certificates 96
H.1 Design certificate 96
H.2 Installation certificate 97
H.3 Commissioning certificate 98
H.4 Acceptance certificate 100
H.5 Verification certificate (optional) 101
H.6 Inspection and servicing certificate 102
H.7 Modification certificate 104
Annex I (informative) Measuring STI with hearing loop systems (HLS) 106
I.1 Causes of loss of intelligibility 106
I.2 Measurement method 106

I.2.1 General 106
I.2.2 Limitations of the method 106
I.2.3 Measurement equipment 106
I.2.4 Procedure 107
Annex J (informative) Example of an architect's specification for an HLS 108
Annex K (informative) Control of time-differences between information presented to a recipient via two transmission channels or media 109
K.1 General 109
K.2 Audible speech signals 109
K.3 Audible speech signal and video display of the talker 109
K.4 Priority 109
Bibliography 110

Figure 1 – Symbol for use on diagrams 13
Figure 2 – Symbol for multiple loops for use on diagrams 13
Figure 3 – Sign for display in premises to indicate that an HLS is installed and for HLS equipment identification 14
Figure 4 – Sign to show seating areas where HLS reception is not satisfactory 14
Figure 5 – Pictorial view of the magnetic field (lines of force) of a rectangular loop 22
Figure 6 – Directional response of a hearing aid telecoil 24
Figure 7 – Variation of the strength of the perpendicular component of the magnetic field across an axis of a rectangular loop, with listening height as parameter 25
Figure 8 – Variation across the median of a square loop of the perpendicular and coplanar components of the magnetic field at a height ratio h_n = 1 26
Figure 9 – Variation across the diagonal of a square loop of the perpendicular and coplanar components of the magnetic field at a height ratio h_n = 1 26
Figure 10 – Variation with frequency of the logarithm of the impedance of loops of constant inductance *L*, with the loop resistance *R* as parameter 30
Figure 11 – Circuit diagram of a "high-level" equalizer (for insertion between the amplifier and the loop) 34
Figure 12 – Preferred loop layout in a steel-framed building 35
Figure 13 – Methods of breaking eddy current paths in metal structures 36
Figure 14 – Filter for attenuating VHF signals picked up by the loop 36
Figure 15 – Methods of "breaking" loops into which interference voltages could be induced by an HLS 37
Figure 16 – Multiple loop layouts 39
Figure 17 – Variation across an axis of the system, at a height ratio of 0,32, of the component of the field strength, for a loop system similar to that shown in Figure 16 c), compared with the corresponding variations for a conventional single loop 41
Figure 18 – Horizontal directional response of an omni-directional microphone with its axis vertical: decibel scale 48
Figure 19 – Directional response of a cardioid microphone: decibel scale 48
Figure 20 – Directional response of a supercardioid microphone: decibel scale 49
Figure 21 – Directional response of a hypercardioid microphone: decibel scale 49
Figure 22 – Directional response of a highly directional shotgun (rifle) microphone where *f* = 250 Hz and barrel length is 275 mm 49
Figure 23 – Directional response of the same microphone where *f* = 2,5 kHz 49
Figure 24 – Directional response of the same microphone where *f* = 10 kHz 49

Figure 25 – Relative operating distances of directional microphones for equal direct-to-reverberant signal ratios 50
Figure 26 – Two methods of positioning microphones on a conference table 51
Figure 27 – The 3-to-1 ratio for microphone positioning (normal) 51
Figure 28 – A reduced 3-to-1 ratio using angled microphones 51
Figure 29 – Illustrations of good and bad microphone placements 52
Figure 30 – Optimization of the height of the microphone above the table 52
Figure 31 – Measuring field strength of type 2 HLS – Plan views 59
Figure C.1 – Generation of magnetic fields 73
Figure C.2 – Diagram for calculating magnetic field strength at the centre of a rectangular loop 76
Figure C.3 – Diagram for calculating magnetic field strength at an arbitrary point 77
Figure C.4 – Diagram for calculating cosΦ and sinΦ 78
Figure C.5 – Diagram for calculating magnetic field strength at point (x, y, z) 80
Figure C.6 – Circuit diagram of a “high-level” or Poperwell equalizer (for insertion between the amplifier and the loop) 86
Figure C.7 – Frequency response obtained with a high-level equalizer 87
Figure E.1 – "EQ" or "wideband" frequency response: target curve and tolerances on response 90
Figure F.1 – Magnetic field patterns 92
Figure F.2 – Magnetic field directions for a floor-level loop 93
Figure F.3 – Magnetic field directions for a ceiling-level loop 94

Table 1 – Classes of loop system 20
Table 2 – Relative operating distances of directional microphones for equal direct-to-reverberant signal ratios 50
Table C.1 – Factor by which the loop current has to be increased, compared with that required for a given magnetic field strength at the centre of a square loop, to obtain the same field strength for a rectangular loop at a point at height ratio of h_n above or below the centre of the loop 74
Table C.2 – Class 5 flexible annealed copper conductors for standard single-core and multi-core cables 81
Table C.3 – Class 1 solid annealed copper conductors for single-core and multi-core cables 82
Table C.4 – Ratio of approximate to exact inductance 84
Table C.5 – Values of $L_{|z|}$ 85

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

CODE OF PRACTICE FOR HEARING-LOOP SYSTEMS (HLS)

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

DISCLAIMER
This Consolidated version is not an official IEC Standard and has been prepared for user convenience. Only the current versions of the standard and its amendment(s) are to be considered the official documents.

This Consolidated version of IEC TR 63079 bears the edition number 1.1. It consists of the first edition (2017-04) [documents 29/917/DTR and 29/923/RVC], its amendment 1 (2018-09) [documents 29/983/DTR and 29/992/RVDTR] and its amendment 2 (2020-04) [documents 29/1037/DTR and 29/1046/RVDTR]. The technical content is identical to the base edition and its amendments.

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendments 1 and 2. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 63079, which is a Technical Report, has been prepared by IEC technical committee 29: Electroacoustics.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The performance of induction-loop systems is specified in IEC 60118-4, whereas IEC TR 63079 gives recommendations and guidance for their design, planning, installation, testing, operation and maintenance. Provisions for components of a system are given in IEC 62489-1. Methods of calculation and measurement of the magnetic field, in the context of human exposure, are given in IEC 62489-2.

This document takes the form of guidance and recommendations. It should not be quoted as if it were a specification and particular care should be taken to ensure that claims of compliance are not misleading.

Any user claiming compliance with this document is expected to be able to justify any course of action that deviates from its recommendations.

CODE OF PRACTICE FOR HEARING-LOOP SYSTEMS (HLS)

1 Scope

This document, which is a Technical Report, gives recommendations for and guidance on the design, planning, installation, testing, operation and maintenance of a hearing-loop system (HLS) intended for communicating speech, music and/or other signals. It is mainly concerned with HLS for hearing enhancement, in which the signals are communicated to users of hearing aids equipped with magnetic pick-up coils.

This document does not apply to induction-loop systems which use a carrier frequency, nor to other systems for hearing enhancement purposes which do not use magnetic induction.

2 Normative references

~~There are no normative references in this document.~~

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60118-4:2014, *Electroacoustics – Hearing aids – Part 4: Induction-loop systems for hearing aid purposes – System performance requirements*

IEC 60268-16, *Sound system equipment – Part 16: Objective rating of speech intelligibility by speech transmission index*

IEC TR 63079

Edition 1.2 2020-04

FINAL VERSION

colour inside

Code of practice for hearing-loop systems (HLS)



IEC TR 63079:2017-04+AMD1:2018-09+AMD2:2020-04 CSV(en)

CONTENTS

FOREWORD 7
INTRODUCTION 9
1 Scope 10
2 Normative references 10
3 Terms, definitions, signs and symbols 10
3.1 Terms and definitions 10
3.2 Signs and symbols 12
3.2.1 Symbol for an induction-loop 12
3.2.2 Symbol for multiple loops 13
3.2.3 Sign for display in premises where an HLS is installed and for HLS equipment identification 13
3.2.4 Identification of areas where reception of the HLS is not satisfactory 14
4 General 14
4.1 How to use this document 14
4.1.1 Persons addressed 14
4.1.2 Objectives 14
4.2 Specialist advice 15
4.3 Safety aspects 15
4.4 Conforming to existing performance documents 15
5 Technical advice 15
5.1 Complying with this document 15
5.2 Seeking technical advice 16
5.3 The nature of the advice 16
5.4 Professional (consultancy) advice 16
6 Purpose of the system 16
7 Choosing the system supplier 17
7.1 General 17
7.2 Approaching a contractor 17
7.3 Approaching a manufacturer of HLS equipment 17
7.4 Approaching a specialist consultant 17
8 Contractual provisions 18
8.1 Performance specification 18
8.2 Verifying that the completed system delivers its intended performance 18
8.3 Arbitration 18
9 Classification of systems 19
10 Design 20
10.1 General 20
10.2 Symbols 21
10.3 Basic theory 21
10.3.1 Production of a magnetic field 21
10.3.2 Directional pattern of the magnetic field 23
10.3.3 Uniformity of the magnetic field strength 27
10.3.4 Reference points for magnetic field strength 27
10.3.5 Relationship between the requirements of IEC 60118-4 and the characteristics of hearing aids and speech signals 28

10.3.6 Impedance of the loop 29
10.3.7 Selection of the method of driving the loop 30
10.3.8 Current-driven loop 30
10.3.9 Voltage-driven loop 31
10.3.10 Voltage-driven loop with high-level equalization 32
10.3.11 Voltage-driven loop with low-level equalization 34
10.3.12 Use of transformers 34
10.3.13 Effects of building construction 35
10.3.14 Electromagnetic compatibility (EMC) 36
10.3.15 Tone signals 38
10.3.16 Equalization, other than for compensating loop impedance characteristics 38
10.3.17 Multiple loops 38
10.3.18 Protection of loop conductors 41
10.3.19 Automatic gain control (AGC), compression, limiting, noise gating and voice control 42
10.3.20 Signal-to-noise ratio 42
10.3.21 HLS for purposes other than assisted hearing 43
10.3.22 Time-differences between related information streams 44
10.4 System components 44
10.4.1 Final amplifiers 44
10.4.2 Preamplifiers and mixers 44
10.4.3 Signal sources 45
10.5 Objective measurement of intelligibility 52
10.6 Safety and reliability considerations 53
10.7 Designing for monitoring and maintenance 53
10.8 External factors 53
10.8.1 Magnetic noise interference 53
10.8.2 Effect of metal in the building 54
10.9 Magnetic field overspill 54
10.10 The role of the system designer in commissioning 54
11 Responsibility of the installer 54
12 Installation practices and workmanship 56
13 Inspection and testing of wiring 57
14 Commissioning 58
15 Documentation 60
16 Certification 60
17 Acceptance 61
18 Verification 62
19 Owner responsibilities 63
19.1 Signage 63
19.2 User feedback 63
19.3 Staff training 63
20 Operation and maintenance 63
20.1 General 63
20.2 Routine testing 63
20.3 Inspection and servicing 64
20.4 Non-routine attention 65

20.5 Special inspection on appointment of a new maintenance organization 65
20.6 Arrangements for repair of faults or damage 65
20.7 Modifications to the system 66
21 User responsibilities 66
21.1 Responsible person 66
21.2 Logbook 67
Annex A (informative) HLS monitoring receivers 68
A.1 General 68
A.2 Recommendations for fixed receivers 68
A.3 Recommendations for portable receivers 69
Annex B (informative) What is a hearing-loop system (HLS) and how does it work? 70
B.1 General 70
B.2 Benefits of HLS (for hearing enhancement) 70
B.3 Limitations of HLS 71
Annex C (informative) Explanations of the basis of the design formulas 72
C.1 Magnetic field strength 72
C.1.1 Magnetic field strength produced by an element of conductor 72
C.1.2 Field strength produced by a circular loop at a point on its axis 72
C.2 Magnetic field strength at the centre of a rectangular loop 74
C.3 Magnetic field strength at an arbitrary point 75
C.4 Loop conductor sizes and resistances 80
C.4.1 General 80
C.4.2 Resistance of the loop conductor and relation between conductor size and cut-off frequency for a voltage-driven loop 80
C.4.3 Quick reference tables (derived from IEC 60228) 81
C.4.4 Inductance of two parallel wires, leading to the inductance of a rectangular loop 81
C.4.5 Variation of the impedance of a loop of fixed dimensions with conductor resistance 84
C.4.6 High-level equalizer 84
Annex D (informative) Explanation of the specification and measurement of magnetic field strength of induction-loop systems 87
Annex E (normative) Specification of the PPM-based field strength meter 89
E.1 General 89
E.2 Checking magnetic field strength meters 90
Annex F (informative) Magnetic field direction near the loop conductor 91
Annex G (informative) Direct-to-reverberant sound pressure ratio 94
Annex H (informative) Model certificates 95
H.1 Design certificate 95
H.2 Installation certificate 96
H.3 Commissioning certificate 97
H.4 Acceptance certificate 99
H.5 Verification certificate (optional) 100
H.6 Inspection and servicing certificate 101
H.7 Modification certificate 103
Annex I (informative) Measuring STI with hearing loop systems (HLS) 105
I.1 Causes of loss of intelligibility 105
I.2 Measurement method 105

I.2.1 General 105
I.2.2 Limitations of the method 105
I.2.3 Measurement equipment 105
I.2.4 Procedure 106
Annex J (informative) Example of an architect's specification for an HLS 107
Annex K (informative) Control of time-differences between information presented to a recipient via two transmission channels or media 108
K.1 General 108
K.2 Audible speech signals 108
K.3 Audible speech signal and video display of the talker 108
K.4 Priority 108
Bibliography 109

Figure 1 – Symbol for use on diagrams 13
Figure 2 – Symbol for multiple loops for use on diagrams 13
Figure 3 – Sign for display in premises to indicate that an HLS is installed and for HLS equipment identification 14
Figure 4 – Sign to show seating areas where HLS reception is not satisfactory 14
Figure 5 – Pictorial view of the magnetic field (lines of force) of a rectangular loop 22
Figure 6 – Directional response of a hearing aid telecoil 24
Figure 7 – Variation of the strength of the perpendicular component of the magnetic field across an axis of a rectangular loop, with listening height as parameter 25
Figure 8 – Variation across the median of a square loop of the perpendicular and coplanar components of the magnetic field at a height ratio h_n = 1 26
Figure 9 – Variation across the diagonal of a square loop of the perpendicular and coplanar components of the magnetic field at a height ratio h_n = 1 26
Figure 10 – Variation with frequency of the logarithm of the impedance of loops of constant inductance *L*, with the loop resistance *R* as parameter 30
Figure 11 – Circuit diagram of a "high-level" equalizer (for insertion between the amplifier and the loop) 34
Figure 12 – Preferred loop layout in a steel-framed building 35
Figure 13 – Methods of breaking eddy current paths in metal structures 36
Figure 14 – Filter for attenuating VHF signals picked up by the loop 36
Figure 15 – Methods of "breaking" loops into which interference voltages could be induced by an HLS 37
Figure 16 – Multiple loop layouts 39
Figure 17 – Variation across an axis of the system, at a height ratio of 0,32, of the component of the field strength, for a loop system similar to that shown in Figure 16 c), compared with the corresponding variations for a conventional single loop 41
Figure 18 – Horizontal directional response of an omni-directional microphone with its axis vertical: decibel scale 48
Figure 19 – Directional response of a cardioid microphone: decibel scale 48
Figure 20 – Directional response of a supercardioid microphone: decibel scale 49
Figure 21 – Directional response of a hypercardioid microphone: decibel scale 49
Figure 22 – Directional response of a highly directional shotgun (rifle) microphone where *f* = 250 Hz and barrel length is 275 mm 49
Figure 23 – Directional response of the same microphone where *f* = 2,5 kHz 49
Figure 24 – Directional response of the same microphone where *f* = 10 kHz 49

Figure 25 – Relative operating distances of directional microphones for equal direct-to-reverberant signal ratios 50
Figure 26 – Two methods of positioning microphones on a conference table 51
Figure 27 – The 3-to-1 ratio for microphone positioning (normal) 51
Figure 28 – A reduced 3-to-1 ratio using angled microphones 51
Figure 29 – Illustrations of good and bad microphone placements 52
Figure 30 – Optimization of the height of the microphone above the table 52
Figure 31 – Measuring field strength of type 2 HLS – Plan views 59
Figure C.1 – Generation of magnetic fields 73
Figure C.2 – Diagram for calculating magnetic field strength at the centre of a rectangular loop 75
Figure C.3 – Diagram for calculating magnetic field strength at an arbitrary point 77
Figure C.4 – Diagram for calculating cosΦ and sinΦ 77
Figure C.5 – Diagram for calculating magnetic field strength at point (x, y, z) 79
Figure C.6 – Circuit diagram of a “high-level” or Poperwell equalizer (for insertion between the amplifier and the loop) 86
Figure C.7 – Frequency response obtained with a high-level equalizer 86
Figure E.1 – "EQ" or "wideband" frequency response: target curve and tolerances on response 89
Figure F.1 – Magnetic field patterns 91
Figure F.2 – Magnetic field directions for a floor-level loop 92
Figure F.3 – Magnetic field directions for a ceiling-level loop 93

Table 1 – Classes of loop system 20
Table 2 – Relative operating distances of directional microphones for equal direct-to-reverberant signal ratios 50
Table C.1 – Factor by which the loop current has to be increased, compared with that required for a given magnetic field strength at the centre of a square loop, to obtain the same field strength for a rectangular loop at a point at height ratio of h_n above or below the centre of the loop 73
Table C.2 – Class 5 flexible annealed copper conductors for standard single-core and multi-core cables 81
Table C.3 – Class 1 solid annealed copper conductors for single-core and multi-core cables 81
Table C.4 – Ratio of approximate to exact inductance 84
Table C.5 – Values of $L_{|z|}$ 84

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

CODE OF PRACTICE FOR HEARING-LOOP SYSTEMS (HLS)

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

DISCLAIMER
This Consolidated version is not an official IEC Standard and has been prepared for user convenience. Only the current versions of the standard and its amendment(s) are to be considered the official documents.

This Consolidated version of IEC TR 63079 bears the edition number 1.1. It consists of the first edition (2017-04) [documents 29/917/DTR and 29/923/RVC], its amendment 1 (2018-09) [documents 29/983/DTR and 29/992/RVDTR] and its amendment 2 (2020-04) [documents 29/1037/DTR and 29/1046/RVDTR]. The technical content is identical to the base edition and its amendments.

This Final version does not show where the technical content is modified by amendments 1 and 2. A separate Redline version with all changes highlighted is available in this publication.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 63079, which is a Technical Report, has been prepared by IEC technical committee 29: Electroacoustics.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The performance of induction-loop systems is specified in IEC 60118-4, whereas IEC TR 63079 gives recommendations and guidance for their design, planning, installation, testing, operation and maintenance. Provisions for components of a system are given in IEC 62489-1. Methods of calculation and measurement of the magnetic field, in the context of human exposure, are given in IEC 62489-2.

This document takes the form of guidance and recommendations. It should not be quoted as if it were a specification and particular care should be taken to ensure that claims of compliance are not misleading.

Any user claiming compliance with this document is expected to be able to justify any course of action that deviates from its recommendations.

CODE OF PRACTICE FOR HEARING-LOOP SYSTEMS (HLS)

1 Scope

This document, which is a Technical Report, gives recommendations for and guidance on the design, planning, installation, testing, operation and maintenance of a hearing-loop system (HLS) intended for communicating speech, music and/or other signals. It is mainly concerned with HLS for hearing enhancement, in which the signals are communicated to users of hearing aids equipped with magnetic pick-up coils.

This document does not apply to induction-loop systems which use a carrier frequency, nor to other systems for hearing enhancement purposes which do not use magnetic induction.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60118-4:2014*, Electroacoustics – Hearing aids – Part 4: Induction-loop systems for hearing aid purposes – System performance requirements*

IEC 60268-16*, Sound system equipment – Part 16: Objective rating of speech intelligibility by speech transmission index*