IEC TS 61851-3-6

Edition 1.0 2023-07

TECHNICAL SPECIFICATION

Electric vehicles conductive charging system – Part 3-6: DC EV supply equipment where protection relies on double or reinforced insulation – Voltage converter unit communication



IEC TS 61851-3-6:2023-07(en)



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC TS 61851-3-6

Edition 1.0 2023-07

TECHNICAL SPECIFICATION

Electric vehicles conductive charging system – Part 3-6: DC EV supply equipment where protection relies on double or reinforced insulation – Voltage converter unit communication

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 43.120

ISBN 978-2-8322-5752-4

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 10
INTRODUCTION 12
1 Scope 13
2 Normative references 13
3 Terms and definitions 13
4 Symbols and abbreviated terms 13
5 Operating principles 14
5.1 General 14
5.2 Voltage converter unit specific FSA 14
5.3 State definitions 15
5.4 Transitions in the FSA for VCUs 17
6 Object dictionary 18
6.1 General 18
6.2 Additional definitions to general application objects 18
6.2.1 General 18
6.2.2 Object 6001_h: Control word 18
6.2.3 Object 6002_h: Status word 18
6.3 Produced application objects by AC-DC converter functionality (mandatory) 19
6.3.1 General 19
6.3.2 Object $60A0_h$: AC-DC converter capability 19
6.4 Produced application objects by AC-DC converter (optional) 23
6.4.1 General 23
6.4.2 Object $60A1_h$: AC-DC converter minimum AC voltage 23
6.4.3 Object $60A2_h$: AC-DC converter maximum AC voltage 24
6.4.4 Object $60A3_h$: AC-DC converter maximum AC current 26
6.4.5 Object $60A4_h$: AC-DC converter maximum AC power 28
6.4.6 Object $60AA_h$: AC-DC converter power transfer time 29
6.4.7 Object $60AB_h$: AC-DC converter discharging power transfer time 31
6.4.8 Object $60AC_h$: AC-DC converter power transfer Ah counter 32
6.4.9 Object $60AD_h$: AC-DC converter discharging Ah counter 34
6.4.10 Object $60AE_h$: AC-DC converter power transfer Wh counter 36
6.4.11 Object $60AF_h$: AC-DC converter discharging Wh counter 37
6.4.12 Object $60B0_h$: AC-DC converter actual AC voltage 39
6.4.13 Object $60B1_h$: AC-DC converter actual AC current 40
6.4.14 Object $60B2_h$: AC-DC converter actual AC power 42
6.4.15 Object $60B3_h$: AC-DC converter power transfer count number 44
6.4.16 Object $60B4_h$: AC-DC converter discharging count number 45
6.4.17 Object $60B5_h$: AC-DC converter temperature switch off counter 47
6.4.18 Object $60B6_h$: AC-DC converter short cuts switch off counter 48
6.4.19 Object $60B7_h$: AC-DC converter minimum DC voltage 50
6.4.20 Object $60B8_h$: AC-DC converter maximum DC voltage 52

6.4.21 Object $60B9_h$: AC-DC converter maximum DC current 53
6.4.22 Object $60BA_h$: AC-DC converter maximum DC power 55
6.5 Produced application objects by voltage converter unit (optional) 56
6.5.1 General 56
6.5.2 Object $60A5_h$: VCU position and class 56
6.5.3 Object $60D0_h$ 3P topology DC1 positive voltage 59
6.5.4 Object $60D1_h$ 3P topology DC1 negative voltage 61
6.5.5 Object $60D2_h$ 3P topology DC2 positive voltage 62
6.5.6 Object $60D3_h$ 3P topology DC2 negative voltage 64
6.5.7 Object $60D4_h$ Overload capability DC1 65
6.5.8 Object $60D5_h$ Overload capability DC2 67
6.5.9 Object $60D6_h$ Overload capability AC1 69
6.5.10 Object $60D7_h$ Overload capability AC2 71
6.5.11 Object $60D8_h$ VCU frequency thresholds AC1 72
6.5.12 Object $60D9_h$ VCU frequency thresholds AC2 74
6.5.13 Object $60DA_h$ Maximum L1 apparent power AC1 76
6.5.14 Object $60DB_h$ Maximum L2 apparent power AC1 77
6.5.15 Object $60DC_h$ Maximum L3 apparent power AC1 79
6.5.16 Object $60DD_h$ Maximum L1 apparent power AC2 81
6.5.17 Object $60DE_h$ Maximum L2 apparent power AC2 82
6.5.18 Object $60DF_h$ Maximum L3 apparent power AC2 84
6.5.19 Object $60E1_h$ Maximum L1 real power AC1 85
6.5.20 Object $60E2_h$ Maximum L2 real power AC1 87
6.5.21 Object $60E3_h$ Maximum L3 real power AC1 89
6.5.22 Object $60E4_h$ Maximum L1 real power AC2 90
6.5.23 Object $60E5_h$ Maximum L2 real power AC2 92
6.5.24 Object $60E6_h$ Maximum L3 real power AC2 93
6.5.25 Object $60E7_h$ Maximum L1 reactive power AC1 95
6.5.26 Object $60E8_h$ Maximum L2 reactive power AC1 97
6.5.27 Object $60E9_h$ Maximum L3 reactive power AC1 98
6.5.28 Object $60EA_h$ Maximum L1 reactive power AC2 100
6.5.29 Object $60EB_h$ Maximum L2 reactive power AC2 101
6.5.30 Object $60EC_h$ Maximum L3 reactive power AC2 103
6.5.31 Object $60ED_h$ Maximum L1 current AC1 105
6.5.32 Object $60EE_h$ Maximum L2 current AC1 106
6.5.33 Object $60EF_h$ Maximum L3 current AC1 108
6.5.34 Object $609A_h$ Maximum L1 current AC2 109
6.5.35 Object $609B_h$ Maximum L2 current AC2 111
6.5.36 Object $609C_h$ Maximum L3 current AC2 113
6.5.37 Object $609D_h$ Maximum N current AC1 114
6.5.38 Object $609E_h$ Maximum N current AC2 116

6.5.39 Object $603F_h$: DC-DC converter actual current side B 117
6.5.40 Object 6041_h: DC-DC converter actual voltage side B 119
6.6 Consumed application objects by AC-DC converter (optional) 121
6.6.1 General 121
6.6.2 Object $60BE_h$: AC-DC converter set maximum AC power 121
6.7 Consumed application objects for power transfer 122
6.7.1 General 122
6.7.2 Object $60F0_h$: Connected battery systems data - Instance 122
6.7.3 Object $60F1_h$: Connected battery system data - Node-ID 125
6.7.4 Object $60F2_h$: Connected battery system data - Device alarm capability (optional) 126
6.7.5 Object $60F3_h$: Connected battery system data - Type of battery cells 128
6.7.6 Object $60F4_h$: Connected battery system data - Battery system rated Wh capacity 130
6.7.7 Object $60F5_h$: Connected battery system maximum voltage 131
6.7.8 Object $60F6_h$: Connected battery system minimum voltage 132
6.7.9 Object $60F7_h$: Connected battery system maximum input current during charge 133
6.7.10 Object $60F8_h$: Requested battery system charge limit 134
6.7.11 Object $60F9_h$: Connected battery system data - maximum charge temperature (optional) 136
6.7.12 Object $60FA_h$: Connected battery system data - Battery system minimum charge temperature (optional) 137
6.7.13 Object $60FB_h$: Connected battery system data - Device alarm status (optional) 138
6.7.14 Object $60FC_h$: Connected battery system data - Control word 140
7 Consumed application objects by VCU in stationary applications (optional) 141
7.1 General 141
7.2 Object $60BF_h$: Frequency setpoint AC1 141
7.3 Object $60C0_h$: Frequency setpoint AC2 142
7.4 Object $60C4_h$: Current setpoint AC1 143
7.5 Object $60C1_h$: Current setpoint AC2 145
7.6 Object $60C2_h$: Voltage setpoint AC1 146
7.7 Object $60C3_h$: Voltage setpoint AC2 147
7.8 Object $60A8_h$: Reactive power control 148
7.9 Object $60A9_h$: Power limitation setpoint 150
7.10 Object $60AA_h$: Constant reactive power setpoint 151
7.11 Object $60AB_h$: Constant power factor cos φ setpoint 152
7.12 Object $60AC_h$: Characteristic curve cos φ (P_N) 154
7.13 Object $60AD_h$: Characteristic curve $Q(U)$ 157
Bibliography 162

Figure 1 – FSA for voltage converter unit 15
Figure 2 – Value structure 19

Figure 3 – Object structure 57
Figure 4 – Object structure 65
Figure 5 – Object structure 67
Figure 6 – Object structure 69
Figure 7 – Object structure 71
Figure 8 – Object structure 72
Figure 9 – Object structure 74
Figure 10 – Object structure supported virtual devices (informative) 122
Figure 11 – Object structure (informative) 126
Figure 12 – Object structure constant reactive power setpoint 151
Figure 13 – Object structure constant reactive power setpoint 153
Figure 14 – Object structure fitting point 154
Figure 15 – Object structure power factor 155
Figure 16 – Object structure fitting point control 158

Table 1 – States behaviour 16
Table 2 – Transitions, events and actions 17
Table 3 – Value definition for VD specific FSA control 18
Table 4 – Value definition for virtual device FSA state 19
Table 5 – Value definition 20
Table 6 – Object description 21
Table 7 – Entry description 21
Table 8 – Object description 23
Table 9 – Entry description 23
Table 10 – Object description 25
Table 11 – Entry description 25
Table 12 – Object description 26
Table 13 – Entry description 26
Table 14 – Object description 28
Table 15 – Entry description 28
Table 16 – Object description 29
Table 17 – Entry description 30
Table 18 – Object description 31
Table 19 – Entry description 31
Table 20 – Object description 33
Table 21 – Entry description 33
Table 22 – Object description 34
Table 23 – Entry description 34
Table 24 – Object description 36
Table 25 – Entry description 36
Table 26 – Object description 37
Table 27 – Entry description 38
Table 28 – Object description 39

Table 29 – Entry description 39
Table 30 – Object description 41
Table 31 – Entry description 41
Table 32 – Object description 42
Table 33 – Entry description 42
Table 34 – Object description 44
Table 35 – Entry description 44
Table 36 – Object description 45
Table 37 – Entry description 46
Table 38 – Object description 47
Table 39 – Entry description 47
Table 40 – Object description 49
Table 41 – Entry description 49
Table 42 – Object description 50
Table 43 – Entry description 50
Table 44 – Object description 52
Table 45 – Entry description 52
Table 46 – Object description 53
Table 47 – Entry description 54
Table 48 – Object description 55
Table 49 – Entry description 55
Table 50 – Value definition 57
Table 51 – Object description 58
Table 52 – Entry description 58
Table 53 – Object description 59
Table 54 – Entry description 59
Table 55 – Object description 61
Table 56 – Entry description 61
Table 57 – Object description 62
Table 58 – Entry description 63
Table 59 – Object description 64
Table 60 – Entry description 64
Table 61 – Object description 66
Table 62 – Entry description 66
Table 63 – Object description 67
Table 64 – Entry description 68
Table 65 – Object description 69
Table 66 – Entry description 69
Table 67 – Object description 71
Table 68 – Entry description 71
Table 69 – Object description 73
Table 70 – Entry description 73
Table 71 – Object description 74

Table 72 – Entry description 75
Table 73 – Object description 76
Table 74 – Entry description 76
Table 75 – Object description 78
Table 76 – Entry description 78
Table 77 – Object description 79
Table 78 – Entry description 79
Table 79 – Object description 81
Table 80 – Entry description 81
Table 81 – Object description 82
Table 82 – Entry description 83
Table 83 – Object description 84
Table 84 – Entry description 84
Table 85 – Object description 86
Table 86 – Entry description 86
Table 87 – Object description 87
Table 88 – Entry description 87
Table 89 – Object description 89
Table 90 – Entry description 89
Table 91 – Object description 90
Table 92 – Entry description 91
Table 93 – Object description 92
Table 94 – Entry description 92
Table 95 – Object description 94
Table 96 – Entry description 94
Table 97 – Object description 95
Table 98 – Entry description 95
Table 99 – Object description 97
Table 100 – Entry description 97
Table 101 – Object description 98
Table 102 – Entry description 99
Table 103 – Object description 100
Table 104 – Entry description 100
Table 105 – Object description 102
Table 106 – Entry description 102
Table 107 – Object description 103
Table 108 – Entry description 103
Table 109 – Object description 105
Table 110 – Entry description 105
Table 111 – Object description 106
Table 112 – Entry description 107
Table 113 – Object description 108
Table 114 – Entry description 108

Table 115 – Object description 110
Table 116 – Entry description 110
Table 117 – Object description 111
Table 118 – Entry description 111
Table 119 – Object description 113
Table 120 – Entry description 113
Table 121 – Object description 114
Table 122 – Entry description 115
Table 123 – Object description 116
Table 124 – Entry description 116
Table 125 – Object description 118
Table 126 – Entry description 118
Table 127 – Object description 119
Table 128 – Entry description 119
Table 129 – Object description 121
Table 130 – Entry description 121
Table 131 – Value definition for bit fields (informative) 122
Table 132 – Object description 124
Table 133 – Entry description 124
Table 134 – Value definition 125
Table 135 – Object description 125
Table 136 – Entry description 125
Table 137 – Value definition (informative) 126
Table 138 – Object description 127
Table 139 – Entry description 128
Table 140 – Object description 129
Table 141 – Entry description 129
Table 142 – Object description 130
Table 143 – Entry description 130
Table 144 – Object description 131
Table 145 – Entry description 131
Table 146 – Object description 132
Table 147 – Entry description 132
Table 148 – Object description 133
Table 149 – Entry description 134
Table 150 – Value definition 135
Table 151 – Object description 135
Table 152 – Entry description 135
Table 153 – Object description 136
Table 154 – Entry description 136
Table 155 – Object description 137
Table 156 – Entry description 138
Table 157 – Object description 139

Table 158 – Entry description 139
Table 159 – Object description..... 140
Table 160 – Entry description 140
Table 161 – Object description..... 141
Table 162 – Entry description 141
Table 163 – Object description..... 142
Table 164 – Entry description 143
Table 165 – Object description..... 144
Table 166 – Entry description 144
Table 167 – Object description..... 145
Table 168 – Entry description 145
Table 169 – Object description..... 146
Table 170 – Entry description 146
Table 171 – Object description..... 147
Table 172 – Entry description 147
Table 173 – Value definition for reactive power control 148
Table 174 – Object description..... 149
Table 175 – Entry description 149
Table 176 – Object description..... 150
Table 177 – Entry description 150
Table 178 – Value definition for constant reactive power setpoint 151
Table 179 – Object description..... 151
Table 180 – Entry description 152
Table 181 – Value definition for constant reactive power setpoint 153
Table 182 – Object description..... 153
Table 183 – Entry description 153
Table 184 – Value definition fitting point control..... 155
Table 185 – Value definition for constant reactive power setpoint 155
Table 186 – Object description..... 155
Table 187 – Entry description 155
Table 188 – Value definition fitting point control..... 158
Table 189 – Object description..... 158
Table 190 – Entry description 158

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

ELECTRIC VEHICLES CONDUCTIVE CHARGING SYSTEM –

Part 3-6: DC EV supply equipment where protection relies on double or reinforced insulation – Voltage converter unit communication

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 61851-3-6 has been prepared by IEC technical committee 69: Electrical power/energy transfer systems for electrically propelled road vehicles and industrial trucks. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
69/652/DTS	69/673/RVDTS 69/673A/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

In this document, the following print types are used:

– requirements: in roman type;

– notes: in small roman type;

– **text formatted in bold and using mixed capital and underline are used as state names and are not to be translated**.

A list of all parts in the IEC 61851 series, published under the general title *Electric vehicles conductive charging system,* can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

This document is published in separate parts according to the following structure:

IEC TS 61851-3-1, *Electric vehicles conductive charging system – Part 3-1: DC EV supply equipment where protection relies on double or reinforced insulation – General rules and requirements for stationary equipment*

IEC TS 61851-3-2, *Electric vehicles conductive charging system – Part 3-2: DC EV supply equipment where protection relies on double or reinforced insulation – Particular requirements for portable and mobile equipment*

IEC TS 61851-3-4, *Electric vehicles conductive charging system – Part 3-4: DC EV supply equipment where protection relies on double or reinforced insulation – General definitions and requirements for CANopen communication*

IEC TS 61851-3-5, *Electric vehicles conductive charging system – Part 3-5: DC EV supply equipment where protection relies on double or reinforced insulation – Pre-defined communication parameters and general application objects*

IEC TS 61851-3-6, *Electric vehicles conductive charging system – Part 3-6: DC EV supply equipment where protection relies on double or reinforced insulation – Voltage converter unit communication*

IEC TS 61851-3-7, *Electric vehicles conductive charging system – Part 3-7: DC EV supply equipment where protection relies on double or reinforced insulation – Battery system communication*

ELECTRIC VEHICLES CONDUCTIVE CHARGING SYSTEM –

Part 3-6: DC EV supply equipment where protection relies on double or reinforced insulation – Voltage converter unit communication

1 Scope

This part of IEC 61851, which is a Technical Specification, applies to CANopen communication for the conductive transfer of electric power between the supply network and an electric road vehicle or a removable RESS or traction-battery of an electric road vehicle.

This document provides application objects provided by the AC/DC VCU or DC/DC VCU.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TS 61851-3-2:2023, *Electric vehicles conductive charging system – Part 3-2: DC EV supply equipment where protection relies on double or reinforced insulation – Particular requirements for portable and mobile equipment*

IEC TS 61851-3-4: 2023, *Electric vehicles conductive charging system – Part 3-4:DC EV supply equipment where protection relies on double or reinforced insulation – General definitions and requirements for CANopen communication*

IEC TS 61851-3-5: 2023, *Electric vehicles conductive charging system – Part 3-5: DC EV supply equipment where protection relies on double or reinforced insulation – Pre-defined communication parameters and general application objects*

EN 50325-4:2002, *Industrial communications subsystem based on ISO 11898 (CAN) for controller- device interfaces – Part 4: CANopen*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC TS 61851-3-4:2023 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

4 Symbols and abbreviated terms

For the purposes of this document, the symbols and abbreviated terms given in IEC TS 61851-3-4:2023 apply.