IEC TS 62271-316

Edition 1.0 2024-11
EXTENDED VERSION

TECHNICAL SPECIFICATION



This full version of IEC TS 62271-316:2024 includes the content of the references made to IEC TS 62271-5:2024

High-voltage switchgear and controlgear – Part 316: Direct current by-pass switches and paralleling switches

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.130.10

ISBN 978-2-8327-0050-1

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

CONTENTS

FOREWORD 7
INTRODUCTION to IEC TS 62271-5:2024 9
1 Scope 10
2 Normative references 10
3 Terms and definitions 13
3.1 General terms and definitions 13
3.2 Assemblies of switchgear and controlgear 19
3.3 Parts of assemblies 19
3.4 Switching devices 19
3.5 Parts of switchgear and controlgear 23
3.6 Operational characteristics of switchgear and controlgear 28
3.7 Characteristic quantities 34
3.8 Index of definitions 41
4 Normal and special service conditions 45
4.1 Normal service conditions 45
4.2 Special service conditions 46
5 Ratings 48
5.1 General 48
5.2 Rated direct voltage (U_{rd}) 49
5.3 Rated insulation level (U_{dd}, U_p, U_s) 50
5.4 Rated continuous current (I_{rd}) 53
5.5 Rated values of short-time withstand current 54
5.6 Rated supply voltage of auxiliary and control circuits (U_a) 56
5.7 Rated supply frequency of auxiliary and control circuits 57
5.101 Rated commutation current 58
5.102 Rated operating sequence 58
6 Design and construction 58
6.1 Requirements for liquids in switchgear and controlgear 58
6.2 Requirements for gases in switchgear and controlgear 58
6.3 Earthing of switchgear and controlgear 58
6.4 Auxiliary and control equipment and circuits 59
6.5 Dependent power operation 63
6.6 Stored energy operation 63
6.7 Independent unlatched operation (independent manual or power operation) 64
6.8 Manually operated actuators 65
6.9 Operation of releases 65
6.10 Pressure/level indication 65
6.11 Nameplates 66
6.12 Locking devices 69
6.13 Position indication 69
6.14 Degrees of protection provided by enclosures 69
6.15 Creepage distances for outdoor insulators 70
6.16 Gas and vacuum tightness 70
6.17 Tightness for liquid systems 71
6.18 Fire hazard (flammability) 71

6.19 Electromagnetic compatibility (EMC) 71
6.20 X-ray emission 72
6.21 Corrosion 72
6.22 Filling levels for insulation, switching and/or operation 72
6.101 Design of BPSs and PSs 72
6.102 General requirement for operation 73
6.103 Pressure limits of fluids for operation 73
6.104 Time quantities 73
6.105 Static mechanical loads 74
7 Type tests 74
7.1 General 74
7.2 Dielectric tests 76
7.3 Resistance measurement 85
7.4 Continuous current tests 86
7.5 Short-time withstand current and peak withstand current tests 93
7.6 Verification of the protection 95
7.7 Tightness tests 96
7.8 Electromagnetic compatibility tests (EMC) 99
7.9 Additional tests on auxiliary and control circuits 105
7.10 X-radiation test for vacuum interrupters 108
7.101 Mechanical and environmental tests 110
7.102 Current commutation test 119
8 Routine tests 119
8.1 General 119
8.2 Dielectric test on the main circuit 120
8.3 Tests on auxiliary and control circuits 121
8.4 Measurement of the resistance of the main circuit 122
8.5 Tightness test 122
8.6 Design and visual checks 123
8.101 Mechanical operating tests 123
9 Guide to the selection of switchgear and controlgear (informative) 124
9.1 General 124
9.2 Selection of rated values 125
9.3 Cable-interface considerations 127
9.4 Continuous or temporary overload due to changed service conditions 127
9.5 Environmental aspects 127
10 Information to be given with enquiries, tenders and orders (informative) 128
10.1 General 128
10.2 Information with enquiries and orders 128
10.3 Information with tenders 130
11 Transport, storage, installation, operating instructions and maintenance 132
11.1 General 132
11.2 Conditions during transport, storage and installation 132
11.3 Installation 132
11.4 Operating instructions 140
11.5 Maintenance 140
11.101 Resistors and capacitors 143
12 Safety 143

12.1 General 143
12.2 Precautions by manufacturers 144
12.3 Precautions by users 144
13 Influence of the product on the environment 145
Annex A (informative) Examples of HVDC side switchgear arrangement for one pole in an HVDC substation 146
Annex B (informative) Exposure to pollution 148
B.1 General 148
B.2 Minimum requirements for switchgear in normal service condition 148
B.3 Minimum requirements for switchgear in special service condition 148
Annex C (informative) Preferred insulation levels for rated voltages lower than 105 kV 149
Annex D (informative) Short-circuit current in HVDC systems 150
D.1 VSC HVDC 150
D.2 LCC HVDC 151
D.3 Special case of LCC HVDC DC faults – LCC as diode bridge 151
D.4 HVDC systems with DC circuit-breakers 153
D.5 Calculation of the rated short-time withstand direct current 154
D.6 Calculation of Joule integral value (E_j) 155
Annex E (informative) References for auxiliary and control circuit components 156
Annex F (informative) List of symbols 158
Annex G (normative) Method for the weatherproofing test for outdoor switchgear and controlgear 160
Annex H (normative) Tolerances on test quantities during tests 163
Annex I (informative) Extension of validity of type tests 166
I.1 General 166
I.2 Dielectric tests 166
I.3 Short-time withstand current and peak withstand current tests 166
I.4 Electromagnetic immunity test on auxiliary and control circuits 166
I.5 Environmental tests on auxiliary and control circuits 166
Annex J (normative) Identification of test objects 168
J.1 General 168
J.2 Data 168
J.3 Drawings 168
Annex K (informative) Test circuit for superimposed impulse voltage tests 170
K.1 General 170
K.2 Test circuit using blocking capacitor 170
K.3 Test circuit using sphere gap 170
Annex L (informative) Information and technical requirements to be given with enquiries, tenders and orders 172
L.1 General 172
L.2 Normal and special service conditions (refer to Clause 4) 172
L.3 Ratings (refer to Clause 5) 173
L.4 Design and construction (refer to Clause 6) 173
L.5 System information 174
L.6 Documentation for enquiries and tenders 174
Annex M (informative) Electromagnetic compatibility on site 175
Annex N (informative) Standardization activities of HVDC 176

Annex A (normative) Tolerances on test quantities during type tests 177
Annex B (normative) Records and reports of type tests 180
B.1 Information and results to be recorded 180
B.2 Information to be included in type test reports 180
Annex C (informative) Voltages associated with BPSs in different configurations 182
C.1 General 182
C.2 Case 1: BPS consisting of a single switching unit 182
C.3 Case 2: BPS consisting of two series connected switching units 184
Annex D (normative) Use of mechanical characteristics and related requirements 186
Bibliography 190

Figure 1 – Example of the location of BPSs in an HVDC transmission system 21
Figure 2 – Example of the location of a CPS in an HVDC transmission system 22
Figure 3 – Example of the location of a LPS in an HVDC transmission system 22
Figure 4 – BPS and PS – Opening and closing operations 36
Figure 5 – BPS and PS – Close-open cycle 37
Figure 6 – BPS and PS – Open-close cycle 38
Figure 1 – Schematic representation of superimposed impulse voltage tests 53
Figure 2 – Typical waveform of a short-circuit current in an HVDC system 55
Figure 3 – Examples of classes of contacts 63
Figure 7 – Example of two series connected BPSs 72
Figure 4 – Diagram of connections of a switching device 79
Figure 5 – Test sequence for polarity reversal tests 84
Figure 6 – Diagram of a test circuit for the radio interference voltage test 100
Figure 7 – Test location of radiation survey instrument 109
Figure 8 – Test sequence for low temperature test 114
Figure 9 – Test sequence for high temperature test 116
Figure 10 – Humidity test 118
Figure A.1 – Example of HVDC side switchgear arrangement for one pole in an HVDC substation 147
Figure D.1 – VSC HVDC under worst-case, pole-pole DC fault 150
Figure D.2 – LCC HVDC under worst-case, pole-pole DC fault 151
Figure D.3 – Special case LCC HVDC under worst-case, pole-pole DC fault 152
Figure D.4 – HVDC system with DC circuit-breaker under worst-case, pole-pole DC fault 153
Figure D.5 – DC circuit-breaker simple model 153
Figure D.6 – Equivalent fault current for calculation of rated short time withstand direct current 154
Figure G.1 – Arrangement for weatherproofing test 161
Figure G.2 – Nozzle for weatherproofing test 162
Figure K.1 – Test circuit for superimposed impulse tests using blocking capacitor 170
Figure K.2 – Test circuit for superimposed impulse tests using sphere gap 171
Figure C.1 – HVDC system with 3 series connected converter units per pole 182
Figure C.2 – Different ways to connect a BPS to the grid 183
Figure C.3 – HVDC system with 2 series connected converter units per pole 184

Figure D.1 – Example of reference mechanical characteristics (idealised curve) 187
Figure D.2 – Reference mechanical characteristics of Figure D.1 with the envelopes centred over the reference curve (+5 %, –5 %) 187
Figure D.3 – Reference mechanical characteristics of Figure D.1 with the envelope fully displaced upward from the reference curve (+10 %, –0 %) 188
Figure D.4 – Reference mechanical characteristics of Figure D.1 with the envelope fully displaced downward from the reference curve (+0 %, –10 %) 189

Table 1 – Preferred rated insulation levels 51
Table 2 – Direct voltage of auxiliary and control circuits 57
Table 3 – Alternating voltage of auxiliary and control circuits 57
Table 4 – Auxiliary contact classes 62
Table 1 – Nameplate information 66
Table 5 – Nameplate information 68
Table 2 – Examples of static horizontal and vertical forces for static terminal load 74
Table 3 – Mandatory type tests 75
Table 6 – Test conditions in general case 79
Table 4 – Test conditions in general case for BPSs according to Alternative 1 80
Table 5 – Test conditions in general case for BPSs according to Alternative 2 81
Table 6 – Test conditions in general case for PSs 81
Table 7 – Test conditions in case of impulse voltage tests across the isolating distance (or open switching device) 81
Table 8 – Test conditions in case of superimposed impulse voltage tests 82
Table 9 – Test conditions for polarity reversal tests 84
Table 10 – Limits of temperature and temperature rise for various parts, materials and dielectrics of high-voltage switchgear and controlgear 90
Table 11 – Permissible leakage rates for gas systems 97
Table 12 – Application of voltages at the fast transient/burst test 103
Table 13 – Application of voltage at the damped oscillatory wave test 103
Table 14 – Assessment criteria for transient disturbance immunity 104
Table 7 – Number of operating sequences 113
Table C.1 – Preferred insulation levels for rated voltages lower than 105 kV 149
Table E.1 – List of reference documents for auxiliary and control circuit components 156
Table H.1 – Tolerances on test quantities for type test 163
Table J.1 Drawing list and contents 168
Table A.1 – Tolerances on test quantities for type tests 178
Table C.1 – Voltage across the post insulator 184

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR –

Part 316: Direct current by-pass switches and paralleling switches

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

This extended version (EXV) of the official IEC Standard provides the user with the full content of the Standard.

IEC TS 62271-316:2024 EXV includes the content of IEC TS 62271-316:2024, and the references made to IEC TS 62271-5:2024.

The specific content of IEC TS 62271-316:2024 is displayed on a blue background.

IEC TS 62271-316 has been prepared by subcommittee 17A: Switching devices, of IEC technical committee 17: High-voltage switchgear and controlgear. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
17A/1407/DTS	17A/1414/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

This document shall be read in conjunction with IEC TS 62271-5:2024, to which it refers, and which is applicable unless otherwise specified in this document. In order to simplify the indication of corresponding requirements, the same numbering of clauses and subclauses is used as in IEC TS 62271-5. Modifications to these clauses and subclauses are given under the same references whilst additional subclauses are numbered from 101.

A list of all parts in the IEC 62271 series, published under the general title *High-voltage switchgear and controlgear,* can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION to IEC TS 62271-5:2024

This Technical Specification has been prepared by TC 17 and it defines common specifications for high-voltage direct current (HVDC) switchgear and controlgear covering both types of air insulated (AIS) and gas insulated (GIS) equipment of HVDC substations. This document includes rules for service conditions, ratings, design and construction requirements. Test requirements and criteria to proof for passing type and routine tests are defined in this document for development and manufacturing of HVDC switchgear.

This specification is applicable for both LCC and VSC HVDC technology.

SC 17A is in the process of preparing documents for the following HVDC switching devices:

– circuit-breakers (IEC TS 62271-313 [1])[1];
– disconnectors and earthing switches (IEC TS 62271-314 [2]);
– transfer switches (IEC TS 62271-315 [3]);
– by-pass switches and paralleling switches (IEC TS 62271-316 [4]).

SC 17C is in the process of preparing a document for DC gas insulated switchgears (IEC TS 62271-318 [5]).

Standardization of direct voltages is the responsibility of TC 8 (System aspects of electrical energy supply).

TC 99 (Insulation co-ordination and system engineering of high voltage electrical power installations above 1,0 kV AC and 1,5 kV DC) defines requirements of DC substations for safety of insulation, equipment, installation and earthing (IEC 61936-2).

TC 115 (High Voltage Direct Current (HVDC) transmission for DC voltages above 100 kV) is responsible for DC transmission system aspects. It is the responsibility of TC 115 to define requirements for different equipment (e. g. switching devices) from system point of view. These definitions are implemented in documents from other TCs. Several Working Groups and Maintenance Teams are preparing documents on reliability, EMC, asset management, system design, DC harmonics, testing, HVDC grids, VSC and LCC converter and insulation coordination for HVDC systems.

[1] Numbers in square brackets refer to the Bibliography.

HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR –

Part 316: Direct current by-pass switches and paralleling switches

1 Scope

This part of IEC 62271, which is a Technical Specification, is applicable to direct current (DC) by-pass switches (BPS) and paralleling switches (PS) designed for indoor or outdoor installation and for operation on HVDC transmission systems having direct voltages of 100 kV and above.

Switches other than mechanical switching devices used for the same applications specified here are not covered by this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60038:2009, *IEC standard voltages*

IEC 60050-151, *International Electrotechnical Vocabulary (IEV) – Part 151: Electrical and magnetic devices*, (available at www.electropedia.org)

IEC 60050-441, *International Electrotechnical Vocabulary (IEV) – Part 441: Switchgear, controlgear and fuses*, (available at www.electropedia.org)

IEC 60050-442, *International Electrotechnical Vocabulary (IEV) – Part 442: Electrical accessories*, (available at www.electropedia.org)

IEC 60050-461, *International Electrotechnical Vocabulary (IEV) – Part 461: Electric cables*, (available at www.electropedia.org)

IEC 60050-601, *International Electrotechnical Vocabulary (IEV) – Part 601: Generation, transmission and distribution of electricity – General*, (available at www.electropedia.org)

IEC 60050-614, *International Electrotechnical Vocabulary – Part 614: Generation, transmission and distribution of electricity – Operation*, (available at www.electropedia.org)

IEC 60050-811, *International Electrotechnical Vocabulary (IEV) – Part 811: Electric traction*

IEC 60050-826:2022, *International Electrotechnical Vocabulary (IEV) – Part 826: Electrical installations*

IEC 60060-1, *High-voltage test techniques – Part 1: General definitions and test requirements*

IEC 60068-2-1:2007, *Environmental testing – Part 2-1: Tests – Test A: Cold*

IEC 60068-2-2:2007, *Environmental testing – Part 2-2: Tests – Test B: Dry heat*

IEC 60068-2-17:1994, *Basic environmental testing procedures – Part 2-17: Tests – Test Q: Sealing*

IEC 60068-2-30:2005, *Environmental testing – Part 2-30: Tests – Test Db: Damp heat, cyclic (12 h + 12 h cycle)*

IEC 60071-1:2019, *Insulation co-ordination – Part 1: Definitions, principles and rules*

IEC 60071-2:2018, *Insulation co-ordination – Part 2: Application guidelines*

IEC 60071-11:2022, *Insulation coordination – Part 11: Definitions, principles and rules for HVDC system*

IEC 60071-12:2022, *Insulation coordination – Part 12: Application guidelines for LCC HVDC converter stations*

IEC 60085:2007, *Electrical insulation – Thermal evaluation and designation*

IEC 60255-21-1:1988, *Electrical relays – Part 21: Vibration, shock, bump and seismic tests on measuring relays and protection equipment – Section One: Vibration tests (sinusoidal)*

IEC 60270, *High-voltage test techniques – Partial discharge measurements*

IEC 60296, *Fluids for electrotechnical applications – Mineral insulating oils for electrical equipment*

IEC 60376, *Specification of technical grade sulphur hexafluoride (SF_6) and complementary gases to be used in its mixtures for use in electrical equipment*

IEC 60417:2006, *Graphical symbols for use on equipment (available at http://www.graphical-symbols.info/equipment)*

IEC 60437, *Radio interference test on high-voltage insulators*

IEC 60480, *Specifications for the re-use of sulphur hexafluoride (SF_6) and its mixtures in electrical equipment*

IEC 60512-2-2, *Connectors for electronic equipment – Tests and measurements – Part 2-2: Electrical continuity and contact resistance tests – Test 2b: Contact resistance – Specified test current method*

IEC 60529:1989, *Degrees of protection provided by enclosures (IP Code)*
IEC 60529:1989/AMD1:1999
IEC 60529:1989/AMD2:2013

IEC 60633:2019, *High-voltage direct current (HVDC) transmission – Vocabulary*

IEC TS 60815-4:2016, *Selection and dimensioning of high-voltage insulators intended for use in polluted conditions – Part 4: Insulators for DC systems*

IEC 61000-4-4, *Electromagnetic compatibility (EMC) – Part 4-4: Testing and measurement techniques – Electrical fast transient/burst immunity test*

IEC 61000-4-11, *Electromagnetic compatibility (EMC) – Part 4-11: Testing and measurement techniques – Voltage dips, short interruptions and voltage variations immunity tests for equipment with input current up to 16 A per phase*

IEC 61000-4-17:1999, *Electromagnetic compatibility (EMC) – Part 4-17: Testing and measurement techniques – Ripple on d.c. input power port immunity test*

IEC 61000-4-18, *Electromagnetic compatibility (EMC) – Part 4-18: Testing and measurement techniques – Damped oscillatory wave immunity test*

IEC 61000-4-29, *Electromagnetic compatibility (EMC) – Part 4-29: Testing and measurement techniques – Voltage dips, short interruptions and voltage variations on DC input power port immunity tests*

IEC 61000-6-2*, Electromagnetic compatibility (EMC) – Part 6-2: Generic standards – Immunity standard for industrial environments*

IEC 61000-6-5, *Electromagnetic compatibility (EMC) – Part 6-5: Generic standards – Immunity for equipment used in power station and substation environment*

IEC 61180, *High-voltage test techniques for low-voltage equipment – Definitions, test and procedure requirements, test equipment*

IEC TS 61245, *Artificial pollution tests on high-voltage ceramic and glass insulators to be used on DC systems*

IEC 61810-7:2006, *Electromechanical elementary relays – Part 7: Test and measurement procedures*

IEC 62262:2002, *Degrees of protection provided by enclosures for electrical equipment against external mechanical impacts (IK code)*

IEC 62271-1:2017, *High-voltage switchgear and controlgear – Part 1: Common specifications for alternating current switchgear and controlgear*
IEC 62271-1:2017/AMD1:2021

IEC 62271-4, *High-voltage switchgear and controlgear – Part 4: Handling procedures for gases for insulation and/or switching*

IEC TS 62271-5:2024, *High-voltage switchgear and controlgear – Part 5: Common specifications for direct current switchgear*

IEC 62271-102:2018, *High-voltage switchgear and controlgear – Part 102: Alternating current disconnectors and earthing switches*
IEC 62271-102:2018/AMD1:2022

IEC TS 62271-315:2024, *High-voltage switchgear and controlgear – Part 315: Direct current (DC) transfer switches*

CISPR 11:2015, *Industrial, scientific and medical equipment – Radio-frequency disturbance characteristics – Limits and methods of measurement*

CISPR 16-1 (all parts), *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1: Radio disturbance and immunity measuring apparatus*

CISPR TR 18-2, *Radio interference characteristics of overhead power lines and high-voltage equipment – Part 2: Methods of measurement and procedure for determining limits*

IEC TS 62271-316

Edition 1.0 2024-11

TECHNICAL SPECIFICATION

High-voltage switchgear and controlgear –
Part 316: Direct current by-pass switches and paralleling switches



IEC TS 62271-316:2024-11(en)

CONTENTS

FOREWORD 5
1 Scope 7
2 Normative references 7
3 Terms and definitions 8
3.1 General terms and definitions 8
3.2 Assemblies of switchgear and controlgear 9
3.3 Parts of assemblies 9
3.4 Switching devices 9
3.5 Parts of switchgear and controlgear 11
3.6 Operational characteristics of switchgear and controlgear 13
3.7 Characteristic quantities 15
3.8 Index of definitions 20
4 Normal and special service conditions 22
5 Ratings 22
5.1 General 22
5.2 Rated direct voltage (U_{rd}) 23
5.3 Rated insulation level (U_{dd}, U_p, U_s) 24
5.4 Rated continuous current (I_{rd}) 24
5.5 Rated values of short-time withstand current 24
5.6 Rated supply voltage of auxiliary and control circuits (U_a) 24
5.7 Rated supply frequency of auxiliary and control circuits 24
5.8 Rated pressure of compressed gas supply for controlled pressure systems 24
5.101 Rated commutation current 25
5.102 Rated operating sequence 25
6 Design and construction 25
6.1 Requirements for liquids in switchgear and controlgear 25
6.2 Requirements for gases in switchgear and controlgear 25
6.3 Earthing of switchgear and controlgear 25
6.4 Auxiliary and control equipment and circuits 25
6.5 Dependent power operation 26
6.6 Stored energy operation 26
6.7 Independent unlatched operation (independent manual or power operation) 26
6.8 Manually operated actuators 26
6.9 Operation of releases 26
6.10 Pressure/level indication 26
6.11 Nameplates 26
6.12 Locking devices 28
6.13 Position indication 28
6.14 Degrees of protection provided by enclosures 28
6.15 Creepage distances for outdoor insulators 28
6.16 Gas and vacuum tightness 28
6.17 Tightness for liquid systems 28
6.18 Fire hazard (flammability) 28
6.19 Electromagnetic compatibility (EMC) 28
6.20 X-ray emission 28
6.21 Corrosion 28

6.22 Filling levels for insulation, switching and/or operation 28
6.101 Design of BPSs and PSs 29
6.102 General requirement for operation 29
6.103 Pressure limits of fluids for operation 30
6.104 Time quantities 30
6.105 Static mechanical loads 30
7 Type tests 31
7.1 General 31
7.2 Dielectric tests 32
7.3 Resistance measurement 35
7.4 Continuous current tests 35
7.5 Short-time withstand current and peak withstand current tests 36
7.6 Verification of the protection 36
7.7 Tightness tests 36
7.8 Electromagnetic compatibility tests (EMC) 36
7.9 Additional tests on auxiliary and control circuits 37
7.10 X-radiation test procedure for vacuum interrupters 38
7.101 Mechanical and environmental tests 38
7.102 Current commutation test 47
8 Routine tests 47
8.1 General 47
8.2 Dielectric test on the main circuit 47
8.3 Tests on auxiliary and control circuits 48
8.4 Measurement of the resistance of the main circuit 48
8.5 Tightness test 48
8.6 Design and visual checks 48
8.101 Mechanical operating tests 48
9 Guide to the selection of switchgear and controlgear (informative) 50
9.1 General 50
9.2 Selection of rated values 50
9.3 Cable-interface connections 52
9.4 Continuous or temporary overload due to changed service conditions 52
9.5 Environmental aspects 53
10 Information to be given with enquiries, tenders and orders (informative) 53
10.1 General 53
10.2 Information with enquiries and orders 53
10.3 Information to be given with tenders 54
11 Transport, storage, installation, operation instructions and maintenance 55
11.1 General 55
11.2 Conditions during transport, storage and installation 55
11.3 Installation 55
11.4 Operating instructions 61
11.5 Maintenance 61
11.101 Resistors and capacitors 61
12 Safety 61
13 Influence of the product on the environment 61
Annex A (normative) Tolerances on test quantities during type tests 62
Annex B (normative) Records and reports of type tests 65

B.1 Information and results to be recorded 65
B.2 Information to be included in type test reports 65
Annex C (informative) Voltages associated with BPSs in different configurations 67
C.1 General 67
C.2 Case 1: BPS consisting of a single switching unit 67
C.3 Case 2: BPS consisting of two series connected switching units 69
Annex D (normative) Use of mechanical characteristics and related requirements 71
Bibliography 75

Figure 1 – Example of the location of BPSs in an HVDC transmission system 10
Figure 2 – Example of the location of a CPS in an HVDC transmission system 11
Figure 3 – Example of the location of a LPS in an HVDC transmission system 11
Figure 4 – BPS and PS – Opening and closing operations 15
Figure 5 – BPS and PS – Close-open cycle 16
Figure 6 – BPS and PS – Open-close cycle 17
Figure 7 – Example of two series connected BPSs 29
Figure 8 – Test sequence for low temperature test 42
Figure 9 – Test sequence for high temperature test 44
Figure 10 – Humidity test 46
Figure C.1 – HVDC system with 3 series connected converter units per pole 67
Figure C.2 – Different ways to connect a BPS to the grid 68
Figure C.3 – HVDC system with 2 series connected converter units per pole 70
Figure D.1 – Example of reference mechanical characteristics (idealised curve) 72
Figure D.2 – Reference mechanical characteristics of Figure D.1 with the envelopes centred over the reference curve (+5 %, –5 %) 72
Figure D.3 – Reference mechanical characteristics of Figure D.1 with the envelope fully displaced upward from the reference curve (+10 %, –0 %) 73
Figure D.4 – Reference mechanical characteristics of Figure D.1 with the envelope fully displaced downward from the reference curve (+0 %, –10 %) 74

Table 1 – Nameplate information 27
Table 2 – Examples of static horizontal and vertical forces for static terminal load 30
Table 3 – Mandatory type tests 31
Table 4 – Test conditions in general case for BPSs according to Alternative 1 33
Table 5 – Test conditions in general case for BPSs according to Alternative 2 34
Table 6 – Test conditions in general case for PSs 34
Table 7 – Number of operating sequences 40
Table A.1 – Tolerances on test quantities for type tests 63
Table C.1 – Voltage across the post insulator 69

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR –

Part 316: Direct current by-pass switches and paralleling switches

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights..

IEC TS 62271-316 has been prepared by subcommittee 17A: Switching devices, of IEC technical committee 17: High-voltage switchgear and controlgear. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
17A/1407/DTS	17A/1414/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

This document shall be read in conjunction with IEC TS 62271-5:2024, to which it refers, and which is applicable unless otherwise specified in this document. In order to simplify the indication of corresponding requirements, the same numbering of clauses and subclauses is used as in IEC TS 62271-5. Modifications to these clauses and subclauses are given under the same references whilst additional subclauses are numbered from 101.

A list of all parts in the IEC 62271 series, published under the general title *High-voltage switchgear and controlgear*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR –

Part 316: Direct current by-pass switches and paralleling switches

1 Scope

This part of IEC 62271, which is a Technical Specification, is applicable to direct current (DC) by-pass switches (BPS) and paralleling switches (PS) designed for indoor or outdoor installation and for operation on HVDC transmission systems having direct voltages of 100 kV and above.

Switches other than mechanical switching devices used for the same applications specified here are not covered by this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-151, *International Electrotechnical Vocabulary (IEV) – Part 151: Electrical and magnetic devices*, (available at www.electropedia.org)

IEC 60050-441, *International Electrotechnical Vocabulary (IEV) – Part 441: Switchgear, controlgear and fuses*, (available at www.electropedia.org)

IEC 60050-442, *International Electrotechnical Vocabulary (IEV) – Part 442: Electrical accessories*, (available at www.electropedia.org)

IEC 60050-461, *International Electrotechnical Vocabulary (IEV) – Part 461: Electric cables*, (available at www.electropedia.org)

IEC 60050-601, *International Electrotechnical Vocabulary (IEV) – Part 601: Generation, transmission and distribution of electricity – General*, (available at www.electropedia.org)

IEC 60050-614, *International Electrotechnical Vocabulary – Part 614: Generation, transmission and distribution of electricity – Operation*, (available at www.electropedia.org)

IEC 60060-1, *High-voltage test techniques – Part 1: General definitions and test requirements*

IEC 60071-11:2022, *Insulation coordination – Part 11: Definitions, principles and rules for HVDC system*

IEC 60071-12:2022, *Insulation coordination – Part 12: Application guidelines for LCC HVDC converter stations*

IEC 60296, *Fluids for electrotechnical applications – Mineral insulating oils for electrical equipment*

IEC 60376, *Specification of technical grade sulphur hexafluoride (SF_6) and complementary gases to be used in its mixtures for use in electrical equipment*

IEC 60480, *Specifications for the re-use of sulphur hexafluoride (SF_6) and its mixtures in electrical equipment*

IEC 60633:2019, *High-voltage direct current (HVDC) transmission – Vocabulary*

IEC TS 62271-5:2024, *High-voltage switchgear and controlgear – Part 5: Common specifications for direct current switchgear*

IEC 62271-102:2018, *High-voltage switchgear and controlgear – Part 102: Alternating current disconnectors and earthing switches*
IEC 62271-102:2018/AMD1:2022

IEC TS 62271-315:2024, *High-voltage switchgear and controlgear – Part 315: Direct current (DC) transfer switches*