IEC TS 62607-3-5

Edition 1.0 2026-08

TECHNICAL SPECIFICATION

Nanomanufacturing - Key control characteristics -
Part 3-5: Nanophotonic products - Light conversion efficiency of quantum dot enabled light conversion films: luminance meter

ICS 07.120

ISBN 978-2-8327-1401-0

IEC TS 62607-3-5:2026-08(en)

THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD 2
INTRODUCTION 4
1 Scope 5
2 Normative references 5
3 Terms, definitions and abbreviated terms 5
3.1 Terms and definitions 5
3.2 Abbreviated terms 6
4 General 6
4.1 Ambient conditions for measurement 6
4.2 Standard darkroom conditions for LCE test 6
4.3 Measurement system for LCE test 7
5 Measurement of light conversion efficiency 8
5.1 General 8
5.2 Spectral radiance measurement instrument 8
5.3 Display backlight test platform 8
5.4 Sample preparation 8
5.5 Backlight setting 9
5.6 Measurement procedure 9
6 Test report 10
Bibliography 12

Figure 1 – Standard measurement system 7
Figure 2 – Schematic structure of Q-LCF 9

Table 1 – Test report - LCE of Q-LCF (blank) 11

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

Nanomanufacturing - Key control characteristics - Part 3-5: Nanophotonic products - Light conversion efficiency of quantum dot enabled light conversion films: luminance meter

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 62607-3-5 has been prepared by IEC technical committee 113: Nanotechnology for electrotechnical products and systems. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
113/957/DTS	113/986/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts of the IEC 62607 series, published under the general title *Nanomanufacturing - Key control characteristics,* can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

– reconfirmed,

– withdrawn, or

– revised.

INTRODUCTION

This document specifies how to measure the light conversion efficiency, which is one of key control characteristics of quantum dot enabled light conversion films (Q-LCFs).

Quantum dot (QD) is a kind of representative nanomaterial, has typical quantum confinement effects and exhibits distinct size-dependent properties, that is, the luminescence peak is adjustable with the QD size. QDs have broad absorption spectra, as the absorption edge is continuous for all wavelengths shorter than the absorption edge. They are also known for narrow emission spectra – a trait that arises when QDs are consistent in both size and composition. Using the same excitation source, commonly blue light-emitting diode, to excite quantum dots of different particle sizes, QDs of different particle sizes can emit spectra with different peak wavelengths which are larger than the excitation wavelength. Based on the above unique characteristics, Q-LCFs are used in display products, greatly improving the colour gamut. Currently Q-LCFs are widely adopted by television makers (manufacturers, suppliers, etc.) to add a new feature to liquid crystal displays.

Although they have such advantageous features, quantum dots are sensitive to water, oxygen, light, high temperature and so on. During the manufacturing process of Q-LCFs, various chemicals are used to form a solid matrix in which quantum dots are dispersed. After the quantum dots have been encapsulated in the films, water and oxygen still can pass through the polymer matrix and reach the quantum dots to a certain degree, depending on the barrier property of the matrix and encapsulation layer. During and after manufacturing, adverse effects, such as lowering of quantum efficiency and stability of quantum dots, will occur.

It is critical to measure quantum efficiency of quantum dots in Q-LCFs; however, measurement of this characteristic by integrating sphere is relatively complicated and of low test efficiency, the integrating sphere test has limitations, such as the sample size must be smaller than the size of the integrating sphere, and the luminance range of backlight is narrow. The light conversion efficiency (LCE) parameter is more meaningful than the quantum efficiency (QE) parameter in practical industrial applications, as the LED backlight usually has higher luminance. For measuring LCE, a luminance meter is used as the test tool, which only measures the number of photons within 2π steradian directly in front of the backlight after excitation of the sample. This is significantly less than the number of photons collected by the integrating sphere. So the light conversion efficiency (LCE) measured by this document is directly related to the luminance actually detected in the display industry, whereas the quantum efficiency is not. It is for this reason that LCE, a more straightforward characteristic, is measured instead. Brighter Q-LCFs correlate with higher quantum efficiency of the quantum dots inside the film.

These characteristics will enable supplier and purchaser of Q-LCFs to determine rapidly whether the quantum dots are stable and of high quantum efficiency in the matrix, or whether the quantum dots and matrix are matched, or whether the Q-LCFs satisfy the luminance and lifetime requirements, by using common equipment to test.

For predictable and reproducible results to be used in diversified situations, it is essential for characteristics to be described and assessed in a standardized manner and to standardize the methods for quality control of the manufacturing processes.

This document can also apply to other quantum dot conversion members such as quantum dot diffusing plate.

1 Scope

WARNING – Persons using this document should be familiar with normal laboratory practice. This document does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user to establish appropriate safety and health practices and to ensure compliance with any national regulatory conditions.

This part of IEC 62607 establishes a standardized method to determine the optical key control characteristic

– light conversion efficiency

for quantum dot enabled light conversion films (Q-LCFs) by

– luminance meter.

The light conversion efficiency is derived by the photoluminescence spectrum.

The typical application areas of this standardized measurement method are the nano-photoelectric display devices using Q-LCF as key component, and other relevant optical conversion devices.

2 Normative references

There are no normative references in this document.

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

– IEC Electropedia: available at https://www.electropedia.org/
– ISO Online browsing platform: available at https://www.iso.org/obp

3.1.1
quantum dot
QD
crystalline nanoparticle that exhibits size-dependent properties due to quantum confinement effects on the electronic states

[SOURCE: ISO/TS 27687:2008 [1], 4.7]

3.1.2
quantum dot enabled light conversion film
Q-LCF
optical film based on quantum dots that converts high-energy light at a particular wavelength into low-energy light at another wavelength

Note 1 to entry: Q-LCF is fabricated using quantum dots and a high-stability optical adhesive.