IEC TS 62607-4-10

Edition 1.0 2026-07

TECHNICAL SPECIFICATION

Nanomanufacturing - Key control characteristics -
Part 4-10: Nano-enabled energy storage - Electrochemical characteristics of carbon nanomaterial for the electrodes of electric double-layer capacitors: coin cell method

ICS 07.120

ISBN 978-2-8327-1356-3

IEC TS 62607-4-10:2026-07(en)

THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD 3
INTRODUCTION 5
1 Scope 6
2 Normative references 6
3 Terms and definitions 6
4 General 9
4.1 Preparation of the coin-type EDLCs of the tested carbon nanomaterial 9
4.2 Overview of the test 10
4.2.1 Test sequence 10
4.2.2 Test efficiency 10
4.3 Test conditions 11
4.4 Description of measurement equipment / apparatus 11
4.4.1 Potentiostat/galvanostat equipment 11
4.4.2 Environmental heating chamber 11
5 Measurement 11
5.1 Pre-conditioning of the coin-type EDLC samples 11
5.2 Specific capacitance 11
5.2.1 Charging and discharging process (CCC-CVC-CCD) 11
5.2.2 Data analysis 12
5.3 Rate capacitance 13
5.3.1 Charging and discharging process (CCC-CVC-CCD at different currents) 13
5.3.2 Data analysis 14
5.4 Voltage maintenance rate 15
5.4.1 Charging and discharging process (CCC-CVC process) 15
5.4.2 Data analysis 15
5.5 Endurance in cycling 16
5.5.1 Charging and discharging process (CCC-CCD) 16
5.5.2 Data analysis 17
5.6 Temperature endurance 17
5.6.1 Charging and discharging process (CVC) 17
5.6.2 Data analysis 18
6 Results to be reported 19
6.1 General 19
6.2 Sample identification 19
6.3 Assembly information of the coin-type EDLC 19
6.4 Test results 19
Annex A (informative) Test report 20
Annex B (informative) Case study - Nanoporous activated carbon 22
B.1 Sample information 22
B.2 Equipment 22
B.3 Specific capacitance 23
B.3.1 CCC-CVC-CCD process 23
B.3.2 Calculation 24
B.3.3 Post-treatment 25
B.4 Rate capacitance 25

B.4.1 CCC-CVC-CCD process 25
B.4.2 Calculation 26
B.5 Voltage maintenance rate 26
B.5.1 CCC-CVC process 26
B.5.2 Calculation 27
B.6 Endurance in cycling 27
B.6.1 CCC-CVC process 27
B.6.2 Calculation 28
B.7 Temperature endurance 29
B.7.1 Equipment 29
B.7.2 Testing results 30
B.7.3 Test report 30
Bibliography 33

Figure 1 – Overview of the test 10
Figure 2 – Voltage–time profile of the coin-type EDLC during the CCC-CVC-CCD process 12
Figure 3 – Rate capacitance test diagram 14
Figure 4 – Voltage maintenance rate test diagram 15
Figure 5 – Endurance in cycling test diagram 17
Figure 6 – Temperature endurance test diagram 18
Figure B.1 – Potentiostat/galvanostat equipment 23
Figure B.2 – V - t curve of the CCC-CVC-CCD process of the coin-type EDLC No.1 24
Figure B.3 – Rate capacitance results of the nanoporous activated carbon 26
Figure B.4 – V - t curves of coin-type EDLC No.12, No.14 and No.15 27
Figure B.5 – Endurance-in cycling test steps of coin-type EDLC No.12 28
Figure B.6 – Endurance-in cycling results of the nanoporous activated carbon 29
Figure B.7 – The environment heating chamber for temperature endurance testing 30
Figure B.8 – Temperature endurance results of the nanoporous activated carbon 30

Table 1 – Primary supporting materials 19
Table A.1 – Sample identification (according to IEC TS 62565-5-1) 20
Table A.2 – Assembly information and data 20
Table A.3 – Test results 21
Table B.1 – Coin-type EDLC sample information for electrochemical performance characterization of the nanoporous activated carbon 22
Table B.2 – Specific capacitance of the nanoporous activated carbon 25
Table B.3 – Specific capacitance ratio under different rate 26
Table B.4 – The voltage maintenance rate results of the nanoporous activated carbon 27
Table B.5 – Endurance in cycling results of the nanoporous activated carbon 29
Table B.6 – Sample identification of the sample nanoporous activated carbon 31
Table B.7 – Assembly information of the sample nanoporous activated carbon 31
Table B.8 – Test results of the sample nanoporous activated carbon 32

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

Nanomanufacturing - Key control characteristics - Part 4-10: Nano-enabled energy storage - Electrochemical characteristics of carbon nanomaterial for the electrodes of electric double-layer capacitors: coin cell method

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 62607-4-10 has been prepared by IEC technical committee 113: Nanotechnology for electrotechnical products and systems. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
113/959/DTS	113/983/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts of the IEC 62607 series, published under the general title *Nanomanufacturing - Key control characteristics,* can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

– reconfirmed,

– withdrawn, or

– revised.

INTRODUCTION

Electrochemical capacitors are widely used in electric vehicles, high-speed trains, aviation, photovoltaics, wind power and electronics, due to their ultra-fast charge/discharge capability, long cycle life, wide working temperature range, high safety and reliability and low maintenance costs.

Electric double-layer capacitors (EDLCs) are a category of the electrochemical capacitors. The mechanism of energy storage for EDLCs relies on reversible ion adsorption at the interface between the active material and electrolyte. Therefore, materials with a large specific surface area - such as nanoporous carbon materials - are commonly employed as active materials in EDLCs. Additionally, to enhance electrode conductivity, high-conductivity materials (e.g. carbon black, graphene, and carbon nanotubes/CNTs) serve as conductive agents in EDLCs. Thus, carbon nanomaterials play an irreplaceable and critical role in EDLCs, directly determining their electrochemical performance.

The electrochemical performance of the carbon nanomaterial used in EDLC is evaluated using the assembled device, like coin-type EDLCs, three-electrode EDLC cells or cylindrical EDLC cells. Coin-cell-based characterization offers advantages including low cost, versatility, and high efficiency, making it widely used in both academic and industrial settings.

This document introduces standard methods to determine the electrochemical key control characteristics of the carbon nanomaterial based on the coin-type EDLCs.

1 Scope

This part of IEC TS 62607 establishes standardized methods to determine the electrochemical key control characteristics, including:

– specific capacitance, voltage maintenance rate, endurance in cycling and temperature endurance of carbon nanomaterials by determining the standard coin-type EDLC.

The electrochemical key control characteristics are derived by calculating the recording curve at the specific charging and discharging process.

– The document is applicable for coin-type EDLC assembled from carbon nanomaterials, such as nanoporous activated carbon, carbon aerogel, carbon nanotube, carbon black, graphene, nano graphite sheet, vapor-grown carbon fibre and so on.
– Typical application areas of this method are research, manufacturer and downstream use to guide material processing and quality control.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TS 62565-5-1:2023, *Nanomanufacturing - Product specifications - Part 5-1: Nanoporous activated carbon - Blank detail specification: Electrochemical capacitor*

IEC TS 62607-4-9, *Nanomanufacturing - Key control characteristics - Part 4-9: Nano-enabled energy storage - Electrochemical characteristics of carbon nanomaterial for the electrodes of electric double layer capacitors (EDLC): Coin cell preparation*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

– IEC Electropedia: available at https://www.electropedia.org/
– ISO Online browsing platform: available at https://www.iso.org/obp

3.1
electric double-layer capacitor
EDLC
device for electrostatic storage of electrical energy achieved by separation of charge in a double layer

[SOURCE: ISO 18300:2016, 3.8]