INTERNATIONAL STANDARD

ISO 10360-10

Second edition
2021-08

Geometrical product specifications (GPS) — Acceptance and reverification tests for coordinate measuring systems (CMS) —

Part 10: Laser trackers

Spécification géométrique des produits (GPS) — Essais de réception et de vérification périodique des systèmes à mesurer tridimensionnels (SMT) —

Partie 10: Laser de poursuite

Reference number
ISO 10360-10:2021(E)

© ISO 2021



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword ... **iv**
Introduction ... **v**
1 Scope ... **1**
2 Normative references ... **1**
3 Terms and definitions ... **1**
4 Symbols ... **6**
5 Rated operating conditions ... **7**
5.1 Environmental conditions ... 7
5.2 Operating conditions ... 7
6 Acceptance tests and reverification tests ... **8**
6.1 General ... 8
6.2 Probing size and form errors ... 8
6.2.1 Principle ... 8
6.2.2 Reference artefact ... 8
6.2.3 Procedure ... 9
6.2.4 Derivation of test results ... 11
6.3 Location errors (two-face tests) ... 11
6.3.1 Principle ... 11
6.3.2 Reference artefact ... 11
6.3.3 Procedure ... 11
6.3.4 Derivation of test results ... 12
6.4 Length errors ... 13
6.4.1 General ... 13
6.4.2 Principle ... 13
6.4.3 Reference artefacts ... 13
6.4.4 Procedure ... 14
6.4.5 Derivation of test results ... 17
7 Conformity with specification ... **17**
7.1 Acceptance tests ... 17
7.2 Reverification tests ... 18
8 Applications ... **18**
8.1 Acceptance test ... 18
8.2 Reverification test ... 18
8.3 Interim check ... 18
9 Alternative unformatted presentation of symbols ... **19**
Annex A (informative) **Forms** ... **21**
Annex B (normative) **Calibrated test lengths** ... **25**
Annex C (normative) **Thermal compensation of workpieces** ... **27**
Annex D (informative) **Specification of MPEs** ... **28**
Annex E (informative) **Interim testing** ... **32**
Annex F (normative) **Testing of a stylus and retroreflector combination (SRC)** ... **39**
Annex G (normative) **Testing of an optical distance sensor and retroreflector combination (ODR)** ... **42**
Annex H (informative) **Relation to the GPS matrix model** ... **45**
Bibliography ... **46**

© ISO 2021 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 213, *Dimensional and geometrical product specifications and verification*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 290, *Dimensional and geometrical product specification and verification,* in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 10360-10:2016), which has been technically revised.

The main changes to the previous edition are as follows:

— the number of lengths tested has been reduced;

— user-selectable positions for two-face testing have been added;

— more guidance on interim testing has been added;

— symbol E_{Uni} revised to E_{Vol}.

A list of all parts in the ISO 10360 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2021 – All rights reserved

Introduction

This document is a geometrical product specification (GPS) standard and is to be regarded as a general GPS standard (see ISO 14638). It influences chain link F of the chain of standards on size, distance, form, orientation, location and run-out.

The ISO/GPS matrix model given in ISO 14638 gives an overview of the ISO/GPS system of which this document is a part. The fundamental rules of ISO/GPS given in ISO 8015 apply to this document and the default decision rules given in ISO 14253-1 apply to specifications made in accordance with this document, unless otherwise indicated.

More detailed information on the relation of this document to other standards and the GPS matrix model can be found in Annex H.

The objective of this document is to provide a well-defined testing procedure for:

a) laser tracker manufacturers to specify performance by maximum permissible errors (MPEs); and

b) to allow testing of these specifications using calibrated and traceable test lengths, test spheres and flats.

The benefits of these tests are that the measured result has a direct traceability to the unit of length, the metre, and that it gives information on how the laser tracker will perform on similar length measurements.

This document is distinct from ISO 10360-2, which is for coordinate measuring machines (CMMs) equipped with contact probing systems, in that the orientation of the calibrated test lengths reflects the different instrument geometry and error sources within the instrument.

© ISO 2021 – All rights reserved

Geometrical product specifications (GPS) — Acceptance and reverification tests for coordinate measuring systems (CMS) —

Part 10: Laser trackers

1 Scope

This document specifies the acceptance tests for verifying the performance of a laser tracker by measuring calibrated test lengths, according to the specifications of the manufacturer. It also specifies the reverification tests that enable the user to periodically reverify the performance of the laser tracker. The acceptance and reverification tests given in this document are applicable to laser trackers utilizing a retroreflector, or a retroreflector in combination with a stylus or optical distance sensor, as a probing system. Laser trackers that use interferometric measurement (IFM), absolute distance measurement (ADM) or both can be verified using this document. This document can also be used to specify and verify the relevant performance tests of other spherical coordinate measurement systems that use cooperative targets, such as "laser radar" systems.

NOTE Systems which do not track the target, such as laser radar systems, will not be tested for probing performance.

This document does not explicitly apply to measuring systems that do not use a spherical coordinate system. However, interested parties can apply this document to such systems by mutual agreement.

This document specifies:

— performance requirements that can be assigned by the manufacturer or the user of the laser tracker;

— the manner of execution of the acceptance and reverification tests to demonstrate the stated requirements;

— rules for proving comformity;

— applications for which the acceptance and reverification tests can be used.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10360-8:2013, *Geometrical product specifications (GPS) — Acceptance and reverification tests for coordinate measuring systems (CMS) — Part 8: CMMs with optical distance sensors*

ISO 10360-9:2013, *Geometrical product specifications (GPS) — Acceptance and reverification tests for coordinate measuring systems (CMS) — Part 9: CMMs with multiple probing systems*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

© ISO 2021 – All rights reserved

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp


— IEC Electropedia: available at http://www.electropedia.org/

3.1
laser tracker
coordinate measuring system in which a cooperative target is followed with a laser beam and its location determined in terms of a distance (range) and two angles

Note 1 to entry: The two angles are referred to as azimuth, θ, (rotation about a vertical axis – the standing axis of the laser tracker) and either elevation, φ, (angle above a horizontal plane – perpendicular to the standing axis) or zenith (angle from the standing axis).

Note 2 to entry: Care should be used with the symbols associated with spherical coordinate systems, as different conventions exist. For example, the description of a spherical coordinate system in ISO 80000-2 uses the symbols differently and uses the zenith angle (away from vertical) rather than elevation.

Note 3 to entry: See Figure 1



Key
A standing axis
B horizontal plane (of the laser tracker)
θ azimuth angle
φ elevation angle

Figure 1 — Coordinate system of a laser tracker

3.2
interferometric measurement mode
IFM mode
measurement method that uses a laser displacement interferometer integrated in a *laser tracker* (3.1) to determine distance (range) to a target

Note 1 to entry: Displacement interferometers can only determine differences in distance, and therefore require a reference distance (e.g. home position).

© ISO 2021 – All rights reserved

3.3
absolute distance measurement mode
ADM mode
measurement method that uses time of flight instrumentation integrated in a *laser tracker* (3.1) to determine the distance (range) to a target

Note 1 to entry: Time of flight instrumentation may include a variety of modulation methods to calculate the distance to the target.

3.4
retroreflector
passive device designed to reflect light back parallel to the incident direction over a range of incident angles

Note 1 to entry: Typical retroreflectors are the cat's-eye, the cube corner and spheres of special material.

Note 2 to entry: Retroreflectors are cooperative targets.

Note 3 to entry: For certain systems, for example laser radar, the retroreflector will possibly be a cooperative target such as a polished sphere.

3.5
spherically mounted retroreflector
SMR
retroreflector (3.4) that is mounted in a spherical housing

Note 1 to entry: In the case of an open-air cube corner, the vertex is typically adjusted to be coincident with the sphere centre.

Note 2 to entry: The tests in this document are typically executed with a spherically mounted retroreflector.


Note 3 to entry: See Figure 2.

3.6
stylus and retroreflector combination
SRC
probing system that determines the measurement point utilizing a probe stylus to contact the workpiece, a *retroreflector* (3.4) to determine the base location of the probe, and other means to find the stylus orientation unit vector

Note 1 to entry: The datum for the stylus tip offset (l) is the centre of the retroreflector.

Note 2 to entry: See Figure 2.

© ISO 2021 – All rights reserved



a) SMR **b) SRC**

Key

A laser beam
B retroreflector
C measurement point
D contact point
E base location
F normal probing direction vector
G stylus tip offset length *l*

Figure 2 — Representation of SMR versus SRC (simplified figures)

3.7
optical distance sensor and retroreflector combination
ODR
probing system that determines the measurement point utilizing an optical distance sensor to measure the workpiece, a *retroreflector* (3.4) to determine the base location of the optical distance sensor and other means to find the orientation of the optical distance sensor

3.8
target nest
nest
device designed to repeatably locate an *SMR* (3.5)

3.9
length measurement error
$E_{\text{Vol:L:LT}}$
$E_{\text{Bi:L:LT}}$
error of indication when performing an averaged ($E_{\text{Vol:L:LT}}$) or bidirectional ($E_{\text{Bi:L:LT}}$) point-to-point distance measurement of a calibrated test length using a laser tracker with a stylus tip offset of L

Note 1 to entry: $E_{\text{Vol:0:LT}}$ and $E_{\text{Bi:0:LT}}$ (used frequently in this document) correspond to the common case of no stylus tip offset, as the retroreflector optical centre is coincident with the physical centre of the probing system for *spherically mounted retroreflectors* (3.5).

© ISO 2021 – All rights reserved

3.10
normal CTE material
material with a coefficient of thermal expansion (CTE) between 8×10^{-6}/°C and 13×10^{-6}/°C

Note 1 to entry: Some documents may express CTE in units 1/K or K^{-1}, which is equivalent to 1/°C.

[SOURCE: ISO 10360-2:2009, 3.3, modified — Note 1 to entry added.]

3.11
probing form error
$P_{\text{Form.Sph.1x25:SMR:LT}}$
error of indication within which the range of Gaussian radial distances can be determined by a least-squares fit of 25 points measured by a *laser tracker* (3.1) on a spherical material standard of size

Note 1 to entry: Only one least-squares fit is performed, and each point is evaluated for its distance (radius) from this fitted centre.

3.12
probing size error
$P_{\text{Size.Sph.1x25:SMR:LT}}$
error of indication of the diameter of a spherical material standard of size as determined by a least-squares fit of 25 points measured with a *laser tracker* (3.1)

3.13
location error
two-face error
plunge and reverse error
$L_{\text{Dia.2x1:P\&R:LT}}$
distance, perpendicular to the beam path, between two measurements of a stationary *retroreflector* (3.4), where the second measurement is taken with the *laser tracker* (3.1) azimuth angle at approximately 180° from the first measurement and the laser tracker elevation angle is approximately the same

Note 1 to entry: This combination of axis rotations is known as a 'two-face' or 'plunge and reverse' test.

Note 2 to entry: The laser tracker base is fixed during this test.

3.14
maximum permissible error of length measurement
$E_{\text{Vol:L:LT, MPE}}$
$E_{\text{Bi:L:LT, MPE}}$
extreme value of the *length measurement error* (3.9), $E_{\text{Bi:L:LT}}$ or $E_{\text{Vol:L:LT}}$, permitted by specifications

Note 1 to entry: $E_{\text{Vol:0:LT}}$ and $E_{\text{Bi:0:LT}}$ (used frequently in this document) correspond to the common case of no stylus tip offset, as the retroreflector optical centre is coincident with the physical centre of the probing system for *spherically mounted retroreflectors* (3.5).

3.15
maximum permissible error of probing form
$P_{\text{Form.Sph.1x25:SMR:LT, MPE}}$
extreme value of the *probing form error* (3.11), $P_{\text{Form.Sph.1x25:SMR:LT}}$, permitted by specifications

3.16
maximum permissible error of probing size
$P_{\text{Size.Sph.1x25:SMR:LT, MPE}}$
extreme value of the *probing size error* (3.12), $P_{\text{Size.Sph.1x25:SMR:LT}}$, permitted by specifications

3.17
maximum permissible error of location
$L_{\text{Dia.2x1:P\&R:LT, MPE}}$
extreme value of the location error, $L_{\text{Dia.2x1:P\&R:LT}}$, permitted by specifications

© ISO 2021 – All rights reserved

3.18
rated operating condition
operating condition that must be fulfilled, according to specification, during measurement in order that a measuring instrument or measuring system performs as designed

Note 1 to entry: Rated operating conditions generally specify intervals of values for a quantity being measured and for any influence quantity.

Note 2 to entry: Within the ISO 10360 series, the term “as designed” in the definition means “as specified by MPEs”.

Note 3 to entry: When the rated operating conditions are not met in a test according to the ISO 10360 series, neither comformity nor non-comformity to specifications can be determined.

[SOURCE: ISO/IEC Guide 99:2007, 4.9, modified — definition revised and Notes 2 and 3 to entry added.]

4 Symbols

For the purpose of this document, the symbols in Table 1 apply.

Table 1 — Symbols of specification quantities

Symbol	Meaning
$E_{Vol:L:LT}$ $E_{Bi:L:LT}$	Length measurement error (averaged or bi-directional lengths) where L is the stylus tip offset
$P_{Form.Sph.1x25:SMR:LT}$	Probing form error
$P_{Size.Sph.1x25:SMR:LT}$	Probing size error
$L_{Dia.2x1:P\&R:LT}$	Location error (from two-face tests)
$E_{Vol:L:LT,MPE}$ $E_{Bi:L:LT,MPE}$	Maximum permissible error of length measurement where L is the stylus tip offset
$P_{Form.Sph.1x25:SMR:LT,MPE}$	Maximum permissible error of probing form
$P_{Size.Sph.1x25:SMR:LT,MPE}$	Maximum permissible error of probing size
$L_{Dia.2x1:P\&R:LT,MPE}$	Maximum permissible error of location (from two-face tests)
Accessory sensor testing – SRC	
$P_{Form.Sph.1x25:SRC:LT}$	Probing form error for SRC
$P_{Size.Sph.1x25:SRC:LT}$	Probing size error for SRC
$P_{Dia.15x1:SRC:LT}$	Orientation error for SRC
$P_{Form.Sph.1x25:SRC:LT,MPE}$	Maximum permissible error of probing form for SRC
$P_{Size.Sph.1x25:SRC:LT,MPE}$	Maximum permissible error of probing size for SRC
$P_{Dia.15x1:SRC:LT,MPE}$	Maximum permissible error of orientation for SRC
Accessory sensor testing – ODR	
$P_{Form.Sph.1 \times 25:ODR:LT}$	Probing form error for ODR (25 points)
$P_{Form.Sph.D95\ \%:ODR:LT}$	Probing form error for ODR (95 % of the points)
$P_{Size.Sph.1 \times 25:ODR:LT}$	Probing size error for ODR (25 points)
$P_{Size.Sph.All:ODR:LT}$	Probing size error for ODR (all points)
$E_{Form.Pla.D95\ \%:ODR:LT}$	Flat form error of measurement with ODR (95 % of the points)
$P_{Form.Sph.1 \times 25:ODR:LT,MPE}$	Maximum permissible error of probing form for ODR (25 points)
$P_{Form.Sph.D95\ \%:ODR:LT,MPE}$	Maximum permissible error of probing form for ODR (95 % of the points)
$P_{Size.Sph.1 \times 25:ODR:LT,MPE}$	Maximum permissible error of probing size for ODR (25 points)
$P_{Size.Sph.All:ODR:LT,MPE}$	Maximum permissible error of probing size for ODR (all points)

© ISO 2021 – All rights reserved