INTERNATIONAL STANDARD

ISO 10715

Second edition
2022-10

Natural gas — Gas sampling

Gaz naturel — Échantillonnage de gaz

Reference number
ISO 10715:2022(E)

© ISO 2022



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

© ISO 2022 – All rights reserved

Contents

Page

Foreword ... **vi**
Introduction ... **vii**
1 Scope ... **1**
2 Normative references ... **1**
3 Terms and definitions ... **1**
4 Safety considerations ... **4**
5 Principles of sampling ... **4**
6 The concept of representative sample ... **4**
7 Types of sampling ... **5**
7.1 Sampling method considerations ... 5
7.2 Spot sampling ... 6
7.2.1 General ... 6
7.2.2 Fill-and-empty method ... 6
7.2.3 Controlled-rate method ... 7
7.2.4 Evacuated-cylinder method ... 7
7.2.5 Helium pre-fill method ... 7
7.2.6 Floating-piston cylinder method ... 7
7.2.7 Single cavity sample cylinder ... 7
7.2.8 Sampling frequency ... 7
7.3 Incremental sampling (continuous or composite) ... 9
7.3.1 General considerations ... 9
7.3.2 Intervals ... 9
7.3.3 System considerations ... 9
7.3.4 Monitoring the filling process ... 10
7.3.5 Cylinder tracking ... 10
7.3.6 Overpressure protection ... 10
7.4 Online or direct sampling ... 10
7.4.1 General considerations ... 10
7.4.2 Automatic drainage ... 12
7.4.3 Reducing the pressure ... 12
7.4.4 Inert-gas purging ... 13
7.4.5 Safety/pressure relief valve ... 13
7.4.6 Heating of sample line ... 13
8 Sampling location ... **13**
8.1 General ... 13
8.2 Sampling place ... 13
8.2.1 General ... 13
8.2.2 Relevant gas ... 14
8.2.3 Undisturbed gas ... 14
8.2.4 Access ... 14
8.3 Sampling position ... 15
8.4 Sampling point ... 15
9 Ideal implementation of gas sampling ... **16**
9.1 General ... 16
9.2 Gas sorption ... 16
9.2.1 General ... 16
9.2.2 Surface treatment ... 17
9.2.3 Sorption considerations regarding sampling equipment ... 17
9.2.4 Equilibrating of sampling equipment ... 17
9.3 Materials used in sampling ... 18
9.3.1 General considerations ... 18

© ISO 2022 – All rights reserved

9.3.2 Steel grades 19
9.3.3 Epoxy coatings 19
9.3.4 Other polymers 19
9.3.5 Rubbers 19
9.3.6 Bimetallic corrosion 19
9.4 Sample contamination 19
9.4.1 Cleanliness 19
9.4.2 Cleaning sampling systems 19
9.4.3 Pre-charging of sample cylinders 20
9.5 Sample condensation 20
9.5.1 Temperature 20
9.5.2 Pressure reduction and Joule Thomson cooling 20
9.5.3 Condensation and revaporization 22
9.6 Disturbance of the flow through the sampling system 24
9.7 Delay time 24
9.7.1 Direct sampling method 24
9.7.2 Indirect sampling method 25
10 Sampling equipment 26
10.1 General 26
10.2 Probes 27
10.2.1 General 27
10.2.2 Straight-tube probe 27
10.2.3 Probe regulator 28
10.2.4 Pitot probe 29
10.3 Tubings 30
10.3.1 Sampling and sample lines 30
10.3.2 Bypass constructions 31
10.4 Filters, membranes and separators 31
10.5 Valves and safety valves 32
10.6 Fittings 33
10.7 Flow monitoring and control 33
10.8 Pressure reducers 33
10.9 Pressure sensor/manometers 33
10.10 Heating devices 33
10.11 Seals and lubricants 34
10.12 Sample containers or cylinders 34
10.12.1 General 34
10.12.2 Standard or single cavity cylinder 35
10.12.3 Floating-piston cylinders or Constant Pressure cylinders 35
10.13 Concentration devices 36
10.14 Number and sequence of equipment 37
11 Verification of the system 38
12 Troubleshooting 39
Annex A (informative) **Purposes of sampling, panel of compounds and information in the sampling report 41**
Annex B (informative) **Procedures for sampling 42**
Annex C (informative) **Gas sorption effect: adsorption/desorption 49**
Annex D (informative) **Cleaning of steel sampling cylinders 50**
Annex E (informative) **Joule-Thomson cooling and phase behaviour 51**
Annex F (informative) **Vortex shedding and associated problems 54**
Annex G (informative) **Guidelines for the calculation of the residence time 58**
Annex H (informative) **Protocol for gas sampling system verification 66**

© ISO 2022 – All rights reserved

Annex I (informative) **Number of samples** **68**
Bibliography **70**

© ISO 2022 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 193, *Natural Gas*, Subcommittee SC 1, *Natural gas analysis*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 238, *Test gases, test pressures and categories of appliances,* in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 10715:1997), which has been technically revised.

The main changes are as follows:

— This new edition has placed a significant relevance on regular service, maintenance and validation of installed sample systems which previously have not been given proper attention. Sample systems, or at least the fixed/installed portion of them, have all too often been installed and forgotten without realization that through use they become more and more contaminated leading to distortions of the composition of the gas being sampled.

— Introduction of new sampling devices.

Any feedback or questions on this document should be directed to the user’s national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2022 – All rights reserved

Introduction

The composition, quality, and properties of natural gas vary according to amongst others its source, level of processing, natural mixing at interconnection points, storage facilities, blending stations, fluctuating demand for some of its derivatives such as LPG (Liquefied Petroleum Gases), and increasingly the need to transport unconventional and renewable gases in the same network etc.

The variations that occur are closely monitored and controlled to ensure safety of the general public as well as operational staff, plant, equipment and the gas infrastructures in general. Additionally and commercially critical the energy content of the gas differs with these variations and is very accurately monitored for billing and fiscal purposes because of the very large sums of money involved.

The variations that occur can be best collectively grouped under the generic term “Gas Quality” which is subsequently referred to as GQ in this document.

For monitoring and controlling GQ, samples are taken at many and various stages along the way and analysed. Such samples are taken under many different process parameters with a need to always ensure that any gas that is subsequently analysed for such monitoring purposes is truly representative of the bulk.

Methods of measuring GQ are well specified in numerous ISO standards as are the means of calibrating such measuring instruments, however all those measurements and calibrations are all but futile if the samples used for making such measurements are not representative.

This document provides means to ensure sampling systems and sampling processes are designed, located, installed, operated, and maintained such that samples obtained are representative of the bulk to which they are attributed. It also specifies comprehensive information on the way that samples can be contaminated, altered, modified or degraded and methods, means and procedures for ensuring that the sample remains representative from the start of the sampling process to the point where the sample is presented to the analytical device.

© ISO 2022 – All rights reserved

Natural gas — Gas sampling

WARNING — General quality aspects of natural gas are detailed in ISO 13686[1]. However, it is possible that the standard does not cover all the trace constituents that are increasingly necessary to monitor for various reasons.

1 Scope

This document gives means for ensuring that samples of natural gas and natural gas substitutes that are conveyed into transmission and distribution grids are representative of the mass to which they are allocated.

NOTE To ensure that a particular gas is taken into account in the standard, please see Annex A.

This document is applicable for sampling at sites and locations where interchangeability criteria, energy content and network entry conditions are measured and monitored and is particularly relevant at cross border and fiscal measurement stations. It serves as an important source for control applications in natural gas processing and the measurement of trace components.

This document is applicable to natural dry gas (single phase - typically gas transiting through natural gas pipelines) sampling only. On occasion a natural gas flow can have entrained liquid hydrocarbons. Attempting to sample a wet natural gas flow introduces the possibility of extra unspecified uncertainties in the resulting flow composition analysis. Sampling a wet gas (two or three phases) flow is outside the scope of this document.

This document does not apply to the safety issues associated with gas sampling.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 14532, *Natural gas — Vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions from ISO 14532 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at https://www.electropedia.org/

3.1
absorption
extraction of one or more components from a mixture of gases when brought into contact with a liquid

Note 1 to entry: The assimilation or extraction process causes (or is accompanied by) a physical or chemical change, or both, in the sorbent material.

Note 2 to entry: The gaseous components are retained by capillary, osmotic, chemical, or solvent action.

EXAMPLE Removal of water from natural gas using glycol.

© ISO 2022 – All rights reserved

[SOURCE: ISO 14532:2014, 2.2.2.6]

3.2
adsorption
retention, by physical or chemical forces of gas molecules, dissolved substances, or liquids by the surfaces of solids or liquids with which they are in contact

Note 1 to entry: For example, retention of methane by carbon.

[SOURCE: ISO 14532:2014, 2.2.2.7]

3.3
contaminant
constituent in very low levels, such as particulates, glycol, compressor oil, etc., that are assumed to be intrusive and not part of the gas to be sampled

Note 1 to entry: Such contaminants are generally harmful to the analytical equipment and if they enter the sampling process they need to be removed from the sample before it enters the analyser. However, once the contaminants enter the sampling process they continue to influence any following sample that come into contact with them. Over a period of time the accumulation of contamination in the sampling system can have a profound effect on the sample such that it is no longer representative of the mass.

Note 2 to entry: Contaminants are not to be confused with trace components that are inherent to the gas to be sampled.

3.4
desorption
removal of a sorbed substance by the reverse process of adsorption or absorption

Note 1 to entry: From solution in a liquid phase for example.

[SOURCE: ISO 14532:2014, 2.2.2.8, modified — Note 1 to entry added.]

3.5
direct sampling
sampling in situations where there is a direct connection between the natural gas to be sampled and the analytical unit

3.6
floating-piston cylinder
container which has a moving piston separating the sample from a buffer gas, where the pressures are in balance on both sides of the piston

3.7
gas sorption effect
physical process whereby some gases are adsorbed onto or desorbed from the surfaces of a solid without transformation of the molecules

Note 1 to entry: The force of attraction between some gases and solids is purely physical and depends on the nature of the participating material. Natural gas can contain several components that exhibit strong sorption effects. Special care should be taken when determining trace concentrations such as heavy hydrocarbons, water, sulfur compounds, mercury and hydrogen.

[SOURCE: ISO 14532:2014, 2.3.4.6]

3.8
high-pressure natural gas
natural gas with a pressure exceeding 0,2 MPa

3.9
hydrocarbon dew point
temperature, at a given pressure, at which hydrocarbon vapour condensation begins

© ISO 2022 – All rights reserved

3.10
incremental sampler
sampler which accumulates a series of spot samples into one composite sample

3.11
indirect sampling
sampling in situations where there is no direct connection between the natural gas to be sampled and the analytical unit

3.12
liquid separator
unit, in the sample line, used to collect liquid fall-out

3.13
purging time
period of time during which a sample purges a piece of equipment

3.14
representative sample
sample having the same composition as the natural gas it is attributed to, when the latter is considered as a homogeneous whole

[SOURCE: ISO 14532:2014, 2.3.4.2]

3.15
residence time
time it takes for a sample to flow through a piece of equipment

3.16
retrograde condensation
production of a liquid phase of heavy hydrocarbons at a particular pressure and temperature where, at that same temperature, the gas stays in a single phase at a higher pressure as well as at a lower pressure

Note 1 to entry: Retrograde behaviour describes the non-ideal phase properties of hydrocarbon gas mixtures, such as natural gas.

3.17
sample container
container for collecting the gas sample when indirect sampling is necessary

3.18
sample line
line provided to transfer a sample of the gas from the *sampling point* (3.21) to the sampling device or the analytical unit

Note 1 to entry: Devices necessary to prepare the sample for transportation and analysis (conditioning unit) can be part of it.

3.19
sample probe
device inserted into the gas source, used to extract a sample and to which a *sample line* (3.18) is connected

3.20
sampling place
whereabouts along the gas pipeline or on the process plant where the *sample probe* (3.19) is located

3.21
sampling point
exact point in space defined by the *sampling place* (3.20), the *sampling position* (3.22) and by the location of the inlet on the *sample probe* (3.19)

© ISO 2022 – All rights reserved

3.22
sampling position
location within the cross-sectional area of the gas pipeline or process plant at the *sampling place* from where a sample is taken

3.23
spot sample
sample of specified volume taken at a specified place at a specified time from a stream of gas

3.24
trace component
component present at very low levels

Note 1 to entry: Trace components generally include hydrocarbons or groups of hydrocarbons above n-pentane and other components listed in ISO 14532.

3.26
wetted surface
surface of the material in contact with the sampled gas

4 Safety considerations

The use of this document can involve working with high pressure flammable gases and other hazardous materials which can be located in areas designated as hazardous (potentially explosive and or toxic atmospheres). This document does not address the safety issues associated with such situations. It is the user's responsibility to establish appropriate design rules, installation, operating, testing and maintenance procedures for pressurized equipment, equipment located in potentially hazardous areas, the control, handling and transportation of substances potentially hazardous to health, etc.

International and national regulations on safety requirements should be followed closely and carry more weight than this document.

5 Principles of sampling

Natural gas sampling is the process of acquiring a sample from a source of interest, conditioning the sample (where necessary) and delivering the sample to an analytical instrument, either directly or indirectly via a vessel or other transport medium.

The methods and equipment for each of these steps are described within this document.

The purpose of the sampling system is to ensure that the sample acquired is representative of the source gas desired and that in the process of delivering the sample to the analytical instrument the chemical and physical state remain unchanged, even on a molecular level.

Considering the equipment is relied on to fulfil this purpose for many years of operation, careful consideration should be applied to the design (considering application-specific conditions and measurement objectives), manufacturing, operation, maintenance and performance evaluation of the system.

6 The concept of representative sample

In order to show that any information gained from a sample of natural gas is truly representative of the whole quantity to which the information is to be attributed we use the term "representative sample"

A representative sample is established by two main criteria:

a) The sample is not altered in any way, or more realistically in any avoidable way, during the process of collecting, handling, containing or preparing the sample for analysis or measurement. The condition of the sample being the same in composition and phase -absolute or essential sameness

© ISO 2022 – All rights reserved