INTERNATIONAL STANDARD

ISO 11819-1

Second edition
2023-02

Acoustics — Measurement of the influence of road surfaces on traffic noise —

Part 1: Statistical pass-by method

Acoustique — Mesurage de l'influence des revêtements de chaussées sur le bruit émis par la circulation —

Partie 1: Méthode statistique au passage

Reference number
ISO 11819-1:2023(E)

© ISO 2023



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

© ISO 2023 – All rights reserved

Contents

Page

Foreword ..... **v**
Introduction ..... **vii**
1 Scope **1**
2 Normative references **1**
3 Terms and definitions **2**
3.1 Types of noise 2
3.2 Measurement method 2
3.3 Road speed categories 2
3.4 Vehicle categories 3
3.5 Measured noise quantities 3
3.6 Road surface terms applicable in this method 4
3.7 Backing board terms 4
4 Symbols and abbreviated terms **4**
5 Measuring principle **5**
6 Instrumentation **5**
6.1 Instruments for acoustical measurements 5
6.1.1 General 5
6.1.2 Verification 5
6.2 Instruments for vehicle speed measurements 6
6.2.1 General 6
6.2.2 Verification 6
6.3 Instruments for temperature measurements 6
6.3.1 General 6
6.3.2 Verification 6
7 Test sites **6**
7.1 Selection of measuring site 6
7.2 Deviations from free-field conditions 7
7.3 Considerations of guard rails and other barriers which can reflect or screen the sound 7
7.4 Surface between the tested road surface and microphone 7
7.5 Backing board 10
8 Traffic conditions **10**
8.1 Vehicle classification 10
8.2 Selection of vehicles for measurement 10
8.3 Minimum number of vehicles 11
8.4 Road speed categories 12
9 Measuring procedure **12**
9.1 Microphone position 12
9.2 Calibrations 13
9.3 Sound level measurement 14
9.4 Frequency spectrum measurement 14
9.5 Speed measurement 14
9.6 Temperature measurement 14
10 Meteorological conditions **14**
10.1 Wind 14
10.2 Temperature 14
10.3 Recommendations on road surface moisture 14
11 Background noise **15**
12 Normalization of data **15**

© ISO 2023 – All rights reserved

12.1 Compensating for the effect of the additional (higher) microphone position 15
12.2 Combining vehicle categories H2 and H3+ into a common heavy vehicle category H 15
12.3 Noise versus speed - regression analysis (for passenger cars) 16
12.4 Noise versus speed – normalization to reference speed (for heavy vehicles) 16
12.5 Noise versus speed – normalization of frequency spectra for vehicles in categories P and H 18
12.6 Determination of SPB sound level at reference speeds 18
12.7 Useful speed range for the speed normalization 18
12.8 Correction of sound levels according to temperature 18

13 Measurement uncertainty 19

14 Reported data 20
14.1 General information 20
14.2 Information relating to the location and appearance of the test site 21
14.3 Information relating to the type and construction of the tested road surface 21
14.4 Information relating to the condition of the tested surface and environmental factors 21
14.5 Road speed category and vehicle information 21
14.6 Measured and calculated sound level and speed data 21
14.7 Others 22

Annex A (normative) **Vehicle categories 23**

Annex B (informative) **Determination of the statistical pass-by index (SPBI) 27**

Annex C (informative) **The backing board variant 29**

Annex D (informative) **Adding 95 % confidence intervals 34**

Annex E (informative) **Validity and stability of the method 35**

Annex F (informative) **Reference road surface 36**

Annex G (informative) **Monitoring the stability of sound levels of vehicle fleets 38**

Annex H (informative) **Uncertainty 40**

Annex I (informative) **Example of test report 43**

Bibliography 47

© ISO 2023 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*, in collaboration with ISO Technical Committee TC 227, *Road materials*, in accordance with the agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition of ISO 11819-1:1997 and ISO/PAS 11819-4:2013, which have been technically revised.

The main changes are as follows:

— ISO/PAS 11819-4 has now been integrated as Annex C;

— the backing board method makes possible a wider application of the method, where the old version would not meet the acoustical free field conditions;

— changes to nomenclature for vehicle categories in 3.1, including the introduction of a 'generic' vehicle category and the introduction of a minimum gross vehicle weight (8 t) for dual-axle heavy vehicles;

— changes to some key symbols and abbreviations in Clause 4;

— using a generic speed exponent for heavy vehicles instead of calculating a speed exponent from each measurement;

— using a correction to 2-axle medium vehicles for correcting them to a level typical of 3-axle heavy vehicles;

— more liberal requirement regarding the number of heavy vehicles to measure;

— an additional microphone position (at the height of 3,0 m) can be used in cases where reflecting objects could influence the results.

The objective of the changes and supplements is to make SPB measurements more practical while maintaining or reducing uncertainties.

© ISO 2023 – All rights reserved

A list of all parts in the ISO 11819 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2023 – All rights reserved

Introduction

The emission of road traffic noise greatly depends on road surface characteristics, notably on texture and porosity; the latter due to the flow resistivity of the air voids. Both these characteristics influence the generation of tyre/road noise and, in addition, the porosity can influence the emission of sound, particularly when the emission takes place close to the surface. Power unit noise, which is usually generated at a greater height above the road surface than tyre/road noise, can also be affected during emission by the porosity characteristics of the road surface. These effects lead to differences in sound levels, associated with a given traffic flow and composition, from different road surfaces of up to 15 dB, which can have a substantial impact on the environmental acoustic quality alongside a road.

It is therefore important to be able to measure this influence by a standardized method and to arrive at a quantitative ranking of road surfaces with respect to traffic noise. This document offers such a method, the objective of which is to satisfy a need expressed by road planners, road administrators, contractors, manufacturers of so-called "low-noise surfaces" and by other parties concerned with the prediction and control of road traffic noise.

© ISO 2023 – All rights reserved

Acoustics — Measurement of the influence of road surfaces on traffic noise —

Part 1: Statistical pass-by method

1 Scope

This document specifies a method of comparing traffic noise on different road surfaces for various compositions of road traffic for the purpose of evaluating different road surface types. Sound levels representing either light or heavy vehicles at selected speeds are assigned to a certain road surface. The method is applicable to traffic travelling at constant speed, i.e. free-flowing conditions at posted speeds of 50 km/h and upwards. For conditions where traffic is not free flowing, such as at junctions and where the traffic is congested, the method is not applicable.

A standard method for comparing the noise characteristics of road surfaces gives road and environment authorities a tool for establishing common practices or limits regarding the use of road surfaces meeting certain noise criteria. However, it is not within the scope of ISO 11819 (all parts) to suggest such criteria.

The statistical pass-by (SPB) method is suitable for use for the following main purposes:

— to classify road surfaces according to their influence on traffic noise (surface classification);

— to assist in verifying conformity of production of road surfaces;

— to evaluate acoustic performance of road surfaces throughout operation relative to new condition;

— to evaluate the influence of different road surfaces on traffic noise at sites irrespective of condition and service time;

— to evaluate acoustic performance of a road surface relative to a reference surface.

Due to practical restrictions, the method cannot be applied at all possible locations. However, the backing board method can allow some locations to be tested that were not previously acceptable.

Clause 5 gives a general description of the SPB method.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1996-2, *Acoustics — Description, measurement and assessment of environmental noise — Part 2: Determination of sound pressure levels*

ISO/IEC 17025, *General requirements for the competence of testing and calibration laboratories*

ISO/IEC Guide 98-3, *Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

IEC 60942:2017, *Electroacoustics — Sound calibrators*

IEC 61183, *Electroacoustics - Random-incidence and diffuse-field calibration of sound level meters*

© ISO 2023 – All rights reserved

IEC 61260-1, *Electroacoustics — Octave-band and fractional-octave-band filters — Part 1: Specifications*

IEC 61672-1, *Electroacoustics — Sound level meters — Part 1: Specifications*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at https://www.electropedia.org/

3.1 Types of noise

3.1.1
vehicle noise
total noise from an individual vehicle, including the two major components of *power unit noise* (3.1.3) and *tyre/road noise* (3.1.2)

3.1.2
tyre/road noise
noise generated by the tyre/road interaction

3.1.3
power unit noise
noise generated by the vehicle engine, exhaust system, air intake, fans, transmission, etc.

3.1.4
background noise
unwanted noise interfering with the noise that is intended to be measured

3.2 Measurement method

3.2.1
statistical pass-by method
SPB method
measurement procedure designed to evaluate vehicle and traffic noise generated on different sections of road surface under specific traffic conditions

Note 1 to entry: The measurements are taken from a great number of vehicles operating normally on the road. Results obtained using this procedure are normalized to standard speeds according to the category or type of road being considered.

3.3 Road speed categories

NOTE Three categories of roads are defined with respect to the range of speeds at which the traffic flows and usually associated with certain areas (urban, suburban, rural, etc.).

3.3.1
"low" speed road
road category where traffic operates at an average speed of 45 km/h to 64 km/h

3.3.2
"medium" speed road
road category where traffic operates at an average speed of 65 km/h to 99 km/h

Note 1 to entry: These conditions are mostly found in suburban areas or on rural highways.

© ISO 2023 – All rights reserved

3.3.3
"high" speed road
road category where cars operate at an average speed of 100 km/h or more; but where heavy vehicles may operate at lower average speed due to speed restrictions

Note 1 to entry: These conditions are usually associated with motorway traffic in rural or suburban areas.

3.3.4
reference speed
v_{ref}
preferred speed for uniform reporting of measured data

Note 1 to entry: The reference speed is expressed in kilometres per hour. Most commonly used reference speeds are 50 km/h, 80 km/h and 110 km/h (also in ISO 11819-2) but alternative speeds may be used, if required for technical, safety and legislative reasons.

3.4 Vehicle categories

3.4.1
vehicle category
category of vehicles that have certain common features easy to identify in the traffic stream, such as the number of axles and the size, that are assumed to correspond to similarities in sound emission when driven under the same operating conditions

3.4.2
category P – passenger cars
vehicles used for passenger transportation, having two axles and having typically 4 to 5 seats

Note 1 to entry: See further Annex A.

3.4.3
category H – heavy vehicles
categories H2 (3.4.3.1) and *category H3+* (3.4.3.2) combined

3.4.3.1
category H2 – dual-axle heavy vehicles
trucks, buses and coaches with two axles and four or six wheels, and having a gross vehicle mass of at least 8 t

Note 1 to entry: See Annex A.

3.4.3.2
category H3+ – multi-axle heavy vehicles
trucks, buses and coaches with more than two axles

Note 1 to entry: See Annex A.

3.5 Measured noise quantities

3.5.1
maximum sound level
$L_{A,max}$
highest A-weighted sound pressure level recorded by the measuring instrument during a vehicle pass-by, using time weighting F

3.5.2
SPB sound level
$L_{SPB:P,vref}$ or $L_{SPB:H,vref}$
maximum A-weighted sound pressure level determined at a reference speed, v_{ref}, calculated for either vehicle *category P* (3.4.2) or *category H* (3.4.3)

© ISO 2023 – All rights reserved

3.5.3
statistical pass-by index
SPBI
noise index for comparison of road surfaces, based on the *SPB sound levels* (3.5.2), $L_{SPB:P,vref}$ and $L_{SPB:H,vref}$, and considering the mix and speeds of vehicles

3.6 Road surface terms applicable in this method

3.6.1
dense road surface
road surface featuring a wearing course with a void content of not more than 10 % (by volume)

3.6.2
porous road surface
road surface featuring a wearing course with a void content of equal to or more than 18 % (by volume)

3.6.3
negatively textured road surface
road surface featuring a relatively flat upper part and relatively narrow valleys or troughs between the main aggregate

Note 1 to entry: The skewness of its profile according to ISO 13473-2 is negative.

3.6.4
reference surface
virtual reference surface
surface which is not existing but being considered as an "average" of a dense asphalt concrete and a stone mastic asphalt surface with a maximum aggregate size of 11 mm

Note 1 to entry: The above definition is incomplete. For further details, refer to Annex F.

Note 2 to entry: This definition is valid only in ISO 11819 (all parts).

3.7 Backing board terms

3.7.1
backing board
rectangular, hard, reflective board on which a microphone is mounted

3.7.2
surface microphone
flush-mounted microphone designed to measure sound pressure on a surface without requiring the drilling of a hole through it

4 Symbols and abbreviated terms

Table 1 lists the symbols used in this document. All acoustic variables are A-weighted.

Table 1 — Symbols and abbreviated terms used in this standard and their value or unit

Symbol	Value/unit	Explanation
$L_{A,max,i,v}$	dB	The maximum sound level, A-weighted, for vehicle No. i when it passes-by at speed v
$L_{SPB:P,v_{ref}}$	dB	The SPB sound level, for vehicle category P (passenger cars), at the reference speed v_{ref}
$L_{SPB:H,v_{ref}}$	dB	The SPB sound level, for vehicle category H (heavy vehicles), at the reference speed v_{ref}

© ISO 2023 – All rights reserved