INTERNATIONAL STANDARD

ISO 12217-2

Fourth edition
2022-12

Small craft — Stability and buoyancy assessment and categorization —

Part 2: Sailing boats of hull length greater than or equal to 6 m

Petits navires — Évaluation et catégorisation de la stabilité et de la flottabilité —

Partie 2: Bateaux à voiles d'une longueur de coque supérieure ou égale à 6 m

Reference number
ISO 12217-2:2022(E)

© ISO 2022



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

© ISO 2022 – All rights reserved

Contents

Page

Foreword ..... **v**
Introduction ..... **vi**
1 Scope **1**
2 Normative references **1**
3 Terms and definitions **2**
3.1 Primary 2
3.2 Hazards 4
3.3 Downflooding 4
3.4 Dimensions, areas and angles 5
3.5 Condition, mass and volume 6
3.6 Other terms and definitions 9
4 Symbols **12**
5 Procedure **13**
5.1 Maximum load 13
5.2 Sailing or non-sailing 13
5.3 Tests, calculations and requirements to be applied 13
5.4 Variation in input parameters 14
6 Requirements for monohull boats **14**
6.1 Requirements to be applied 14
6.2 Downflooding 15
6.2.1 Downflooding openings 15
6.2.2 Downflooding height 18
6.2.3 Downflooding angle 19
6.3 Recess size 19
6.3.1 Application 19
6.3.2 Simplified methods 20
6.3.3 Direct calculation method 22
6.4 Minimum righting energy 22
6.5 Angle of vanishing stability 23
6.5.1 General 23
6.5.2 Normal requirement 23
6.5.3 Alternative requirement for design category B 23
6.6 Stability index (STIX) 24
6.6.1 Method 24
6.6.2 Dynamic stability factor (FDS) 25
6.6.3 Inversion recovery factor (FIR) 25
6.6.4 Knockdown recovery factor (FKR) 25
6.6.5 Displacement-length factor (FDL) 26
6.6.6 Beam-displacement factor (FBD) 26
6.6.7 Wind moment factor (FWM) 26
6.6.8 Downflooding factor (FDF) 27
6.6.9 Calculation of the stability index (STIX) 27
6.7 Knockdown-recovery test 27
6.8 Wind stiffness test 28
6.8.1 General 28
6.8.2 Practical test 28
6.8.3 Compliance by calculation 30
6.8.4 Requirements 31
6.9 Flotation requirements 32
6.10 Capsize-recovery test 32
6.11 Detection and removal of water 34
7 Requirements for catamarans, trimarans and form-stable monohulls **35**

© ISO 2022 – All rights reserved

7.1 Requirements to be applied ... 35
7.2 Downflooding openings ... 35
7.3 Downflooding height ... 35
7.4 Recess size ... 35
7.5 Stability information ... 35
7.6 Safety signs ... 36
7.7 Bare poles factor ... 37
7.8 Rolling in breaking waves ... 37
7.9 Pitchpoling ... 38
7.10 Diagonal stability ... 38
7.11 Habitable multihull boats ... 38
7.12 Buoyancy when inverted ... 40
7.13 Escape after inversion ... 41

8 Safety signs ... 42

9 Application ... 42
9.1 Deciding the design category ... 42
9.2 Meaning of the design categories ... 42

Annex A (normative) **Full method for required downflooding height ... 44**

Annex B (normative) **Methods for calculating downflooding angle ... 46**

Annex C (normative) **Determining the curve of righting moments ... 48**

Annex D (normative) **Method for calculating reserve of buoyancy after inversion or swamping ... 51**

Annex E (normative) **Flotation material and elements ... 53**

Annex F (normative) **Information for the craft's owner's manual ... 55**

Annex G (normative) **Determination of safe wind speed information ... 59**

Annex H (normative) **Determination of longitudinal righting characteristics ... 62**

Annex I (informative) **Summary of requirements ... 65**

Annex J (informative) **Worksheets ... 68**

Annex K (informative) **Illustration of recess retention level ... 87**

Bibliography ... 88

© ISO 2022 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 188, *Small craft*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 464, *Small Craft*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This fourth edition cancels and replaces the third edition (ISO 12217-2:2015), of which it constitutes a minor revision. The main changes are as follows:

— the Normative references have been updated;

— the "allowance for the maximum mass of optional equipment and fittings not included in the manufacturer's basic outfit" has been moved from 3.5.4 (maximum load) to 3.5.5 (maximum load condition);

— in Clause F.1, the first paragraph has been slightly reworded as a Note, so as to clearly make an informative reference to ISO 10240, which has been moved from Clause 2 to the Bibliography;

— in Annex J, the calculation worksheet No. 1 has been corrected to reflect the changes in 3.5.4 and 3.5.5;

— minor editorial changes throughout the document.

A list of all parts in the ISO 12217 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2022 – All rights reserved

Introduction

This document enables the determination of limiting environmental conditions for which an individual boat has been designed.

It enables the boat to be assigned to a design category appropriate to its design and maximum load. The design categories used align with those in the Recreational Craft Directive of the European Union, EU Directive 2013/53/EU.

Annex J provides worksheets to assist in the systematic assessment of a boat according to this document.

© ISO 2022 – All rights reserved

Small craft — Stability and buoyancy assessment and categorization —

Part 2:
Sailing boats of hull length greater than or equal to 6 m

CAUTION — Compliance with this document does not guarantee total safety or total freedom of risk from capsize or sinking.

IMPORTANT — The electronic file of this document contains colours which are considered to be useful for the correct understanding of the document. Users should therefore consider printing this document using a colour printer.

1 Scope

This document specifies methods for evaluating the stability and buoyancy of intact (i.e. undamaged) boats. The flotation characteristics of boats susceptible to swamping are also encompassed.

The evaluation of stability and buoyancy properties using this document will enable the boat to be assigned to a design category (A, B, C or D) appropriate to its design and maximum load.

This document is principally applicable to boats propelled primarily by sail (even if fitted with an auxiliary engine) of 6 m up to and including 24 m hull length. However, it can also be applied to boats less than 6 m if they are habitable multihulls or can be applied if they do not attain the desired design category specified in ISO 12217-3 and they are decked and have quick-draining recesses which comply with ISO 11812.

In relation to habitable multihulls, this document includes assessment of susceptibility to inversion, definition of viable means of escape and requirements for inverted flotation.

This document excludes:

— inflatable and rigid-inflatable boats covered by the ISO 6185 series, except for references made in the ISO 6185 series to specific clauses of the ISO 12217 series;

— gondolas and pedalos;

— surfboards including sailing surfboards; and

— hydrofoils and foil stabilized boats when not operating in the displacement mode.

NOTE Displacement mode means that the boat is only supported by hydrostatic forces.

It does not include or evaluate the effects on stability of towing, fishing, dredging or lifting operations, which need to be separately considered if appropriate.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2896:2001, *Rigid cellular plastics — Determination of water absorption*

© ISO 2022 – All rights reserved

ISO 3864-1:2011, *Graphical symbols — Safety colours and safety signs — Part 1: Design principles for safety signs and safety markings*

ISO 8666:2020, *Small craft — Principal data*

ISO 9093, *Small craft — Seacocks and through-hull fittings*

ISO 9094, *Small craft — Fire protection*

ISO 11812, *Small craft — Watertight or quick-draining recesses and cockpits*

ISO 12216, *Small craft — Windows, portlights, hatches, deadlights and doors — Strength and watertightness requirements*

ISO 12217-1:2022, *Small craft — Stability and buoyancy assessment and categorization — Part 1: Non-sailing boats of hull length greater than or equal to 6 m*

ISO 14946:2021, *Small craft — Maximum load capacity*

ISO 15083, *Small craft — Bilge-pumping systems*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at https://www.electropedia.org/

NOTE The meanings of certain symbols used in the definitions are given in Clause 4.

3.1 Primary

3.1.1
design category
description of the sea and wind conditions for which a boat is assessed to be suitable

Note 1 to entry: See also 9.2.

3.1.2
sailing boat
boat for which the primary means of propulsion is by wind power, having *reference sail area* (3.4.8) $A_S \geq 0{,}07(m_{LDC})^{2/3}$

Note 1 to entry: m_{LDC} is the mass of the boat in the maximum load condition, expressed in kilograms.

3.1.3
catamaran
boat with two main load-bearing hulls

EXAMPLE Boats with a centreline or bridge-deck nacelle which supports less than 30 % of the mass in the maximum load condition are considered to be catamarans. Proas are asymmetric catamarans.

3.1.4
trimaran
boat with a centre main hull and two sidehulls in which the centre hull, when the boat is upright, supports 30 % or more of the mass in the maximum load condition

© ISO 2022 – All rights reserved

3.1.5
recess
volume open to the air that might retain water within the range of loading conditions and corresponding trims

EXAMPLE Cockpits, wells, open volumes or areas bounded by bulwarks or coamings.

Note 1 to entry: Cabins, shelters or lockers provided with closures according to the requirements of ISO 12216 are not recesses.

Note 2 to entry: Cockpits that are open aft to the sea are considered to be recesses. Flush decks without bulwarks or coamings are not recesses.

3.1.6
quick-draining recess
recess fulfilling all the requirements of ISO 11812 for "quick-draining cockpits and recesses"

Note 1 to entry: According to its characteristics, a cockpit may be considered to be quick-draining for one design category, but not for a higher category.

Note 2 to entry: ISO 11812 contains requirements with which most sailing dinghies cannot comply.

3.1.7
watertight recess
recess fulfilling all the requirements of ISO 11812 for "watertight cockpits and recesses"

Note 1 to entry: This term only implies requirements in respect of watertightness and sill heights, but not those for drainage.

3.1.8
fully enclosed boat
boat in which the horizontal projection of the sheerline area comprises any combination of

— watertight deck and superstructure, and/or

— quick-draining recesses which comply with ISO 11812, and/or

— watertight recesses complying with ISO 11812 with a combined volume of less than $(L_H B_H F_M)/40$, and

all closing appliances have their degree of watertightness in accordance with ISO 12216

Note 1 to entry: The size of recesses permitted for boats of design category A, B or some boats of design category C is restricted by the requirements of 6.3.

3.1.9
habitable boat
boat having a fully enclosed cabin with rigid roof fitted with one or more bunks, benches, pipecots, hammocks or similar locations that can be used for sleeping when the boat is under way

Note 1 to entry: A boat is considered to be "habitable" if a fabric closure is used instead of a rigid door, or the cabin has fabric sides.

Note 2 to entry: The following are not considered to render a boat "habitable":

— a cockpit tent, or

— an open-sided cuddy intended to provide limited protection from spray, provided it is not fitted with fabric closures all round.

Note 3 to entry: Locations used for sleeping have minimum dimensions of 1,5 m diagonal length, 0,4 m width at the widest point, and with a minimum headroom of 0,4 m over the length. The cabin sole and compartments designated by the builder to be used exclusively for storage and referenced in the owner's manual are not included.

© ISO 2022 – All rights reserved

3.1.10
habitable part of a boat
spaces within a habitable boat with rigid roof that are fitted with a toilet or in which there is provision for any of the following activities: sitting, sleeping, cooking, eating, washing, navigation, steering

Note 1 to entry: Compartments designated by the builder to be used exclusively for storage and referenced in the owner's manual are not included.

3.2 Hazards

3.2.1
capsize
event when a boat reaches any heel angle from which it is unable to recover to equilibrium near the upright without intervention

3.2.2
knockdown
event when a boat reaches a heel angle sufficient to immerse the masthead, and from which it may or may not recover without intervention

3.2.3
inversion
event when a boat becomes upside down

3.3 Downflooding

3.3.1
downflooding opening
opening in the hull or deck (including the edge of a recess) that might admit water into the interior or bilge of a boat, or a recess, apart from those excluded in 6.2.1.6

3.3.2
downflooding angle
ϕ_D
angle of heel at which downflooding openings (apart from those excluded in 6.2.1.6) become immersed, when the boat is in calm water and in the appropriate loading condition at design trim

Note 1 to entry: Where openings are not symmetrical about the centreline of the boat, the case resulting in the smallest angle is used.

Note 2 to entry: The following are specifically considered:

— ϕ_D is the downflooding angle to any downflooding opening;

— ϕ_{DA} is the angle of heel at which openings which are not marked "KEEP SHUT WHEN UNDER WAY" having a combined total area, expressed in square centimetres (cm^2), greater than the number represented by $1{,}2 L_H B_H F_M$ first become immersed;

— ϕ_{DC} is the downflooding angle at which recesses which are not quick-draining begin to fill with water;

— ϕ_{DH} is the downflooding angle at which any main access hatch (i.e. having an opening area greater than 0,18 m^2 each) giving direct access to the main open air helm position first begins to become immersed.

Note 3 to entry: Downflooding angle is expressed in degrees.

© ISO 2022 – All rights reserved

3.3.3
downflooding height
h_D
smallest height above the waterline to any downflooding opening, apart from those excluded in 6.2.1.6, when the boat is upright in calm water and in the maximum load condition, measured to the critical downflooding point which might be within pipes or ducts inside the hull

Note 1 to entry: Downflooding height is expressed in metres.

Note 2 to entry: See Figure B.1.

3.4 Dimensions, areas and angles

3.4.1
length of hull
L_H
length of the hull measured according to ISO 8666

Note 1 to entry: Length of hull is expressed in metres.

3.4.2
length waterline
L_{WL}
waterline length measured according to ISO 8666 when the boat is upright in calm water, in the appropriate loading condition and at design trim

Note 1 to entry: For multihull boats, L_{WL} relates to that of the longest individual hull.

Note 2 to entry: Length waterline is expressed in metres.

3.4.3
beam of hull
B_H
maximum beam of the hull using the method of ISO 8666; for catamaran and trimaran boats, maximum beam across the outer hulls

Note 1 to entry: Beam of hull is expressed in metres.

3.4.4
beam waterline
B_{WL}
greatest beam measured according to ISO 8666 at the waterline in calm water which, for multihull boats, is the sum of the maximum waterline beams of each of the hulls, the boat being upright, in the appropriate loading condition and at design trim

Note 1 to entry: Beam waterline is expressed in metres.

3.4.5
beam between hull centres
B_{CB}
on catamaran and trimaran boats, the transverse distance between the centres of buoyancy of the outer hulls

Note 1 to entry: Beam between hull centres is expressed in metres.

© ISO 2022 – All rights reserved

3.4.6
freeboard amidships
F_M
distance of the sheerline or deck above the waterline at $L_{WL}/2$ measured according to ISO 8666, the boat being upright, in the appropriate loading condition and at design trim

Note 1 to entry: Freeboard amidships is expressed in metres.

Note 2 to entry: Where no loading condition is specified, maximum load condition should be assumed.

3.4.7
draught of canoe body
T_C
draught of the main buoyant part of the hull(s) below the waterline, as defined in ISO 8666, the boat being upright in the appropriate loading condition and at design trim

Note 1 to entry: Draught of canoe body excludes appendages such as rudders or skegs, and is expressed in metres.

3.4.8
reference sail area
A_S
actual profile area of sails set abaft a mast, plus the maximum profile areas of all masts, plus reference triangle area(s) forward of each mast as defined in ISO 8666

Note 1 to entry: Sail area is expressed in square metres.

3.4.9
standard sail area
A'_S
actual profile area of the largest sail plan suitable for windward sailing in true winds of 10–12 kn (5,1–6,2 m/s), including overlaps, and supplied or recommended by the builder as standard

Note 1 to entry: Sail area is expressed in square metres.

3.4.10
angle of vanishing stability
ϕ_V
angle of heel nearest the upright (other than upright) in the appropriate loading condition at which the transverse stability righting moment is zero

Note 1 to entry: This is determined assuming that there is no offset load, and that all potential downflooding openings are considered to be watertight.

Note 2 to entry: Where a boat has recesses which are not quick-draining, ϕ_V is to be taken as the downflooding angle to these recesses, unless the loss of buoyancy due to such recesses is fully accounted for in determining ϕ_V.

Note 3 to entry: Angle of vanishing stability is expressed in degrees.

3.5 Condition, mass and volume

3.5.1
empty craft condition
empty boat including fittings and equipment as listed below but excluding all optional equipment and fittings not included in the manufacturer's basic outfit:

a) structure: comprising all the structural parts, including any fixed ballast keel and/or drop keel/centreboard/daggerboard(s) and rudder(s);

b) ballast: any fixed ballast installed;

© ISO 2022 – All rights reserved

c) internal structure and accommodation: bulkheads and partitions, insulation, lining, built-in furniture, flotation material, windows, hatches and doors, permanently installed mattresses and upholstery materials;

d) permanently installed engine(s) and fuel system: comprising inboard engine(s), including all supplies and controls as needed for their operation, permanently installed fuel systems, including tanks;

e) fluids in permanently installed systems: residual working fluids as needed for their operation (see examples below), but excluding contents of fluid ballast systems and tanks, and main storage tanks (which are included in maximum load);

EXAMPLE Fluids in hot or cold water, fuel, lubricating or hydraulic oil systems.

f) internal equipment, including:

— all items of equipment permanently attached to the craft, e.g. tanks, toilet system(s), water transfer equipment;

— bilge pumping system(s), cooking and heating devices, cooling equipment, ventilation system(s);

— electrical installation and equipment, including permanently installed batteries mounted in the position intended by the builder;

— fixed navigational and electronic equipment;

— fixed firefighting equipment, where fitted;

g) external equipment, including:

— all permanently attached standard or specified deck fittings, e.g. guardrails, pulpits and pushpits, bowsprits and their attachments, bathing platforms, boarding ladders, steering equipment, winches, sprayhood(s);

— awning(s), cockpit tables, gratings, signal mast(s), where fitted;

— mast(s), boom(s), spinnaker poles and other pole(s), standing and running rigging, in the stowed position ready for use; all standing and running rigging in place

Note 1 to entry: The mass in the empty craft condition is denoted by m_{EC} and is expressed in kilograms.

3.5.2
light craft condition
empty craft condition plus standard equipment (3.6.12) plus removable ballast (whether solid or liquid) when supplied and/or intended by the manufacturer to be carried when the boat is afloat, with elements positioned as follows:

a) where provision is made for propulsion by outboard engine(s) of more than 3 kW, the heaviest engine(s) recommended for the boat by the manufacturer is(are) mounted in the working position(s);

b) where batteries are fitted, they are mounted in the position intended by the builder, and if there is no specific stowage provided for batteries, the mass of one battery for each engine over 7 kW is allowed for, and located within 1,0 m of the engine location;

c) all upwind sails supplied or recommended by the builder as standard, onboard and rigged ready for use, but not hoisted, e.g. mainsail on boom, roller furling sails furled, hanked foresails on stay stowed on foredeck

Note 1 to entry: For the minimum mass of outboard engines and batteries, refer to ISO 12217-3:2022, Tables C.1 and C.2.

Note 2 to entry: The mass in the light craft condition is denoted by m_{LC} and is expressed in kilograms.

© ISO 2022 – All rights reserved

3.5.3
minimum operating condition
boat in the light craft condition with the following additions:

a) mass to represent the crew, positioned on the centreline near the main control position of

   — 75 kg where $L_H \leq 8$ m,

   — 150 kg where 8 m < $L_H \leq 16$ m,

   — 225 kg where 16 m < $L_H \leq 24$ m;

b) non-edible stores and equipment normally carried on the boat and not included in the manufacturer's list of standard equipment

EXAMPLE Loose internal equipment and tools, spare parts, dishes, kitchenware and cutlery, additional anchors or sails, dinghy and outboard if carried aboard.

Note 1 to entry: Liquids in main storage tanks (e.g. fuel, drinking water, black and grey water, live wells, bait tanks, etc.) are excluded.

Note 2 to entry: Water ballast in tanks which are symmetrical about the centreline and which are intended by the builder to be used for variable asymmetric ballasting while under way is excluded.

Note 3 to entry: Elements with transversally variable position (e.g. canting keels, movable solid ballast, tilting masts) are positioned symmetrically about the centreline of the boat. Elements with longitudinally variable position (e.g. tilting masts or keels) are positioned so that the VCG is maximized.

Note 4 to entry: Any centreboard or keel is in the raised position unless it can be fixed in the lowered position and an appropriate instruction is given in the owner's manual.

Note 5 to entry: The mass in the minimum operating condition is denoted by m_{MO} and is expressed in kilograms.

3.5.4
maximum load
load which the boat is designed to carry in addition to the light craft condition, comprising:

— the crew limit at 75 kg each;

— the personal effects of the crew;

— stores and cargo (if any), dry provisions, consumable liquids;

— contents of all permanently installed storage tanks filled to 95 % of their maximum capacity, including fuel, drinking water, black water, grey water, lubricating and hydraulic oil, bait tanks and/or live wells; plus ballast water at 100 % capacity;

— consumable liquids in portable tanks (drinking water, fuel) filled to 95 % of the maximum capacity;

— dinghy or other small craft intended to be carried aboard, and any outboard motor associated with them;

— liferaft(s) if carried in excess of the minimum required in essential safety equipment;

— non-edible stores and equipment normally carried on the boat and not included in the manufacturer's list of standard equipment, e.g. loose internal equipment and tools, spare parts, additional anchors or sails, dinghy and outboard if carried aboard;

Note 1 to entry: Liferafts are not included in essential safety equipment for Categories C and D.

Note 2 to entry: As a guide, not less than 20 kg per person should be allowed for personal effects on habitable boats.

© ISO 2022 – All rights reserved

Note 3 to entry: As a guide, the mass of yachting liferafts varies from approximately 12 + 2CL (kg) to double this, according to specification.

Note 4 to entry: Unless otherwise required, variable position elements (e.g. canting keels, movable solid ballast, tilting masts) are positioned symmetrically about the centreline of the boat.

Note 5 to entry: Any centreboard or keel is in the raised position unless it can be fixed in the lowered position and an appropriate instruction is given in the owner's manual.

Note 6 to entry: The mass of maximum load is denoted by m_{ML} and is expressed in kilograms.

3.5.5
maximum load condition
boat in the light craft condition with the maximum load added and an allowance for the maximum mass of optional equipment and fittings not included in the manufacturer's basic outfit so as to produce the design trim, the crew corresponding to the minimum operating condition being located at the main control position, the remainder positioned at sheerline height at the mid-length of L_H

Note 1 to entry: The mass in the maximum load condition is denoted by m_{LDC} and is expressed in kilograms.

3.5.6
loaded arrival condition
boat in the maximum load condition minus 85 % of the maximum capacity of fixed or portable storage tanks for fuel, oils and drinking water, and minus 90 % of edible stores, but including the worst combination of optional fittings or equipment with respect to stability

Note 1 to entry: In this condition, tanks have 10 % of their maximum capacity remaining.

Note 2 to entry: The mass in the loaded arrival condition is denoted by m_{LA} and is expressed in kilograms.

Note 3 to entry: Unless otherwise required, variable position elements (e.g. canting keels, movable solid ballast, tilting masts) are positioned symmetrically about the centreline of the boat.

3.5.7
displacement volume
V_D
volume of displacement of the boat that corresponds to the appropriate loading condition, taking the density of water as 1 025 kg/m^3

Note 1 to entry: Displacement volume is expressed in cubic metres.

3.6 Other terms and definitions

3.6.1
calculation wind speed
v_W
wind speed used in calculations

Note 1 to entry: Calculation wind speed is expressed in metres per second or in knots.

3.6.2
crew
collective description of all persons onboard a boat

3.6.3
crew limit
CL
maximum number of persons (with a mass of 75 kg each) used when assessing the design category

© ISO 2022 – All rights reserved

3.6.4
design trim
longitudinal attitude of a boat when upright, with crew, fluids, stores and equipment in the positions designated by the designer or builder

Note 1 to entry: Crew are assumed to be in positions designated by the builder. In the absence of builder's instructions, crew and gear are assumed to be positioned in a manner most likely to provide a favourable test result, provided that such positions are consistent with the proper operation of the boat, and that crew are assumed to be either standing at designated positions fitted with handholds, or seated.

3.6.5
essential safety equipment
loose equipment considered essential to the safe operation of the boat, which may include distress flares and rockets, lifebuoy with light and battery, first aid box, wire cutters for standing rigging, lifejackets, safety harnesses and lines, portable firefighting equipment, flashlight, binoculars, radio (e.g. VHF), ball and cone visual signals, charts, navigational publications and for design categories A and B, liferaft(s) sufficient for the crew limit in the corresponding design category

Note 1 to entry: Quantities carried may vary according to the size of boat, design category and crew limit.

Note 2 to entry: As a guide, the mass allowed for essential safety equipment but excluding any liferaft(s) should not be less than $3L_H$ (kg).

Note 3 to entry: The mass of yachting liferafts varies from approximately 12 + 2CL (kg) to double this, according to specification.

Note 4 to entry: Liferafts are not considered to be essential safety equipment in design categories C and D.

3.6.6
flotation element
element which provides buoyancy to the boat and thus influences the flotation characteristics

3.6.6.1
air tank
tank made of hull construction material, and integral with hull or deck structure

3.6.6.2
air container
container made of stiff material, and not integral with the hull or deck structure

3.6.6.3
low density material
material with a specific gravity of less than 1,0 primarily incorporated into the boat to enhance the buoyancy when swamped

3.6.6.4
inflated bag
bag made of flexible material, not integral with hull or deck, accessible for visual inspection and intended always to be inflated when the boat is being used

Note 1 to entry: Bags intended to be inflated automatically when immersed (e.g. at the masthead as a means to prevent inversion) are not regarded as flotation elements.

3.6.7
inclining experiment
method by which the vertical position of the centre of gravity (VCG) of a boat can be determined

Note 1 to entry: The VCG, together with a knowledge of the shape of the hull (the lines plan) and the position of the waterline in a known loading condition, enable all the intact stability parameters to be calculated.

Note 2 to entry: A full description of how to conduct an inclining experiment is given in standard naval architecture textbooks, e.g. References [6] and [8].

© ISO 2022 – All rights reserved

3.6.8
righting lever
GZ
at a specific heel (or trim) angle in calm water, the distance in both the horizontal and transverse (or horizontal and longitudinal) planes between the centre of buoyancy and the centre of gravity

Note 1 to entry: Righting lever usually refers to the transverse plane, but may be in the longitudinal plane where longitudinal stability is concerned.

Note 2 to entry: Righting lever is equal to the righting moment divided by the product of mass, expressed in kilograms, and acceleration due to gravity (9,806 m/s^2) and is expressed in metres.

3.6.9
righting moment
RM
at a specific heel (or trim) angle in calm water, the restoring moment generated by the transverse (or longitudinal) offset of the centre of buoyancy of the submerged part of the hull from the centre of gravity of the boat

Note 1 to entry: Righting moment usually refers to the transverse plane, but may be in the longitudinal plane where longitudinal stability is concerned.

Note 2 to entry: The righting moment varies with heel (or trim) angle and is usually plotted graphically against heel (or trim) angle. Righting moments are most accurately derived by computer from a knowledge of the hull shape and the location of the centre of gravity. Other more approximate methods are also available. The righting moment varies substantially with hull form, centre of gravity position, boat mass and trim attitude.

Note 3 to entry: Righting moment is expressed in newton metres or kilonewton metres.

3.6.10
loaded waterline
waterline of the boat when upright in the maximum load condition

3.6.11
recess retention level
level of water in recesses, when the boat is at design trim, at which 20 % of the uppermost periphery of the surrounding coaming (measured in horizontal plane parallel to waterline at design trim) would be covered by water, assuming that all gates, doors or drainage openings are considered to be sealed

Note 1 to entry: This definition is illustrated in Annex K.

3.6.12
standard equipment
devices including outboard motors (excluding those for tenders), loose furniture and furnishings such as tables, chairs, non-permanently installed mattresses, curtains, etc., portable bilge pumping equipment anchors, chain, warps, sails, loose external equipment such as fenders, boathook and boarding ladder, oars (if appropriate), and essential safety equipment

Note 1 to entry: Where outboard engine(s) are fitted, the heaviest engine(s) recommended for the boat by the manufacturer is(are) included, the mass allowed for outboard engines and their batteries (if not permanently installed) not being less than that given in ISO 12217-1:2022, Tables F.1 and F.2, columns 1 and 3, or ISO 12217-3:2022, Tables C.1 and C.2.

Note 2 to entry: As a guide, the mass allowed for anchors, anchor chain, warps and fenders should not be less than about $0{,}25 L_H^{2,2}$ (kg). In some cases, up to double this mass may be appropriate.

3.6.13
watertightness degree
degree of watertightness as specified in ISO 11812 and ISO 12216

Note 1 to entry: The degree of watertightness is summarized as follows:

© ISO 2022 – All rights reserved

— Degree 1: Degree of tightness providing protection against effects of continuous immersion in water.
— Degree 2: Degree of tightness providing protection against effects of temporary immersion in water.
— Degree 3: Degree of tightness providing protection against splashing water.
— Degree 4: Degree of tightness providing protection against water drops falling at an angle of up to 15° from the vertical.

3.6.14
under way
not at anchor, or made fast to the shore, or aground

4 Symbols

For the purposes of this document, the symbols and associated units in Table 1 apply.

Table 1 — Symbols

Symbol	Unit	Meaning
ϕ	degree (°)	Angle of heel
ϕ_D	degree (°)	Actual downflooding angle of any downflooding opening, see 3.3.2
$\phi_{D(R)}$	degree (°)	Required downflooding angle, see 6.2.3
ϕ_{DA}	degree (°)	Downflooding angle at which a certain total area of openings is submerged, see 3.3.2
ϕ_{DC}	degree (°)	Downflooding angle to cockpits that are not quick-draining according to ISO 11812, see 3.3.2
ϕ_{DH}	degree (°)	Downflooding angle to any main access hatchway, see 3.3.2
ϕ_{GZmax}	degree (°)	Angle of heel at which maximum righting moment or lever occurs
ϕ_V	degree (°)	Angle of vanishing stability, see 3.4.10
$\phi_{V(R)}$	degree (°)	Required angle of vanishing stability, see 6.5
A_{GZ}	m · degree	Positive area under righting lever curve, see 6.4 and 6.6.2
A_S	m^2	Reference sail area according to ISO 8666 and 3.4.8
A'_S	m^2	Standard sail area, see 3.4.9
B_{CB}	m	Beam between centres of buoyancy of sidehulls, see 3.4.5
B_H	m	Beam of hull according to ISO 8666
B_{WL}	m	Beam waterline in the appropriate loading condition according to ISO 8666 and 3.4.4. In the case of multihulls, it is the sum of the maximum waterline beams of each of the hulls.
CL		Crew limit = maximum number of persons on board, see 3.6.3
F_M	m	Freeboard amidships at the appropriate loading condition according to 3.4.6
GM_T	m	Transverse metacentric height, see 6.3
GZ	m	Righting lever = righting moment (N·m)/[mass (kg) × 9,806 (m/s^{-2})], see 3.6.8
GZ_{90}	m	Righting lever at 90° heel
h_{CE}	m	Height of centre of area of A_S above waterline at the appropriate loading condition, see 6.8
h'_{CE}	m	Height of centre of area of A'_S above waterline at the appropriate loading condition, see 6.8
h_D	m	Actual downflooding height, see 3.3.3
$h_{D(R)}$	m	Required downflooding height, see 6.2.2
h_{LP}	m	Height of waterline at the appropriate loading condition above centre of area of immersed profile area including keel(s) and rudder(s), see 6.8.2 and 6.8.3
L_{BS}	m	Length base size = $(2L_{WL} + L_H)/3$

© ISO 2022 – All rights reserved