International Standard

ISO 13165-4

First edition
2025-08

Water quality — Radium-226 —

Part 4: Test method using alpha spectrometry

Qualité de l'eau — Radium 226 —

Partie 4: Méthode d'essai par spectrométrie alpha

Reference number
ISO 13165-4:2025(en)

© ISO 2025



COPYRIGHT PROTECTED DOCUMENT

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword ... **iv**
Introduction ... **v**
1 Scope ... **1**
2 Normative references ... **1**
3 Terms and definitions ... **2**
4 Symbols ... **2**
5 Principle ... **4**
6 Sampling, handling and storage ... **5**
7 Procedure ... **6**
8 Quality assurance and quality control program ... **6**
8.1 General ... 6
8.2 Instrument verification ... 6
8.3 Contamination ... 6
8.4 Interference control ... 6
8.5 Alpha resolution ... 7
8.6 Method verification ... 7
8.7 Demonstration of analyst capability ... 7
9 Expression of results ... **7**
9.1 General ... 7
9.2 Tracer activity added ... 7
9.3 Count rate and net count rate ... 7
9.4 Total recovery ... 8
9.5 Activity concentration of ^{226}Ra ... 9
9.6 Combined uncertainties ... 9
9.7 Decision threshold ... 9
9.8 Detection limit ... 10
9.9 Probabilistically symmetric coverage interval ... 10
9.9.1 Limits of the probabilistically symmetric coverage interval ... 10
9.9.2 Shortest coverage interval ... 11
10 Test report ... **11**
Annex A (informative) **Radioactive interferences and an example of alpha spectrum** ... **13**
Annex B (informative) **Preparation of thin alpha source by electrodeposition** ... **14**
Annex C (informative) **Preparation of thin alpha source by barium sulfate micro-precipitation** ... **17**
Annex D (informative) **Method 1: Radium separation using a solid phase extraction disc** ... **19**
Annex E (informative) **Method 2: Radium pre-concentration, separation with a MnO_2 resin and removal of potential radioactive interferences using an extraction chromatography resin** ... **21**
Annex F (informative) **Method 3: Preconcentration of radium using $CaCO_3$, separation of Ra from potential interferences using a cation exchange resin and extraction chromatography resin** ... **24**
Annex G (informative) **Method 4: Preconcentration of Ra using a lead sulfate coprecipitation and separation of Ra from potential interferences using a complexing agent** ... **27**
Bibliography ... **30**

© ISO 2025 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 147 *Water quality*, Subcommittee SC 3, *Radioactivity measurements*.

Any feedback or questions on this document should be directed to the user’s national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2025 – All rights reserved

Introduction

Radionuclides are present throughout the environment; thus, water bodies (e.g. surface waters, ground waters, sea waters) contain radionuclides, which can be of either natural or anthropogenic origin.

— Naturally-occurring radionuclides, including ^{3}H, ^{14}C, ^{40}K and those originating from the thorium and uranium decay series, in particular ^{210}Pb, ^{210}Po, ^{222}Rn, ^{226}Ra, ^{228}Ra, ^{227}Ac, ^{232}Th, ^{231}Pa, ^{234}U and ^{238}U, can be found in water bodies due to either natural processes (e.g. desorption from the soil and runoff by rain water) or released from technological processes involving naturally occurring radioactive materials (e.g. mining, mineral processing, oil, gas and coal production, water treatment, and the production and use of phosphate fertilisers).

— Anthropogenic radionuclides such as ^{55}Fe, ^{59}Ni, ^{63}Ni, ^{90}Sr, ^{99}Tc, transuranic elements (e.g. Np, Pu, Am, Cm), and some gamma emitting radionuclides, such as ^{60}Co and ^{137}Cs, can also be found in natural waters. Small quantities of anthropogenic radionuclides can be discharged from nuclear facilities to the environment as a result of authorized routine releases. The radionuclides present in liquid effluents are usually controlled before being discharged to the environment[1] and water bodies. Anthropogenic radionuclides used for medical and industrial applications can be released to the environment after use. Anthropogenic radionuclides are also found in waters due to contamination from fallout resulting from above-ground nuclear detonations and accidents such as those that have occurred at the Chornobyl and Fukushima nuclear facilities.

Radionuclide activity concentrations in water bodies can vary according to local geological characteristics and climatic conditions and can be locally and temporally enhanced by releases from nuclear facilities during planned, existing, and emergency exposure situations[2][3]. Some drinking water sources can thus contain radionuclides at activity concentrations that can present a human health risk. The World Health Organization (WHO) recommends to routinely monitor radioactivity in drinking waters[4] and to take proper actions when needed to minimize the health risks.

National regulations usually specify the activity concentration limits that are authorized in drinking waters, water bodies, and liquid effluents to be discharged to the environment. These limits can vary for planned, existing and emergency exposure situations. As an example, during either a planned or existing situation, the WHO guidance level for ^{226}Ra in drinking water is 1 $Bq \cdot l^{-1}$[4], see NOTES 1 and 2. Compliance with these limits is assessed by measuring radioactivity in water samples and by comparing the results obtained, with their associated uncertainties, as specified by ISO/IEC Guide 98-3[5] and ISO 5667-20[6].

NOTE 1 If the value is not specified in Annex 6 of Reference [4], the value has been calculated using the formula provided in Reference [4] and the dose coefficient data from References [7] and [8].

NOTE 2 The guidance level calculated in Reference [4] is the activity concentration that results in an effective dose of 0,1 $mSv \cdot a^{-1}$ to members of the public for an intake of 2 $l \cdot d^{-1}$ of drinking water for one year. This is an effective dose that represents a very low level of risk to human health and which is not expected to give rise to any detectable adverse health effects[4].

This document contains method(s) to support laboratories, which need to determine ^{226}Ra in water samples. The method(s) described in this document can be used for various types of waters (see Clause 1). Minor modifications such as sample volume and counting time can be made if needed to ensure that the decision threshold, detection limit and uncertainties are below the required limits. This can be done for several reasons such as emergency situations, lower national guidance limits and operational requirements.

© ISO 2025 – All rights reserved

Water quality — Radium-226 —

Part 4: Test method using alpha spectrometry

WARNING — Persons using this document should be familiar with normal laboratory practices. This document does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user to establish appropriate safety and health practices and to determine the applicability of any other restrictions.

IMPORTANT — It is essential that tests conducted according to this document be carried out by suitably trained staff.

1 Scope

This document specifies methods to determine ^{226}Ra by alpha spectrometry in supply water, drinking water, rainwater, surface and ground water, marine water, as well as cooling water, industrial water, domestic, and industrial wastewater after proper sampling, handling and test sample preparation.

The detection limit depends on the sample volume, the instrument used, the background count rate, the detection efficiency, the counting time and the chemical yield. The detection limit of the methods described in this document, using currently available alpha spectrometry apparatus, is equal to or lesser than 3 mBq·l^{-1} (or mBq·kg^{-1}), which is lower than the WHO criteria for safe consumption of drinking water (1 Bq·l^{-1})[4]. This value can typically be achieved with a counting time of 48 h for a test sample volume of 40 ml.

The method described in this document is applicable in the event of an emergency situation.

Filtration of the test sample is necessary for the methods described in this document if suspended solids are present. The analysis of ^{226}Ra adsorbed to suspended matter is not covered by this method, because it requires a mineralization step. In this case, the measurement is made on the different phases obtained. The final activity is the sum of all the measured activity concentrations.

It is the user's responsibility to ensure the validity of this test method for the water samples tested.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC Guide 98-3, *Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

ISO/IEC Guide 99, *International vocabulary of metrology — Basic and general concepts and associated terms (VIM)*

ISO 5667-1, *Water quality — Sampling — Part 1: Guidance on the design of sampling programmes and sampling techniques*

ISO 5667-3, *Water quality — Sampling — Part 3: Preservation and handling of water samples*

ISO 5667-10, *Water quality — Sampling — Part 10: Guidance on sampling of waste water*

ISO 11929 (all parts), *Determination of the characteristic limits (decision threshold, detection limit and limits of the confidence interval) for measurements of ionizing radiation — Fundamentals and application*

© ISO 2025 – All rights reserved

ISO/IEC 17025, *General requirements for the competence of testing and calibration laboratories*

ISO 80000-10, *Quantities and units — Part 10: Atomic and nuclear physics*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at https://www.electropedia.org/

4 Symbols

For the purposes of this document, the symbols and designations given in ISO/IEC Guide 98-3, ISO/IEC Guide 99, ISO 80000-10, the ISO 11929 series and the following shall apply.

A_T	Activity of ^{225}Ra, the tracer added	Bq
α	Probability of the false positive decision	
β	Probability of the false negative decision	
c_A	Activity concentration of ^{226}Ra, the measurand	Bq·l^{-1}
c_A^*	Decision threshold of ^{226}Ra, the measurand	Bq·l^{-1}
$c_A^\#$	Detection limit of ^{226}Ra, the measurand	Bq·l^{-1}
$c_A^\triangleleft, c_A^\triangleright$	Lower and upper limits of the probabilistically symmetric coverage interval of ^{226}Ra, the measurand, respectively	Bq·l^{-1}
$c_A^<, c_A^>$	Lower and upper limits of the shortest coverage interval of ^{226}Ra, the measurand, respectively	Bq·l^{-1}
$\widetilde{c_A}$	Possible or assumed true quantity values of ^{226}Ra, the measurand	Bq·l^{-1}
c_{A_T}	Activity concentration of ^{225}Ra tracer solution at the moment of separation	Bq·g^{-1}
ε	Counting efficiency	
Φ	Distribution function of the standardized normal distribution; $\Phi(k_p) = p$ applies	
$1 - \gamma$	Probability for the coverage interval of ^{226}Ra, the measurand	
k_p	Quantiles of the standardized normal distribution for the probabilities p (for instance, $p = 1 - \alpha$, $1 - \beta$ or $1 - \gamma / 2$)	
k_q	Quantiles of the standardized normal distribution for the probabilities q (for instance, $q = 1 - \alpha$, $1 - \beta$ or $1 - \gamma / 2$)	
λ	Decay constant of the isotope (e.g. $\lambda_{215_{Po}}$ is the decay constant of ^{215}Po)	s^{-1}
m	Sample mass	kg
m_{ST}	Mass of tracer solution	g

© ISO 2025 – All rights reserved