INTERNATIONAL STANDARD

ISO 14246

Third edition
2022-02

Gas cylinders — Cylinder valves — Manufacturing tests and examinations

Bouteilles à gaz — Robinets de bouteilles à gaz — Essais de fabrication et contrôles

Reference number
ISO 14246:2022(E)

© ISO 2022



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

© ISO 2022 – All rights reserved

Contents

Page

Foreword ..... **iv**
Introduction ..... **v**
1 Scope **1**
2 Normative references **1**
3 Terms and definitions **1**
4 Cleanliness **2**
5 Manufacturing tests and examinations **2**
5.1 General 2
5.2 Valve test pressure 3
5.3 Tests to be performed on each valve 3
5.4 Inspections and examinations to be performed on a sample and verification of the batch documentation 4
5.5 Procedures to verify materials of construction and components 5
Annex A (informative) **Example of test protocol on each valve** **6**
Bibliography **7**

© ISO 2022 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 2, *Cylinder fittings*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 23, *Transportable gas cylinders*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 14246:2014), which has been technically revised. It also incorporates Amendment ISO 14246:2014/Amd 1:2017. The main changes are as follows:

— in Clause 4, a maximum level of hydrocarbon contamination of 220 mg/m^2 and a maximum particle size of 200 µm has been introduced for valves for oxygen and other oxidizing gases for general purpose applications, and the mandatory reference to ISO 15001 has been changed to an example for medical applications;

— in 5.2, indent c), the value of the test pressure for specific acetylene valves has been reduced from 37 bar to 35 bar;

— in 5.4, the requirements concerning the verification of the assembly with regard to the use of correct components and assembly torques have been clarified.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2022 – All rights reserved

Introduction

This document covers the function of a valve as a closure (defined by the UN Model Regulations). Additional features of valves (e.g. pressure regulators, residual pressure-retaining devices, non-return devices and pressure relief devices) might be covered by other standards and/or regulations.

Valves conforming to this document can be expected to perform satisfactorily under normal service conditions.

This document pays particular attention to manufacturing tests and examinations of valves designed and type tested in accordance with ISO 10297.

This document has been written so that it is suitable to be referenced in the UN Model Regulations[1].

In this document, the unit bar is used, due to its universal use in the field of technical gases. It should, however, be noted that bar is not an SI unit, and that the corresponding SI unit for pressure is Pa (1 bar = 10^5 Pa = 10^5 N/m^2).

Pressure values given in this document are given as gauge pressure (pressure exceeding atmospheric pressure) unless noted otherwise.

© ISO 2022 – All rights reserved

Gas cylinders — Cylinder valves — Manufacturing tests and examinations

1 Scope

This document specifies the procedures and acceptance criteria for manufacturing tests and examinations (sometimes called "initial inspection and tests") of valves designed and type tested in accordance with ISO 10297.

This document is applicable to:

a) cylinder valves intended to be fitted to refillable transportable gas cylinders;

b) main valves (excluding ball valves) for cylinder bundles;

c) cylinder valves or main valves with integrated pressure regulator (VIPR);

d) valves for pressure drums and tubes.

NOTE Where there is no risk of ambiguity, cylinder valves, main valves, VIPR and valves for pressure drums and tubes are addressed with the collective term “valves” within this document.

The principles of these manufacturing tests and examinations can be beneficially applied to cylinder valves type tested to national or International Standards other than ISO 10297.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10286, *Gas cylinders — Vocabulary*

ISO 10297, *Gas cylinders — Cylinder valves — Specification and type testing*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 10286 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at https://www.electropedia.org/

3.1
valve working pressure
p_w
settled pressure of a compressed gas at a uniform reference temperature of 15 °C in a full gas cylinder for which the valve is intended

Note 1 to entry: This definition does not apply to liquefied gases (e.g. carbon dioxide) or dissolved gases (e.g. acetylene).

[SOURCE: ISO 10297:2014, 3.6, modified — “or cylinder bundle” has been deleted from the definition and Note 2 to entry has been deleted.]

© ISO 2022 – All rights reserved

3.2
valve test pressure
p_{vt}
minimum pressure applied to a valve through a gas during testing

[SOURCE: ISO 10297:2014, 3.8, modified — "through a gas" has been added to the definition and the note to entry has been deleted.]

3.3
external leak tightness
leak tightness to atmosphere (leakage in and/or leakage out) when the valve is open

[SOURCE: ISO 10297:2014, 3.4, modified — Note 1 to entry and Figure 1 have been deleted.]

3.4
internal leak tightness
leak tightness across the valve seat (leakage in and/or leakage out) when the valve is closed

[SOURCE: ISO 10297:2014, 3.5, modified — Note 1 to entry and Figure 2 have been deleted.]

3.5
batch
quantity of valves of the same type tested design and production order, which is produced as a controlled number in a specified time period

3.6
sample
quantity of valves selected from a *batch* (3.5) according to a recognized sampling procedure

Note 1 to entry: The ISO 2859 series specifies sampling procedures for inspection.

4 Cleanliness

The manufacturing process including all tests shall be such that the valves are supplied clean and dry to meet the requirements of the intended service, e.g. see ISO 15001 for medical applications.

Gas wetted components of valves for oxygen and other oxidizing gases (see ISO 10156) shall be clean of oil and grease so that the level of hydrocarbon contamination is not greater than 220 mg/m^2. In addition, components shall be free from particles of a size larger than 200 µm. This shall be verified by an appropriate method, e.g. as given in ISO 15001.

Consideration shall be given to minimize the introduction of particles and the risk of contamination during the assembly process.

5 Manufacturing tests and examinations

5.1 General

Tests and examinations performed to demonstrate compliance with this document shall be conducted using instruments calibrated before being put into service and thereafter according to an established programme.

Manufacturing tests and examinations, which are further specified in 5.3, 5.4 and 5.5, shall include:

— tests to be performed on each valve;

— inspections and examinations to be performed on a sample, and verification of the batch documentation;

— procedures to verify materials of construction and components.

© ISO 2022 – All rights reserved