INTERNATIONAL STANDARD

ISO 15727

First edition
2020-01

UV-C devices — Measurement of the output of a UV-C lamp

Dispositifs UV-C — Mesurage de la sortie d'une lampe UV-C

Reference number
ISO 15727:2020(E)

© ISO 2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

 © ISO 2020 – All rights reserved

Contents

Page

Foreword ... **iv**
Introduction ... **v**
1 Scope ... **1**
2 Normative references ... **1**
3 Terms and definitions ... **1**
4 Types of UV-C lamps and ballasts ... **2**
4.1 General ... 2
4.2 Types of UV-C lamps ... 2
4.2.1 General ... 2
4.2.2 Linear UV-C lamps ... 3
4.3 Type of ballasts ... 3
4.3.1 General ... 3
4.3.2 Magnetic ballasts ... 3
4.3.3 Electronic ballasts ... 4
5 Measurement of the output of a UV-C lamp ... **4**
5.1 Measurement method classification ... 4
5.2 Measurement of the output of a UV-C lamp in a darkroom ... 4
5.2.1 Instrument ... 4
5.2.2 Calibration ... 5
5.2.3 UV-C radiation power calculation ... 5
5.2.4 Necessary conditions ... 6
5.2.5 Measurements ... 6
5.3 Measurement of the output of a UV-C lamp in a test chamber ... 10
6 Safety issues ... **10**
6.1 General ... 10
6.2 Protective clothing and eyewear ... 10
6.3 UV-C photodegradation of organics ... 10
6.4 Ozone production ... 10
6.5 UV-C internal and external leakage ... 10
6.6 Mercury content of the UV-C lamp ... 11
6.7 Personal protective equipment ... 11
Annex A (informative) **Suggested methods to minimize the effects of reflected UV-C** ... **12**
Annex B (normative) **Measurement of the output of a UV-C lamp in a test chamber** ... **13**
Bibliography ... **20**

© ISO 2020 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 142, *Cleaning equipment for air and other gases*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2020 – All rights reserved

Introduction

The First World Health Organization (WHO) Global Conference on Air Pollution and Health took place at WHO headquarters in Geneva, Switzerland from 30 October to 1 November 2018. The conference participants considered the scientific evidence on air pollution and health and emphasized: Air pollution — both ambient and household — is estimated to cause 7 million deaths per year; 5,6 million deaths are from noncommunicable diseases and 1,5 million from pneumonia. There is an urgent need to scale up the global response to prevent diseases and deaths (available at http://www.who.int/phe/news/clean-air-for-health/en/).

Research shows that indoor air pollution can be 2 to 5 times greater than outdoor pollution and under particular circumstances; it can be up to 100 times. Since people generally spend more than 80 % to 90 % of our time indoors, the quality of indoor air pollution is a key element to good health of people. At the same time, indoor air pollution is one of 5 environmental risk factors to the public health. Under most indoor environments, microbial suspension in the air is the chief culprit to transmitted diseases and it is a factor that many people ignore because these organisms, whose body size is ranging from several micrometres to more than 10 micrometres, are invisible to the naked eye.

In recent years, these germs bring much more intense effect, including frequent occurrences of sick building syndrome, elevated nosocomial infection rate, rapid increase of air-conditioning energy consumption (a microbe film a few millimetres thick accumulates on the air conditioner coil, reducing the heat transfer efficiency of the air treatment unit), smelly air-conditioned rooms and resurgence of tuberculosis. Many people have a drop in their own productivity and spend more on medical care because headache, chest congestion, disturbance in respiration, neurasthenia, nausea and state of mind are fidgety are the most common symptoms for people staying in the air-conditioned rooms. In addition, people in air-conditioned rooms are more susceptible to the infection of ophthalmic and nasitis.

Meanwhile, clinical medical evidence suggests that various diseases, such as heart disease, neurasthenia, memory decline and influenza, correlate with polluted indoor air. The improvement of indoor air quality is desperately needed.

Ultraviolet air disinfection devices are invented in such circumstances. Most ultraviolet air disinfection devices circulate the air indoors. With media filtration and a high-efficiency UV-C lamp, disinfection devices have good effects of filtration of dust in air, meanwhile, it can kill germs and viruses directly and cut the spread of disease. Disinfection devices application can reduce indoor air pollution, improve indoor air quality and provide protection against pneumonia, influenza and other respiratory diseases.

© ISO 2020 – All rights reserved

UV-C devices — Measurement of the output of a UV-C lamp

1 Scope

This document specifies the measurement of the output of a UV-C lamp, types of UV-C lamp, lamp ballast, and safety issues.

It is applicable to the output measurement of linear UV-C disinfection lamps.

This document specifies a measurement method for evaluating output power of UV-C lamps installed in heating, ventilation and air conditioning (HVAC) systems. The method includes the simulation measurement of UV-C output power of UV-C lamps under various temperatures and various air velocities, and under conditions that the axial direction of the lamp is parallel or perpendicular to the air flow direction. It can reliably evaluate and compare the UV-C output power of UV-C lamps in the ultraviolet germicidal irradiation (UVGI) device based on the testing results. If the microbial inactivation rate of a particular UVGI device equipped with the same type of UV-C lamp is known, the microbial inactivation rate of the UVGI device at various temperatures and at various air velocities can be evaluated.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15858, *UV-C Devices — Safety information — Permissible human exposure*

ISO 29464:2017, *Cleaning of air and other gases — Terminology*

ISO/IEC 17025, *General requirements for the competence of testing and calibration laboratories*

CIE S 017, *International Lighting Vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 29464, CIE S 017 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

3.1
ultraviolet radiation
UV radiation
wavelength of the electromagnetic spectrum of radiation from 10 nm to 400 nm

Note 1 to entry: The range between 100 nm and 400 nm is commonly subdivided into:

— UV-A: 315 nm to 400 nm;

— UV-B: 280 nm to 315 nm;

— *UV-C* (3.2): 200 nm to 280 nm;

© ISO 2020 – All rights reserved

— Vacuum UV: 100 nm to 200 nm.

[SOURCE: ISO 29464:2017, 3.6.18, modified — "UVA", "UVB" and "UVC" have been changed to "UV-A", "UV-B" and "UV-C".]

3.2
ultraviolet C
UV-C
ultraviolet radiation (3.1) from 200 nm to 280 nm

3.3
UV-C disinfection
disinfection method that uses *ultraviolet radiation* (3.1) with a wavelength between 200 nm and 280 nm to kill microorganisms

Note 1 to entry: *UV-C* (3.2) radiation attacks the vital DNA of the bacteria directly. The bacteria lose their reproductive capability and are destroyed.

3.4
UV-C irradiance
power passing through a unit area perpendicular to the direction of propagation

Note 1 to entry: *UV-C* (3.2) irradiance is typically reported in watt per square metre (W/m^2). It is also usually reported in mW/cm^2 or uW/cm^2.

3.5
low pressure UV-C lamp
discharge lamp of the mercury vapour type, without a coating of phosphors, in which the partial pressure of the vapour does not exceed 100 Pa during operation and which mainly produces ultraviolet radiation of 253,7 nm

3.6
UV-C radiation conversion efficiency
ability of a *UV-C* (3.2) lamp to convert electrical power into UV-C radiation power

Note 1 to entry: The ratio is the UV-C radiation power accounting for the electrical power of the UV-C lamp. The UV-C conversion efficiency of a *low pressure UV-C lamp* (3.5) at 253,7 nm is between 25 % and 45 %. The UV-C conversion efficiency should be not less than 30 % in an air disinfection field under all circumstances due to energy consumption of the system.

3.7
UV-C radiometer
instrument used to measure *UV-C* (3.2) radiometric quantities, particularly *UV-C irradiance* (3.4) or fluence

[SOURCE: ISO 29464:2017, 3.6.15]

4 Types of UV-C lamps and ballasts

4.1 General

Ballasts shall comply with requirements for starting parameters and operating parameters of UV-C lamps. Lamps bases of UV-C lamps and cables between UV-C lamps and ballasts shall comply with performance and safety requirements.

4.2 Types of UV-C lamps

4.2.1 General

UV-C lamps are divided into medium pressure UV-C lamps and low pressure UV-C lamps; air disinfection devices usually use low pressure UV-C lamps. The low pressure UV-C lamps are made of liquid mercury

© ISO 2020 – All rights reserved